INTERNATIONAL STANDARD





INTERNATIONAL ORGANIZATION FOR STANDARDIZATION ORGANISATION INTERNATIONALE DE NORMALISATION МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ

Road vehicles - Fuel injection pump testing -

Part 3: Application and test procedures

Véhicules routiers — Essais des pompes d'injection à gazole —

Partie 3: Application et modes opératoires d'essai

ISO 4008-3:1987

ttps://standards.iteh.ai/catalog/standards/iso/82c3a633-891d-4d54-9b57-8dd348c95d7f/iso-4008-3-1987

Reference number ISO 4008-3:1987 (

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council. They are approved in accordance with ISO procedures requiring at least 75 % approval by the member bodies voting.

International Standard ISO 4008-3 was prepared by Technical Committee ISO/TC 22, *Road vehicles*.

Users should note that all International Standards undergo revision from time to time and that any reference made herein to any other International Standard implies its reveal latest edition, unless otherwise stated.

<u>ISO 4008-3:1987</u>

https://standards.iteh.ai/catalog/standards/iso/82c3a633-891d-4d54-9b57-8dd348c95d7f/iso-4008-3-1987

© International Organization for Standardization, 1987 •

Printed in Switzerland

Conte	ents		Page
0 Introc	duction		1
1 Scop	e		1
2 Field	of appl	ication	1
3 Refer	ences .		1
4 Termi	inology	andards	1
5 Validi https://st	ity	dards.iteh.ai)	1
Docum	5.1.1	Parameters of a valid ISO test	1
	5.1.2	Peak injection pressure, limiting delivery values	2
<u>IS</u> ttps://standards.iteh.i	5.1.3	Calculated values of limiting delivery	2
891d-4d54-91 5.2 -8	Equipn	nent)5d7f/iso-4008-3-1987	2
	5.2.1	Minimum conditions mandatory to an ISO test	2
	5.2.2	Statement of ISO test conditions	3
	5.2.3	Non-mandatory conditions	3
6 Equip	oment		3
6.1	Test be	enches	3
	6.1.1	Conformity and recognition	3
	6.1.2	Instructions and maintenance	3
6.2	Test in	jectors	3
	6.2.1	Conformity and recognition	3
	6.2.2	Maintenance	3
6.3	High-p	ressure pipes	3
	6.3.1	Conformity and recognition	3
	6.3.2	Care and maintenance	3

ISO 4008-3 : 1987 (E)

	6.4	Calibr	ation fluid	4			
		6.4.1	Conformity and recognition	4			
		6.4.2	Instruction and preservation	4			
7	Test	ing		4			
	7.1	Test s	chedules	4			
		7.1.1	Application	4			
		7.1.2	Content	4			
	7.2	Test p	rocedure	5			
		7.2.1	Injection pump testing	5			
		7.2.2	Verification of equipment	5			
		7.2.3	Overloading and misuse	5			
8	Envi	ronmer	t	6			
9	Pers	onnel a	nd authorization	6			
Aı	nnexe	es					
A	Dov exce	wnrating eeds 62	g test bench capacity when injection pump peak pressure 5 bar	s teh.ai)			
в	3 Test injector maintenance						
С	Test	t injecto	r setting and testing values	12			
D	lder	ntificatio	on of high-pressure pipes	13			
E	Stat	ement	of the ISO test conditions and ards/iso/82c3a633-891d-4d54-9	9 <mark>14</mark> 57-8dd348c95d7f/iso-4008			
F	Defi	nitions		15			

Road vehicles — Fuel injection pump testing —

Part 3: Application and test procedures

0 Introduction

This International Standard aims to achieve correct setting and adjustment of fuel injection pumps for the subject types of compression ignition engines by providing standardized conditions for testing.

Part 3 of ISO 4008 is a document for use in the workshop. It forms the complement to the injection pump test schedules and coordinates the detailed technical requirements of parts 1 and 2 and further referenced standards (see clause 3) with the procedural instructions necessary to apply and validate this International Standard as a whole.

1 Scope

This part of ISO 4008 defines conditions, in addition to those contained in parts 1 and 2, which are mandatory to the performance of fuel injection pump tests in conformity with the International Standard as a whole. Reference is also made to non-mandatory but desirable conditions.

2 Field of application

The conditions of this part of ISO 4008 apply to tests performed in accordance with fuel injection pump manufacturers', engine manufacturers' or other admissible test schedules which refer to ISO 4008 conditions of test.

This part of ISO 4008 is deemed to form an integral part of all such admissible test schedules.

3 References

ISO 4008-1, Road vehicles — Fuel injection pump testing — Part 1: Dynamic conditions.

ISO 4008-2, Road vehicles – Fuel injection pump testing – Part 2: Static conditions.

ISO 4010, Road vehicles — Calibrating nozzle, delay pintle type.

ISO 4020-1, Road vehicles – Fuel filters for automotive compression ignition engines – Part 1: Test methods.

ISO 4020-2, Road vehicles — Fuel filters for automotive compression ignition engines — Part 2: Test values and classification.

ISO 4093, Road vehicles — Fuel injection pumps — High pressure pipes for testing.

ISO 4113, Road vehicles — Calibration fluid for diesel injection equipment.

ISO 7440-1, Road vehicles — Fuel injection equipment testing — Part 1: Calibrating nozzle and holder assemblies.

ISO 7440-2, Road vehicles — Fuel injection equipment testing — Part 2: Orifice plate flow measurement.

ISO 8984-1, Road vehicles — Fuel injector testing — Part 1: Hand lever operated testing and setting apparatus.¹⁾

ISO 8984-2, Road vehicles — Fuel injector testing — Part 2: Testing procedures.¹⁾ 348-95677180-4008-1987

4 Terminology

Many general terms, as well as those particular to this International Standard, are included in a list of definitions in annex F. This annex does not form an integral part of this International Standard.

5 Validity

5.1 Documentation

5.1.1 Parameters of a valid ISO test

A valid ISO test (see 5.2.2) shall include the parameters listed in table 1.

¹⁾ At present at the stage of draft.

Reference line	Parameter			Unit	s	Value*	Origin and/or derivation of information
(1)	Test bench flywheel moment of inertia				1 ²	0,5	
(2)	Test bench driveshaft stiffness			N∙m	/°	9 940	Figure 2 of ISO 4008-1 (This shall be supplied with an ISO test bench)
(3)	Coupling stiffness			N · m.	/0	800	
(4)	Calibration fluid specification				ISC) 4113	Clause 5.2.1 of ISO 4008-3
(5)	Calibration fluid viscosity (actual v	/alue)		mm ²	/s	2,8	Measurement
(6)	Calibration fluid temperature			°C		41	Measurement
(7)	High-pressure pipes (ISO No. or non-standard specification)				ISO 4093-2		Injection pump test schedule
(8)	Calibration or test injector (ISO No. or non-standard specification) Nozzle Holder				ISO 4010 ISO 7440		
(9)	Calibration or test injector opening pressure			bar		175	Table 5 of ISO 4008-3
. (10)	Test No.	1*	2*	3	4	5	Test schedule
(11)	Test speed, min ⁻¹	1 080	245				Test schedule
(12)	Max. effective flywheel capacity, mm ³ /stroke	1 215	62,5				A.1 of ISO 4008-1 calculate** : (line 1) × (line 11) ² /480
(13)	Max. effective driveshaft capacity, mm ³ /stroke	355	355	tandauda			A.2 of ISO 4008-1 calculate** : (line 2)/28
(14)	Max. effective coupling capacity, mm ³ /stroke	160	160		51	uus •	A.3 of ISO 4008-1 (line 3)/5 (stated on coupling)**
(15)	Max. effective pump mounting capacity, mm ³ /stroke	475	240		ſC	IS.Ite	Figure 2 of ISO 4008-1 (supplied with ISO test bench)

* The values and facts in these columns are examples of a typical test (see footnote to 5.1.3).

** Refers to the reference lines in this table.

5.1.2 Peak injection pressure, limiting delivery values (see 5.2.3)

If the test schedule states a peak injection pressure, p_p , exceeding 625 bar¹⁾, the limiting delivery values in lines (12), (13), (14) and (15) of table 1 shall be reduced as stated in annex A.

5.1.3 Calculated values of limiting delivery

When the values of limiting delivery have been calculated for lines (12), (13), (14) or (15) in table 1^{2} , none of the readings of the pump delivery in any of the tests conducted under ISO test conditions shall exceed any of these calculated values.

5.2 Equipment

5.2.1 Minimum conditions mandatory to an ISO test

A valid ISO test shall be conducted in accordance with the minimum requirements given in table 2. Where non-mandatory equipment or conditions are adopted for test purposes (see 5.2.3), it is stressed that they shall conform to the mandatory serviceability requirements (see 6.3.2 and B.2 and B.3 of annex B).

Table 2 - Minimum test conditions for ISO test

ltem	International Standard specifying requirements to be met		
Test bench	ISO 4008-1		
	ISO 4008-2		
	ISO 4008-3 (see 6.1.1, 6.1.2,		
	7.2.3)		
Test injectors	ISO 4008-3 (see 6.2)		
High-pressure pipes	ISO 4008-3 (see 6.3)		
Calibration fluid	ISO 4113 and ISO 4008-3 (see 6.4)		
Calibration fluid temperature	ISO 4008-3 (see 6.4.2.7)		
Environment	ISO 4008-3 (see clause 8)		
Personnel and authorization	ISO 4008-3 (see clause 9)		
Test schedule	ISO 4008-3 (see 7.1)		
Test procedure	ISO 4008-3 (see 7.2)		
Verification of equipment	ISO 4008-3 (see 7.2.2)		

^{1) 1} bar = 10^5 N/m^2 = 100 kPa

²⁾ In the example in table 1, if the pump delivery were, for example, 85 mm³/stroke in test 1 and 84 mm³/stroke in test 2, test 1 would be acceptable to ISO conditions and test 2 would not, because the flywheel was overloaded owing to insufficient moment of inertia.

5.2.2 Statement of ISO test conditions

The identity of the test facility shall be stated on the statement of ISO test, and the information entered thereon (including all relative requirements in this part of ISO 4008 deemed to be an integral part of the ISO test) shall be vouched for by the signature of an authorized person responsible for the ISO test. When a statement is requested it shall conform with annex E.

5.2.3 Non-mandatory conditions

Conformity of test injectors, nozzle opening pressure and highpressure injection pipes to one of the relevant International Standards shall not be mandatory to the validity of an ISO test, or statements of ISO test conditions, provided that the test schedule defines them as specified in 7.1.2 (see 5.2.1).

6 Equipment

6.1 Test benches

6.1.1 Conformity and recognition

Test benches suitable for ISO testing shall be supplied with a certificate of conformity prepared and vouched by its manufacturer, stating compliance of the bench with ISO 4008-1 and ISO 4008-2. The graphs in figures 1 and 2 of ISO 4008-1 shall form an integral part of the certificate.

6.1.2 Instructions and maintenance

6.1.2.1 It is mandatory that the test bench manufacturer shall provide with the test bench proper operation, installation and maintenance instructions in conformity with the requirements of ISO 4008.

6.1.2.2 These instructions shall clarify and evaluate the errors which can occur if they are not fully observed. Particular attention shall be given to injection pump mounting adaptors, couplings, low-pressure pipes and the proper use of the pump delivery measurement system.

6.1.2.3 No spare parts which are not authenticated by the test bench manufacturer shall be fitted. This applies to mechanisms, or constituent components of mechanisms, regulated by sub-clause 5.1 of ISO 4008-1 and clause 8 of ISO 4008-2 respectively.

6.2 Test injectors

6.2.1 Conformity and recognition

6.2.1.1 Calibrating injectors

Injectors and nozzles conforming to the appropriate calibrating injector International Standard shall be accompanied by documentation¹⁾ vouched for by the manufacturer and defining

feature(s) on the injector and nozzle component(s) identifying the manufacturer and claiming conformity with the pertinent Standard.

6.2.1.2 Other test injectors

These are the other injector and nozzle types which may be specified in the appropriate pump test schedule.

6.2.2 Maintenance

6.2.2.1 A record shall be kept of the number of pumps tested with each test injector.

6.2.2.2 The test injector maintenance schedule, as detailed in annex B, is mandatory for calibrating injectors, and unless otherwise stated by the manufacturer, it is mandatory for use with other test injectors.

6.3 High-pressure pipes

6.3.1 Conformity and recognition

6.3.1.1 ISO high-pressure pipes for testing shall all bear the following two identification marks and be dimensioned in accordance with ISO 4093:

a) the manufacturer's mark which shall vouch for conformity with ISO 4093;

b) the ISO identification code which relates to the nominal dimensions shown in annex D.

6.3.1.2 Other high-pressure pipes have dimensions specified in the appropriate pump test schedule. Pipe dimensions in common usage and specified in ISO 4093 are tabulated in annex D.

6.3.2 Care and maintenance

The following requirements are mandatory for all high-pressure pipes.

6.3.2.1 Pipes shall be kept clean internally and externally and the ends shall be capped when not in use.

6.3.2.2 Pipes shall not be bent round a radius less than that shown in table 6 in annex D.

6.3.2.3 At least weekly, a reamer of a diameter 0,025 mm less than the nominal bore size shall be inserted through the nipple to prevent throttling. Proper care and cleanliness shall be maintained.

6.3.2.4 The overall length over the pipe ends shall not be reduced by more than 5 mm below the nominal length. Check by passing a flexible wire through the bore.

¹⁾ For example, by labelling or in the packaging.

6.3.2.5 In use, after blowing off with air, no seepage of fluid shall be visible at either connection.

6.4 Calibration fluid

6.4.1 Conformity and recognition

Calibration fluid conforming to ISO 4113 shall be obtained in sealed metal drums bearing two identification marks:

a) the manufacturer's (or supplier's) name which shall vouch for conformity with the relevant International Standard;

b) the number of the International Standard to which the fluid purports to conform. The manufacturer's code number shall not constitute an acceptable description.

6.4.2 Instruction and preservation

6.4.2.1 Calibration fluid shall be stored, in its sealed original identifiable container, under cover, until required for use.

6.4.2.2 Oil which has been subjected to temperatures below -10 °C shall not be used without reference to, and advice from, the manufacturer.

6.4.2.3 Conditions, in storage or in use, which could result in pollution by condensed moisture shall not be allowed to develop.

6.4.2.4 In use, deterioration of calibration fluid, due to evaporation of the more volatile constituents and to unavoidable contamination by lubricating and fuel oils, shall not be permitted beyond the point where the viscosity at 40 °C exceeds 3,0 mm²/s.

6.4.2.5 The viscosity shall be measured weekly.

6.4.2.6 No attempt shall be made to compensate for deterioration by mixing with other liquids.

6.4.2.7 In use, the calibration fluid temperature shall be maintained at a true value of 40 \pm 2 °C. This temperature shall be measured at the test bench bulkhead connection for the fuel pipe¹⁾.

7 Testing

7.1 Test schedules (see 5.2.1)

7.1.1 Application

The three basic forms of the test schedule are as defined in annex F. Notwithstanding that production test schedules may be found in service workshops, this International Standard shall apply in all cases where ISO tests are specified. Where ISO tests are not specified, existing custom and practice will apply.

7.1.2 Content

7.1.2.1 All ISO test schedules shall be complete in themselves. They may require dependence on other data issued by the same source as part of the test schedule. ISO 4008-3 shall form an integral part of an ISO test schedule.

7.1.2.2 Test schedules shall state at least the following and shall not cancel any statement or requirement of this part of ISO 4008:

a) test schedule identity;

b) the injection pump manufacturer and address for enquiries;

c) the injection pump type(s) (complete details; description and type code);

d) the nature of the test;

e) test injectors², nozzle opening pressure;

f) high-pressure pipes³⁾, details of pump end pipe fitting;

g) pump mounting details: base, cradle, spigot, flange or other, including centre height and drive input details, and technical requirements for any special drive adaptor(s);

h) special services needed (other than obligatory) — for example: return flow measurement, control lever quadrant, automatic advance measurement, solenoids (electrical details), air pressure/vacuum, special pressure gauges;

i) test reference number for each test (or setting);

i) all test conditions for each test (or setting); tolerances shall be stated making allowance for permissible instrument error stated in clause 8 of ISO 4008-2;

- k) injection pump delivery values in mm³/stroke/cylinder;
- I) speed in revolutions per minute (\min^{-1}) ;

1) As stated in 6.1.2 d) of ISO 4008-2.

²⁾ Any type may be stated, provided the nozzle, holder and edge filter (where applicable) are completely specified, but ISO types are preferable. They will be more accurate and are more likely to be available.

³⁾ Any type may be stated, provided they are specified by outside diameter/inside diameter and length, but ISO types are preferable. They will be more accurate and are more likely to be available.

m) test numbers that shall be nominated ISO tests (i.e. conducted under ISO 4008-1 dynamic test conditions as specified in 5.2);

n) direction of rotation of injection pump;

o) power required by injection pump in kilowatts (kW);

p) peak injection pressure (p_p) if it exceeds 625 bar (see 6.8 of ISO 4008-1 and annex A);

q) warming-up procedure and stabilization procedure between successive ISO test elements.

NOTE - Only ISO 4113 calibration fluid is permissible for ISO tests (see table 2).

7.1.2.3 An instruction referring to test bench operation given in a test schedule shall not override a test bench manufacturer's instruction given with the test bench (for example, graduate drainage time, number of strokes over which to take a measurement, etc.).

7.2 Test procedure

7.2.1 Injection pump testing

The following processes shall be observed.

7.2.1.1 Check the identity of the injection pump to be tested in comparison with the test schedule. Clean outside of pump.

7.2.1.2 Check the characteristics of the pump to be tested in comparison with the permissible operating envelope and basic data and the test bench power and speed characteristics published with the ISO test bench to be used.

7.2.1.3 Check that the test injectors, high- and low-pressure pipes, pump mounting and any other accessories agree with both the test schedule and/or test bench instructions.

Pumps which may contain foreign matter should not be run initially using calibrating injectors. They shall first be run using any suitable slave injectors. (This applies, for example, to pumps which have been stored for a time or have been received from a customer and have not been overhauled.) **7.2.1.4** Only couplings permitting no backlash and carrying a maximum ISO rating in mm^3 /stroke and also the torsional stiffness, S_c , in N·m/° may be used in an ISO test.

7.2.1.5 Check the integrity of the element connecting the drive coupling on the test bench to the drive shaft of the pump. This element shall be exactly as specified by either the test bench manufacturer or the pump manufacturer. If the pump requires a specially designed drive mechanism, the pump manufacturer's recommendation shall be followed.

7.2.1.6 The test bench shall be operated according to its manufacturer's instructions. When the manufacturer has not issued specific instructions regarding the operation of the fuel measuring system, the following rules shall be observed for ISO tests :

a) the graduates shall be drained for a period of $30 \pm 3 s$;

b) a reading of pump delivery shall be taken over an unbroken number of consecutive strokes sufficient to ensure that the graduates are filled to more than 50 % of their calibrated scale(s).

7.2.2 Verification of equipment

7.2.2.1 Equipment shall be subjected to a verification test at the time intervals stated in table 3, or more frequently if the equipment instructions or the test results so indicate. A purpose-made audit kit, having parallel reference equipment, the resolution of which is at least five times better than that of the equipment to be verified (where applicable), is desirable.

7.2.3 Overloading and misuse Piso-4008-3-1987

NOTE — Using test equipment beyond its technical capability results in a change in injection pump delivery which can amount to over 10 %. Departure from specified equipment such as high-pressure pipes and injectors can change pump delivery by a further similar amount. Departure from the test bench manufacturer's instructions in the use of the test bench flow measuring system can impair its accuracy. The following requirements are of great importance.

7.2.3.1 Test benches shall not be used outside the area of the "permissible operating envelope" published with ISO test benches. See figure 2 of ISO 4008-1, shown in annex A.

ltem	Test method	Accuracy of reference equipment and method	Rectification	Months
Pressure gauge(s)	Parallel reference	\pm 0,2 % of full scale	Replace, rectify or add correction label	3
Temperature gauge(s)	Run fluid over reference	± 0,2 °C	Replace, rectify or add correction label	3
Tachometer	Tachometer reference	± 1 min - 1	Replace, rectify or add correction label	3
Fluid measure- ment system	See clause A.2 of ISO 4008-2	See 8.10.2 of ISO 4008-2	Rectify	6

Table 3 — Test schedule for measuring equipment $^{1)}$

1) See clause 8 of ISO 4008-2 for acceptable tolerances.

7.2.3.2 Couplings shall not be used beyond the maximum rating displayed on them.

7.2.3.3 The correct coupling/injection pump shaft adaptors shall be used.

7.2.3.4 The injection pump shall be mounted using the proper mounting adaptors supplied by the test bench manufacturer for the pump being tested and which shall be in accordance with any special requirements in the test schedule.

7.2.3.5 Injection pumps with governors, requiring readings to be taken or adjustments to be made at conditions where the pump delivery is directly under governor control, shall not be tested on benches which are not capable of maintaining speed stability at these conditions. The speed droop of the test bench in use, as shown in the "power and speed droop characteristics" supplied with ISO test benches, should not be more than approximately half that of the governor under test (at the power required by the pump).

8 Environment

In the absence of appropriate national rules or legislation, the following minimum conditions shall apply.

8.1 The test bench and all other workshop equipment shall be properly installed following the manufacturer's instructions.

8.2 Forced filtered ventilation shall provide fresh clean air to the working area. A small positive pressure is desirable.

8.3 Atmospheric condensation shall be prevented at all times.

8.4 Floors, walls, ceilings and work surfaces shall not have loose finishes which could release dust or abrasive matter.

9 Personnel and authorization

9.1 A person shall be authorized to be responsible for the maintenance and operation of the whole test facility and the servicing of fuel injection equipment in conformity with this International Standard.

9.2 The authorized person(s) (see 5.2.2) shall be in possession of a certificate issued by the test equipment manufacturers and the fuel injection equipment manufacturers, certifying that appropriate instruction in the servicing of the fuel injection equipment and/or test equipment in question has been given to the authorized person(s).

9.3 At least one authorized person shall be available on the premises at all reasonable times.

9.4 Persons engaged in servicing of fuel injection equipment who are not authorized shall operate only under the supervision of an authorized person.

<u>ISO 4008-3:1987</u>

https://standards.iteh.ai/catalog/standards/iso/82c3a633-891d-4d54-9b57-8dd348c95d7f/iso-4008-3-1987