

Designation: F2480 - 06 (Reapproved 2012) F2480 - 06 (Reapproved 2017) American National Standard

Standard Guide for In-ground Concrete Skatepark¹

This standard is issued under the fixed designation F2480; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

- 1.1 This guide covers safety and performance guidelines pertaining to in-ground skatepark facilities built primarily out of concrete and other designed materials. This guide pertains to any concrete materials and other designed materials intended to be used in the performance of the sports including skateboarding, inline skating and BMX biking. Items such as fencing, lighting, and operational structures are not intended to be a part of this guide.
- 1.2 Tolerance: General Measures, Tolerances, and Conversions—General dimensional tolerances for this guide (unless otherwise noted) follow. These tolerances still apply to a dimension even when terms like greater than, less than, minimum, or maximum are used.

- 1.3 The values stated in inch-pound units are to be regarded as standard.
- 1.4 This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.
- 1.5 This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.

2. Referenced Documents

2.1 ASTM Standards:²

A184/A184M Specification for Welded Deformed Steel Bar Mats for Concrete Reinforcement

A185/A185M Specification for Steel Welded Wire Reinforcement, Plain, for Concrete (Withdrawn 2013)³ 2480-062017

A497/A497M Specification for Steel Welded Wire Reinforcement, Deformed, for Concrete (Withdrawn 2013)³

A615/A615M Specification for Deformed and Plain Carbon-Steel Bars for Concrete Reinforcement

A616/A616M Specification for Rail-Steel Deformed and Plain Bars for Concrete Reinforcement (Withdrawn 1999)³

A617/A617M Specification for Axle-Steel Deformed and Plain Bars for Concrete Reinforcement (Withdrawn 1999)³

C33 Specification for Concrete Aggregates

C94/C94M Specification for Ready-Mixed Concrete

C125 Terminology Relating to Concrete and Concrete Aggregates

C150 Specification for Portland Cement

C260 Specification for Air-Entraining Admixtures for Concrete

C494/C494M Specification for Chemical Admixtures for Concrete

C1116 Specification for Fiber-Reinforced Concrete and Shotcrete

C1141 Specification for Admixtures for Shotcrete


C1436 Specification for Materials for Shotcrete

¹ This guide is under the jurisdiction of ASTM Committee F08 on Sports Equipment, Playing Surfaces, and Facilities and is the direct responsibility of Subcommittee F08.66 on Sports Facilities.

Current edition approved July 1, 2012 April 1, 2017. Published August 2012 April 2017. Originally approved in 2006. Last previous edition approved in 2006 approved in 2006. Last previous edition approved in 2006 approved in 2006. Last previous edition approved in 2006 approved in 2006. Last previous edition approved in 2006.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ The last approved version of this historical standard is referenced on www.astm.org.



C1480 Specification for Packaged, Pre-Blended, Dry, Combined Materials for Use in Wet or Dry Shotcrete Application

C1582/C1582M Specification for Admixtures to Inhibit Chloride-Induced Corrosion of Reinforcing Steel in Concrete

E1155 Test Method for Determining F_F Floor Flatness and F_L Floor Levelness Numbers

2.2 ACI Standards:⁴

ACI 117-90 Specifications for Tolerances for Concrete Construction and Materials

ACI 302.1R-04 Guide for Concrete Floor and Slab Construction

ACI 309R Guide for Consolidation of Concrete

2.3 ANSI Standards:⁵

ANSI 2535.4 Product Safety Signs and Labels

3. Terminology

- 3.1 Definitions:
- 3.1.1 bowl—fully enclosed or partially enclosed free-flowing form with specific transitions.
- 3.1.2 *coping*—circular pipe or other material installed on some features.
- 3.1.3 extension—additional elevation of the top-riding surface within the platform area.
- 3.1.4 *features*—sections of the skate surface, which is level, inclined, or curved solid surface on which the user of skateboards, inline skates, and BMX bicycles can maneuver.
 - 3.1.5 *flat bottom*—horizontal part of the riding surface between the transitions.
 - 3.1.6 flat ground —flat, horizontal space, which is greater than 12 in. long.
- 3.1.7 *flatness*—degree to which a line or surface approximates a plane and is a measurement of local surface bumpiness/undulation.
 - 3.1.8 free falling height—perpendicular distance between the floor space and an adjacent low-lying space.
- 3.1.9 *in-ground concrete skatepark*—any concrete structure placed in ground that is to be used for skateboarding, inline skating, and BMX bicycles.
- 3.1.10 *levelness*—degree to which a line or surface parallels horizontal or design grade; and is a measurement of local conformance to design grade over a distance.
- 3.1.11 *performance edging*—durable material installed on the accessible edges or surfaces of intersecting and terminating planes on features for performance purposes.
- 3.1.12 *pool coping*—manufactured masonry product similar in shape and function to that typically manufactured for swimming pools. (See *coping* in 3.1.2.)
- 3.1.13 *protective edging*—durable material that protects accessible edges of intersecting and terminating planes on the riding surfaces for the purposes of reducing wear.
 - 3.1.14 *transition/radius*—radial change in slope between two elevations.
- 3.1.15 resting area—sport-functional clearance required for standing out of the flow of active skaters and clearing the active skating zone to avoid a collision.
 - 3.1.16 riding surface—part of skatepark structure on which the skater will be in contact.
- 3.1.17 *skatepark* —element, feature, structure, or group of elements, features, structures within a defined boundary for use by skateboarders, inline skaters, or BMX bikers.
- 3.1.18 *specified surface, plane, or line*—surface, plane, or line specified by the contract documents; specified planes and lines may slope and specified surfaces may have curvature.
- 3.1.19 *tolerance*—(1) the permitted variation from a given dimension or quantity; (2) the range of variation permitted in maintaining a specified dimension; and (3) A permitted variation from location or alignment.
 - 3.1.20 *vert*—vertical part of the riding surface.
- 3.1.21 *vertical alignment*—location relative to specified vertical plane or a specified vertical line or from a line or plane reference to a vertical line or plane. When applied to battered walls, abutments, or other nearly vertical surfaces, vertical alignment is defined as the horizontal location of the surface relative to the specified profile.

4. Materials

- 4.1 General—All materials used shall fulfill the sport-specific requirements for skatepark facilities.
- 4.2 Steel Elements—All exposed steel shall be inherently corrosion resistant or be provided with a corrosion resistant coating.

⁴ Available from American Concrete Institute (ACI), P.O. Box 9094, Farmington Hills, MI 48333-9094, http://www.aci-int.org.

⁵ Available from American National Standards Institute (ANSI), 25 W. 43rd St., 4th Floor, New York, NY 10036, http://www.ansi.org.