
International Standard



4036

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

Hexagon thin nuts — Product grade B (unchamfered)

Écrous bas hexagonaux — Classe de produit B (sans chanfrein)

First edition — 1979-06-01

Corrected and reprinted — 1984-11-15

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 4036:1979](#)

<https://standards.iteh.ai/catalog/standards/sist/e1daf80e-17dd-46a7-a048-12464751a1df/iso-4036-1979>

UDC 621.882.31

Ref. No. ISO 4036-1979 (E)

Descriptors : fasteners, nuts (fasteners), hexagonal nuts, specifications, dimensions, designation.

FOREWORD

ISO (the International Organization for Standardization) is a worldwide federation of national standards institutes (ISO member bodies). The work of developing International Standards is carried out through ISO technical committees. Every member body interested in a subject for which a technical committee has been set up has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council.

International Standard ISO 4036 was developed by Technical Committee ISO/TC 2, *Fasteners*, and was circulated to the member bodies in December 1977.

It has been approved by the member bodies of the following countries :

Australia	Hungary	ISO 4036:1979
Belgium	India	Norway
Canada	Ireland	Poland
Chile	Israel	Romania
Czechoslovakia	Italy	South Africa, Rep. of
Denmark	Korea, Rep. of	Spain
Egypt, Arab Rep. of	Mexico	Sweden
Finland	Netherlands	United Kingdom
Germany, F. R.	New Zealand	USA
		Yugoslavia

The member bodies of the following countries expressed disapproval of the document on technical grounds :

France
USSR

Hexagon thin nuts — Product grade B (unchamfered)

iTeh STANDARD PREVIEW (standards.iteh.ai)

0 INTRODUCTION

This International Standard is part of the complete ISO product standards series on hexagon drive fasteners. The series comprises :

- a) Hexagon head bolts (ISO 4014, ISO 4015 and ISO 4016)
 - b) Hexagon head screws (ISO 4017 and ISO 4018)
 - c) Hexagon nuts (ISO 4032, ISO 4033, ISO 4034, ISO 4035 and ISO 4036)
 - d) Hexagon flanged bolts
 - e) Hexagon flanged screws
 - f) Hexagon flanged nuts
 - g) Structural bolting
- } (in preparation)

1 SCOPE AND FIELD OF APPLICATION

This International Standard gives specifications for hexagon


thin nuts with metric dimensions and thread diameters from 1,6 up to and including 10 mm and product grade B.

If, in special cases, specifications other than those listed in this International Standard are required, they should be selected from existing International Standards, for example ISO 261, ISO 898, ISO 965, ISO 4759/1.

2 REFERENCES

- ISO 261, *ISO general purpose metric screw threads — general plan.*
- ISO 898, *Mechanical properties of fasteners.*
- ISO 965, *ISO general purpose metric screw threads — Tolerances.*
- ISO 4759/1, *Tolerances for fasteners — Part 1 : Bolts, screws and nuts with thread diameters $\geq 1,6 \leq 150$ mm and product grades A, B and C.*

3 DIMENSIONS



Dimensions in millimetres

Thread size <i>d</i>		M1,6	M2	M2,5	M3	(M3,5)	M4	M5	M6	M8	M10
<i>P</i>	1)	0,35	0,4	0,45	0,5	0,6	0,7	0,8	1	1,25	1,5
<i>e</i>	min.	3,28	4,18	5,31	5,87	6,44	7,50	8,63	10,89	14,20	17,59
<i>m</i>	max.	1	1,2	1,6	1,8	2	2,2	2,7	3,2	4	5
	min.	0,6	0,8	1,2	1,4	1,6	1,8	2,3	2,72	3,52	4,52
<i>s</i>	max.	3,2	4	5	5,5	6	7	8	10	13	16
	min.	2,9	3,7	4,7	5,2	5,7	6,64	7,64	9,64	12,57	15,57

1) *P* = pitch of the thread.

(standards.iteh.ai)

4 SPECIFICATIONS AND REFERENCE STANDARDS ISO 4036:1979

<https://standards.iteh.ai/catalog/standards/sist/e1daf80e-17dd-46a7-a048-11464751a1df/iso-4036-1979>

Material		Steel	Non-ferrous metal
Thread	Tolerance	6 H	
	International Standards	ISO 261, ISO 965	
Mechanical properties	Class (Hardness)	HV 110 min.	...
	International Standards		ISO ... ¹⁾
Tolerance	Product grade	B	
	International Standard	ISO 4759/1	
Finish		as processed	plain
		Requirements for electroplating are covered in ISO ... ¹⁾ . If different electroplating requirements are desired or if requirements are needed for other finishes, they should be negotiated between customer and supplier.	
Acceptability		For acceptance procedure see ISO ... ¹⁾ .	

1) In preparation.

5 DESIGNATION

Example for the designation of a hexagon thin nut with metric thread *d* = M6 made from steel with HV 110 min. (st) :

Hexagon nut ISO4036 M6-st

ANNEX

This annex is included for explanatory and informative purposes only and is not to be considered as part of this International Standard.

This International Standard incorporates some changes, primarily in width across flats, from the previous metric practice in a number of countries. These changes were made to achieve international agreement and to improve product design and utilization of material.

At its meeting in May 1977, ISO/TC 2 studied several technical reports analysing design considerations influencing determination of the best series of widths across flats for hexagon bolts, screws and nuts. A primary technical objective was to achieve a logical ratio between underhead bearing surface area (which determines the

magnitude of the compressive stress on the bolted members) and the tensile stress area of the screw thread (which governs the clamping force which can be developed by tightening the fastener).

Table 1 lists the ratios for the sizes selected by ISO/TC 2 to be ISO standard (bold type) and in addition two sizes type) which currently are being produced and used in substantial quantities in many countries of the world.

The two sizes (widths across flats of 15 and 17 mm for M10) will be phased out of production and use. During a transitional period, to assist designers and manufacturers, and in particular to give needed information for maintenance and repair requirements, the dimensions of these sizes are given in table 2.

TABLE 1

Nominal thread diameter mm	Width across flats mm	Annular bearing area
		Thread stress area *
5	8	1,08
6	10	1,44
8	13	1,23
10	15	0,90
	16	1,30
	17	1,73

TABLE 2

Thread size <i>d</i>	M10	
<i>P</i> 1)	1,5	
<i>e</i> min.	16,46	18,73
max.	5	5
<i>m</i> min.	4,52	4,52
max.	15	17
<i>s</i> min.	14,57	16,57

* Calculation based on clearance holes ISO 273 (revised), medium series.

ISO 4036:1979
<https://standards.iteh.ai/catalog/standards/sist/1e1daf80e-17dd-46a7-3d18-12464751a1df/iso-4036-1979>
 1) *P* = pitch of the thread.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

This page intentionally left blank

[ISO 4036:1979](#)

<https://standards.iteh.ai/catalog/standards/sist/e1daf80e-17dd-46a7-a048-12464751a1df/iso-4036-1979>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

This page intentionally left blank

[ISO 4036:1979](#)

<https://standards.iteh.ai/catalog/standards/sist/e1daf80e-17dd-46a7-a048-12464751a1df/iso-4036-1979>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

This page intentionally left blank

[ISO 4036:1979](#)

<https://standards.iteh.ai/catalog/standards/sist/e1daf80e-17dd-46a7-a048-12464751a1df/iso-4036-1979>