

Designation: D6367 - 17

Standard Specification for AMS $(\alpha$ -Methylstyrene)¹

This standard is issued under the fixed designation D6367; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

- 1.1 This specification covers AMS (α-Methylstyrene).
- 1.2 The following applies to all limits in this specification: for purposes of determining conformance with this specification, an observed value or a calculated value shall be rounded off "to the nearest unit" in the last right-hand digit used in expressing the specification limit, in accordance with the rounding-off method of Practice E29.
- 1.3 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.
- 1.4 Consult current OSHA regulations, suppliers' Safety Data Sheets, and local regulations for all materials used in this specification.
- 1.5 This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.

- D3160 Test Method for Phenol Content of Cumene (Isopropylbenzene) or AMS (α–Methylstyrene)
- D3437 Practice for Sampling and Handling Liquid Cyclic Products
- D4590 Test Method for Colorimetric Determination of *p-tert*-Butylcatechol In Styrene Monomer or AMS (α–Methylstyrene) by Spectrophotometry
- D5386 Test Method for Color of Liquids Using Tristimulus Colorimetry
- D6144 Test Method for Analysis of AMS (α-Methylstyrene) by Capillary Gas Chromatography
- D7977 Test Methods for Polymer Content of AMS (α-Methylstyrene)
- D8005 Test Method for Color of Clear Liquids (Platinum-Cobalt Scale)
- E29 Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications
- E2680 Test Method for Appearance of Clear, Transparent Liquids (Visual Inspection Procedure)
- 2.2 Other Documents:
- OSHA Regulations 29 CFR paragraphs 1910.1000 and 1910.1200³

2. Referenced Documents catalog/standards/sist/2d8

2.1 ASTM Standards:²

3. Properties

3.1 AMS shall conform to the requirements shown in Table 1.

4. Sampling

4.1 Sample the material in accordance with Practice D3437.

¹ This specification is under the jurisdiction of ASTM Committee D16 on Aromatic, Industrial, Specialty and Related Chemicals and is the direct responsibility of Subcommittee D16.07 on Styrene, Ethylbenzene and C9 and C10 Aromatic Hydrocarbons.

Current edition approved June 1, 2017. Published June 2017. Originally approved in 1999. Last previous edition approved in 2016 as D6367 – 16. DOI: 10.1520/D6367-17.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ Available from U.S. Government Printing Office Superintendent of Documents, 732 N. Capitol St., NW, Mail Stop: SDE, Washington, DC 20401, http://www.access.gpo.gov.