



Designation: D1265 – 11 (Reapproved 2017)^{ε1}

Standard Practice for Sampling Liquefied Petroleum (LP) Gases, Manual Method¹

This standard is issued under the fixed designation D1265; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

^{ε1} NOTE—SI units formatting was corrected editorially in July 2017.

1. Scope

1.1 This practice covers equipment and procedures for obtaining a representative sample of specification Liquefied Petroleum Gas (LPG), such as specified in Specification **D1835**, GPA 2140, and comparable international standards.

1.2 This practice is suitable for obtaining representative samples for all routine tests for LP gases required by Specification **D1835**. In the event of a dispute involving sample integrity when sampling for testing against Specification **D1835** requirements, Practice **D3700** shall be used as the referee sampling procedure.

1.3 This practice may also be used for other Natural Gas Liquid (NGL) products that are normally single phase (NGL mix, field butane, etc.), defined in other industry specifications or contractual agreements. It is not intended for non-specification products that contain significant quantities of undissolved gases (N₂, CO₂), free water or other separated phases, such as raw or unprocessed gas/liquids mixtures and related materials. The same equipment can be used for these purposes, but additional precautions are generally needed to obtain representative samples of multiphase products (see Appendix X1 on Sampling Guidelines in Practice **D3700**).

NOTE 1—Practice **D3700** describes a recommended practice for obtaining a representative sample of a light hydrocarbon fluid and the subsequent preparation of that sample for laboratory analysis when dissolved gases are present. Use of Practice D1265 will result in a small but predictable low bias for dissolved gases due to the liquid venting procedure to establish the 20 % minimum ullage.

1.4 This practice includes recommendations for the location of a sample point in a line or vessel. It is the responsibility of the user to ensure that the sampling point is located so as to obtain a representative sample.

1.5 The values stated in SI units are to be regarded as standard.

1.5.1 *Exception*—Non-SI units are shown in parentheses for information only.

1.6 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

1.7 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 *ASTM Standards:*²

D1835 Specification for Liquefied Petroleum (LP) Gases
D3700 Practice for Obtaining LPG Samples Using a Floating Piston Cylinder

2.2 *Other Regulations:*

Canadian Transportation of Dangerous Goods Regulations³
GPA 2140 Gas Processors Association Liquefied Petroleum Gas Specifications & Test Methods⁴
IATA Transportation of Dangerous Goods by Air⁵
U.S. CFR 49 Transportation⁶

3. Terminology

3.1 *Definitions:*

3.1.1 *high pressure sample cylinder, n*—a container used for storage and transportation of a sample obtained at pressures above atmospheric pressure.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ Available from the Canadian General Standards Board, Sales Centre, Gatineau, Canada K1A 1G6, <http://www.ongc-cgsb.gc.ca/>.

⁴ Available from Gas Processors Association (GPA), 6526 E. 60th St., Tulsa, OK 74145, <http://www.gpaglobal.org>.

⁵ Available from IATA Customer Care, 800 Place Victoria, PO Box 113, Montréal, Quebec H4Z 1M1. www.iata.org.

⁶ Available from U.S. Government Printing Office Superintendent of Documents, 732 N. Capitol St., NW, Mail Stop: SDE, Washington, DC 20401, <http://www.access.gpo.gov>.

¹ This practice is under the jurisdiction of ASTM Committee **D02** on Petroleum Products, Liquid Fuels, and Lubricants and is the direct responsibility of Subcommittee **D02.H0** on Liquefied Petroleum Gas.

Current edition approved May 1, 2017. Published July 2017. Originally approved in 1953. Last previous edition approved in 2011 as D1265 – 11. DOI: 10.1520/D1265-11R17E01.

3.1.2 *maximum fill density (reduced fill density)*, n —the volume of a container occupied by the sample.

3.1.2.1 *Discussion*—Maximum fill density is usually expressed as a percentage of the total capacity.

4. Summary of Practice

4.1 A liquid sample of LPG is transferred from the source into a sample container by purging the container and filling it with liquid, then providing a minimum 20 % outage by venting liquid, so that 80 % or less of the liquid volume remains.

5. Significance and Use

5.1 Samples of liquefied petroleum gases are examined by various test methods to determine physical and chemical characteristics and conformance with specifications.

5.2 Equipment described by this practice may be suitable for transportation of LPG samples, subject to applicable transportation regulations.

6. General Information

6.1 Considerable effort is required to obtain a representative sample, especially if the material being sampled is a mixture of liquefied petroleum gases. Consider the following factors:

6.1.1 Obtain samples of the liquid phase only.

6.1.2 When it is definitely known that the material being sampled is composed predominantly of only one liquefied petroleum gas, a liquid sample may be taken from any part of the vessel.

6.1.3 When the material being sampled has been mixed or circulated until it is homogeneous, a liquid sample may be taken from any part of the vessel.

6.1.4 Because of wide variation in the construction details of containers for liquefied petroleum gases, it is difficult to specify a uniform method for obtaining representative samples of heterogeneous mixtures. If it is not practicable to homogenize a mixture to ensure uniformity, obtain liquid samples by a procedure which has been agreed upon by the contracting parties.

6.1.5 Directions for sampling cannot be made explicit enough to cover all cases. They must be supplemented by judgment, skill and sampling experience. Extreme care and good judgment are necessary to ensure samples which represent the general character and average condition of the material. Because of the hazards involved, liquefied petroleum gases should be sampled by, or under the supervision of, persons familiar with the necessary safety precautions.

NOTE 2—Samples to be tested for presence of corrosive compounds or sulfur compounds should be taken in inert containers equipped with stainless steel valves; otherwise, determinations of mercaptans and hydrogen sulfide, for example, can be misleading. Internal surfaces of sample containers and associated lines and fittings may be surface coated to reduce bare metal surfaces reacting with trace reactive components.

6.1.6 Control hydrocarbon vapors vented during sampling to ensure compliance with applicable safety and environmental regulations.

7. Apparatus

7.1 *High Pressure Sample Cylinder*—Use corrosion resistant metal sample containers certified by the authority having

jurisdiction for pressure vessels with adequate pressure rating for the product being sampled. Suitable materials include stainless steel, Monel, and possibly other materials. Protective internal coatings or surface treatments to render the internal surface inert are acceptable. The size of the container depends upon the amount of sample required for the laboratory tests to be made. If the container is to be transported, it shall also conform to specifications published in transportation legislation such as U.S. CFR 49 or Canadian Transportation of Dangerous Goods Regulations, and their supplements, issuances, or similar regulations in other jurisdictions.

NOTE 3—It has been common practice to refer to LPG sample containers as “sample bombs.” Use of this term is discouraged because of obvious misunderstanding by many people. Alternate names such as “pressurized sample container” or “high pressure sample cylinder” are recommended.

NOTE 4—DOT 3E cylinders are exempt from requalification in some jurisdictions. Other cylinders may need to be requalified according to local regulations.

7.1.1 The sample container should be fitted with an internal outage (ullage) tube to permit release of a minimum 20 % of the container capacity as a liquid. The end of the container fitted with the outage (ullage) tube shall be clearly marked. Typical sample containers are shown in [Figs. 1 and 2](#).

7.1.2 Sample containers without an internal outage (ullage) tubes are acceptable. Alternative purging and venting procedures to obtain a minimum 20 % ullage in the container, as described in [11.2.1](#), are required.

7.1.3 Verify the high pressure sample cylinder and associated valving for gas tightness by leak testing at a minimum of 3450 kPa (500 psig) with inert gas prior to first use, whenever pressure-containing components of the assembly are replaced, or otherwise on an annual basis.

7.2 *Sample Transfer Line* made of stainless steel tubing or other flexible metal hose, impervious to the product being sampled, is required. The most satisfactory line is one equipped with two valves on the sample-container end, [Fig. 1](#), a sampling valve, *A*, and a vent valve, *B*.

PROCEDURE

8. Purging Sample Transfer Line

8.1 Connect the ends of the sample transfer line securely to the product source and to Valve *C* (inlet) ([Fig. 1](#)) of the container. Close Valve *A* (sampling), Valve *B* (vent), and Valve *C* (inlet). Open the valve at the product source and purge the transfer line by opening Valve *A* (sampling) and Valve *B* (vent).

9. Purging the Sample Container

9.1 If the history of the sample container contents is not known, or if traces of the previous product could affect the analysis to be carried out, or both, use one of the following two purge procedures:

9.1.1 Ensure that Valve *C* ([Fig. 2](#)) and Valve *D* on the high pressure sample cylinder are closed. Connect a sample transfer line (with closed Valves *A* and *B*) to the cylinder at Valve *D* and to the sample source. Maintain the cylinder in an upright position such that Valve *C* is at the top.