



Designation: **C1475 – 05 (Reapproved 2010)<sup>ε1</sup> C1475 – 17**

## Standard Guide for Determination of Neptunium-237 in Soil<sup>1</sup>

This standard is issued under the fixed designation C1475; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

---

<sup>ε1</sup> NOTE—Editorial changes were made throughout in June 2010.

---

### 1. Scope

1.1 This guide covers the determination of neptunium-237 in soil by means of radiochemical separations and alpha spectrometry. This guide provides options in the selection of sample preparation, separation, and measurement. Although neptunium-237 is not a component of global fallout, it is a product of production reactors and spent fuel processing. This guide is designed for analysis of ten grams of soil previously collected and treated in accordance with Practices C998 and C999. Larger-size samples of environmental soil may also be analyzed, as long as the concentrations of interferences such as uranium and thorium are at or near environmental concentrations. Depending on the choice of a sample dissolution method, all chemical forms of neptunium may not be completely solubilized. This guide should allow the determination of neptunium-237 concentrations from sub becquerel per gram levels to applicable standards depending on count time, sample size, detector efficiency, background, and tracer yield.

1.2 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.* Specific precautionary statements are given in Section 89.

1.4 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

### 2. Referenced Documents

#### 2.1 ASTM Standards:<sup>2</sup>

- C859 Terminology Relating to Nuclear Materials
- C998 Practice for Sampling Surface Soil for Radionuclides
- C999 Practice for Soil Sample Preparation for the Determination of Radionuclides
- C1000 Test Method for Radiochemical Determination of Uranium Isotopes in Soil by Alpha Spectrometry
- C1001 Test Method for Radiochemical Determination of Plutonium in Soil by Alpha Spectroscopy
- C1163 Practice for Mounting Actinides for Alpha Spectrometry Using Neodymium Fluoride
- C1284 Practice for Electrodeposition of the Actinides for Alpha Spectrometry
- C1317 Practice for Dissolution of Silicate or Acid-Resistant Matrix Samples (Withdrawn 2001)<sup>3</sup>
- C1342 Practice for Flux Fusion Sample Dissolution (Withdrawn 2001)<sup>3</sup>
- C1387 Guide for the Determination of Technetium-99 in Soil
- C1412 Practice for Microwave Oven Dissolution of Glass Containing Radioactive and Mixed Wastes (Withdrawn 2001)<sup>3</sup>
- D1193 Specification for Reagent Water
- D1890 Test Method for Beta Particle Radioactivity of Water
- D3084 Practice for Alpha-Particle Spectrometry of Water
- D4962 Practice for NaI(Tl) Gamma-Ray Spectrometry of Water

<sup>1</sup> This guide is under the jurisdiction of ASTM Committee C26 on Nuclear Fuel Cycle and is the direct responsibility of Subcommittee C26.05 on Methods of Test. Current edition approved June 1, 2010/June 1, 2017. Published June 2010/July 2017. Originally approved in 2000. Last previous edition approved in 2005/2010 as C1475 – 05-C1475 – 05 (2010)<sup>ε1</sup>. DOI: 10.1520/C1475-05R10E01-10.1520/C1475-17.

<sup>2</sup> For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

<sup>3</sup> The last approved version of this historical standard is referenced on www.astm.org.

## 2.2 Other Documents:

[IEEE/ASTM SI-10 Standard for the Use of the International System of Units \(SI\): The Modern Metric System](#)

## 3. Terminology

3.1 Except as otherwise defined herein, definitions of terms are as given in Terminology [C859](#).

## 4. Summary of Guide

4.1 This guide may be used to determine neptunium-237 in soil at potential release sites. A neptunium-239 yield monitor is added to the soil aliquot and the sample solubilized by one of several methods, such as those described in Guide [C1387](#). The neptunium is separated from the resulting solution using an extraction chromatography column. A valence adjustment is performed prior to loading the sample onto the conditioned chromatography column. The sample is passed through the column, which retains the neptunium in the +4 oxidation state. The column is washed to remove interferences and selectively eluted with dilute acid. The samples are prepared for measurement by neodymium fluoride co-precipitation or electrodeposition, and the neptunium-237 content determined by alpha spectrometry. The neptunium-239 yield monitor is determined by beta or gamma-ray counting.

## 5. Significance and Use

5.1 A soil sampling and analysis program provides a direct means of determining the concentration and distribution of radionuclides in soil. The presence and extent of neptunium-237 is of particular interest because it is one of the more mobile transuranics in terms of migration and plant uptake. Since soil is an integrator and a reservoir on long-lived radionuclides, and serves as an intermediary in several pathways of potential importance to humans, knowledge of the concentration of neptunium-237 in soil is essential.

## 6. Interferences

6.1 Phosphates present in the sample matrix will interfere with the separation chemistry. Aluminum nitrate may be added to the load solution to minimize this problem.

6.2 High concentrations of uranium or thorium can overload the column, resulting in low recoveries of neptunium or spectral interferences. A preliminary separation may be required to avoid spectral interference from uranium, see Test Method [C1000](#). The presence of uranium-233 and uranium-234 could cause spectral interferences with the neptunium-237 determination.

## 7. Apparatus

7.1 Apparatus for the sample dissolution and measurement are identified within the selected test method.

7.2 *Extraction Columns*, with a bed volume of several millilitres for the extraction chromatography resin.<sup>4</sup>

## 8. Reagents

8.1 *Purity of Reagents*—Reagent grade chemicals shall be used in all tests. Unless otherwise indicated, it is intended that all reagents shall conform to the specifications of the Committee on Analytical Reagents of the American Chemical Society where such specifications are available.<sup>5</sup> Other grades may be used, provided it is first ascertained that the reagent is of sufficiently high purity to permit its use without lessening the accuracy of the determination.

8.2 *Purity of Water*—Unless otherwise indicated, references to water shall be understood to mean reagent water as defined in Specification [D1193](#).

8.3 *Aluminum Nitrate Hydrate* [Al(NO<sub>3</sub>)<sub>3</sub>·9H<sub>2</sub>O].

8.4 *Aliphatic Quaternary Amine Extraction Chromatography Resin*.<sup>4</sup>

8.5 *Ferrous Sulfamate* [Fe(SO<sub>3</sub>NH<sub>2</sub>)<sub>2</sub>], 1.0M—Dissolve 38.8 g of sulfamic acid (NH<sub>2</sub>SO<sub>3</sub>H) and 11.6 g of iron powder in approximately 150 mL of water. Stir while heating until dissolved and then dilute to 200 mL with water. Prepare fresh each week or keep under a nitrogen blanket to minimize oxidation.

8.6 *Hydrofluoric Acid* (48 to 51 %)—Concentrated hydrofluoric acid (HF).

8.7 *Iron Powder*.

8.8 *Nitric Acid* (sp gr 1.42)—Concentrated nitric acid (HNO<sub>3</sub>).

8.9 *Nitric Acid*, 3.0M—Add 189 mL of concentrated nitric acid to 400 mL of water and dilute to 1.0 L with water and mix.

<sup>4</sup> Prepacked columns of TEVA Resin from Eichrom Technologies, Inc., Lisle, IL, have been found to be satisfactory for this purpose.

<sup>5</sup> *Reagent Chemicals, American Chemical Society Specifications*, American Chemical Society, Washington, DC. For suggestions on the testing of reagents not listed by the American Chemical Society, see *Analar Standards for Laboratory Chemicals*, BDH Ltd., Poole, Dorset, U.K., and the *United States Pharmacopeia and National Formulary*, U.S. Pharmacopeial Convention, Inc. (USPC), Rockville, MD.