



Designation: **D8076—17 D8076 – 17a**

# Standard Specification for 100 Research Octane Number Test Fuel for Automotive Spark-Ignition Engines<sup>1</sup>

This standard is issued under the fixed designation D8076; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

## 1. Scope—Scope\*

1.1 This specification covers the requirements of a high octane number test fuel suitable for spark-ignition engines to be utilized in ground vehicles that will require 100 research octane number (RON) minimum rated fuel.

1.1.1 The fuels described by this specification are intended for developing technologies that lead to reduced vehicle energy consumption, such as higher compression ratio, higher power density, increased turbocharger boost pressure, smaller swept displacement volume, and operation at lower engine speeds.

1.1.2 The fuels described in this test fuel specification may ~~or may not~~ meet all of the performance or regulatory requirements for use in vehicles using commercial gasoline.

1.2 The fuels covered in this specification may contain oxygenates, such as alcohols and ethers, at up to 50 % by volume. This specification covers fuels that may contain both fossil and bio-derived components.

1.2.1 Fuels containing methanol are not included in this specification.

1.3 This specification provides a description of high RON test fuel for automotive spark-ignition engines that are not currently in the marketplace but are being developed and require a defined standard test fuel. The high RON fuel could become available in the marketplace if/when such engines are introduced in commerce. The specification is under continuous review, which can result in revisions based on changes in fuel, automotive requirements, or test methods, or a combination thereof. All users of this specification, therefore, should refer to the latest edition.

NOTE 1—If there is any doubt as to the latest edition of Specification D8076, contact ASTM International Headquarters.

1.4 The values stated in SI units are the standard.

1.4.1 *Exception*—Non-SI values are provided for information only. U.S. federal regulations frequently specify non-SI units.

1.5 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.6 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

## 2. Referenced Documents

2.1 *ASTM Standards:*<sup>2</sup>

[D86 Test Method for Distillation of Petroleum Products and Liquid Fuels at Atmospheric Pressure](#)

[D130 Test Method for Corrosiveness to Copper from Petroleum Products by Copper Strip Test](#)

[D381 Test Method for Gum Content in Fuels by Jet Evaporation](#)

[D525 Test Method for Oxidation Stability of Gasoline \(Induction Period Method\)](#)

[D1266 Test Method for Sulfur in Petroleum Products \(Lamp Method\)](#)

[D2622 Test Method for Sulfur in Petroleum Products by Wavelength Dispersive X-ray Fluorescence Spectrometry](#)

[D2699 Test Method for Research Octane Number of Spark-Ignition Engine Fuel](#)

<sup>1</sup> This specification is under the jurisdiction of ASTM Committee D02 on Petroleum Products, Liquid Fuels, and Lubricants and is the direct responsibility of Subcommittee D02.A0.01 on Gasoline and Gasoline-Oxygenate Blends.

Current edition approved ~~March 1, 2017~~ Aug. 1, 2017. Published ~~March 2017~~ August 2017. Originally approved in 2017. Last previous edition approved in 2017 as D8076 – 17. DOI: ~~10.1520/D8076-17~~ 10.1520/D8076-17A.

<sup>2</sup> For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

\*A Summary of Changes section appears at the end of this standard

- D2700 Test Method for Motor Octane Number of Spark-Ignition Engine Fuel
- D3120 Test Method for Trace Quantities of Sulfur in Light Liquid Petroleum Hydrocarbons by Oxidative Microcoulometry
- D3237 Test Method for Lead in Gasoline by Atomic Absorption Spectroscopy
- D3831 Test Method for Manganese in Gasoline By Atomic Absorption Spectroscopy
- D4057 Practice for Manual Sampling of Petroleum and Petroleum Products
- D4175 Terminology Relating to Petroleum Products, Liquid Fuels, and Lubricants
- D4176 Test Method for Free Water and Particulate Contamination in Distillate Fuels (Visual Inspection Procedures)
- D4177 Practice for Automatic Sampling of Petroleum and Petroleum Products
- D4306 Practice for Aviation Fuel Sample Containers for Tests Affected by Trace Contamination
- D4806 Specification for Denatured Fuel Ethanol for Blending with Gasolines for Use as Automotive Spark-Ignition Engine Fuel
- D4814 Specification for Automotive Spark-Ignition Engine Fuel
- D4815 Test Method for Determination of MTBE, ETBE, TAME, DIPE, tertiary-Amyl Alcohol and C<sub>1</sub> to C<sub>4</sub> Alcohols in Gasoline by Gas Chromatography
- D4953 Test Method for Vapor Pressure of Gasoline and Gasoline-Oxygenate Blends (Dry Method)
- D5059 Test Methods for Lead in Gasoline by X-Ray Spectroscopy
- D5191 Test Method for Vapor Pressure of Petroleum Products (Mini Method)
- D5453 Test Method for Determination of Total Sulfur in Light Hydrocarbons, Spark Ignition Engine Fuel, Diesel Engine Fuel, and Engine Oil by Ultraviolet Fluorescence
- D5482 Test Method for Vapor Pressure of Petroleum Products (Mini Method—Atmospheric)
- D5599 Test Method for Determination of Oxygenates in Gasoline by Gas Chromatography and Oxygen Selective Flame Ionization Detection
- D5842 Practice for Sampling and Handling of Fuels for Volatility Measurement
- D5845 Test Method for Determination of MTBE, ETBE, TAME, DIPE, Methanol, Ethanol and *tert*-Butanol in Gasoline by Infrared Spectroscopy
- D5854 Practice for Mixing and Handling of Liquid Samples of Petroleum and Petroleum Products
- D5983 Specification for Methyl Tertiary-Butyl Ether (MTBE) for Downstream Blending for Use in Automotive Spark-Ignition Engine Fuel
- D6378 Test Method for Determination of Vapor Pressure (VP<sub>x</sub>) of Petroleum Products, Hydrocarbons, and Hydrocarbon-Oxygenate Mixtures (Triple Expansion Method)
- D6920 Test Method for Total Sulfur in Naphthas, Distillates, Reformulated Gasolines, Diesels, Biodiesels, and Motor Fuels by Oxidative Combustion and Electrochemical Detection
- D7039 Test Method for Sulfur in Gasoline, Diesel Fuel, Jet Fuel, Kerosine, Biodiesel, Biodiesel Blends, and Gasoline-Ethanol Blends by Monochromatic Wavelength Dispersive X-ray Fluorescence Spectrometry
- D7220 Test Method for Sulfur in Automotive, Heating, and Jet Fuels by Monochromatic Energy Dispersive X-ray Fluorescence Spectrometry
- D7319 Test Method for Determination of Existent and Potential Sulfate and Inorganic Chloride in Fuel Ethanol and Butanol by Direct Injection Suppressed Ion Chromatography
- D7328 Test Method for Determination of Existent and Potential Inorganic Sulfate and Total Inorganic Chloride in Fuel Ethanol by Ion Chromatography Using Aqueous Sample Injection
- D7667 Test Method for Determination of Corrosiveness to Silver by Automotive Spark-Ignition Engine Fuel—Thin Silver Strip Method
- D7671 Test Method for Corrosiveness to Silver by Automotive Spark-Ignition Engine Fuel—Silver Strip Method
- D7862 Specification for Butanol for Blending with Gasoline for Use as Automotive Spark-Ignition Engine Fuel
- E29 Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications

## 2.2 Government Regulations:

CFR Title 40 Protection of Environment<sup>3</sup>

CCR Title 17—Public Health—Section 60100–60114 Description of California Air Basins<sup>4</sup>

## 2.3 Technical Report:

CRC Report No. 660 Fuel Antiknock Quality—Engine Response to RON Versus MON Scoping Tests, Final Report, May 2011<sup>5</sup>

## 3. Terminology

3.1 For general terminology, refer to Terminology D4175.

3.2 *Definitions:*

<sup>3</sup> Available from U.S. Government Printing Office, Superintendent of Documents, 732 N. Capitol St., NW, Mail Stop: SDE, Washington, DC 20401.

<sup>4</sup> Available from Barclays, 50 California Street, San Francisco, CA 94111.

<sup>5</sup> Available from Coordinating Research Council, 5755 North Point Parkway, Suite 265, Alpharetta, GA 30022, <http://www.crao.org>.

3.2.1 *finished fuel, dry vapor pressure equivalent (DVPE), n*—a homogeneous mixture of blendstocks and fuel additives meeting all specification and regulatory requirements for its intended use at value calculated by a defined correlation equation that is expected to be comparable to the vapor pressure value obtained by Test Method **D4953** the location where sold., Procedure A. **D4814****D4953**

3.2.2 *gasoline, n*—a volatile mixture of liquid hydrocarbons, generally containing small amounts of additives, suitable for use as a fuel in spark-ignition, internal combustion engines. **D4814**

3.2.3 *gasoline-oxygenate blend, n*—a fuel consisting primarily of gasoline along with a substantial amount (more than 0.35 % by mass oxygen) of one or more oxygenates. **D4814**

3.2.4 *octane sensitivity (S), n*—the mathematical difference between RON and MON ( $S = RON - MON$ ).

3.2.5 *oxygenate, n*—an oxygen-containing, ashless, organic compound, such as an alcohol or ether, which can be used as a fuel or fuel supplement. **D4814**

#### 4. Ordering Information

- 4.1 The volatility of the fuel shall be agreed upon between buyer and seller.
- 4.2 State the concentration and types of oxygenates present as agreed upon between buyer and seller.

#### 5. Performance Requirements for High Octane Number Test Fuel

5.1 High octane number test fuel shall conform to the requirements of **Table 1**, and meet the volatility requirements of **Table 2**. The significance of each of the properties of this specification is shown in **Appendix X1**.

5.1.1 The user is advised to review applicable national, state, provincial, or local fuel requirements.

5.1.1.1 In the United States there may be additional Clean Air Act requirements that must be fulfilled prior to introduction of the high octane number fuel into commerce. See **Appendix X3** in Specification **D4814** for information on U.S. Environmental Protection Agency (EPA) regulations for spark-ignition engine fuels.

5.1.2 The following applies to all specified limits in this specification: For purposes of determining conformance with these specifications, an observed value or a calculated value shall be rounded to the nearest unit in the right-most significant digit used in expressing the specification limit, in accordance with the rounding method of Practice **E29**. For a specification limit expressed as an integer, a trailing zero is significant only if the decimal point is specified. For a specified limit expressed as an integer, and the right-most digit is non-zero, the right-most digit is significant without a decimal point being specified. This convention applies to specified limits in **Tables 1 and 2**.

5.2 RON and octane sensitivity are critical performance parameters for the fuels described in this specification. Engine knock and laboratory octane number are described in **X1.2** and **X1.3**, respectively.

5.2.1 For engines with increased compression ratio, higher boost pressure, operating at slower speeds, and smaller swept displacement volume, a high RON, combined with high octane sensitivity, are well correlated with knock resistance.

5.2.2 Octane sensitivity is the mathematical difference between the research and motor octane numbers and is considered a measure of the autoignition temperature sensitivity of a fuel. In high compression ratio, highly boosted engines operating at low engine speeds, if RON is held constant, a fuel with greater octane sensitivity (all other factors being equal) will provide greater knock resistance.

5.2.2 A minimum motor octane number (MON) is required to ensure antiknock performance for all engines at high ambient temperature and certain other conditions (see CRC Report No. 660).

**TABLE 1 High Octane Number Test Fuel Specifications<sup>A</sup>**

Property	Limit	ASTM Test Method
Research octane number, min	100.	<b>D2699</b>
Motor octane number, min	86	<b>D2700</b>
Sensitivity, min	8	<b>D2699, D2700</b>
Inorganic chloride, mg/kg, max	1	<b>D7319</b> or <b>D7328</b> as modified in 7.1.12
Lead content, g/L (g/U.S. gal), max	0.013 (0.05)	<b>D3237</b> or <b>D5059</b>
Sulfur, mg/kg, max	10	<b>D1266, D2622, D3120, D5453, D6920, or D7039</b>
Manganese content, mg/L (mg/U.S. gal), max <sup>B</sup>	See <b>6.3</b>	<b>D3831</b>
Manganese content, mg/L, max <sup>B</sup>	0.25 <sup>C</sup>	<b>D3831</b>
Copper strip corrosion, max	No. 1	<b>D130</b>
Silver strip corrosion, max	No. 1	<b>D7667</b> or <b>D7671</b>
Solvent-washed gum content, mg/100 mL, max	5	<b>D381</b>
Oxidation stability, minutes, min	240.	<b>D525</b>

<sup>A</sup> See **5.1.2** for determining conformance with numerical specification limits in this table.

<sup>B</sup> See **Appendix X2** for information on U.S. EPA and California Air Resources Board regulations for manganese in gasoline.

<sup>C</sup> This level represents the lower limit of the Test Method **D3831** scope.

**TABLE 2 Vapor Pressure and Distillation Requirements<sup>A</sup>**

Property	Vapor Pressure/ Distillation	ASTM Test Methods
Vapor pressure, at 37.8 °C (100 °F), kPa (psi), max	62 (9.0)	<b>D4953, D5191, D5482, or D6378</b>
Distillation temperatures, °C (°F), at % evaporated and 101.3 kPa pressure (760 mm Hg)		
10 % by volume, max	70. (158)	
50 % by volume min	66 (150.)	<b>D86</b>
max	121 (250.)	
90 % by volume, max	190. (374)	
End point, max	225 (437)	
Distillation residue, % by volume, max	2	<b>D86</b>

<sup>A</sup> See 5.1.2 for determining conformance with numerical specification limits in this table.

5.3 Volatility requirements for the high octane number test fuel are specified in Table 2. Different limits on dry vapor pressure equivalent (DVPE), T50, and other volatility parameters may be agreed upon between buyer and seller. For guidance on volatility requirements for specific climatic conditions, consult section 5.2.1 of Specification D4814.

#### 5.4 Oxygenate Blendstock Requirements:

5.4.1 Denatured fuel ethanol used in blending high octane number fuel shall conform to the requirements of Specification D4806.

5.4.2 Butanol used in blending high octane number fuel shall conform to the requirements of Specification D7862.

5.4.3 Methyl *tert*-butyl ether (MTBE) used in blending high octane number fuel shall conform to the requirements of Specification D5983.

5.5 Deposit control additives are added to spark-ignition engine fuel to help keep fuel injectors and intake valves clean.

5.5.1 In the United States, deposit control additives used in gasoline are required to be certified by the EPA. As this specification is for a test fuel, requirements for deposit control additives have not been determined.

## 6. Workmanship

6.1 The ~~finished test~~ fuel shall be visually free of undissolved water, sediment, and suspended matter; it shall be clear and bright at the fuel temperature at the point of custody transfer or at a lower temperature agreed upon by the purchaser and seller.

NOTE 2—Test Method D4176 can be helpful for evaluating the product.

6.1.1 ~~Avoiding Water Haze and Phase Separation—Finished~~ The test fuel should not contain a separate water or water-alcohol phase at the time it is introduced into a vehicle or equipment fuel tank or under the conditions the fuel is used. Water that is dissolved in fuel at the point of use does not generally cause engine problems. However, if excess water is present in spark-ignition fuel, a separate phase, either ‘free water’ or a water-alcohol mixture, can form. Either condition can lead to engine damage, engine failing to start, or failing to operate properly. A separated water-rich phase can be observed as a haze, as water droplets, or as a distinct lower layer. This lower aqueous phase can be corrosive to many metals and the engine cannot operate on it. Similarly, the upper hydrocarbon phase may no longer meet volatility and antiknock properties.

6.2 The ~~finished test~~ fuel shall also be free of any adulterant or contaminant that can render the fuel unacceptable for its commonly used applications.

6.3 ~~Vehicles to be developed using this test fuel are anticipated to meet U.S. Tier 2, Euro 5, or more stringent emissions standards, therefore methylecyclopentadienyl manganese tricarbonyl (MMT) is limited to a maximum concentration of 0.25 mg Mn/L, until such time as data are produced to support its use at higher concentrations.~~

## 7. Test Methods

7.1 The requirements of this specification shall be determined in accordance with the methods listed below. The scopes of some of the test methods listed below do not include gasoline-ethanol blends or other gasoline-oxygenate blends. Refer to the listed test methods to determine applicability or required modifications for use with gasoline-oxygenate blends. The precision of these test methods can differ from the reported precisions when testing gasoline-ethanol blends or other gasoline-oxygenate blends.

7.1.1 *Distillation*—Test Method D86.

7.1.2 *Vapor Pressure*—Test Methods D4953, D5191, D5482, or D6378.

7.1.2.1 When using Test Method D6378, determine VP<sub>4</sub> at 37.8 °C (100 °F) using a sample from a 1 L container and convert to DVPE (D5191 equivalence) using the following equation: