



Designation: E2779 – 10 (Reapproved 2017)

Standard Test Method for Determining Particulate Matter Emissions from Pellet Heaters¹

This standard is issued under the fixed designation E2779; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This test method covers the fueling and operating protocol for determining particulate matter emissions from fires in pellet or other granular or particulate biomass burning room heaters and fireplace inserts.

1.2 The values stated in SI units are to be regarded as standard. The values given in parentheses are mathematical conversions to inch-pound units that are provided for information only and are not considered standard.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.4 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 *ASTM Standards:*²

[D1102 Test Method for Ash in Wood](#)

[D3176 Practice for Ultimate Analysis of Coal and Coke](#)

[D4442 Test Methods for Direct Moisture Content Measurement of Wood and Wood-Based Materials](#)

[D5373 Test Methods for Determination of Carbon, Hydrogen and Nitrogen in Analysis Samples of Coal and Carbon in Analysis Samples of Coal and Coke](#)

[E631 Terminology of Building Constructions](#)

[E711 Test Method for Gross Calorific Value of Refuse-](#)

[Derived Fuel by the Bomb Calorimeter \(Withdrawn 2011\)](#)³

[E777 Test Method for Carbon and Hydrogen in the Analysis Sample of Refuse-Derived Fuel \(Withdrawn 2017\)](#)³

[E778 Test Methods for Nitrogen in Refuse-Derived Fuel Analysis Samples](#)

[E871 Test Method for Moisture Analysis of Particulate Wood Fuels](#)

[E2515 Test Method for Determination of Particulate Matter Emissions Collected by a Dilution Tunnel](#)

2.2 *Other Standards:*

[CSA B415.1 \(3rd Edition\) Performance Testing of Solid-Fuel-Burning Heating Appliances](#)⁴

[PFI Standard Specifications for Residential/Commercial Densified Fuel](#)⁵

3. Terminology

3.1 *Definitions*—Terms used in this test method are defined in Terminology [E631](#).

3.2 *Definitions of Terms Specific to This Standard:*

3.2.1 *automatically controlled heater, n*—a heater where the burn rate is controlled by a means other than the direct action of adjustment of a burn rate control device by the heater user. This includes heaters with thermostats, proportional controllers or other electronic or mechanical devices that control the heater operation in response to a room or other temperature set point.

3.2.2 *burn pot, n*—the vessel or other defined area within the firebox where fuel and air meet to initiate combustion.

3.2.3 *burn rate, n*—the rate at which test fuel is consumed in the pellet heater during a test run. Measured in kilograms (lb) (dry basis) per hour.

3.2.4 *firebox, n*—the chamber in the pellet heater in which primary combustion of the fuel occurs.

3.2.5 *fuel feed system, n*—mechanism for delivering fuel from the hopper to the burn pot.

¹ This test method is under the jurisdiction of ASTM Committee E06 on Performance of Buildings and is the direct responsibility of Subcommittee E06.54 on Solid Fuel Burning Appliances.

Current edition approved Sept. 1, 2017. Published September 2017. Originally approved in 2010. Last previous edition approved in 2010 as E2779-10. DOI: 10.1520/E2779-10R17.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ The last approved version of this historical standard is referenced on www.astm.org.

⁴ Available from Canadian Standards Association (CSA), 178 Rexdale Blvd., Toronto, ON M9W 1R3, Canada, <http://www.csagroup.org>.

⁵ Available from Pellet Fuels Institute (PFI), 2150 N 107th St, Suite 205, Seattle, WA 98133, <http://www.pelletheat.org>.

3.2.6 *fuel grade, n*—variations in the properties of fuel within any given fuel type. For wood pellets, grading is in accordance with PFI Standard Specification for Residential/Commercial Densified Fuel is an example. For other fuel types, certain physical or chemical properties may be used to differentiate between higher and lower fuel grades.

3.2.7 *fuel hopper, n*—container where fuel is held before being delivered to the burn pot by the fuel feed system.

3.2.8 *fuel type, n*—for a pelletized fuel, the fuel type is defined by the material that was pelletized (for example, “wood pellets” or “switch grass pellets”), and for non-pelletized fuel, the fuel type is defined by the material itself (for example, “corn,” “walnut hulls” or “cherry pits”).

3.2.9 *manually controlled heater, n*—a heater where the burn rate is controlled by the direct action of adjustment of a burn rate control device by the heater user.

3.2.10 *manufacturer’s written instructions, n*—specific information regarding the fueling and operation procedures recommended by the heater manufacturer and included with the heater. These instructions must be consistent with information provided to the heater end-user in the owner’s manual or equivalent.

3.2.11 *owner’s manual, n*—written information provided to the heater end-user regarding the installation and recommended fueling and operating procedures that will help the heater user to achieve the best heater performance. It is also referred as the installation and operation guide or other equivalent title.

3.2.12 *particulate matter (PM), n*—all gas-borne matter resulting from combustion of solid fuel, as specified in this test method, which is collected in accordance with Test Method E2515.

3.2.13 *pellet burning heater, n*—a heater specifically designed to burn pellet, granular or particulate fuels only, and which includes a fuel hopper and fuel feed system as integral parts.

3.2.14 *pellet heater venting, n*—venting system or components specified for use with the pellet heater by the pellet heater manufacturer.

3.2.15 *test facility, n*—the area in which the pellet heater is installed, operated, and sampled for emissions.

3.2.16 *test fuel, n*—for any fuel type recommended by the manufacturer in the manufacturer’s written instructions or the owner’s manual for use in the pellet heater, the test fuel when more than one fuel grade is recommended is the lowest recommended grade of that fuel type.

3.2.17 *test fuel weight, n*—the mass of fuel burned in the pellet heater during the test run or test run segment.

3.2.18 *test run, n*—an integrated emission test cycle including test run segments ranging from minimum to maximum burn rates.

3.2.19 *test run segments, n*—individual portions of the test run conducted at the minimum, medium, and maximum burn rates achievable by the pellet heater.

3.2.20 *wood heater, n*—an enclosed, wood burning appliance capable of, and intended for, space heating and/or domestic water heating.

4. Summary of Test Method

4.1 This test method is used in conjunction with Test Method E2515. The pellet heater under evaluation is fueled with the fuel type or types specified by the pellet heater manufacturer. The fuel types may be any pelletized, granular or particulate biomass fuel for which the pellet heater has been designed to combust. The fuels must be able to be fed to the pellet heater burn pot from a fuel storage hopper using an auger or other fuel feeding mechanism. An integrated test run is conducted including three burn rate segments ranging from low to maximum. The length of time of each burn rate segment determines the weighting given to each segment in the integrated test result. The weight of the fuel is measured as the change in weight of the heater from the beginning to end of each burn rate segment of the test run. Burn rate for each test run segment is determined based on the weight of the fuel consumed during the segment divided by the length of the segment and corrected to a dry fuel basis. Particulate sampling begins after the heater has been in operation at the burn rate setting for the first test run segment for at least one hour and the test run is terminated after the integrated test run cycle is complete. The total particulate emissions are determined over the full integrated test run length. The average particulate emissions rate is then determined from the total particulate emissions determined using Test Method E2515 divided by the length of the integrated test run and is reported in grams of particulate per hour. The average particulate emission factor may also be determined from the total particulate emissions divided by the total dry basis weight of the fuel consumed during the integrated test run and is reported in grams of particulate per dry kilogram of fuel. If the efficiency of the heater is measured, average particulate emissions may also be reported in grams of particulate per unit of average heat delivered over the integrated test run. A separate test run is required for each fuel type specified by the manufacturer for use with the heater. If more than one grade of a given fuel type is recommended by the manufacturer in the manufacturer’s written instructions for use in the heater, the test fuel shall be the lowest recommended grade.

5. Significance and Use

5.1 This test method is used for determining average emission rates and average emission factors for pellet heaters.

5.1.1 The emission factor is useful for determining emission performance during product development.

5.1.2 The emission factor is useful for the air quality regulatory community for determining compliance with emission performance limits.

5.1.3 The emission rate may be useful for the air quality regulatory community for determining impacts on air quality from pellet heaters.

5.2 The reporting units are grams of particulate per hour and grams of particulate per kilogram of dry fuel.

5.2.1 Appropriate reporting units for comparing emissions from all types of solid fuel fired appliances: g/kg.

5.2.2 Appropriate reporting units for predicting atmospheric emission impacts: g/h or g/MJ.

6. Safety

6.1 *Disclaimer*—This test method may involve hazardous materials, operations, and equipment. This test method may not address all of the safety problems associated with its use. It is the responsibility of the user of this test method to establish appropriate safety and health practices and to determine the applicability of regulatory limitations prior to performing this test method.

7. Equipment and Supplies

7.1 *Platform Scale*—A scale capable of weighing the test pellet heater and attached venting, including the weight of the test fuel, to within 0.05 kg (0.1 lb). Must meet the calibration requirements specified in 8.1.

7.2 *Pellet Heater Flue Gas Temperature Measurement Device*—A 3.2 mm (0.125 in.) diameter sheathed, non-isolated junction Type K thermocouple capable of measuring flue gas temperature with an accuracy of 2.2 °C (4.0 °F) or 0.75 % of the reading, whichever is greater. Must meet calibration requirements specified in 8.2.

8. Calibration and Standardization

8.1 *Platform Scale*—Perform a multipoint calibration (at least five points spanning the operational range) of the platform scale before its initial use. The scale manufacturer's calibration results are sufficient for this purpose. Before each certification test, audit the scale with the test fireplace in place by weighing at least one calibration weight (ASTM Class F) that corresponds to between 20 and 80 % of the expected test fuel charge weight. If the scale cannot reproduce the value of the calibration weight within 0.05 kg (0.1 lb) or 1 % of the expected test fuel charge weight, whichever is greater, recalibrate the scale before use with at least five calibration weights spanning the operational range of the scale.

8.2 *Temperature Sensors*—Temperature measuring equipment shall be calibrated before initial use and at least semi-annually thereafter. Calibrations shall be in compliance with National Institute of Standards and Technology (NIST) Monograph 175—Standard Limits of Error.

9. Procedure

9.1 *Pre-conditioning of the Pellet Heater*—The pellet heater must be pre-conditioned before a test series begins.

9.1.1 Set up the pellet heater in accordance with written instructions provided by the manufacturer. The total vent height measured from the floor or top of the platform scale shall be 4.6 ± 0.3 m (15 ± 1 ft) unless otherwise specified in the manufacturer's written instructions. The venting type used shall be in accordance manufacturer's written instructions.

9.1.2 Install a flue-gas temperature measurement device at the center of the flue, 2.6 ± 0.15 m (8.5 ± 0.5 ft) above the floor or top of the platform scale.

9.1.3 Operate the pellet heater for at least 48 hours at a medium burn rate as defined in 9.5.1 using any fuel specified by the manufacturer for use in the appliance. The hours of operation do not need to be continuous. Additional pre-conditioning is not required when additional fuel types are tested in the same test series.

9.1.4 Record the time and weight for all fuel added.

9.1.5 Record the flue-gas temperature at least once during each hour of operation.

9.1.6 Allow the pellet heater to cool to room temperature and remove all ash, or other debris from the firebox.

9.1.7 Clean the venting system using a standard chimney brush appropriately sized for the chimney.

9.2 Install the pellet heater in the test facility.

9.2.1 Set up the pellet heater in accordance with instructions provided by the manufacturer. Place the pellet heater centrally on the platform scale. The total vent height measured from the top of the platform scale shall be 4.6 ± 0.3 m (15 ± 1 ft) unless otherwise specified in the manufacturer's written instructions. The venting type used shall be in accordance manufacturer's written instructions.

NOTE 1—The venting that is used for testing should be documented in the test data and test report.

9.2.2 Center the vent outlet under the dilution tunnel hood. Refer to Test Method E2515 for specific requirements including positioning the flue outlet to meet induced draft and smoke capture requirements.

9.2.3 Install a flue-gas temperature measurement device at the center of the vent, 2.6 ± 0.15 m (8.5 ± 0.5 ft) above the top of the platform scale.

9.3 *Fuel:*

9.3.1 *Fuel Properties*—A representative sample of the fuel used for any test run, shall be analyzed for Higher Heating Value in accordance with Test Method E711. Moisture content shall be determined in accordance with Test Methods D4442 or Test Method E871.

9.3.1.1 If determining optional thermal efficiency and heat output in accordance with 9.5.1 and Annex A1, a representative sample of the fuel used for any test run shall be analyzed for ash in accordance with Test Method D1102 and carbon, hydrogen, nitrogen, and oxygen (ultimate analysis) in accordance with Test Methods E777 and E778, or Practice D3176 and Test Methods D5373.

9.3.2 *Fuel Temperature*—The test fuel temperature shall be within the allowable test facility temperature range as in accordance with Test Method E2515. The fuel temperature may be determined by measuring the temperature of the room where the test fuel has been stored for at least 24 hours immediately prior to use in a test run.

9.4 *Test Run Requirements:*

9.4.1 *Integrated Test Run*—A single test run comprised of minimum, medium, and maximum burn rate segments shall be conducted. The burn rate requirements for each segment, except as allowed in 9.4.1.4 or 9.4.1.5, as well as the length of time for each segment are specified in Table 1.

9.4.1.1 *Maximum Burn Rate*—For the maximum burn rate category, the pellet heater shall be operated with the control or