

---

**Akustika - Statistične metode za ugotavljanje in preverjanje nazivnih podatkov o emisiji hrupa naprav in opreme - 4. del: Metode za nazivne podatke za skupine istovrstnih strojev (ISO 7574-4:1985)**

Acoustics - Statistical methods for determining and verifying stated noise emission values of machinery and equipment - Part 4: Methods for stated values for batches of machines (ISO 7574-4:1985)

**Akustik - Statistische Verfahren zur Festlegung und Nachprüfung angegebener (oder vorgegebener) Geräuschemissionswerte von Maschinen und Geräten - Teil 4: Verfahren für Angaben (oder Vorgaben) für Maschinenlose (ISO 7574-4:1985)**

[SIST EN 27574-4:1997](https://standards.iteh.ai/catalog/standards/sist/db4d450b-b1eb-496f-8741-1032257441997)

<https://standards.iteh.ai/catalog/standards/sist/db4d450b-b1eb-496f-8741-1032257441997>  
**Acoustique - Méthodes statistiques pour la détermination et le contrôle des valeurs déclarées d'émission acoustique des machines et équipements - Partie 4: Méthodes pour valeurs déclarées de lots de machines (ISO 7574-4:1985)**

**Ta slovenski standard je istoveten z: EN 27574-4:1988**

---

**ICS:**

17.140.20	Emisija hrupa naprav in opreme	Noise emitted by machines and equipment
-----------	--------------------------------	---

**SIST EN 27574-4:1997**

**en**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN 27574-4:1997](https://standards.iteh.ai/catalog/standards/sist/db4d450b-b1eb-496f-8741-4a6ed5d575de/sist-en-27574-4-1997)

<https://standards.iteh.ai/catalog/standards/sist/db4d450b-b1eb-496f-8741-4a6ed5d575de/sist-en-27574-4-1997>

**EUROPEAN STANDARD**  
**NORME EUROPÉENNE**  
**EUROPÄISCHE NORM**

**EN 27 574**

Part 4

December 1988

UDC 534.6:534.835.46:519.22

Key words : Acoustics, Noise: sound, Engine noise, Statistical quality control, Statistical analysis, Sampling, Standard deviation

**English version**

**Acoustics**

**Statistical methods for determining and verifying  
 stated noise emission values of machinery and equipment  
 Part 4: Methods for stated values for batches of machines  
 (ISO 7574/4, edition 1985)**

Acoustique; Méthodes statistiques pour la détermination et le contrôle des valeurs déclarées d'émission acoustique des machines et équipements; Partie 4: Méthodes pour valeurs déclarées de lots de machines (ISO 7574/4, édition 1985)

Akustik; Statistische Verfahren zur Festlegung und Nachprüfung angegebener (oder vorgegebener) Geräuschemissionswerte von Maschinen und Geräten; Teil 4: Verfahren für Angaben (oder Vorgaben) für Maschinenlose (ISO 7574/4, Ausgabe 1985)

This European Standard was accepted by CEN on 1988-11-15. CEN members are bound to comply with the requirements of the CEN/CENELEC Rules which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.  
[standards.iteh.ai/catalog/standards/sist/db4d450b-b1eb-496f-8741-4a6ed5d575de/sist-en-27574-4-1997](http://standards.iteh.ai/catalog/standards/sist/db4d450b-b1eb-496f-8741-4a6ed5d575de/sist-en-27574-4-1997)

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN Central Secretariat or to any CEN member.

This European Standard exists in the official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to CEN Central Secretariat has the same status as the official versions.

CEN members are the national standards organizations of Austria, Belgium, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxemburg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.

**CEN**

**European Committee for Standardization  
 Comité Européen de Normalisation  
 Europäisches Komitee für Normung**

**Central Secretariat : Rue Bréderode 2, B-1000 Brussels**

© CEN 1988 Copyright reserved to all CEN members

Ref.No. EN 27 574-4:1988 E

### BRIEF HISTORY

The Technical Board decided with Resolution BT 84/1988 to submit the International Standard

ISO 7574/4-1985 'Acoustics; Statistical methods for determining and verifying stated noise emission values of machinery and equipment;  
Part 4: Methods for stated values for batches of machines'

to the Fomal Vote.

Since this standard passed the Fomal Vote positively without modification, it was approved by CEN as European Standard EN 27 574 Part 4.

In accordance with the Common CEN/CENELEC Rules, the following countries are bound to implement this European Standard:

Austria, Belgium, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxemburg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.

### STATEMENT

The text of the International Standard ISO 7574/4, edition 1985 was approved by CEN as a European Standard without any modification.

---

# International Standard



# 7574/4

---

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

---

## Acoustics — Statistical methods for determining and verifying stated noise emission values of machinery and equipment — Part 4 : Methods for stated values for batches of machines

iTeh STANDARD PREVIEW

(standards.iteh.ai)

*Acoustique — Méthodes statistiques pour la détermination et le contrôle des valeurs déclarées d'émission acoustique des machines et équipements — Partie 4 : Méthodes pour valeurs déclarées de lots de machines*

[SIST EN 27574-4:1997](#)

First edition — 1985-12-15 <https://standards.iteh.ai/catalog/standards/sist/db4d450b-b1eb-496f-8741-4a6ed5d575de/sist-en-27574-4-1997>

---

UDC 534.835.46 : 512.24

Ref. No. ISO 7574/4-1985 (E)

Descriptors : acoustics, machinery, noise (sound), statistical quality control, statistical analysis.

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council. They are approved in accordance with ISO procedures requiring at least 75 % approval by the member bodies voting.

International Standard ISO 7574/4 was prepared by Technical Committee ISO/TC 43, *Acoustics*.

Users should note that all International Standards undergo revision from time to time and that any reference made herein to any other International Standard implies its latest edition, unless otherwise stated.

<http://standards.iteh.ai/catalog/standards/sist/db4d450b-b1eb-496f-8741-4a6ed5d575de/sist-en-27574-4-1997>

## Contents

	Page
<b>0</b> Introduction .....	1
<b>1</b> Scope and field of application .....	1
<b>2</b> References .....	1
<b>3</b> Definitions .....	1
<b>4</b> General .....	1
<b>5</b> Guidelines for the determination of the labelled value, $L_C$ , by the labeller .....	2
<b>6</b> Verifying the labelled value for a batch of machines .....	3
<b>6.1</b> General .....	3
<b>6.2</b> Single sampling inspection .....	3
<b>6.3</b> Double sampling inspection .....	4
<b>6.4</b> Sequential sampling inspection .....	4
<b>7</b> Information to be given in a specific labelling code for a specific family of machines .....	5
 <b>Annexes</b>	
<b>A</b> Operating characteristic curves and examples of single, double and sequential sampling .....	6
<b>B</b> Guidelines for estimating standard deviations and for the use of operating characteristic curves .....	9
<b>C</b> List of symbols .....	14
 <b>Bibliography</b> .....	 14

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/db4d450b-b1eb-496f-8741-4a663d700956/sist-en-27574-4-1997>

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

This page intentionally left blank

[SIST EN 27574-4:1997](#)

<https://standards.iteh.ai/catalog/standards/sist/db4d450b-b1eb-496f-8741-4a6ed5d575de/sist-en-27574-4-1997>

# Acoustics — Statistical methods for determining and verifying stated noise emission values of machinery and equipment —

## Part 4: Methods for stated values for batches of machines

### 0 Introduction

A general introduction to the four-part series of ISO 7574 is given in ISO 7574/1.

For the purposes of this part of ISO 7574, the term "labelled value" stands for all kinds of stated value (e.g. information on a label, the upper noise limit set by an authority, the agreed contract value) for which the methods may be applied.

This part of ISO 7574 contains statistical sampling methods for checking the stated noise emission values for batches (lots) of machines. The labelled value for all machines in a batch is checked by sampling procedures. A reference standard deviation is required when testing the compliance of a batch of a specific family of machines. In addition, information on the type of sampling to be used (single, double or sequential) and the sample size is required. The procedures specified in this part of ISO 7574 assume that the noise emission values of a batch (lot) of machines will follow a normal distribution. The statistical parameters upon which this part of ISO 7574 is based assume that there is a 95 % probability of acceptance if no more than 6,5 % of the noise emission values in a batch exceed the labelled value. Information is included to assist the labeller in determining a labelled value based on these statistical parameters.

The methods given in this part of ISO 7574 ensure that a batch (lot) of machines labelled in accordance with the specifications for the verification procedure have a predetermined probability of acceptance.

### 1 Scope and field of application

This part of ISO 7574 provides guidelines for determining the labelled value,  $L_C$ , by the labeller and specifies statistical sampling procedures for verifying compliance of the noise emissions of a batch (lot) of machinery and equipment with its labelled value.

This part of ISO 7574 is intended to assist those parties responsible for drawing up specific labelling codes for specific families

of machines. It is also intended to be of use to labellers who want their batches of machines to conform with verification procedures that are in accordance with the specifications given in the specific labelling codes based on clause 7.

This part of ISO 7574 does not deal with the consequences that ensue if the stated value is not confirmed as verified for a batch (lot) of machines.

### 2 References

ISO 3951, *Sampling procedures and charts for inspection by variables for percent defective*.

ISO 4871, *Acoustics — Noise labelling of machinery and equipment*.

ISO 7574/1, *Acoustics — Statistical methods for determining and verifying stated noise emission values of machinery and equipment — Part 1: General considerations and definitions*.

### 3 Definitions

For the purposes of this part of ISO 7574, the definitions given in ISO 7574/1 apply.

### 4 General

For a batch of machines, the noise emission values will cover a certain range due to the variability between the machines (relevant measure: standard deviation of production,  $\sigma_p$ ) and due to measurement errors occurring under reproducibility conditions (relevant measure: standard deviation of reproducibility,  $\sigma_R$  — see 3.17 in ISO 7574/1). The measure for the overall variability is the total standard deviation,  $\sigma_T$ .

The aim of labelling a batch of machines is to indicate as labelled value,  $L_C$ , a limit below which a specified large propor-

## ISO 7574/4-1985 (E)

tion of the noise emission values of the batch shall lie.  $L_c$  is expressed as an integer in decibels.

When used for checking the compliance of a batch of machines with the labelled value, this part ISO 7574 works on the principle that only a sample from the batch is measured. This principle is appropriate for mass-produced machines. This part of ISO 7574 considers the need to control machines which are too noisy compared with the labelled value; therefore, it applies to one-sided cases for checking an upper limit, not to two-sided cases which would also exclude machines which are too quiet. The principle is based on balancing risks which are expressed by a pair of values: a specified proportion,  $p_{1-\alpha}$ , of noise emission values of the batch exceeding the labelled value and a specified probability of rejection,  $\alpha$ , for a lot with this proportion  $p_{1-\alpha}$ .

Verifying compliance of the lot with the labelled value is based on the following assumptions:

- that the noise emission values of the batch approximate to a normal distribution, characterized by the mean value  $\mu$  and the specified reference standard deviation  $\sigma_M$ ; and
- that the rejection probability for a batch is equal to a specified value  $\alpha$  if the labelled value  $L_c$  is chosen so that the proportion of noise emission values of the batch exceeding  $L_c$  is equal to the specified value  $p_{1-\alpha}$ .

Procedures in this part of ISO 7574 are based on  $\alpha = 5\%$  and  $p_{1-\alpha} = 6,5\%$ .

NOTE — The fixed value of 6,5 % was chosen in order

- to comply with the definition for  $L_c$ ;
- to make sure that the difference between  $L_c$  and the mean for the batch is reasonably limited; and
- to achieve a common understanding, comparability and compatibility of different  $L_c$  values for different machines from different families of machines.

If the batch and the labelled value,  $L_c$ , conform with these values, the sampling inspection procedures are set in such a way that the batch will be accepted with the probability of  $1 - \alpha = 95\%$  and the mean value will be expected to lie approximately  $1,5 \sigma_M$  below the labelled value.

## NOTES

- If it is explicitly known that a stated value is not an upper value as  $L_c$  but represents a mean value (which is not in accordance with ISO 4871), the checking procedure might also be used by adding  $1,5 \sigma_M$  to this mean value to obtain  $L_c$ .
- Methods for estimating risk factors are given in annexes A and B; they may be replaced by repeated, simulated application of the checking procedure using actual measurement data, if the assumption that the noise emission values of the batch approximate to a normal distribution is uncertain. Normality tests will be described in a future International Standard.
- The sampling inspection by variables for isolated batches of machines, as described in this part of ISO 7574, broadly conforms to ISO 3951 which is, however, designed for the inspection of batches from continuous production. ISO 3951 does not provide for double and sequential sampling inspection, and the operating characteristic curves do not intersect exactly at the producer's risk point; this is, however, the aim of this part of ISO 7574 with the view to establishing the meaning of  $L_c$  unambiguously.

It should be noted that fixing  $\alpha$  and  $p_{1-\alpha}$  results in all operating characteristic curves (OCs) intersecting at the producer's risk point.

If the actual total standard deviation is different from the reference standard deviation  $\sigma_M$ , guidance for the labeller is given in clause 5 and annex B.

NOTE — In the application of this part of ISO 7574, it is assumed that all measurements will be performed by a testing laboratory which has appropriate test facilities and trained staff.

## 5 Guidelines for the determination of the labelled value, $L_c$ , by the labeller

As the determination of the labelled value for a batch of machines is the sole responsibility of the labeller, this clause is given for guidance only to provide a predictable probability of acceptance.

$L_c$  can only be determined in accordance with this part of ISO 7574 if a specific labelling code in conformity with clause 7 exists [see, in particular, 7 c) to f)].

A reasonably large number of measured values of individual machines,  $L_i^*$ , are determined in accordance with the specific measurement test code for the specific family of machines. (The asterisk in the symbols is used here to differentiate between measurements in conformity with this clause and those in conformity with clause 6.)

The mean value,  $\bar{L}^*$ , and the total standard deviation,  $s_t^*$ , are calculated from the measured values,  $L_i^*$ , of the individual machines in a sample (see also clause B.2).

$\bar{L}^*$  and  $s_t^*$  are estimates of the mean value  $\mu$  and the total standard deviation,  $\sigma_t$ , of the batch to be labelled.

In accordance with clause B.3, equation (16), the following equations will provide guidance for the labeller who wants to have a probability of acceptance,  $P_a$ , defined by himself:

$$L_c = \mu + \left( k + \frac{u_{P_a}}{\sqrt{n}} \right) \sigma_M \quad \text{for } \sigma_t = \sigma_M \quad \dots (1)$$

$$L_c = \mu + k \sigma_M + \frac{u_{P_a}}{\sqrt{n}} \sigma_t \quad \text{for } \sigma_t \neq \sigma_M \quad \dots (2)$$

where

$\mu$  is the mean value of the batch;

$n$  is the specified verification sample size for single sampling inspection (6.2) or the equivalent single sample size in the case of double sampling inspection (see 6.3) or sequential sampling inspection (see 6.4);

$k$  is a function of  $n$ , in accordance with table 1;

$u_{P_a}$  is the quantile of the normal distribution for the value  $P_a$  (see table 7);

$\sigma_M$  is the specified reference standard deviation for verification;

$\sigma_t$  is the actual total standard deviation.

If the labeller accepts a risk of rejection of 5 % (i.e. he wants to have a probability of acceptance,  $P_a$ , of 95 %), the above equations result in the following<sup>1)</sup> :

$$L_c = \mu + 1,5 \sigma_M \quad \text{for } \sigma_t = \sigma_M \quad \dots (3)$$

$$L_c = \mu + 1,5 \sigma_t + k(\sigma_M - \sigma_t) \quad \text{for } \sigma_t \neq \sigma_M \quad \dots (4)$$

For examples, see clause B.3.

NOTE — Testing may be necessary from time to time in order to ensure that the labelled value continues to be correct. Testing is also required whenever physical changes are made to the production machines that may affect their noise emissions.

## 6 Verifying the labelled value for a batch of machines

### 6.1 General

Three equivalent procedures for verifying the labelled value of the batch are described in this part of ISO 7574: single sampling, double sampling and sequential sampling. The results obtained from any one of the three procedures will generally be the same if the assumption that the emission values are distributed approximately as a normal distribution is valid.

One and only one of the three procedures shall be chosen and specified in the labelling code for each specific family of machines (see clause 7). All three procedures require a specified reference standard deviation,  $\sigma_M$ , for each specific family of machines.

The sample size,  $n$ , in the case of single sampling (or equivalent sample sizes  $n_1$  and  $n_2$  in the case of double sampling or equivalent maximum sample size  $n_{max}$  in the case of sequential sampling) shall also be specified for each specific family of machines (see annex A). In general, double or sequential sampling results in a somewhat smaller number of machines being tested.

NOTE — The reason for applying only one of the three procedures for a specific family of machines is that the procedures are only equivalent provided that the assumption of normality is absolutely valid.

The procedures outlined in 6.2 to 6.4 are applicable for reproducibility conditions (see 3.17 in ISO 7574/1), and for

repeatability conditions (see 3.16 in ISO 7574/1). It shall be ascertained that no outstanding systematic error of measurement results is connected with relevant laboratories.

For each of the procedures outlined in 6.2 to 6.4, the measured values,  $L_i$ , shall be determined in accordance with the specific measurement test code for the specific family of machines [see clause 7 c) and d)]. The measured values shall not be rounded prior to statistical calculations.

### 6.2 Single sampling inspection

In accordance with 6.1 and clause 7,  $n$  and  $\sigma_M$  have been specified for the relevant family of machines.

Take at random a sample of size  $n$  from the batch under consideration.

The measured values are  $L_i$  ( $i = 1, \dots, n$ ) and their mean value is

$$\bar{L} = \frac{1}{n} \sum_{i=1}^n L_i \quad \dots (5)$$

Determine the value

$$A = L_c - k \sigma_M \quad \dots (6)$$

using the acceptability constant  $k$  calculated from the formula

$$k = u_{1-p_1-\alpha} - \frac{u_{1-\alpha}}{\sqrt{n}} \quad \dots (7)$$

where

$$u_{1-p_1-\alpha} = 1,514$$

$$u_{1-\alpha} = 1,645$$

are the quantiles of the standardized normal distribution for the values  $1 - p_1 - \alpha = 93,5 \%$  and  $1 - \alpha = 95 \%$  respectively.

Table 1 gives the values for  $k$  for different sample sizes  $n$ .

Table 1 — Acceptability constant  $k$  for different sample sizes  $n$

$n$	1	2	3	4	5	6	7	8	9	10
$k$	-0,131	0,351	0,564	0,692	0,778	0,842	0,892	0,932	0,966	0,994

1) Use equation (1) or (2), by replacing  $\frac{u_{P_a}}{\sqrt{n}}$  with  $\frac{u_{1-\alpha}}{\sqrt{n}} = u_{1-p_1-\alpha} - k$  [see equation (7)]

where  $u_{1-p_1-\alpha} \approx 1,5$ .