This document is not an ASTM standard and is intended only to provide the user of an ASTM standard an indication of what changes have been made to the previous version. Because it may not be technically possible to adequately depict all changes accurately, ASTM recommends that users consult prior editions as appropriate. In all cases only the current version of the standard as published by ASTM is to be considered the official document.



Designation: A204/A204M - 12 A204/A204M - 17

# Standard Specification for Pressure Vessel Plates, Alloy Steel, Molybdenum<sup>1</sup>

This standard is issued under the fixed designation A204/A204M; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\varepsilon$ ) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the U.S. Department of Defense.

## 1. Scope\*

1.1 This specification<sup>2</sup> covers molybdenum-alloy steel plates, intended particularly for welded boilers and other pressure vessels.

1.2 Plates under this specification are available in three grades having different strength levels as follows:

Grade	Tensile Strength, ksi [MPa]
A	65-85 [450-585]
В	70–90 [485–620]
С	75–95 [515–655]

1.3 The maximum thickness of plates is limited only by the capacity of the composition to meet the specified mechanical property requirements; however, current practice normally limits the maximum thickness of plates furnished under this specification as follows: requirements.

Grade	Maximum Thickness, in. [mm]
A	<del>6 [150]</del>
B	i ch Standarde 6 [150]
e	

1.4 The values stated in either inch-pound units or SI units are to be regarded separately as standard. Within the text, the SI units are shown in brackets. The values stated in each system are not exact equivalents; therefore, each system must be used independently of the other. Combining values from the two systems may result in nonconformance with this specification.

<u>1.5 This international standard was developed in accordance with internationally recognized principles on standardization</u> established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.

#### 2. Referenced Documents

2.1 ASTM Standards:<sup>3</sup>

A20/A20M Specification for General Requirements for Steel Plates for Pressure Vessels A435/A435M Specification for Straight-Beam Ultrasonic Examination of Steel Plates A577/A577M Specification for Ultrasonic Angle-Beam Examination of Steel Plates A578/A578M Specification for Straight-Beam Ultrasonic Examination of Rolled Steel Plates for Special Applications

#### 3. General Requirements and Ordering Information

3.1 Material supplied to this material specification shall conform to Specification A20/A20M. These requirements outline the testing and retesting methods and procedures, permitted variations in dimensions, and mass, quality and repair of defects, marking, loading, and ordering information.

3.2 In addition to the basic requirements of this specification, certain supplementary requirements are available when additional control, testing, or examination is required to meet end use requirements. The purchaser is referred to the listed supplementary requirements in this specification and to the detailed requirements in Specification A20/A20M.

\*A Summary of Changes section appears at the end of this standard

<sup>&</sup>lt;sup>1</sup> This specification is under the jurisdiction of ASTM Committee A01 on Steel, Stainless Steel and Related Alloys and is the direct responsibility of Subcommittee A01.11 on Steel Plates for Boilers and Pressure Vessels.

Current edition approved May 1, 2012 Nov. 1, 2017. Published June 2012 November 2017. Originally approved in 1937. Last previous edition approved in 20072012 as A204/A204M - 03 (2007). A204/A204M - 12. DOI: 10.1520/A0204\_A0204M-12.10.1520/A0204\_A0204M-12.

<sup>&</sup>lt;sup>2</sup> For ASME Boiler and Pressure Vessel Code applications, see related Specification SA-204/SA 204M in Section II of that Code.

<sup>&</sup>lt;sup>3</sup> For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For Annual Book of ASTM Standards volume information, refer to the standard's Document Summary page on the ASTM website.



## TABLE 1 Chemical Requirements

<b>E</b> I	Composition, %			
Element	Grade A	Grade B	Grade C	
Carbon, max: <sup>A</sup>				
Up to 1 in. [25 mm]	0.18	0.20	0.23	
incl, in thickness				
Over 1 in. to 2 in. [50 mm]	0.21	0.23	0.26	
incl, in thickness				
Over 2 in. to 4 in. [100 mm]	0.23	0.25	0.28	
incl, in thickness				
Over 4 in. [100 mm]	0.25	0.27	0.28	
in thickness				
Manganese, max:				
Heat analysis	0.90	0.90	0.90	
Product analysis	0.98	0.98	0.98	
Phosphorous, max <sup>A</sup>	0.025	0.025	0.025	
Sulfur, max <sup>A</sup>	0.025	0.025	0.025	
Silicon:				
Heat analysis	0.15-0.40	0.15-0.40	0.15-0.40	
Product analysis	0.13-0.45	0.13-0.45	0.13-0.45	
Molybdenum:				
Heat analysis	0.45-0.60	0.45-0.60	0.45-0.60	
Product analysis	0.41-0.64	0.41-0.64	0.41-0.64	

<sup>A</sup> Applies to both heat and product analyses.

3.3 Coils are excluded from qualification to this specification until they are processed into finished plates. Plates produced from coil means plates that have been cut to individual lengths from coil. The processor directly controls, or is responsible for, the operations involved in the processing of coils into finished plates. Such operations include decoiling, leveling, cutting to length, testing, inspection, conditioning, heat treatment (if applicable), packaging, marking, loading for shipment, and certification.

Note 1—For plates produced from coil and furnished without heat treatment or with stress relieving only, three test results are reported for each qualifying coil. Additional requirements regarding plates from coil are described in Specification A20/A20M.

3.4 If the requirements of this specification are in conflict with the requirements of Specification A20/A20M, the requirements of this specification shall prevail.

#### 4. Materials and Manufacture

4.1 Steelmaking Practice—The steel shall be killed.

#### 5. Heat Treatment

<u>ASTM A204/A204M-17</u>

5.1 Plates 1<sup>1</sup>/<sub>2</sub> in. [40 mm] and under in thickness are normally supplied in the as-rolled condition. The plates may be ordered normalized, normalized and tempered, or stress relieved or both. relieved.

5.2 Plates over 1<sup>1</sup>/<sub>2</sub> in. [40 mm] in thickness shall be normalized.normalized or normalized and tempered.

#### 6. Chemical Requirements

6.1 The steel shall conform to the chemical requirements given in Table 1 unless otherwise modified in accordance with Supplementary Requirement S17, Vacuum Carbon-Deoxidized Steel, in Specification A20/A20M.

### 7. Mechanical Requirements

7.1 *Tension Test Requirements*—The plates, as represented by the tension-test specimens, shall conform to the requirements given in Table 2.

#### 8. Keywords

8.1 alloy steel plate; molybdenum-alloy; pressure containing parts; pressure vessel steel plate