

9`Y_fca U[bYfbUnXfi y`^j cgh]b`nUXYj Yj`nj Yn]`n`fUX]`g_`ja`gdY_fca`fØFAŁĚ
FUX]ch`YZ`bg_]`cXXU`b_]`]b`gdfY`Ya b_]`nU`dca c`fg_c`a cV]`bc`glcf]`hYj`ž
i`dcfUV`^bc`bUW`^]bg_]`j`cXb]`dch`Λ`ž_]`XYi`^c`j`dUgcj`]`J<: `Ě`%`r`XY.
HΛ`b]`bY`_U`U`hYf]`gh_]`Y]`b`a`Yf]`bY`a`Ytc`XY

ElectroMagnetic Compatibility and Radio Spectrum Matters (ERM); Radio telephone transmitters and receivers for the maritime mobile service operating in the VHF bands used on inland waterways; Part 1: Technical characteristics and methods of measurement

iteh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 698-1 V1.2.1:2003](https://standards.iteh.ai/catalog/standards/sist/21fb41cf-0521-41e6-a8fc-2547c43b5f80/sist-en-300-698-1-v1-2-1-2003)

<https://standards.iteh.ai/catalog/standards/sist/21fb41cf-0521-41e6-a8fc-2547c43b5f80/sist-en-300-698-1-v1-2-1-2003>

Ta slovenski standard je istoveten z: EN 300 698-1 Version 1.2.1

ICS:

33.060.20	Sprejemna in oddajna oprema	Receiving and transmitting equipment
33.100.01	Elektromagnetna združljivost na splošno	Electromagnetic compatibility in general
47.020.70	Navigacijska in krmilna oprema	Navigation and control equipment

SIST EN 300 698-1 V1.2.1:2003 en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 698-1 V1.2.1:2003

<https://standards.iteh.ai/catalog/standards/sist/21fb41cf-0521-41e6-a8fc-2547c43b5f80/sist-en-300-698-1-v1-2-1-2003>

ETSI EN 300 698-1 V1.2.1 (2000-08)

European Standard (Telecommunications series)

**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
Radio telephone transmitters and receivers
for the maritime mobile service operating
in the VHF bands used on inland waterways;
Part 1: Technical characteristics and
methods of measurement**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 698-1 V1.2.1:2003](https://standards.iteh.ai/catalog/standards/sist/21fb41cf-0521-41e6-a8fc-2547c43b5f80/sist-en-300-698-1-v1-2-1-2003)

<https://standards.iteh.ai/catalog/standards/sist/21fb41cf-0521-41e6-a8fc-2547c43b5f80/sist-en-300-698-1-v1-2-1-2003>



Reference

REN/ERM-RP01-037-1

Keywords

maritime, radio, VHF

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 698-1 V1.2.1:2003

<https://standards.iteh.ai/catalog/standards/sist/21fb41cf-0521-41e6-a8fc-2547c43b5f80/sist-en-300-698-1-v1-2-1-2003>

Important notice

Individual copies of the present document can be downloaded from:
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <http://www.etsi.org/tb/status/>

If you find errors in the present document, send your comment to:
editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2000.
All rights reserved.

Contents

Intellectual Property Rights	7
Foreword	7
Introduction.....	7
1 Scope.....	8
2 References.....	8
3 Definitions and abbreviations	9
3.1 Definitions.....	9
3.2 Abbreviations.....	9
4 General requirements.....	9
4.1 Construction.....	9
4.2 Controls and indicators	10
4.3 Handset and loudspeaker	10
4.4 Switching time	10
4.5 Safety precautions.....	10
4.6 Class of emission and modulation characteristics	11
4.7 Facilities for DSC transmission and reception	11
4.8 Labelling	11
4.9 Warm up	12
5 Test conditions, power sources and ambient temperatures	12
5.1 Normal and extreme test conditions.....	12
5.2 Test power source	12
5.3 Normal test conditions	12
5.3.1 Normal temperature and humidity.....	12
5.3.2 Normal power sources.....	12
5.3.2.1 Mains voltage and frequency	12
5.3.2.2 Battery power source	12
5.3.2.3 Other power sources	12
5.4 Extreme test conditions	13
5.4.1 Extreme temperatures.....	13
5.4.2 Extreme values of test power sources.....	13
5.4.2.1 Mains voltage.....	13
5.4.2.2 Battery power source	13
5.4.2.3 Other power sources	13
5.5 Procedure for tests at extreme temperatures.....	13
6 General conditions of measurement.....	14
6.1 Arrangements for test signals applied to the receiver.....	14
6.2 Squelch.....	14
6.3 Normal test modulation.....	14
6.4 Artificial antenna.....	14
6.5 Arrangements for test signals applied to the transmitter	14
6.6 Tests on equipment with a duplex filter	14
6.7 Test channels.....	14
6.8 Measurement uncertainty and interpretation of the measured results.....	15
6.8.1 Measurement uncertainty.....	15
6.8.2 Interpretation of the measurement results.....	15
7 Environmental tests	15
7.1 Introduction.....	15
7.2 Procedure	16
7.3 Performance check.....	16
7.4 Vibration	16
7.5 Damp heat cycle.....	17

8	Transmitter	17
8.1	Frequency error	17
8.1.1	Definition	17
8.1.2	Method of measurement	17
8.1.3	Limits	17
8.2	Carrier power	17
8.2.1	Definitions	17
8.2.2	Method of measurement	17
8.2.3	Limits	18
8.2.3.1	Normal test conditions	18
8.2.3.2	Extreme test conditions	18
8.3	Frequency deviation	18
8.3.1	Definition	18
8.3.2	Maximum frequency deviation	18
8.3.2.1	Method of measurement	18
8.3.2.2	Limits	18
8.3.3	Frequency deviation at modulation frequencies above 3 kHz	18
8.3.3.1	Method of measurement	18
8.3.3.2	Limits	18
8.4	Limitation characteristics of the modulator	19
8.4.1	Definition	19
8.4.2	Method of measurement	19
8.4.3	Limits	19
8.5	Sensitivity of the modulator, including microphone	19
8.5.1	Definition	19
8.5.2	Method of measurement	20
8.5.3	Limits	20
8.6	Audio frequency response	20
8.6.1	Definition	20
8.6.2	Method of measurement	20
8.6.3	Limit	20
8.7	Audio frequency harmonic distortion of the emission	21
8.7.1	Definition	21
8.7.2	Method of measurement	21
8.7.2.1	Normal test conditions	22
8.7.2.2	Extreme test conditions	22
8.7.3	Limit	22
8.8	Adjacent channel power	22
8.8.1	Definition	22
8.8.2	Method of measurement	22
8.8.3	Limits	22
8.9	Conducted spurious emissions conveyed to the antenna	23
8.9.1	Definition	23
8.9.2	Method of measurement	23
8.9.3	Limit	23
8.10	Residual modulation of the transmitter	23
8.10.1	Definition	23
8.10.2	Method of measurement	23
8.10.3	Limit	23
8.11	Transient frequency behaviour of the transmitter	23
8.11.1	Definitions	23
8.11.2	Method of measurement	24
8.11.3	Limits	25
8.12	Cabinet radiation and conducted spurious emissions other than those conveyed to the antenna	27
8.12.1	Definitions	27
8.12.2	Method of measurement	27
8.12.3	Limits	28
9	Receiver	28
9.1	Harmonic distortion and rated audio frequency output power	28
9.1.1	Definition	28

9.1.2	Method of measurement	28
9.1.3	Limits	29
9.2	Audio frequency response	29
9.2.1	Definition	29
9.2.2	Method of measurement	29
9.2.3	Limits	29
9.3	Maximum usable sensitivity	30
9.3.1	Definition	30
9.3.2	Method of measurement	30
9.3.3	Limits	31
9.4	Co-channel rejection	31
9.4.1	Definition	31
9.4.2	Method of measurement	31
9.4.3	Limit	31
9.5	Adjacent channel selectivity	31
9.5.1	Definition	31
9.5.2	Method of measurement	31
9.5.3	Limits	32
9.6	Spurious response rejection	32
9.6.1	Definition	32
9.6.2	Method of measurement	32
9.6.3	Limit	32
9.7	Intermodulation response	32
9.7.1	Definition	32
9.7.2	Method of measurement	33
9.7.3	Limit	33
9.8	Blocking or desensitization	33
9.8.1	Definition	33
9.8.2	Method of measurement	33
9.8.3	Limit	33
9.9	Conducted spurious emissions conveyed to the antenna	34
9.9.1	Definition	34
9.9.2	Method of measurement	34
9.9.3	Limit	34
9.10	Amplitude response of the receiver limiter	34
9.10.1	Definition	34
9.10.2	Method of measurement	34
9.10.3	Limit	34
9.11	Receiver noise and hum level	34
9.11.1	Definition	34
9.11.2	Method of measurement	35
9.11.3	Limit	35
9.12	Squelch operation	35
9.12.1	Definition	35
9.12.2	Method of measurement	35
9.12.3	Limits	35
9.13	Squelch hysteresis	36
9.13.1	Definition	36
9.13.2	Method of measurement	36
9.13.3	Limit	36
9.14	Radiated spurious emissions	36
9.14.1	Definition	36
9.14.2	Method of measurements	36
9.14.3	Limit	37
10	Duplex operation	37
10.1	Receiver desensitization with simultaneous transmission and reception	37
10.1.1	Definition	37
10.1.2	Method of measurement	37
10.1.3	Limits	38
10.2	Receiver spurious response rejection	38

ITeH STANDARD PREVIEW

(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/21fb41cf-0521-41c6-a8ff-2547c43b5f80/sist-en-300-698-1-v1-2-1-2003>

Annex A (normative):	Power measuring receiver	39
A.1	Power measuring receiver specification	39
A.1.1	IF filter	39
A.1.2	Attenuation indicator	40
A.1.3	RMS value indicator	40
A.1.4	Oscillator and amplifier	40
Annex B (normative):	Automatic Transmitter Identification System (ATIS)	41
B.1	System description	41
B.1.1	General	41
B.1.2	Technical requirements	41
B.1.3	Signal requirements	41
B.1.4	Format of an ATIS signal sequence	42
B.1.5	Dot pattern	43
B.1.6	Phasing	43
B.1.7	Format specifier	44
B.1.8	Identification	44
B.1.9	End of sequence	44
B.1.10	Error check character	44
B.1.11	Conversion of a call sign to MID	44
B.2	ATIS encoder	46
B.2.1	Internally generated signals	46
B.2.2	Frequency error (demodulated signal)	46
B.2.2.1	Definition	46
B.2.2.2	Method of measurement	46
B.2.2.3	Limits	46
B.2.3	Modulation index	46
B.2.3.1	Definition	46
B.2.3.2	Method of measurement	46
B.2.3.3	Limits	46
B.2.4	Modulation rate	46
B.2.4.1	Definition	46
B.2.4.2	Method of measurement	47
B.2.4.3	Limits	47
B.2.5	Testing of the ATIS format	47
Annex C (normative):	Conversion of a radio call sign into an ATIS identification	48
History		49

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document is part 1 of a multi-part deliverable covering the Electromagnetic compatibility and Radio Spectrum Matters (ERM); Radio telephone transmitters and receivers for the maritime mobile service operating in the VHF bands used on inland waterways, as identified below:

Part 1: "Technical characteristics and methods of measurement";

Part 2: "Harmonized EN under article 3.2 of the R&TTE Directive";

Part 3: "Harmonized EN under article 3.3 (e) of the R&TTE Directive".

National transposition dates

Date of adoption of this EN:	EN://standards.iteh.ai/catalog/standards/sist/21fb41cf-052211-2547c43b5f80/sist-en-300-698-1-v1-2-1-2003	21 July 2000
Date of latest announcement of this EN (doa):		31 October 2000
Date of latest publication of new National Standard or endorsement of this EN (dop/e):		30 April 2001
Date of withdrawal of any conflicting National Standard (dow):		30 April 2001

Introduction

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Council Directive 98/34/EC [9] laying down a procedure for the provision of information in the field of technical standards and regulations.

1 Scope

The present document lays down the minimum requirements for VHF radio transmitters and receivers operating on board ships in frequency bands allocated to the maritime mobile service, used on inland waterways as defined by Regional Agreements or responsible Administrations.

The present document applies to VHF transmitters and receivers fitted with a 50 Ω external antenna socket or connector for use on board ships on inland waterways and operating in the bands between 156 and 174 MHz allocated to the maritime mobile service by the Radio Regulations [1], appendices 18 and 19.

For countries where the Automatic Transmitter Identification System (ATIS) is mandatory, the requirements of annex B apply.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, subsequent revisions do apply.
- A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.

- STANDARD PREVIEW**
(standards.iteh.ai)
- [1] ITU Radio Regulations (1990 Revised in 1994).
- [2] ITU-T Recommendation E.161 (1993): "Arrangement of digits, letters and symbols on telephones and other devices that can be used for gaining access to a telephone network".
- [3] ETSI EN 300 338: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Technical characteristics and methods of measurement for equipment for generation, transmission and reception of Digital Selective Calling (DSC) in the maritime MF, MF/HF and/or VHF mobile service".
- [4] IEC 61162-1: "Maritime navigation and radiocommunication equipment and systems - Digital interfaces - Part 1: Single talker and multiple listeners".
- [5] ISO 694: "Ships and marine technology - Positioning of magnetic compasses in ships".
- [6] ETSI ETR 028: "Radio Equipment and Systems (RES); Uncertainties in the measurement of mobile radio equipment characteristics".
- [7] ITU-T Recommendation P.53: "Psophometer for use on telephone-type circuits".
- [8] ITU-R Recommendation M.493: "Digital selective-calling system for use in the maritime mobile service".
- [9] Council Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations.

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in the Radio Regulations [1] apply.

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ad	amplitude difference
ATIS	Automatic Transmitter Identification System
DSC	Digital Selective Calling
DX	first transmission
emf	electromotive force
fd	frequency difference
RF	Radio Frequency
rms	root mean square
RX	re-transmission
SINAD	Signal + Noise + Distortion/Noise + Distortion
VSWR	Voltage Standing Wave Ratio

4 General requirements

4.1 Construction

The mechanical and electrical construction and finish of the equipment shall conform in all respects to good engineering practice, and the equipment shall be suitable for use on board ships.

All controls shall be of sufficient size to enable the usual control functions to be easily performed and the number of controls should be the minimum necessary for simple and satisfactory operation.

For the purpose of conformance testing, relevant technical documentation shall be supplied with the equipment.

The VHF maritime mobile service uses both single-frequency and two-frequency channels. For two-frequency channels the Radio Regulations require a separation of 4,6 MHz between the transmitting frequency and the receiving frequency.

The equipment shall be capable of operating on single frequency and two-frequency channels with manual control (simplex). It may also be capable of operating on two-frequency channels without manual control (duplex).

No scanning or multiple watch facilities shall be implemented.

The equipment shall be able to operate on all channels defined in the Radio Regulations [1], appendix 18.

Operation on channels 75 and 76 shall be prevented by appropriate means.

The equipment shall be so designed that use of channel 70 for purposes other than Digital Selective Calling (DSC) is prevented.

The Administration may grant permission for one or more channels in addition to those as defined by the Radio Regulations [1], appendix 18.

The possibility to apply automatic power reduction to any of these channels shall be available. It shall not be possible for the user to change the programmed settings of these channels.

The output power shall be automatically limited to a value between 0,5 and 1 W on the following channels:

- 6, 8, 10, 11, 12, 13, 14, 15, 17, 71, 72, 74 and 77.

It shall not be possible to transmit while any frequency synthesizer used within the transmitter is out of lock.

It shall not be possible to transmit during channel switching operations.

4.2 Controls and indicators

The equipment shall have a channel selector and shall indicate the designator, as shown in the Radio Regulations [1], appendix 18, of the channel at which the installation is set. The channel designator shall be legible irrespective of the external lighting conditions.

Where an input panel on the equipment for entering the digits 0 - 9 is provided, this shall conform to ITU-T Recommendation E.161 [2].

The equipment shall have the following additional controls and indicators:

- an on/off switch for the entire installation with a visual indication that the installation is in operation;
- a manual non-locking push to talk switch to operate the transmitter;
- a manual switch for reducing the transmitter output power to a value between 0,5 and 1 W;
- an audio frequency power volume control not affecting the audio level of the handset;
- a squelch control;
- a control for reducing the brightness of the equipment illumination to zero;
- an output power detector giving a visual indication that the carrier is being produced.

The equipment shall also meet the following requirements:

- the user shall not have access to any control which, if wrongly set, might impair the technical characteristics of the equipment;
- if the accessible controls are located on a separate console and if there are two or more control consoles, one of the consoles shall have priority over the others. If there are two or more control consoles, the operation of one console shall be indicated on the other consoles.

4.3 Handset and loudspeaker

The equipment shall be fitted with an integral loudspeaker and/or a socket for an external loudspeaker and shall have the facility to be fitted with a telephone handset or a microphone.

During transmission in simplex operation the receiver output shall be muted.

During transmission in duplex operation, only the handset shall be operative. Measures shall be taken to ensure correct operation when duplex is used and precautions shall be taken to prevent harmful electrical or acoustic feedback which might produce oscillations.

4.4 Switching time

The channel switching arrangement shall be such that the time necessary to change over from using one of the channels to using any other channel does not exceed 5 s.

The time necessary to change over from transmission to reception or vice versa, shall not exceed 0,3 s.

4.5 Safety precautions

Measures shall be taken to protect the equipment against the effects of overcurrent or overvoltage.

Measures shall be taken to prevent damage to the equipment if the electrical power source produces transient voltage variations and to prevent any damage that might arise from an accidental reversal of polarity of the electrical power source.

Means shall be provided for earthing exposed metallic parts of the equipment but this shall not cause any terminal of the source of electrical energy to be earthed.

All components and wiring in which the dc or ac voltage (other than radio-frequency voltage) produce, singly or in combination, peak voltages in excess of 50 V shall be protected against any accidental access and shall be automatically isolated from all electrical power sources if the protective covers are removed. Alternatively, the equipment shall be constructed in such a way as to prevent access to components operating at such voltages unless an appropriate tool is used such as a nut-spanner or screwdriver. Conspicuous warning labels shall be affixed both inside the equipment and on the protective covers.

No damage to the equipment shall occur when the antenna port is placed on open circuit or short circuit for a period of at least 5 minutes in each case.

In order to provide protection against damage due to the build up of static voltages at the antenna port, there shall be a dc path from the antenna port to chassis not exceeding 100 k Ω .

The information in any volatile memory device shall be protected from interruptions in the power supply of up to 60 s duration.

4.6 Class of emission and modulation characteristics

The equipment shall use phase modulation, G3E (frequency modulation with a pre-emphasis of 6 dB/octave) for speech, and G2B for ATIS and DSC signalling where provided.

The equipment shall be designed to operate with a channel separation of 25 kHz.

The frequency deviation (G3E) corresponding to 100 % modulation shall be 5 kHz as nearly as practicable.

4.7 Facilities for DSC transmission and reception

VHF transmitters and receivers with an integral DSC modem or to be used with an external DSC modem shall also be tested in accordance with EN 300 338 [3] for DSC equipment.

VHF transmitters and receivers to be used for DSC shall also comply with the following:

- a) the DSC facility shall be capable of operating on at least channel 70;
- b) if the equipment is designed for connection of an external modem to the audio frequency port, the input and output impedances should be 600 Ω free of earth;
- c) if the equipment is designed for connection to an external DSC modem with binary inputs and outputs for DSC signals, the logic level and the appropriate functions shall comply with IEC 61162-1 [4].

4.8 Labelling

All controls, instruments, indicators and ports shall be clearly labelled.

Details of the power supply from which the equipment is intended to operate shall be clearly indicated on the equipment.

The equipment shall be clearly marked on the exterior with the identification of the manufacturer, type designation of the equipment, and the serial number of the unit.

The compass safe distance (ISO 694 [5] Method B) shall be stated on the equipment or in the technical manual.

4.9 Warm up

After being switched on the equipment shall be operational within 1 minute.

5 Test conditions, power sources and ambient temperatures

5.1 Normal and extreme test conditions

Conformance tests shall be made under normal test conditions and also, where stated, under extreme test conditions (subclauses 5.4.1 and 5.4.2 applied simultaneously).

5.2 Test power source

During conformance testing, the equipment shall be supplied from a test power source capable of producing normal and extreme test voltages as specified in subclauses 5.3.2 and 5.4.2.

The internal impedance of the test power source shall be low enough for its effect on the test results to be negligible. For the purpose of testing the power source voltage shall be measured at the power input port of the equipment.

During testing, the power source voltages shall be maintained within a tolerance of ± 3 % relative to the voltage level at the beginning of each test.

5.3 Normal test conditions

5.3.1 Normal temperature and humidity

The normal temperature and humidity conditions for tests shall be a combination of temperature and humidity within the following ranges:

- temperature: +15°C to +35°C;
- relative humidity: 20 % to 75 %.

5.3.2 Normal power sources

5.3.2.1 Mains voltage and frequency

The normal test voltage for equipment to be connected to the ac mains shall be the nominal mains voltage. For the purpose of the present document, the nominal voltage shall be the declared voltage or any of the declared voltages for which the equipment is indicated as having been designed. The frequency of the test voltage shall be 50 Hz \pm 1 Hz.

5.3.2.2 Battery power source

Where the equipment is designed to operate from a battery, the normal test voltage shall be the nominal voltage of the battery (12 V, 24 V etc.).

5.3.2.3 Other power sources

For operation from other power sources the normal test voltage shall be that declared by the manufacturer.

5.4 Extreme test conditions

5.4.1 Extreme temperatures

For tests at extreme temperatures, measurements shall be made in accordance with subclause 5.5, at a lower temperature of $-15^{\circ}\text{C} \pm 3^{\circ}\text{C}$ and an upper temperature of $+55^{\circ}\text{C} \pm 3^{\circ}\text{C}$.

5.4.2 Extreme values of test power sources

5.4.2.1 Mains voltage

The extreme test voltages for equipment to be connected to the ac mains shall be the nominal mains voltage $\pm 10\%$.

5.4.2.2 Battery power source

Where the equipment is designed to operate from a battery, the extreme test voltages shall be 1,3 and 0,9 times the nominal voltage of the battery (12 V, 24 V etc.).

5.4.2.3 Other power sources

For operation from other power sources the extreme test voltages shall be agreed between the testing authority and the equipment manufacturer.

5.5 Procedure for tests at extreme temperatures

The equipment shall be placed in the test chamber at normal temperature. The maximum rate of raising or reducing the temperature of the chamber shall be $1^{\circ}\text{C}/\text{minute}$. The equipment shall be switched off during the temperature stabilizing periods.

[SIST EN 300 698-1 V1.2.1:2003](https://standards.iteh.ai/catalog/standards/sist/21fb41cf-0521-41e6-a8fc-297c430380/sist/en-300-698-1-v1-2-1-2003)

Before conducting tests at extreme temperatures, the equipment in the test chamber shall have reached thermal equilibrium and be subjected to the extreme temperature for a period of 10 hours to 16 hours.

For tests at the lower extreme temperature, the equipment shall then be switched on to standby or receive condition for one minute, after which the equipment shall meet the requirements of the present document.

For tests at the higher extreme temperature, the equipment shall then be switched on in the high power transmit condition for half an hour, after which the equipment shall meet the requirements of the present document.

The temperature of the chamber shall be maintained at the extreme temperatures for the whole duration of the performance test.

At the end of the test, with the equipment still in the chamber, the chamber shall be brought to normal temperature in not less than 1 hour. The equipment shall then be exposed to normal temperature and relative humidity for not less than 3 hours or until moisture has dispersed, whichever is the longer, before the next test is carried out. Alternatively, observing the same precautions, the equipment may be returned direct to the conditions required for the start of the next test.