



Designation: D4041/D4041M – 05 (Reapproved 2017)

Standard Practice for Determining Spray Patterns of Mechanical Pump Dispensers¹

This standard is issued under the fixed designation D4041/D4041M; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This practice covers the determination of spray patterns from pump dispensers.

1.2 The values stated in either SI units or inch-pound units are to be regarded separately as standard. The values stated in each system may not be exact equivalents; therefore, each system shall be used independently of the other. Combining values from the two systems may result in non-conformance with the standard.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

1.4 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 *ASTM Standards:*²

D996 Terminology of Packaging and Distribution Environments

3. Terminology

3.1 See Terminology D996 for applicable definitions.

4. Significance and Use

4.1 This practice can be used to compare spray patterns of different pump dispensers and of different products.

¹ This practice is under the jurisdiction of ASTM Committee F02 on Primary Barrier Packaging and is the direct responsibility of Subcommittee F02.30 on Mechanical Dispensers.

Current edition approved Nov. 1, 2017. Published November 2017. Originally approved in 1981. Last previous edition approved in 2010 as D4041/D4041M – 05(2010)¹. DOI: 10.1520/D4041_D4041M-05R17.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For Annual Book of ASTM Standards volume information, refer to the standard's Document Summary page on the ASTM website.

4.2 Spray patterns from pump dispensers will vary greatly with the design of the actuator and the nature of the liquid. Liquids with differing physical properties will not necessarily yield the same spray pattern when sprayed from the same actuator. Likewise, actuators of different designs will yield spray patterns distinct from each other when the same liquid is used.

5. Apparatus

5.1 *Target Support Stand*, approximately 250 mm wide with the vertical component approximately 400 mm high. The stand shall be attached securely at right angles to the horizontal component. The component shall be approximately 700 mm long and free of air turbulence, that will provide for stationary positioning of the paper target. An optional paper target is positioned along the length of the horizontal component to record fallout.

5.2 *Container Support Stand*, that will position the pump dispenser and container a specific distance and center them to the target. (Alternatively, the pump dispenser and container may be held firmly by hand on a flat, horizontal surface.)

5.3 *Measuring Rule*.

5.4 *Alcohol-Sensitive Paper*, cut to the desired length and width.

5.5 *Plain White Paper*, cut to the desired length and width.

5.6 *Dyes of Oil Base for Petroleum-Based Products or Water Base for Water-Based Products*—These dyes, when dissolved in the liquid, shall be in sufficient concentrate to give a strong color when sprayed onto the target paper.

NOTE 1—Dyes must be compatible and completely soluble in the test liquid. The dyed liquid shall be filtered prior to use to remove any solid particles.

6. Sampling

6.1 Select an appropriate number of dry, unused dispensers at random for the precision and bias desired.

7. Conditioning

7.1 If possible, condition the test specimens at $23 \pm 3^{\circ}\text{C}$ [$73 \pm 5.4^{\circ}\text{F}$] for not less than 4 h. If the test specimens are not