SLOVENSKI STANDARD
SIST EN 300 607-1 V7.2.1:2005

01-februar-2005

Digitalni celiļ ni telekomunikacijski sistem (faza 2+) - Specifikacija skladnosti mobilne postaje (MS) - 1. del: Specifikacija skladnosti (GSM 11.10-1, razliļ ica 7.2.1, izdaja 1998)

Digital cellular telecommunications system (Phase 2+) (GSM); Mobile Station (MS) conformance specification; Part 1: Conformance specification (GSM 11.10-1 version 7.2.1 Release 1998)

iTeh STANDARD PREVIEW
(standards.iteh.ai)
SIST EN 300 607-1 V7.2.1:2005
https://standards.iteh.ai/catalog/standards/sist/c9ac301b-0878-4c57-b0e0-e6a7988c5019/sist-en-300-607-1-v7-2-1-2005

Ta slovenski standard je istoveten z: **EN 300 607-1 Version 7.2.1**

ICS:

33.070.50	Globalni sistem za mobilno telekomunikacijo (GSM)	Global System for Mobile Communication (GSM)

SIST EN 300 607-1 V7.2.1:2005 **en**

2003-01.Slovenski inštitut za standardizacijo. Razmnoževanje celote ali delov tega standarda ni dovoljeno.

SIST EN 300 607-1 V7.2.1:2005

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 607-1 V7.2.1:2005
https://standards.iteh.ai/catalog/standards/sist/c9ac301b-0878-4c57-b0e0-e6a7988c5019/sist-en-300-607-1-v7-2-1-2005

SIST EN 300 607-1 V7.2.1:2005

ETSI EN 300 607-1 V7.2.1 (2000-08)

European Standard (Telecommunications series)

Digital cellular telecommunications system (Phase 2+); Mobile Station (MS) conformance specification; Part 1: Conformance specification (GSM 11.10-1 version 7.2.1 Release 1998)

iTeh STANDARD PREVIEW
(standards.iteh.ai)
SIST EN 300 607-1 V7.2.1:2005
https://standards.iteh.ai/catalog/standards/sist/c9ac301b-0878-4c57-b0e0-e6a7988c5019/sist-en-300-607-1-v7-2-1-2005

GLOBAL SYSTEM FOR MOBILE COMMUNICATIONS

SIST EN 300 607-1 V7.2.1:2005

Reference
REN/SMG-071110Q7R2-1

Keywords
Digital cellular telecommunications system, Global System for Mobile communications (GSM)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

SIST EN 300 607-1 V7.2.1:2005
https://standards.iteh.ai/catalog/standards/sist/c9ac301b-0878-4c57-b0e0-e6a79880d197/sist-en-300-607-1-v7.2.1-2005

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:
http://www.etsi.org

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at http://www.etsi.org/tb/status/

If you find errors in the present document, send your comment to:
editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2000.
All rights reserved.

SIST EN 300 607-1 V7.2.1:2005

Contents

Intellectual Property Rights....37
Foreword....37
1 Scope....38
2 References....38
3 Definitions, conventions, and applicability....44
3.1 Mobile station definition and configurations....44
3.2 Applicability....44
3.2.1 Applicability of this specification....44
3.2.2 Applicability of the individual tests....45
3.2.3 Applicability to terminal equipment....69
3.3 Definitions....69
3.4 Conventions for mathematical notations....69
3.4.1 Mathematical signs....69
3.4.2 Powers to the base 10....69
3.5 Conventions on electrical terms....70
3.5.1 Radio Frequency (RF) input signal level....70
3.5.2 Reference sensitivity level....70
3.5.3 Power level of fading signal....70
3.6 Terms on test conditions....71
3.6.1 Radio test conditions....71
4 Test Equipment....72
4.1 Terms used to describe test equipment in this EN....72
4.2 Functional requirements of test equipment....72
5 Testing methodology in general (layers 1, 2, and 3)....72
5.1 Testing of optional functions and procedures....72
5.2 Test interfaces and facilities....73
5.3 Different protocol layers....73
5.4 Information to be provided by the apparatus supplier....73
5.5 Definitions of transmit and receive times....73
6 Reference test methods....74
6.1 General....74
6.2 Choice of frequencies in the frequency hopping mode....74
6.3 "Ideal" radio conditions....74
6.4 Standard test signals....75
6.5 Power (control) levels....75
7 Implicit testing....75
8 Measurement uncertainty....75
9 Format of tests....75
10 Generic call set up procedures....76
10.1 Generic call set-up procedure for mobile terminating speech calls....76
10.2 Generic call set-up procedure for mobile originating speech calls....81
10.3 Generic call set-up procedure for mobile terminating data calls....84
10.4 Generic call set-up procedure for mobile originating data calls....86
10.5 Generic call set-up procedure for mobile terminating multislot configuration, minimum number of timeslots allocated....90

iTeh STANDARD PREVIEW
(standards.iteh.ai)
SIST EN 300 607-1 V7.2.1:2005
https://standards.iteh.ai/catalog/standards/sist/c9ac301b-0878-4c57-b0e0-e6a7988c5019/sist-en-300-607-1-v7-2-1-2005

SIST EN 300 607-1 V7.2.1:2005

10.6 Generic call set-up procedure for mobile originating multislot configuration, minimum number of timeslots allocated 93

11 General tests 97
11.1 Verification of support and non-support of services (multiple numbering scheme or ISDN) 97
11.1.1 Mobile Terminated (MT) calls 97
11.1.2 Mobile Originated (MO) calls 98
11.2 Verification of support of the single numbering scheme 99
11.3 Verification of non-support of services (Advice of Charge Charging (AoCC)) 100
11.4 Verification of non-support of services (call hold) 102
11.5 Verification of non-support of services (multiparty) 102
11.6 Verification of non-support of feature (Fixed Dialling Number (FDN)) 103
11.7 IMEI Security 104
11.8 Coding of the Bearer Capability information element 105
11.8.1 Network to MS Direction 106
11.8.1.1 BS 21 to 26 - Asynchronous Service 106
11.8.1.1.1 BS 21 106
11.8.1.1.2 BS 22 110
11.8.1.1.3 BS 24 110
11.8.1.1.4 BS 25 110
11.8.1.1.5 BS 26 110
11.8.1.1.6 BS 23 110
11.8.1.2 BS 31 to 34 - Synchronous Service 111
11.8.1.2.1 BS 32 111
11.8.1.2.2 BS 31 115
11.8.1.2.3 BS 33 116
11.8.1.2.4 BS 34 116
11.8.1.3 BS 61 - Alternate Speech / Data 116
11.8.1.3.1 Speech/Asynchronous Data, Transparent 117
11.8.1.3.2 Speech/Asynchronous Data, Non Transparent 119
11.8.1.3.3 Speech/Synchronous Data 121
11.8.1.4 BS 81 - Speech followed by Data 122
11.8.1.4.1 Speech followed by Asynchronous Data 122
11.8.1.4.2 Speech followed by Synchronous Data 122
11.8.1.5 TS 61 - Alternate Speech / Facsimile group 3 122
11.8.1.5.1 TS 61 - Alternate Speech / Facsimile group 3, Transparent 123
11.8.1.5.2 TS 61 - Alternate Speech / Facsimile group 3, Non-Transparent 124
11.8.1.6 TS 62 - Automatic Facsimile group 3 125
11.8.2 MS to SS direction 125
11.8.2.1 BS 21 to 26 - Asynchronous Service 125
11.8.2.1.1 BS 21 126
11.8.2.1.2 BS 22 130
11.8.2.1.3 BS 24 130
11.8.2.1.4 BS 25 130
11.8.2.1.5 BS 26 130
11.8.2.1.6 BS 23 130
11.8.2.2 BS 31 to 34 - Synchronous Service 131
11.8.2.2.1 BS 32 131
11.8.2.2.2 BS 31 135
11.8.2.2.3 BS 33 136
11.8.2.2.4 BS 34 136
11.8.2.3 BS 41 to 46 - PAD Access Asynchronous 137
11.8.2.3.1 [2)] BS 41 137
11.8.2.3.2 BS 42 139
11.8.2.3.3 BS 44 139
11.8.2.3.4 BS 45 139
11.8.2.3.5 BS 46 139
11.8.2.3.6 BS 43 139

iTeh STANDARD PREVIEW
(standards.iteh.ai)
SIST EN 300 607-1 V7.2.1:2005
https://standards.iteh.ai/catalog/standards/sist/e9ac301b-0878-4e57-b0e0-c6a7e88e5919/sist-en-300-607-1-v7.2.1-2005

SIST EN 300 607-1 V7.2.1:2005

11.8.2.4 BS 51 to 53 - Packet Service Synchronous 140
11.8.2.4.1 [2)] BS 51 140
11.8.2.4.2 BS 52 140
11.8.2.4.3 BS 53 140
11.8.2.5 BS 61 - Alternate Speech / Data 141
11.8.2.5.1 Speech/Asynchronous Data, Transparent 141
11.8.2.5.2 Speech/Asynchronous Data, Non Transparent 144
11.8.2.5.3 Speech/Synchronous Data 146
11.8.2.6 BS 81 - Speech followed by Data 147
11.8.2.6.1 Speech followed by Asynchronous Data 147
11.8.2.6.2 Speech followed by Synchronous Data 147
11.8.2.7 TS 61 - Alternate Speech / Facsimile group 3 147
11.8.2.7.1 TS 61 - Alternate Speech / Facsimile group 3, Transparent 148
11.8.2.7.2 TS 61 - Alternate Speech / Facsimile group 3, Non Transparent 149
11.8.2.8 TS 62 - Automatic Facsimile group 3 150
11.8.2.9 TS 11 and TS 12- Speech 150
11.8.2.9.1 Support of only full/half rate speech version 1 150
11.8.2.9.2 Support of speech full rate version 2 (Enhanced Full Rate) 150

12 Transceiver 152
12.1 Conducted spurious emissions 152
12.1.1 MS allocated a channel 152
12.1.2 MS in idle mode 154
12.2 Radiated spurious emissions 155
12.2.1 MS allocated a channel 155
12.2.2 MS in idle mode 157
12.3 Conducted spurious emissions for MS supporting the R-GSM frequency band 159
12.3.1 MS allocated a channel 159
12.3.2 MS in idle mode 161
12.4 Radiated spurious emissions for MS supporting the R-GSM frequency band 162
12.4.1 MS allocated a channel 163
12.4.2 MS in idle mode 165

13 Transmitter 167
13.1 Frequency error and phase error 167
13.2 Frequency error under multipath and interference conditions 170
13.3 Transmitter output power and burst timing 172
13.4 Output RF spectrum 180
13.5 Intermodulation attenuation 185
13.6 Frequency error and phase error in HSCSD multislot configurations 186
13.7 Transmitter output power and burst timing in HSCSD configurations 189
13.8 Output RF spectrum in HSCSD multislot configuration 198
13.9 Output RF spectrum for MS supporting the R-GSM band 203
13.10 [Reserved for future GSM test] 208
13.11 [Reserved for future GSM test] 208
13.12 [Reserved for future GSM test] 208
13.13 [Reserved for future GSM test] 208
13.14 [Reserved for future GSM test] 208
13.15 [Reserved for future GSM test] 208
13.16 GPRS transmitter tests 208
13.16.1 Frequency error and phase error in GPRS multislot configuration 208
13.16.2 Transmitter output power in GPRS multislot configuration 211
13.16.3 Output RF spectrum in GPRS multislot configuration 219

14 Receiver 225
14.1 Bad frame indication 231
14.1.1 Bad frame indication - TCH/FS 231
14.1.1.1 Bad frame indication - TCH/FS - Random RF input 231

iTeh STANDARD PREVIEW
(standards.iteh.ai)
SIST EN 300 607-1 V7.2.1:2005
https://standards.iteh.ai/catalog/standards/sist/e9ae301b-0878-4e57-b0e0-e6a7988e5019/sist-en-300-607-1-v7.2.1-2005

SIST EN 300 607-1 V7.2.1:2005

14.1.1.2 Bad frame indication - TCH/FS - Frequency hopping and downlink DTX 233
14.1.2 Bad frame indication - TCH/HS 234
14.1.2.1 Bad frame indication - TCH/HS - Random RF input 234
14.1.2.2 Bad frame indication - TCH/HS - Frequency hopping and downlink DTX 235
14.1.3 Bad frame indication - TCH/FS - Frequency hopping and downlink DTX - Phase 2 MS in a phase 1 network 236
14.1.4 Bad frame indication - TCH/HS - Frequency hopping and downlink DTX - Phase 2 MS in a phase 1 network 238
14.2 Reference sensitivity 240
14.2.1 Reference sensitivity - TCH/FS 240
14.2.2 Reference sensitivity - TCH/HS (Speech frames) 242
14.2.3 Reference sensitivity - FACCH/F 244
14.2.4 Reference sensitivity - FACCH/H 245
14.2.5 Reference sensitivity - full rate data channels 246
14.2.6 Reference sensitivity - half rate data channels 247
14.2.7 Reference sensitivity - TCH/EFS 248
14.2.8 Reference sensitivity - full rate data channels in multislot configuration 250
14.2.9 Reference sensitivity - TCH/FS for MS supporting the R-GSM band 252
14.3 Usable receiver input level range 253
14.4 Co-channel rejection 255
14.4.1 Co-channel rejection - TCH/FS 255
14.4.2 Co-channel rejection - TCH/HS 257
14.4.3 Co-channel rejection - TCH/HS (SID frames) 259
14.4.4 Co-channel rejection - FACCH/F 260
14.4.5 Co-channel rejection - FACCH/H 261
14.4.6 Co-channel rejection - TCH/EFS 262
14.4.7 Receiver performance in the case of frequency hopping and co-channel interference on one carrier 264
14.5 Adjacent channel rejection 265
14.5.1 Adjacent channel rejection - speech channels 265
14.5.2 Adjacent channel rejection - control channels 268
14.6 Intermodulation rejection 270
14.6.1 Intermodulation rejection - speech channels 270
14.6.2 Intermodulation rejection - control channels 271
14.7 Blocking and spurious response 273
14.7.1 Blocking and spurious response - speech channels 273
14.7.2 Blocking and spurious response - control channels 276
14.7.3 Blocking and spurious response - speech channels for MS supporting the R-GSM band 279
14.7.4 Blocking and spurious response - control channels for MS supporting the R-GSM band 282
14.8 AM suppression 285
14.8.1 AM suppression - speech channels 285
14.8.2 AM suppression - control channels 287
14.9 Paging performance at high input levels 288
14.10 [Reserved for future GSM test] 289
14.11 [Reserved for future GSM test] 289
14.12 [Reserved for future GSM test] 289
14.13 [Reserved for future GSM test] 289
14.14 [Reserved for future GSM test] 289
14.15 [Reserved for future GSM test] 289
14.16 GPRS receiver tests 289
14.16.1 Minimum Input level for Reference Performance 291
14.16.2 Co-channel rejection 295
14.16.2.1 Co-channel rejection for packet channels 295

15 Timing advance and absolute delay 298
15.1 Definition and applicability 298
15.2 Conformance requirement 298
15.3 Test purpose 298
15.4 Method of test 298

iTeh STANDARD PREVIEW
(standards.iteh.ai)
SIST EN 300 607-1 V7.2.1:2005
https://standards.iteh.ai/catalog/standards/sist/c9ac301b-0878-4c57-b0e0-e6a7988c5019/sist-en-300-607-1-v7-2-1-2005

SIST EN 300 607-1 V7.2.1:2005

15.5 Test requirement....299
15.6 GPRS Timing advance and absolute delay....299

16 Reception time tracking speed....303
16.1 Definition and applicability....303
16.2 Conformance requirement....303
16.3 Test purpose....303
16.4 Method of test....303
16.5 Test requirement....304

17 Access times during handover....305
17.1 Intra cell channel change....305
17.2 Inter cell handover....307

18 Temporary reception gaps....310
18.1 Temporary reception gaps, single slot....310
18.2 Temporary reception gaps in HSCSD multislot configurations....311

19 Channel release after unrecoverable errors....314
19.1 Channel release after unrecoverable errors -1....314
19.2 Channel release after unrecoverable errors - 2....315
19.3 Channel release after unrecoverable errors - 3....316

20 Cell selection and reselection....318
20.1 Cell selection....320
20.2 Cell selection with varying signal strength values....321
20.3 Basic cell reselection....323
20.4 Cell reselection using TEMPORARY_OFFSET, CELL_RESELECT_OFFSET, POWER_OFFSET and PENALTY_TIME parameters....325
20.5 Cell reselection using parameters transmitted in the System Information type 2bis, type 2ter, type 7 and type 8 messages....327
20.6 Cell reselection timings....329
20.7 Priority of cells....331
20.8 Cell reselection when C1 (serving cell) < 0 for 5 seconds....332
20.9 Running average of the surrounding cell BCCH carrier signal levels....334
20.10 Running average of the serving cell BCCH carrier signal level....335
20.11 Updating the list of six strongest neighbour carriers and decoding the BCCH information of a new carrier on the list....336
20.12 Decoding the BCCH information of the neighbour carriers on the list of six strongest neighbour carriers....337
20.13 Decoding the BSIC of the neighbour carriers on the list of six strongest neighbour carriers....338
20.14 Emergency calls....339
20.15 Cell reselection due to MS rejection "LA not allowed"....340
20.16 Downlink signalling failure....342
20.17 Cell selection if no suitable cell found in 10 s....343
20.18 Cell reselection due to MS rejection "Roaming not allowed in this LA"....344
20.19 Cell selection on release of SDCCH and TCH....346
20.20 Multiband cell selection and reselection....347
20.20.1 Multiband cell selection and reselection / Cell Selection....347
20.20.2 Multiband cell selection and reselection / Cell reselection....349
20.21 R-GSM cell selection and reselection....351
20.21.1 R-GSM cell selection....352
20.21.2 R-GMS cell selection with varying signal strength values....354
20.21.3 R-GSM basic cell reselection....356
20.21.4 R-GSM cell reselection using TEMPORARY_OFFSET, CELL_RESELECT_OFFSET, POWER_OFFSET and PENALTY_TIME parameters....358
20.21.5 R-GSM cell reselection using parameters transmitted in the System Information type 2bis, type 2ter, type 7 and type 8 messages....360
20.21.6 R-GSM cell reselection timings....361
20.21.7 R-GSM priority of cells....363

iTeh STANDARD PREVIEW
(standards.iteh.ai)
SIST EN 300 607-1 V7.2.1:2005
https://standards.iteh.ai/catalog/standards/sist/c9ac301b-0878-4c57-b0e0-e6a7988e5010/sist-en-300-607-1-v7-2-1-2005

SIST EN 300 607-1 V7.2.1:2005

20.21.8 R-GSM cell reselection when C1 (serving cell) < 0 for 5 seconds 364
20.21.9 R-GSM running average of the surrounding cell BCCH carrier signal levels 366
20.21.10 R-GSM running average of the serving cell BCCH carrier signal level 367
20.21.11 Updating the list of six strongest neighbour carriers and decoding the BCCH information of a new carrier on the list 368
20.21.12 R-GSM decoding the BCCH information of the neighbour carriers on the list of six strongest neighbour carriers 369
20.21.13 R-GSM decoding the BSIC of the neighbour carriers on the list of six strongest neighbour carriers 370
20.21.14 R-GSM emergency calls 371
20.21.15 R-GSM cell reselection due to MS rejection "LA not allowed" 372
20.21.16 R-GSM downlink signalling failure 374
20.21.17 R-GSM cell selection if no suitable cell found in 10 s 375
20.21.18 R-GSM cell reselection due to MS rejection "Roaming not allowed in this LA" 376
20.21.19 R-GSM cell selection on release of SDCCH and TCH 377
20.22 GPRS Cell Selection and Reselection 378
20.22.1 Cell selection 380
20.22.2 Cell reselection in Packet Idle mode 381
20.22.3 Priority of cells 383
20.22.4 Cell re-selection with cells in different routing area 384
20.22.5 Network controlled Cell re-selection in Transfer Mode 386
20.22.6 Cell reselection timings 387
20.22.7 Downlink signalling failure 388

21 Received signal measurements 390
21.1 Signal strength 390
21.2 Signal strength selectivity 393
21.3 Signal quality under static conditions 394
21.3.1 Signal quality under static conditions - TCH/FS 394
21.3.2 Signal quality under static conditions - TCH/HS 396
21.4 Signal quality under TU50 propagation conditions 398
21.5 Received signal measurements in HSCSD multislot configuration 400
21.5.1 Signal strength 400

22 Transmit power control timing and confirmation 405
22.1 Transmit power control timing and confirmation, single slot 405
22.2 Transmit power control timing and confirmation in HSCSD multislot configurations 406
22.3 GPRS Uplink Power Control - Use of α and Γ_{CH} parameters 408
22.4 GPRS Uplink Power Control – Independence of TS Power Control 411

23 Single frequency reference 413

24 Tests of the layer 1 signalling functions 413

25 Tests of the layer 2 signalling functions 414
25.1 Introduction, objective and scope 414
25.1.1 General 414
25.1.2 Test configurations 414
25.1.3 Pre-conditions 414
25.1.4 Layer 2 test frames 415
25.1.5 Establishment of the dedicated physical resource 416
25.1.6 Release of the dedicated physical resource 416
25.2 Test sequences 416
25.2.1 Initialization 417
25.2.1.1 Initialization when contention resolution required 417
25.2.1.1.1 Normal initialization 417
25.2.1.1.2 Initialization failure 418
25.2.1.1.3 Initialization denial 421
25.2.1.1.4 Total initialization failure 422
25.2.1.2 Initialization, contention resolution not required 423

iTeh STANDARD PREVIEW
(standards.iteh.ai)
SIST EN 300 607-1 V7.2.1:2005
https://standards.iteh.ai/catalog/standards/sist/e0a7988e-5019-4e57-b0e0-e6a7988e5019/sist-en-300-607-1-v7.2.1-2005

SIST EN 300 607-1 V7.2.1:2005

25.2.1.2.1 Normal initialization without contention resolution 423
25.2.1.2.2 Initialization failure 424
25.2.1.2.3 Initialization denial 425
25.2.1.2.4 Total initialization failure 426
25.2.2 Normal information transfer 427
25.2.2.1 Sequence counting and I frame acknowledgements 427
25.2.2.2 Receipt of an I frame in the timer recovery state 430
25.2.2.3 Segmentation and concatenation 432
25.2.3 Normal layer 2 disconnection 435
25.2.4 Test of link failure 435
25.2.4.1 I frame loss (MS to SS) 435
25.2.4.2 RR response frame loss (SS to MS) 437
25.2.4.3 RR response frame loss (MS to SS) 437
25.2.5 Test of frame transmission with incorrect C/R values 438
25.2.5.1 I frame with C bit set to zero 438
25.2.5.2 SABM frame with C bit set to zero 439
25.2.6 Test of errors in the control field 440
25.2.6.1 N(S) sequence error 440
25.2.6.2 N(R) sequence error 442
25.2.6.3 Improper F bit 442
25.2.7 Test on receipt of invalid frames 443

26 Testing of layer 3 functions 448
26.1 Default conditions and structured sequence of tests 448
26.1.1 Default test conditions during layer 3 tests 448
26.1.2 Structured sequence of the tests 450
26.1.3 General rules for message parameters 450
26.1.4 General rules for layer 3 testing 451
26.1.5 Format of layer 3 test descriptions 451
26.2 Initial tests 453
26.2.1 Channel request 453
26.2.1.1 Channel request / initial time 453
26.2.1.2 Channel request / repetition time 454
26.2.1.3 Channel request / random reference 456
26.2.2 IMSI detach and IMSI attach 457
26.2.3 Sequenced MM / CM message transfer 461
26.2.4 Establishment cause 462
26.3 Test of MS functions in idle mode 471
26.3.1 Initial conditions 471
26.3.2 MS indication of available PLMNs 474
26.3.3 MS will send only if BSS is "on air" 474
26.3.4 Manual mode of PLMN selection 475
26.4 Lower layer failures in layer 3 testing 477
26.4.1 Introduction 477
26.4.2 Layer 1 reception failures 477
26.4.3 Data link layer failures 477
26.4.4 Lower layer failures, used for the tests in clause 25 477
26.5 Handling of unknown, unforeseen, and erroneous protocol data, and of parallel transactions 478
26.5.1 Handling of unknown, unforeseen, and erroneous protocol data, and of parallel transactions / unknown protocol discriminator 478
26.5.2 Handling of unknown, unforeseen, and erroneous protocol data, and of parallel transactions / TI and skip indicator 479
26.5.2.1 TI and skip indicator / RR 479
26.5.2.1.1 TI and skip indicator / RR / Idle Mode 479
26.5.2.1.2 TI and skip indicator / RR / RR-Connection established 480
26.5.2.2 TI and skip indicator / MM 482
26.5.2.3 TI and skip indicator / CC 483

iTeh STANDARD PREVIEW
(standards.iteh.ai)
SIST EN 300 607-1 V7.2.1:2005
https://standards.iteh.ai/catalog/standards/sist/e9ac301b-0878-4e57-b0e0-c0a7988e5019/sist-en-300-607-1-v7.2.1-2005

SIST EN 300 607-1 V7.2.1:2005

26.5.3 Handling of unknown, unforeseen, and erroneous protocol data, and of parallel transactions / undefined or unexpected message type....485
26.5.3.1 Undefined or unexpected message type / undefined message type / CC....485
26.5.3.2 Undefined or unexpected message type / undefined message type / MM....486
26.5.3.3 Undefined or unexpected message type / undefined message type / RR....488
26.5.3.4 Undefined or unexpected message type / unexpected message type / CC....489
26.5.4 Handling of unknown, unforeseen, and erroneous protocol data, and of parallel transactions / unforeseen information elements in the non-imperative message part....490
26.5.4.1 Unforeseen information elements in the non-imperative message part / duplicated information elements....490
26.5.5 Handling of unknown, unforeseen, and erroneous protocol data, and of parallel transactions / non-semantical mandatory IE errors....492
26.5.5.1 Non-semantical mandatory IE errors / RR....492
26.5.5.1.1 Non-semantical mandatory IE errors / RR / missing mandatory IE error....492
26.5.5.1.2 Non-semantical mandatory IE errors / RR / comprehension required....494
26.5.5.2 Non-semantical mandatory IE errors / MM....496
26.5.5.2.1 Non-semantical mandatory IE errors / MM / syntactically incorrect mandatory IE....496
26.5.5.2.2 Non-semantical mandatory IE errors / MM / syntactically incorrect mandatory IE....497
26.5.5.2.3 Non-semantical mandatory IE errors / MM / comprehension required....498
26.5.5.3 Non-semantical mandatory IE errors / CC....500
26.5.5.3.1 Non-semantical mandatory IE errors / CC / missing mandatory IE....500
26.5.5.3.2 Non-semantical mandatory IE errors / CC / comprehension required....502
26.5.6 Handling of unknown, unforeseen, and erroneous protocol data, and of parallel transactions / unknown IE, comprehension not required....503
26.5.6.1 Unknown information elements in the non-imperative message part / MM....503
26.5.6.1.1 Unknown IE, comprehension not required / MM / IE unknown in the protocol....503
26.5.6.1.2 Unknown IE, comprehension not required / MM / IE unknown in the message....505
26.5.6.2 Unknown information elements in the non-imperative message part / CC....506
26.5.6.2.1 Unknown information elements in the non-imperative message part / CC / Call establishment....506
26.5.6.2.2 Unknown information elements in the non-imperative message part / CC / disconnect....507
26.5.6.2.3 Unknown information elements in the non-imperative message part / CC / release....508
26.5.6.2.4 Unknown information elements in the non-imperative message part / CC / release complete....510
26.5.6.3 Unknown IE in the non-imperative message part, comprehension not required / RR....511
26.5.7 Handling of unknown, unforeseen, and erroneous protocol data, and of parallel transactions / spare bits....513
26.5.7.1 Spare bits / RR....513
26.5.7.1.1 Spare bits / RR / paging channel....513
26.5.7.1.2 Spare bits / RR / BCCH....514
26.5.7.1.3 Spare bits / RR / AGCH....515
26.5.7.1.4 Spare bits / RR / Connected Mode....517
26.5.7.2 Spare bits / MM....519
26.5.7.3 Spare bits / CC....520
26.5.8 Default contents of messages....522
26.6 Test of the elementary procedures for radio resource management....525
26.6.1 Immediate assignment....525
26.6.1.1 Immediate assignment / SDCCH or TCH assignment....525
26.6.1.2 Immediate assignment / extended assignment....526
26.6.1.3 Immediate assignment / assignment rejection....528
26.6.1.4 Immediate assignment / ignore assignment....530
26.6.1.5 Immediate assignment after immediate assignment reject....532
26.6.2 Test of paging....533
26.6.2.1 Normal paging....533
26.6.2.1.1 Paging / normal / type 1....533
26.6.2.1.2 Paging / normal / type 2....536
26.6.2.1.3 Paging / normal / type 3....538
26.6.2.2 Paging / extended....539
26.6.2.3 Paging / reorganization....542
26.6.2.3.1 Paging / reorganization / procedure 1....542

iTeh STANDARD PREVIEW
(standards.iteh.ai)
SIST EN 300 607-1 V7.2.1:2005
https://standards.iteh.ai/catalog/standards/sist/c9ec301b-0838-4c57-b0e0-a6a7988e5010/sist-en-300-607-1-v7.2.1-2005

SIST EN 300 607-1 V7.2.1:2005

26.6.2.3.2 Paging / reorganization / procedure 2 545
26.6.2.4 Paging / same as before 546
26.6.2.5 Paging / multislot CCCH 547
26.6.3 Test of measurement report 548
26.6.3.1 Measurement / no neighbours 548
26.6.3.2 Measurement / all neighbours present 552
26.6.3.3 Measurement / barred cells and non-permitted NCCs 556
26.6.3.4 Measurement / DTX 560
26.6.3.5 Measurement / Frequency Formats 564
26.6.3.6 Measurement / multiband environment 568
26.6.3.7 Measurement / new cell reporting 573
26.6.4 Test of the channel assignment procedure 579
26.6.4.1 Dedicated assignment / successful case 579
26.6.4.2 Dedicated assignment / failure 589
26.6.4.2.1 Dedicated assignment / failure / failure during active state 589
26.6.4.2.2 Dedicated assignment / failure / general case 591
26.6.5 Test of handover 592
26.6.5.1 Handover / successful / active call / non-synchronized 593
26.6.5.2 Handover / successful / call under establishment / non-synchronized 606
26.6.5.3 Handover / successful / active call / finely synchronized 624
26.6.5.4 Handover / successful / call under establishment / finely synchronized 629
26.6.5.5 Pre-synchronized handovers 639
26.6.5.5.1 Handover / successful / active call / pre-synchronized / Timing Advance IE not included 639
26.6.5.5.2 Handover / successful / call being established / pre-synchronized / timing advance IE is included / reporting of observed time difference requested 641
26.6.5.6 Handover / successful / active call / pseudo synchronized 643
26.6.5.7 Handover / successful / active call / non-synchronized / reporting of observed time difference requested 645
26.6.5.8 Handover / layer 3 failure 647
26.6.5.9 Handover / layer 1 failure 648
26.6.6 Test of frequency redefinition 649
26.6.6.1 Frequency redefinition 649
26.6.7 Test of the channel mode modify procedure 655
26.6.7.1 Test of the channel mode modify procedure / full rate 655
26.6.7.2 Test of the channel mode modify procedure / half rate 657
26.6.8 Test of ciphering mode setting 660
26.6.8.1 Ciphering mode / start ciphering 660
26.6.8.2 Ciphering mode / no ciphering 661
26.6.8.3 Ciphering mode / old cipher key 663
26.6.8.4 Ciphering mode / change of mode, algorithm and key 664
26.6.8.5 Ciphering mode / IMEISV request 671
26.6.9 Test of additional assignment 673
26.6.10 Test of partial release 673
26.6.11 Test of classmark 673
26.6.11.1 Classmark change 673
26.6.11.2 Classmark interrogation 675
26.6.12 Test of channel release 677
26.6.12.1 Channel release / SDCCH 677
26.6.12.2 Channel release / SDCCH - no L2 ACK 679
26.6.12.3 Channel release / TCH-F 680
26.6.12.4 Channel release / TCH-F - no L2 ACK 681
26.6.13 Test of starting time 683
26.6.13.1 Dedicated assignment with starting time / successful case / time not elapsed 684
26.6.13.2 Dedicated assignment with starting time / successful case / time elapsed 686
26.6.13.3 Dedicated assignment with starting time and frequency redefinition / failure case / time not elapsed 688
26.6.13.4 Dedicated assignment with starting time and frequency redefinition / failure case / time elapsed 691
26.6.13.5 Handover with starting time / successful case / time not elapsed 693

iTeh STANDARD PREVIEW
(standards.iteh.ai)
SIST EN 300 607-1 V7.2.1:2005
https://standards.iteh.ai/catalog/standards/sist/c9ac301b-0878-4c57-b0e0-e6a7988c5019/sist-en-300-607-1-v7-2-1-2005

SIST EN 300 607-1 V7.2.1:2005

26.6.13.6 Handover with starting time / successful case / time elapsed 695
26.6.13.7 Handover with starting time and frequency redefinition / failure case / time not elapsed 697
26.6.13.8 Handover with starting time and frequency redefinition / failure case / time elapsed 700
26.6.13.9 Immediate assignment with starting time / successful case / time not elapsed 703
26.6.13.10 Immediate assignment with starting time / successful case / time elapsed 704
26.6.14 Default contents of GSM 900 layer 3 messages for RR tests 706
26.6.15 Default contents of DCS 1 800 layer 3 messages for RR tests 716
26.7 Elementary procedures of mobility management 727
26.7.1 TMSI reallocation 727
26.7.2 Authentication 730
26.7.2.1 Authentication accepted 730
26.7.2.2 Authentication rejected 731
26.7.3 Identification 734
26.7.3.1 General Identification 734
26.7.3.2 Handling of IMSI shorter than the maximum length 736
26.7.4 Location updating 739
26.7.4.1 Location updating / accepted 739
26.7.4.2 Location updating / rejected 744
26.7.4.2.1 Location updating / rejected / IMSI invalid 744
26.7.4.2.2 Location updating / rejected / PLMN not allowed 747
26.7.4.2.3 Location updating / rejected / location area not allowed 751
26.7.4.2.4 Location updating / rejected / roaming not allowed in this location area 754
26.7.4.3 Location updating / abnormal cases 761
26.7.4.3.1 Location updating / abnormal cases / random access fails 761
26.7.4.3.2 Location updating / abnormal cases / attempt counter less or equal to 4, LAI different 763
26.7.4.3.3 Location updating / abnormal cases / attempt counter equal to 4 768
26.7.4.3.4 Location updating / abnormal cases / attempt counter less or equal to 4, stored LAI equal to broadcast LAI 775
26.7.4.4 Location updating / release / expiry of T3240 781
26.7.4.5 Location updating / periodic 782
26.7.4.5.1 Location updating / periodic spread 782
26.7.4.5.2 Location updating / periodic normal / test 1 784
26.7.4.5.3 Location updating / periodic normal / test 2 786
26.7.4.5.4 Location updating / periodic HPLMN search 789
26.7.4.6 Location updating / interworking of attach and periodic 793
26.7.5 MM connection 794
26.7.5.1 Introduction 794
26.7.5.2 MM connection / establishment with cipher 795
26.7.5.3 MM connection / establishment without cipher 796
26.7.5.4 MM connection / establishment rejected 797
26.7.5.5 MM connection / establishment rejected cause 4 798
26.7.5.6 MM connection / expiry T3230 800
26.7.5.7 MM connection / abortion by the network 801
26.7.5.7.1 MM connection / abortion by the network / cause #6 801
26.7.5.7.2 MM connection / abortion by the network / cause not equal to #6 804
26.7.5.8 MM connection / follow-on request pending 805
26.7.5.8.1 MM connection / follow-on request pending / test 1 805
26.7.5.8.2 MM connection / follow-on request pending / test 2 806
26.7.5.8.3 MM connection / follow-on request pending / test 3 808
26.7.6 Default contents of messages 809
26.8 Tests related to circuit switched call control 813
26.8.1 Circuit switched Call Control (CC) state machine verification 813
26.8.1.1 General on CC state machine verification 813
26.8.1.2 Establishment of an outgoing call 814
26.8.1.2.1 Outgoing call / U0 null state 816
26.8.1.2.2 Outgoing call / U0.1 MM connection pending 817
26.8.1.2.3 Outgoing call / U1 call initiated 821

iTeh STANDARD PREVIEW
(standards.iteh.ai)
SIST EN 300 607-1 V7.2.1:2005
https://standards.iteh.ai/catalog/standards/sist/c9ac301b-0878-4c57-b0e0-e6a7988e5010/sist-en-300-607-1-v7-2-1-2005

SIST EN 300 607-1 V7.2.1:2005

26.8.1.2.4 Outgoing call / U3 MS originating call proceeding 830
26.8.1.2.5 Outgoing call / U4 call delivered 846
26.8.1.2.6 U10 call active 856
26.8.1.2.7 U11 disconnect request 864
26.8.1.2.8 U12 disconnect indication 870
26.8.1.2.9 Outgoing call / U19 release request 875
26.8.1.3 Establishment of an incoming call / Initial conditions 882
26.8.1.3.1 Incoming call / U0 null state 884
26.8.1.3.2 Incoming call / U6 call present 885
26.8.1.3.3 Incoming call / U9 mobile terminating call confirmed 887
26.8.1.3.4 Incoming call / U7 call received 896
26.8.1.3.5 Incoming call / U8 connect request 906
26.8.1.4 In call functions 917
26.8.1.4.1 In-call functions / DTMF information transfer 917
26.8.1.4.2 In-call functions / user notification 919
26.8.1.4.3 In-call functions / channel changes 920
26.8.1.4.4 In-call functions / MS terminated in-call modification 924
26.8.1.4.5 In-call functions / MS originated in-call modification 925
26.8.2 Call Re-establishment 941
26.8.2.1 Call Re-establishment/call present, re-establishment allowed 941
26.8.2.2 Call Re-establishment/call present, re-establishment not allowed 943
26.8.2.3 Call Re-establishment/call under establishment, transmission stopped 944
26.8.3 User to user signalling 945
26.8.4 Default contents of message 947
26.9 Structured procedures 955
26.9.1 Structured procedures / general 955
26.9.2 Structured procedures / MS originated call / early assignment 956
26.9.3 Structured procedures / MS originated call / late assignment 958
26.9.4 Structured procedures / MS terminated call / early assignment 960
26.9.5 Structured procedures / MS terminated call / late assignment 963
26.9.6 Structured procedures / emergency call 966
26.9.6.1 Structured procedures / emergency call / idle updated 966
26.9.6.1.1 Structured procedures / emergency call / idle updated / preferred channel rate 966
26.9.6.1.2 Structured procedures / emergency call / idle updated, non-preferred channel rate 969
26.9.6.2 Structured procedures / emergency call / idle, no IMSI 969
26.9.6.2.1 Structured procedures / emergency call / idle, no IMSI / accept case 969
26.9.6.2.2 Structured procedures / emergency call / idle, no IMSI / reject case 971
26.9.7 Directed Retry / Mobile Originated Call 973
26.9.8 Directed Retry / Mobile Terminated Call 979
26.9.9 Default contents of messages 987
26.10 E-GSM or R-GSM signalling 993
26.10.1 E-GSM or R-GSM signalling / general considerations 993
26.10.2 E-GSM or R-GSM signalling / RR 995
26.10.2.1 E-GSM or R-GSM signalling / RR / Measurement 995
26.10.2.2 E-GSM or R-GSM signalling / RR / Immediate assignment 1002
26.10.2.3 E-GSM or R-GSM signalling / RR / channel assignment procedure 1004
26.10.2.4 E-GSM or R-GSM signalling / RR / Handover 1008
26.10.2.4.1 E-GSM or R-GSM signalling / RR / Handover / Successful handover 1008
26.10.2.4.2 E-GSM or R-GSM signalling / RR / Handover / layer 1 failure 1014
26.10.2.5 E-GSM or R-GSM signalling / RR / Frequency Redefinition 1016
26.10.3 E-GSM or R-GSM signalling / Structured procedure 1019
26.10.3.1 E-GSM or R-GSM signalling / Structured procedure / Mobile originated call 1020
26.10.3.2 E-GSM or R-GSM signalling / Structured procedures / emergency call 1022
26.10.3.3 Default contents of messages 1025
26.10.4 E-GSM or R-GSM signalling / Default message contents 1026
26.11 Multiband signalling 1031
26.11.1 General considerations 1031

iTeh STANDARD PREVIEW
(standards.iteh.ai)
SIST EN 300 607-1 V7.2.1:2005
https://standards.iteh.ai/catalog/standards/sist/c9ac301b-0878-4c57-b0e0-e6a7988e5019/sist-en-300-607-1-v7.2.1-2005