

Designation: F1568 – 12 (Reapproved 2017)<sup>ε1</sup>

An American National Standard

# Standard Specification for Food Processors, Electric<sup>1</sup>

This standard is issued under the fixed designation F1568; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

ε<sup>1</sup> NOTE—Corrected footnote 5 editorially in November 2017.

## 1. Scope

- 1.1 This specification covers commercial food processors intended for bench, table, or floor mounting.
- 1.2 The values stated in inch-pound units are to be regarded as standard. The values given in parentheses are mathematical conversions to SI units that are provided for information only and are not considered standard.
- 1.3 The following safety hazards caveat pertains only to the test methods portion, Section 9, of this specification: This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.
- 1.4 This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.

# 2. Referenced Documents

2.1 ASTM Standards:<sup>2</sup>

D3951 Practice for Commercial Packaging

F760 Specification for Food Service Equipment Manuals

F1166 Practice for Human Engineering Design for Marine Systems, Equipment, and Facilities

2.2 ANSI Standards: <sup>3</sup>

ANSI Z1.4 Sampling Procedures and Tables for Inspection by Attributes

# ANSI S1.13 Methods for Measurement of Sound Pressure Levels

2.3 NSF International Standard: 4

NSF/ANSI 8 Commercial Powered Food Preparation Equipment

2.4 UL Standards: 5

ANSI/UL 763 Motor-Operated Commercial Food Preparing Machines

ANSI/UL 969 Marking and Labeling Systems

2.5 Military Standards: 6

MIL-STD-167/1 Mechanical Vibration of Shipboard Equipment (Type I-Environmental and Type II-Internally Excited)

MIL-STD-461 Requirements for the Control of Electromagnetic Interference Characteristics of Subsystems and Equipment

MIL-STD-1399/300 Interface Standard for Shipboard Systems, Section 300A, Electric Power, Alternating Current

# 3. Terminology

- 3.1 Definitions:
- 3.1.1 *bowl*, *n*—the container, with interlocked cover, used to hold a fixed quantity of food product.
- 3.1.2 *discharge chute, n*—the part of the housing, generally located at the front of the unit, that directs the cut product downward for collection into a pan and also helps prevent operator contact with the backside of the slicer or shredder plate.
- 3.1.3 feed head, n—the device for holding food product and directing it into the slicer or shredder plate. The feed head incorporates a food pusher that is interlocked to prevent motor operation whenever the pusher is not in the closed position over the slicer or shredder plate.

<sup>&</sup>lt;sup>1</sup> This specification is under the jurisdiction of ASTM Committee F26 on Food Service Equipment and is the direct responsibility of Subcommittee F26.04 on Mechanical Preparation Equipment.

Current edition approved Nov. 1, 2017. Published December 2017. Originally approved in 1994. Last previous edition approved in 2012 as F1568 – 12. DOI: 10.1520/F1568-12R17E01.

<sup>&</sup>lt;sup>2</sup> For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

 $<sup>^3</sup>$  Available from American National Standards Institute (ANSI), 25 W. 43rd St., 4th Floor, New York, NY 10036.

<sup>&</sup>lt;sup>4</sup> Available from NSF International, P.O. Box 130140, 789 N. Dixboro Rd., Ann Arbor, MI 48113-0140.

<sup>&</sup>lt;sup>5</sup> Available from comm2000, 1414 Brook Dr., Downers Grove, IL 60515, http://www.shopulstandards.com.

<sup>&</sup>lt;sup>6</sup> Available from Standardization Documents Order Desk, Bldg. 4 Section D, 700 Robbins Ave., Philadelphia, PA 19111-5094, Attn: NPODS.

- 3.1.4 food processor, n—machine that reduces food product to a small particle size and uniform geometric shape. Reduction of food product is accomplished by the continuous, manual feeding of uncut food product into contact with a rotating plate or slicing/shredding a quantity of food product in a closed bowl. The food processor shall consist of the following principal parts: motor with housing, product hopper or bowl, hopper/bowl cover with interlock, plates and grids, and controls.
- 3.1.5 *food pusher*, *n*—the hand-operated device used to maintain the uncut food product in contact with the slicer or shredder plate.
- 3.1.6 shredder and slicer plates, n—these devices attach to the food processor drive shaft and convert the rotary motion of the plate into the desired action on the foodstuffs within the feed head.

#### 4. Classification

- 4.1 Food processors covered in this specification are of the following types, sizes, and classes:
  - 4.2 *Types:*
- 4.2.1 *Type I*—This machine shall have a hopper of the continuous, manual-feed type.
- 4.2.1.1 *Size 1*—Slicer/shredder plates less than 8 in. in diameter.
- 4.2.1.2 *Size* 2—Slicer/shredder plates 8 in. or greater in diameter.
  - (1) Class 1—Table- or bench-mounted food processor.
  - (2) Class 2—Floor-mounted food processor.
- 4.2.2 *Type II*—This machine shall have a closed-bowl type of hopper.
- 4.2.2.1 Size 1—Bowl volume less than 4 qt (3.8 L). The machine shall be table- or bench-mounted.
- 4.2.2.2 *Size* 2—Bowl volume between 4 and 8 qt (3.8 and 7.6 L). The machine shall be table- or bench-mounted.
- 4.2.2.3 *Size 3*—Bowl volume shall be 30 qt (28.4 L). The machine shall be floor-mounted.
- 4.2.2.4 Size 4—Bowl volume shall be 45 qt (42.6 L). The machine shall be floor-mounted.

#### 5. Ordering Information

- 5.1 Purchasers should select the food processor and any preferred options and include the following information in the purchasing document:
  - 5.1.1 Title, number, and date of this specification,
- 5.1.2 Type, size, and class of the food processor required (see Section 4),
- 5.1.3 Electrical power supply characteristics (current, voltage, phase, frequency),
- 5.1.4 Accessory equipment, options (slicer, dicer, grater, julienne, and shredder plates), spare parts, and maintenance parts required,
  - 5.1.5 Labeling requirements (if different from Section 13),
  - 5.1.6 Quantity of food processors to be furnished, and
- 5.1.7 Any special requirements or deviations from this specification.
- 5.1.8 When specified, the purchaser shall be furnished certification that samples representing each lot have been tested

- or inspected as directed in this specification and the requirements have been met. When specified, a copy of the test results shall be furnished.
- 5.1.9 When Federal/Military procurement is required, review and implement the applicable supplementary requirements (see S1 through S9).

## 6. Physical Requirements

- 6.1 Design and Manufacture—The food processor shall be complete so that when connected to the specified source of power, the unit can be used for its intended function. The food processor shall be simple to disassemble and reassemble without special tools or equipment. The food processor shall meet the then current applicable requirements of NSF/ANSI 8 and ANSI/UL 763.
- 6.1.1 Compliance with NSF/ANSI 8—Acceptable evidence of meeting the requirements of NSF/ANSI 8 shall be the NSF certification mark on the food processor and listing in the manufacturer's product listings on the NSF website, nsf.org, a certified test report from a recognized independent testing laboratory acceptable to the user, or a certificate issued by NSF under its special one time contract evaluation/certification service.
- 6.1.2 Compliance with ANSI/UL 763—Acceptable evidence of meeting the requirements of ANSI/UL 763 shall be a UL Listing mark on the food processor, or a certified test report from a recognized independent testing laboratory acceptable to the user.
- 6.1.3 *Materials*—Materials used in the construction of food processors shall comply with the applicable requirements of NSF/ANSI 8.
- 6.1.4 *Human Factors Criteria*—Human factors engineering criteria, principles, and practices, as defined in Practice F1166, shall be used in the design of all food processors.
  - 6.2 Electrical Devices:
- 6.2.1 *Power Supply*—The food processor shall be furnished with a 5-ft (1.52-m) minimum length cord and plug with ground or shall be double-insulated. The cord and plug shall be sized for and be the appropriate configuration for the specified electrical characteristics.
- 6.2.2 *Motor*—The food processor motor shall be of the continuous duty type.
- 6.3 Discharge Chute (Type I Machines)—The discharge chute shall be designed to direct sliced or shredded food product into a tray or pan at the front of the unit. When tested in accordance with Section 9, processed food shall be directed from the discharge chute in a manner to permit collection in a container placed below the chute, and the processed food shall not be expelled out of the area of the pan or tray used for collection of the processed food.
- 6.4 *Interchangeability of Items*—All food processors of the same model number and bill of material furnished with similar options under a specific purchase order shall be identical to the extent necessary to ensure interchangeability of component parts, assemblies, and spare parts.
- 6.5 Plates—Manual feed food processors meeting the requirements of this specification must be available with a