



Designation: **F3065/F3065M – 15 F3065/F3065M – 18**

Standard Specification for ~~Installation and Integration of Propeller Systems Aircraft~~ Propeller System Installation¹

This standard is issued under the fixed designation F3065/F3065M; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This specification addresses the airworthiness requirements for the installation and integration of propeller systems.

1.2 This specification is applicable to aeroplanes as defined in F44 terminology standard.

1.3 The applicant for a design approval must seek the individual guidance to their respective CAA body concerning the use of this standard as part of a certification plan. For information on which CAA regulatory bodies have accepted this standard (in whole or in part) as a means of compliance to their Small Aircraft Airworthiness regulations (Hereinafter referred to as “the Rules”), refer to ASTM F44 webpage (www.ASTM.org/COMITTEE/F44.htm) which includes CAA website links.

1.4 *Units*—The values stated are SI units followed by Imperial units in square brackets. The values stated in each system may not be exact equivalents; therefore, each system shall be used independently of the other. Combining values from the two systems may result in non-conformance with the standard.

1.5 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.6 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 *ASTM Standards:*²
F3060 Terminology for Aircraft

3. Terminology

3.1 See Terminology **F3060**.

4. Propeller Installation Aspects

4.1 *Propeller—General:*

4.1.1 Each propeller must:

4.1.1.1 Have a type certificate, or

4.1.1.2 Meet the requirements acceptable to the certifying aviation authority for inclusion in the approved aeroplane.

4.1.2 Engine power and propeller shaft rotational speed may not exceed the limits for which the propeller is certificated or approved.

4.2 *Feathering Propellers*—Each featherable propeller must have a means to un-feather in flight.

4.3 *Variable-Pitch Propellers*—The propeller blade pitch control system must meet the following requirements:

4.3.1 No single failure or malfunction in the propeller system will result in unintended travel of the propeller blades to a position below the in-flight low-pitch position. Failure of structural elements need not be considered if the occurrence of such a failure is shown to be extremely remote.

¹ This specification is under the jurisdiction of ASTM Committee **F44** on General Aviation Aircraft and is the direct responsibility of Subcommittee **F44.40** on Powerplant. Current edition approved ~~May 1, 2015~~ Jan. 1, 2018. Published ~~June 2015~~ January 2018. Originally approved in 2015. Last previous edition approved in 2015 as **F3065/F3065M – 15**. DOI: ~~10.1520/F3065-15~~ 10.1520/F3065_F3065M-18.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard’s Document Summary page on the ASTM website.

4.3.2 For propellers incorporating a method to select blade pitch below the in-flight low pitch position, provisions must be made to sense and indicate to the flight crew that the propeller blades are below that position by a defined amount. The method for sensing and indicating the propeller blade pitch position must be such that its failure does not affect the control of the propeller.

4.3.3 The propeller control system, operating in normal and alternative operating modes and in transition between operating modes, performs the defined functions throughout the declared operating conditions and flight envelope.

4.3.4 The propeller control system functionality is not adversely affected by the declared environmental conditions, including temperature, electromagnetic interference (EMI), high intensity radiated fields (HIRF) and lightning.

4.3.5 A method is provided to indicate that an operating mode change has occurred if flight crew action is required.

4.3.6 No single failure or malfunction of electrical or electronic components in the control system results in a hazardous propeller effect.

4.3.7 Failures or malfunctions directly affecting the propeller control system in a typical airplane, such as structural failures of attachments to the control, fire, or overheat, do not lead to a hazardous propeller effect.

4.3.8 The loss of normal propeller pitch control does not cause a hazardous propeller effect under the intended operating conditions.

4.3.9 The failure or corruption of data or signals shared across propellers does not cause a hazardous propeller effect.

4.3.10 Electronic propeller control system imbedded software must be designed and implemented by a method approved by the Civil Aviation Authority that is consistent with the criticality of the performed functions and that minimizes the existence of software errors.

4.3.11 The propeller control system must be designed and constructed so that the failure or corruption of airplane-supplied data does not result in hazardous propeller effects.

4.3.12 The propeller control system must be designed and constructed so that the loss, interruption or abnormal characteristic of airplane-supplied electrical power does not result in hazardous propeller effects.

4.3.13 Each propeller blade pitch control system component, including governors, pitch change assemblies, and feathering system components, can withstand cyclic operation that simulates the normal load and pitch change travel to which the component would be subjected during a minimum of 1000 h of typical operation in service.

4.3.14 Propeller components that contain hydraulic pressure and whose structural failure or leakage from a structural failure could cause a hazardous propeller effect demonstrate structural integrity by:

4.3.14.1 A proof pressure test to 1.5× the maximum operating pressure for one minute without permanent deformation or leakage that would prevent performance of the intended function, and

4.3.14.2 A burst pressure test to 2.0× the maximum operating pressure for one minute without failure. Leakage is permitted and seals may be excluded from the test.

4.4 *Pusher Propeller Installation:*

4.4.1 All engine cowling, access doors, and other removable items must be designed to have a remote probability of separation that could cause contact with the pusher propeller.

4.4.2 Each pusher propeller must be marked so that the disc is conspicuous under normal daylight ground conditions.

4.4.3 If the engine exhaust gases are discharged into the pusher propeller disc, it must be shown by tests, or analysis supported by tests, that the propeller is capable of continuous safe operation.

4.5 *Propeller Clearance:*

4.5.1 Propeller clearances in section 4.5 are the minimum allowable, unless otherwise substantiated, under the following conditions:

4.5.1.1 ~~With the aeroplane at maximum weight,~~

4.5.1.1 With the most adverse combination of aeroplane weight and center of gravity, and

4.5.1.2 With the propeller in the most adverse pitch position.

4.5.2 *Ground Clearance with Forward Mounted Propellers:*

4.5.2.1 *Normal Operation*—With landing gear statically deflected and the aeroplane in the level, normal takeoff, or taxiing attitude, whichever is most critical; there must be a clearance between each propeller and the ground of at least:

(1) 18 cm [7 in.] for each aeroplane with nose wheel landing gear, or

(2) 23 cm [9 in.] for each aeroplane with tail wheel landing gear.

4.5.2.2 *Deflated and Bottomed Struts*—For each aeroplane with conventional landing gear struts using fluid or mechanical means for absorbing landing shocks, there must be positive clearance between the propeller and the ground in the level takeoff attitude with the critical tire completely deflated and the corresponding landing gear strut bottomed.

4.5.2.3 *Leaf Spring Struts*—Positive clearance for aeroplanes using leaf spring struts is shown with a deflection corresponding to 1.5 g.

4.5.3 *Ground Clearance with Aft-Mounted Propellers*—In addition to the clearances specified in 4.5.2, an aeroplane with an aft mounted propeller must be designed such that the propeller will not contact the runway surface when the aeroplane is in the maximum pitch attitude attainable during normal takeoffs and landings.

4.5.4 *Water Clearance:*

4.5.4.1 There must be a clearance of at least 46 cm [18 in.] between each propeller and the water.