



SLOVENSKI STANDARD
SIST EN 302 404 V8.0.1:2003

01-december-2003

8][JhUb]`W] b] hYY_ca i b] UWg] g]ghYa `fUhU&žLÉ; GA `g]ghYa `VfYnj f j] bY
hYYzb]Y`fH GkÉ: UhU%ÉGdcXbYd`Ugh]fUX]g_Y[Uj a Ygb]_U`nU7 HGÉGkcdbU&
f] GA '\$' ') &zfUh`] JWU, '\$'%'nXU'U% -- Ł

Digital cellular telecommunications system (Phase 2+) (GSM); GSM Cordless Telephony System (CTS), Phase 1; Lower Layers of the CTS Radio Interface; Stage 2 (GSM 03.52 version 8.0.1 Release 1999)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 302 404 V8.0.1:2003](#)

<https://standards.iteh.ai/catalog/standards/sist/06c41a71-bf38-48ed-880d-1ef8e49eaa42/sist-en-302-404-v8-0-1-2003>

Ta slovenski standard je istoveten z: EN 302 404 Version 8.0.1

ICS:

33.070.50	Globalni sistem za mobilno telekomunikacijo (GSM)	Global System for Mobile Communication (GSM)
-----------	---	--

SIST EN 302 404 V8.0.1:2003

en

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

SIST EN 302 404 V8.0.1:2003

<https://standards.iteh.ai/catalog/standards/sist/06c41a71-bf38-48ed-880d-1ef8e49eaa42/sist-en-302-404-v8-0-1-2003>

ETSI EN 302 404 V8.0.1 (2000-09)

European Standard (Telecommunications series)

**Digital cellular telecommunications system (Phase 2+);
GSM Cordless Telephony System (CTS), Phase 1;
Lower Layers of the CTS Radio Interface;
Stage 2
(GSM 03.52 version 8.0.1 Release 1999)**

iTeh STANDARD PREVIEW
(standards.iteh.ai)



GLOBAL SYSTEM FOR
MOBILE COMMUNICATIONS

SIST EN 302 404 V8.0.1:2003

<https://standards.iteh.ai/catalog/standards/sist/06c41a71-bf38-48ed-880d-1ef8e49eaa42/sist-en-302-404-v8-0-1-2003>



Reference

REN/SMG-020352Q8

Keywords

Digital cellular telecommunications system,
 Global System for Mobile communications
 (GSM), GSM Cordless Telephony System (CTS)

ETSI

650 Route des Lucioles
 F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
 Association à but non lucratif enregistrée à la
 Sous-Préfecture de Grasse le 06 N° 7303/88

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 302 404 V8.0.1:2003](#)
<https://standards.iteh.ai/catalog/standards/sist/06c41a71-bf38-48ed-880d-1ef8e49eaa42/sist-en-302-404-v8-0-1-2003>

Important notice

Individual copies of the present document can be downloaded from:
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
 Information on the current status of this and other ETSI documents is available at <http://www.etsi.org/tb/status/>

If you find errors in the present document, send your comment to:
editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
 The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2000.
 All rights reserved.

Contents

Intellectual Property Rights	6
Foreword.....	6
1 Scope	7
2 References	7
3 Definitions and abbreviations.....	8
3.1 Definitions	8
3.2 Abbreviations	8
4 Main concepts of the CTS radio interface.....	8
4.1 Beacon concept	8
4.2 Adaptive Frequency Allocation (AFA) concept.....	9
4.3 Total Frequency Hopping (TFH) concept	9
5 Radio Transmission and Reception.....	9
5.1 Frequency Band and Channel Arrangement.....	9
5.2 Receiver Characteristics	9
5.2.1 CTS-MS characteristics	9
5.2.2 CTS-FP characteristics	9
5.3 Transmitter Characteristics.....	10
5.3.1 CTS-MS characteristics	10
5.3.2 CTS-FP characteristics.....	10
5.4 CTS transmitter / receiver performance	10
6 Modulation and Raw Data Rates.....	10
7 Channel Coding and Interleaving	10
8 Time Slots and TDMA-Frames	10
9 Bursts.....	11
10 Logical Channels.....	11
10.1 CTS Beacon Channel (CTSBCH)	11
10.1.1 CTSBCH format	11
10.1.2 CTSBCH timing	12
10.1.3 CTSBCH radio frequency channel	12
10.1.4 CTSBCH-SB information	12
10.2 CTS Access Request Channel (CTSARCH)	12
10.2.1 CTSARCH format	12
10.2.2 CTSARCH timing	12
10.2.3 CTSARCH radio frequency channel.....	13
10.2.4 CTSARCH information	13
10.3 CTS Access Grant Channel (CTSAGCH).....	13
10.3.1 CTSAGCH format	13
10.3.2 CTSAGCH timing	13
10.3.3 CTSAGCH radio frequency channel	13
10.3.4 CTSAGCH information	14
10.4 CTS Paging Channel (CTSPCH).....	14
10.4.1 CTSPCH format	14
10.4.2 CTSPCH timing	14
10.4.3 CTSPCH radio frequency channel	14
10.4.4 CTSPCH information	14
10.5 SACCH	14
10.6 FACCH	15
10.7 TCH.....	15
10.8 Mapping of the Logical Channels onto Physical Channels	15
10.8.1 Mapping in time of the logical channels onto the physical channels	15

10.8.2	Mapping in frequency of the logical channels onto the physical channels	16
10.8.3	Permitted Channel Combinations	16
11	Lower Layer Procedures	17
11.1	CTSBCH transmission	17
11.2	CTSBCH timeslot management	17
11.3	CTSBCH-FB detection.....	17
11.4	CTSBCH-SB decoding.....	17
11.5	Discontinuous transmission (DTX).....	17
11.6	Interference measurements	17
11.7	MS timing offset measurements	18
12	Radio Resource Management Procedures	18
12.1	Radio Resources management states	18
12.2	General procedures.....	18
12.2.1	Initial synchronization of a CTS-MS and CTS-FP	18
12.2.2	Frequency management	18
12.2.2.1	Interference measurements exchange.....	19
12.2.2.2	Adaptive Frequency Allocation (AFA) algorithm	19
12.2.2.3	AFA / TFH interworking	19
12.2.2.4	CTSBCH frequency selection	19
12.2.3	CTSBCH-SB information	20
12.2.4	Control of CTS-FP service range.....	20
12.2.5	CTS-FP selection	20
12.3	RR Idle state procedures.....	20
12.3.1	CTSBCH monitoring	20
12.3.2	Alive check	20
12.3.3	Establishment of a dedicated RR connection.....	20
12.3.3.1	Timeslot assignment for dedicated connection	20
12.3.3.2	CTS-MS initiated RR connection establishment.....	21
12.3.3.2.1	Non-hopping access procedure.....	21
12.3.3.2.2	Hopping access procedure.....	21
12.3.3.3	CTS-FP initiated RR connection establishment.....	21
12.3.4	CTSBCH failure detection.....	22
12.4	RR Active state procedures	22
12.4.1	Radio link failure detection.....	22
12.4.2	RF power control	22
12.4.3	Intracell handover	22
12.4.4	Channel release	22
Annex A (informative): GSM backwards compatibility issues		23
A.1	Reasons for possible impact of a CTS-FP on a GSM-MS in the PLMN	23
A.1.1	Power measurement of BCCH carrier.....	23
A.1.1.1	Power on CTS-FP beacon frequency seen by the GSM-MS in cell selection.....	23
A.1.1.2	Power on CTS-FP hopping frequencies seen by the GSM-MS in cell selection	24
A.1.2	Synchronisation of a GSM-MS	24
A.2	Scenario 1: PLMN and CTS-GFL have no common frequency in whole coverage area.....	24
A.2.1	Cell Selection	24
A.2.1.1	GSM-MS has no BA list stored on the SIM	24
A.2.1.2	GSM-MS has a stored BA list on the SIM (optional).....	24
A.2.2	Cell reselection	25
A.2.3	Handover	25
A.3	Scenario 2: PLMN and CTS-GFL have locally no common frequency.....	25
A.3.1	Cell Selection	25
A.3.1.1	GSM-MS has no BA list stored on the SIM	25
A.3.1.2	GSM-MS has a stored BA list on the SIM (optional).....	25
A.3.2	Cell reselection	25
A.3.2.1	GSM-MS camping on its home PLMN	25
A.3.2.2	GSM-MS camping on a visited PLMN in home country.....	26
A.3.3	Handover	26

A.4	Scenario 3: PLMN and CTS-GFL have locally some common frequencies.....	26
A.4.1	Cell selection	26
A.4.2	Cell reselection.....	26
A.4.3	Handover	27
A.5	Conclusion.....	27
Annex B (informative):	Document change history.....	28
History		29

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 302 404 V8.0.1:2003
<https://standards.iteh.ai/catalog/standards/sist/06c41a71-bf38-48ed-880d-1ef8e49eaa42/sist-en-302-404-v8-0-1-2003>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Special Mobile Group (SMG).

The present document was submitted to One-step Approval with the ETSI number 301 404. For publication the number was changed to 302 404 because the number 301 404 is reserved and was allocated accidentally.

The present document gives an overall description of the lower layers of the radio interface for GSM based Cordless Telephony Systems.

The contents of the present document is subject to continuing work within SMG and may change following formal SMG approval. Should SMG modify the contents of the present document it will be re-released with an identifying change of release date and an increase in version number as follows:

Version 8.x.y

[SIST EN 302 404 V8.0.1:2003](#)

where:

<https://standards.iteh.ai/catalog/standards/sist/06c41a71-bf38-48ed-880d-1e849ea342/sist-en-302-404-v8-0-1-2003>

- 8 indicates Release 1999 of GSM Phase 2+.
- x the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- y the third digit is incremented when editorial only changes have been incorporated in the specification.

National transposition dates

Date of adoption of this EN:	25 August 2000
Date of latest announcement of this EN (doa):	30 November 2000
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 May 2001
Date of withdrawal of any conflicting National Standard (dow):	31 May 2001

1 Scope

The present document gives an overall description of the lower layers of the radio interface for GSM based Cordless Telephony Systems (GSM-CTS).

The GSM-CTS system is intended to provide a cordless connection between the fixed network and GSM-based CTS Mobile Stations (CTS-MS) via a private CTS Fixed Part (CTS-FP).

Stage 1 is an overall description, from the service subscribers and user's standpoint, that view the network as a single entity which provides service to the user. GSM 02.56 contains the CTS Stage 1 service description.

GSM 03.56 is a Stage 2 document that describes the system architecture of the GSM Cordless Telephone Systems (GSM-CTS), i.e. the system elements, the system interfaces and the functional capabilities.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.
- A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.
- For this Release 1999 document, references to GSM documents are for Release 1999 versions (version 8.x.y). <https://standards.iteh.ai/catalog/standards/sist/06c41a/1-bf38-48ed-880d-1ef8e40cna42/sist-en-302-404-v8-0-1-2003>

- [1] GSM 01.04: "Digital cellular telecommunications system (Phase 2+); Abbreviations and Acronyms".
- [2] GSM 02.56: "Digital cellular telecommunications system (Phase 2+); GSM Cordless Telephone System (CTS); Service Description; Stage 1".
- [3] GSM 03.22: "Digital cellular telecommunications system (Phase 2+); Functions related to Mobile Station (MS) in idle mode and group receive mode".
- [4] GSM 03.20: "Digital cellular telecommunications system (Phase 2+); GSM Cordless Telephone System (CTS); Security related network functions; Stage 2".
- [5] GSM 03.56: "Digital cellular telecommunications system (Phase 2+); GSM Cordless Telephone System (CTS); CTS Architecture Description; Stage 2".
- [6] GSM 04.08: "European digital cellular telecommunications system (Phase 2+); Mobile radio interface layer 3 specification".
- [7] GSM 05.02 (V6.3): "Digital cellular telecommunications system (Phase 2+); Multiplexing and multiple access on the radio path".
- [8] GSM 05.03 (V6.1): "Digital cellular telecommunications system (Phase 2+); Channel coding".
- [9] GSM 05.04: "Digital cellular telecommunications system (Phase 2+); Modulation".
- [10] GSM 05.05: "Digital cellular telecommunications system (Phase 2+); Radio transmission and reception".
- [11] GSM 05.08: "Digital cellular telecommunications system (Phase 2+); Radio subsystem link control".

- [12] GSM 05.10: "Digital cellular telecommunications system (Phase 2+); Radio subsystem synchronization".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

CTS Mobile Station: GSM-MS supporting CTS.

CTS Fixed Part: CTS-FP is a device which acts as a link between the CTS-MS and the fixed network.

GSM-CTS: Cordless Telephony System based on GSM.

3.2 Abbreviations

The following list describes the abbreviations and acronyms used in the present document. The GSM abbreviations explained in GSM 01.04 [1] are not included below.

AFA	Adaptive Frequency Allocation
CTS	Cordless Telephony System
CTSAGCH	CTS Access Grant CHannel
CTSARCH	CTS Access Request CHannel
CTSBCH	CTS Beacon CHannel
CTS-FP	CTS Fixed Part
CTS-MS	CTS Mobile Station
CTSMSI	CTS Mobile Subscriber Identity
CTSPCH	CTS Paging CHannel SIST EN 302 404 V8.0.1:2003
DPLMN	Donor Public Land Mobile Network http://public.iteh.ai/itdh/standards/sist/06c41a71-bf38-48ed-880d-011f42a42/sist-en-302-404-v8-0-1-2003
FPBI	Fixed Part Beacon Identity
GFL	Generic Frequency List
RX	Receive
TFH	Total Frequency Hopping
TX	Transmit

4 Main concepts of the CTS radio interface

The main assumption behind the CTS work item and in particular the CTS radio interface, is that a modified single timeslot state of the art GSM-MS chipset could be used for a home base station, i.e. as a CTS-FP.

The CTS radio interface has been designed to meet a requirement of low generated interference, either from the CTS to existing overlaying PLMNS, either from a CTS to another CTS. This requirement is achieved by the combined usage of the three concepts: beacon concept, AFA concept and TFH concept.

4.1 Beacon concept

A limited number of CTS-MS shall be served by one CTS-FP (see GSM 02.56). Therefore, a broadcast channel continuously transmitted such as the BCCH in GSM is not needed for CTS.

A channel called CTS beacon channel (CTSBCH) is proposed with the following main characteristics: it is transmitted by the CTS-FP every 26 frames in a 52-multiframe pattern, and allows the CTS-MS to synchronise with the CTS-FP. Minimum signalling is also supported by the CTSBCH, so that it is the only logical channel a CTS-FP shall periodically transmit on the CTS radio interface. Every other logical channel is only transmitted "on demand".

4.2 Adaptive Frequency Allocation (AFA) concept

A precise radio frequency planning can not be applied to the CTS-FP/MS pair, as the CTS is intended to be deployed by the end-user. Therefore, a list of frequencies (the GFL) on which it is allowed to operate is given to the CTS. With the AFA, interference measurements will be performed on the frequencies in the GFL to provide a ranking in the AFA table, in order to exclude unacceptably interfered frequencies from the usage in CTS.

4.3 Total Frequency Hopping (TFH) concept

The remaining frequencies are used by the Total Frequency Hopping algorithm in order to reduce the interference of the CTS with the overlaying PLMN and other CTS-FP/MS pairs. With TFH the interference caused by the CTS link is spread across multiple GSM links (interference averaging) and the co-channel interference is due to different users at different locations (interference diversity).

A new hopping algorithm which is especially tailored for use in CTS with improved performance compared to the GSM hopping algorithms shall be used.

5 Radio Transmission and Reception

The CTS-FP and CTS-MS shall in Phase 1 GSM-CTS conform to the transmission and reception specifications of at least one or more of the following cellular standards:

- P-GSM900;
- E-GSM900;
- DCS1800;
- PCS1900.

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

SIST EN 302 404 V8.0.1:2003

The final choice of characteristics and performance requirements depends on system scenario calculations.

1ef8e49eaa42/sist-en-302-404-v8-0-1-2003

5.1 Frequency Band and Channel Arrangement

The frequency band and channel arrangement for the GSM-CTS are as specified in GSM 05.05 clause 2.

5.2 Receiver Characteristics

5.2.1 CTS-MS characteristics

It is the intention to keep the CTS-MS characteristics in line with the GSM-MS characteristics as specified in GSM 05.05 clause 5, but the final decision depends on system scenario calculations.

5.2.2 CTS-FP characteristics

It is the intention to keep the CTS-FP characteristics in line with the GSM-MS characteristics as specified in GSM 05.05 clause 5, but with reversed frequency bands. The final decision depends on system scenario calculations.

5.3 Transmitter Characteristics

5.3.1 CTS-MS characteristics

It is the intention to keep the CTS-MS characteristics as far as possible in line with the GSM-MS characteristics as specified in GSM 05.05 clause 4, but the final decision depends on system scenario calculations.

In addition, it is intended to lower the maximum nominal output power and the lowest nominal output power to values which shall be determined by system scenario calculations. Both values could be below the nominal output powers specified in GSM 05.05 subclause 4.1.1.

5.3.2 CTS-FP characteristics

It is the intention to keep the CTS-FP characteristics as far as possible in line with the GSM-MS characteristics as specified in GSM 05.05 subclause 4, but with reversed frequency bands. The final decision depends on system scenario calculations.

In addition, it is intended to lower the maximum nominal output power and the lowest nominal output power to values which shall be determined by system scenario calculations. Both values could be below the nominal output powers specified in GSM 05.05 subclause 4.1.1.

5.4 CTS transmitter / receiver performance

It is the intention to keep the CTS transmitter / receiver performance in line with the GSM transmitter / receiver performance as specified in GSM 05.05 clause 6.

STANDARD PREVIEW

The GSM requirement on receiver performance for frequency hopping where frequencies are interfered shall be fulfilled by both the CTS-MS and CTS-FP.

SIST EN 302 404 V8.0.1:2003

<https://standards.itec.ai/catalog/standards/sist/06c41a71-bf38-48ed-880d-fc8e49caaf42/SIST-EN-302-404-V8.0.1-2003>

The modulation technique and raw data rates are as specified in GSM 05.04.

7 Channel Coding and Interleaving

The channel coding algorithm and interleaving schemes of existing GSM channels used in the GSM CTS radio interface are as specified in GSM 05.03.

Channel coding algorithms and interleaving schemes for new logical channels are defined in clause 10.

8 Time Slots and TDMA-Frames

The time slot organisation is as specified in GSM 05.02 subclause 4.3.1.

The TDMA frames are organised in multiframe, superframes, and hyperframes. The hyperframe is the longest recurrent time period and consists of $26 \times 51 \times 2048$ TDMA frames. The TDMA frames are numbered modulo this hyperframe, which means that the frame number FN ranges from 0 to $\text{FN_MAX} = (26 \times 51 \times 2^{11}) - 1 = 2715647$. The CTS-FP keeps track of the frame numbering once initialised.

Two types of multiframe exist in the GSM-CTS system:

- a 26-multiframe with a duration of 120 ms, comprising 26 TDMA frames. This multiframe is used to carry TCH, SACCH, and FACCH (see clause 10);