



SLOVENSKI STANDARD

SIST EN 300 940 V6.9.1:2005

01-februar-2005

8 [[[HJb]`W] b]`hY`ca i b]_UW`g_]`g]ghYa `fZhU&ZL!`Ja Ygb]_`nUa cV]b]`fUX]c`!
GdYWZ]_UW]UfYhY`d`Ugh]`f] GA `\$('\$, žfUh`]WU* `"-`%ž]nXUU% - +Ł

Digital cellular telecommunications system (Phase 2+) (GSM); Mobile radio interface layer 3 specification (GSM 04.08 version 6.9.1 Release 1997)

iteh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: ^{SIST EN 300 940 V6.9.1:2005} **EN 300 940 Version 6.9.1**
<https://standards.iteh.ai/catalog/standards/sist/b1ba0f6-9c54-406a-8596-2619ac4208e6/sist-en-300-940-v6-9-1-2005>

ICS:

33.070.01 Mobilni servisi na splošno Mobile services in general

SIST EN 300 940 V6.9.1:2005 en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 940 V6.9.1:2005](https://standards.iteh.ai/catalog/standards/sist/b1fba6f6-9e54-4b6a-8396-2619ac4208e6/sist-en-300-940-v6-9-1-2005)

<https://standards.iteh.ai/catalog/standards/sist/b1fba6f6-9e54-4b6a-8396-2619ac4208e6/sist-en-300-940-v6-9-1-2005>

ETSI EN 300 940 V6.9.1 (2000-09)

European Standard (Telecommunications series)

**Digital cellular telecommunications system (Phase 2+);
Mobile radio interface layer 3 specification
(GSM 04.08 version 6.9.1 Release 1997)**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

GSM®
GLOBAL SYSTEM FOR
MOBILE COMMUNICATIONS

[SIST EN 300 940 V6.9.1:2005](https://standards.iteh.ai/catalog/standards/sist/b1fba6f6-9e54-4b6a-8396-2619ac4208e6/sist-en-300-940-v6-9-1-2005)

<https://standards.iteh.ai/catalog/standards/sist/b1fba6f6-9e54-4b6a-8396-2619ac4208e6/sist-en-300-940-v6-9-1-2005>



Reference

REN/TSGN-010408Q6R4

Keywords

Digital cellular telecommunications system,
Global System for Mobile communications (GSM)**ETSI**

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 940 V6.9.1:2005<https://standards.iteh.ai/catalog/standards/sist/b1fba6f6-9e54-4b6a-8396-2619ac4208e6/sist-en-300-940-v6-9-1-2005>

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <http://www.etsi.org/tb/status/>

If you find errors in the present document, send your comment to:
editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2000.
All rights reserved.

Contents

Intellectual Property Rights	27
Foreword.....	27
Introduction	28
0 Scope	29
0.1 Scope of the Technical Specification	29
0.2 Application to the interface structures.....	29
0.3 Structure of layer 3 procedures.....	29
0.4 Test procedures	29
0.5 Use of logical channels.....	30
0.6 Overview of control procedures	30
0.6.1 List of procedures	30
0.7 Applicability of implementations	32
0.7.1 Voice Group Call Service (VGCS) and Voice Broadcast Service (VBS).....	33
0.7.2 General Packet Radio Service (GPRS).....	33
1 References	34
2 Definitions and abbreviations.....	37
2.1 Random values	37
2.2 Vocabulary	38
3 Radio Resource management procedures.....	39
3.1 Overview/General	39
3.1.1 General.....	39
3.1.2 Services provided to upper layers	39
3.1.2.1 Idle mode	39
3.1.2.2 Dedicated mode.....	40
3.1.2.3 Group receive mode	40
3.1.2.4 Group transmit mode.....	40
3.1.2.5 Packet idle mode	40
3.1.2.6 Packet transfer mode	41
3.1.3 Services required from data link and physical layers.....	41
3.1.4 Change of dedicated channels.....	41
3.1.4.1 Change of dedicated channels using SAPI = 0.....	41
3.1.4.2 Change of dedicated channels using other SAPIs than 0	41
3.1.4.3 Sequenced message transfer operation.....	42
3.1.4.3.1 Variables and sequence numbers.....	42
3.1.4.3.1.1 Send state variable V(SD).....	42
3.1.4.3.1.2 Send sequence number N(SD)	42
3.1.4.3.2 Procedures for the initiation, transfer execution and termination of the sequenced message transfer operation.....	42
3.1.4.3.2.1 Initiation.....	42
3.1.4.3.2.2 Transfer Execution.....	42
3.1.4.3.2.3 Termination.....	42
3.1.5 Procedure for Service Request and Contention Resolution	42
3.2 Idle mode procedures and general procedures in packet idle and packet transfer modes.....	43
3.2.1 Mobile Station side	43
3.2.2 Network side	44
3.2.2.1 System information broadcasting	44
3.2.2.2 Paging	45
3.3 RR connection establishment	45
3.3.1 RR connection establishment initiated by the mobile station	45
3.3.1.1 Entering the dedicated mode : immediate assignment procedure	45
3.3.1.1.1 Permission to access the network	45
3.3.1.1.2 Initiation of the immediate assignment procedure.....	46
3.3.1.1.3 Answer from the network	47

3.3.1.1.3.1	On receipt of a CHANNEL REQUEST message	47
3.3.1.1.3.2	Assignment rejection	48
3.3.1.1.4	Assignment completion	48
3.3.1.1.4.1	Early classmark sending	48
3.3.1.1.4.2	GPRS suspension procedure	49
3.3.1.1.5	Abnormal cases	49
3.3.1.2	Entering the group transmit mode: uplink access procedure	49
3.3.1.2.1	Mobile station side	50
3.3.1.2.1.1	Uplink investigation procedure	50
3.3.1.2.1.2	Uplink access procedure	50
3.3.1.2.2	Network side	51
3.3.1.2.3	Abnormal cases	51
3.3.1.3	Dedicated mode and GPRS	51
3.3.2	Paging procedure for RR connection establishment	51
3.3.2.1	Paging initiation by the network	51
3.3.2.1.1	Paging initiation using paging subchannel on CCCH	52
3.3.2.1.2	Paging initiation using paging subchannel on PCCCH	53
3.3.2.1.3	Paging initiation using PACCH	53
3.3.2.2	Paging response	53
3.3.2.3	Abnormal cases	53
3.3.3	Notification procedure	54
3.3.3.1	Notification of a call	54
3.3.3.2	Joining a VGCS or VBS call	54
3.3.3.3	Reduced NCH monitoring mechanism	55
3.4	Procedures in dedicated mode and in group transmit mode	56
3.4.1	SACCH procedures	56
3.4.1.1	General	56
3.4.1.2	Measurement report	57
3.4.1.3	Extended measurement report \$(MAFA)\$	57
3.4.2	Transfer of messages and link layer service provision	57
3.4.3	Channel assignment procedure	57
3.4.3.1	Channel assignment initiation	58
3.4.3.2	Assignment completion	59
3.4.3.3	Abnormal cases	59
3.4.4	Handover procedure	60
3.4.4.1	Handover initiation	61
3.4.4.2	Physical channel establishment	62
3.4.4.2.1	Finely synchronized cell case	62
3.4.4.2.2	Non synchronized cell case	62
3.4.4.2.3	Pseudo-synchronized cell case	63
3.4.4.2.4	Pre-synchronized cell case	63
3.4.4.3	Handover completion	63
3.4.4.4	Abnormal cases	64
3.4.5	Frequency redefinition procedure	65
3.4.5.1	Abnormal cases	65
3.4.6	Channel mode modify procedure	65
3.4.6.1	Normal channel mode modify procedure	65
3.4.6.1.1	Initiation of the channel mode modify procedure	65
3.4.6.1.2	Completion of channel mode modify procedure	66
3.4.6.1.3	Abnormal cases	66
3.4.6.2	Channel mode modify procedure for a voice group call talker	66
3.4.6.2.1	Initiation of the channel mode modify procedure	66
3.4.6.2.2	Completion of mode change procedure	66
3.4.6.2.3	Abnormal cases	66
3.4.7	Ciphering mode setting procedure	66
3.4.7.1	Ciphering mode setting initiation	67
3.4.7.2	Ciphering mode setting completion	67
3.4.8	Additional channel assignment procedure	67
3.4.8.1	Additional assignment procedure initiation	68
3.4.8.2	Additional assignment procedure completion	68
3.4.8.3	Abnormal cases	68
3.4.9	Partial channel release procedure	68

3.4.9.1	Partial release procedure initiation.....	68
3.4.9.2	Abnormal cases	68
3.4.10	Classmark change procedure	69
3.4.11	Classmark interrogation procedure	69
3.4.11.1	Classmark interrogation initiation	69
3.4.11.2	Classmark interrogation completion	69
3.4.12	Indication of notifications and paging information.....	69
3.4.13	RR connection release procedure.....	69
3.4.13.1	Normal release procedure	69
3.4.13.1.1	Channel release procedure initiation in dedicated mode and in group transmit mode	70
3.4.13.1.2	Abnormal cases	71
3.4.13.2	Radio link failure in dedicated mode	71
3.4.13.2.1	Mobile side	71
3.4.13.2.2	Network side.....	71
3.4.13.3	RR connection abortion in dedicated mode	72
3.4.13.4	Uplink release procedure in group transmit mode	72
3.4.13.5	Radio link failure in group transmit mode	72
3.4.13.5.1	Mobile side	72
3.4.13.5.2	Network side.....	72
3.4.14	Receiving a RR STATUS message by a RR entity.....	73
3.4.15	Group receive mode procedures	73
3.4.15.1	Mobile station side	73
3.4.15.1.1	Reception of the VGCS or VBS channel.....	73
3.4.15.1.2	Monitoring of downlink messages and related procedures.....	73
3.4.15.1.2.1	Spare	73
3.4.15.1.2.2	Spare	73
3.4.15.1.2.3	Channel mode modify procedure.....	73
3.4.15.1.2.4	Notification and paging information.....	73
3.4.15.1.2.4.1	Use of Reduced NCH monitoring.....	74
3.4.15.1.2.5	Uplink status messages	74
3.4.15.1.2.6	Channel release message.....	74
3.4.15.1.2.7	Information on paging channel restructuring.....	74
3.4.15.1.3	Uplink reply procedure.....	74
3.4.15.1.4	Leaving the group receive mode.....	75
3.4.15.1.4.1	Returning to idle mode.....	75
3.4.15.1.4.2	Going to group transmit mode	75
3.4.15.2	Network side	75
3.4.15.2.1	Provision of messages on the VGCS or VBS channel downlink.....	75
3.4.15.2.1.1	General.....	75
3.4.15.2.1.2	Provision of general information messages	75
3.4.15.2.1.3	Provision of messages related to the voice group call uplink channel	76
3.4.15.2.2	Release of the VGCS or VBS Channels	76
3.4.15.3	Failure cases	76
3.4.16	Configuration change procedure	76
3.4.16.1	Configuration change initiation.....	77
3.4.16.2	Configuration change completion	77
3.4.16.3	Abnormal cases	77
3.4.17	Mapping of user data substreams onto timeslots in a multislot configuration	77
3.4.18	Handling of classmark information at band change.....	78
3.4.19	Assignment to a Packet Data channel	78
3.4.19.1	Assignment to PDCH initiation.....	78
3.4.19.2	Completion of the Assignment to PDCH procedure	79
3.4.19.3	Abnormal cases	79
3.4.20	RR-Network Commanded Cell Change Order	80
3.4.20.1	RR-network commanded cell change order initiation.....	80
3.4.20.2	Network controlled cell reselection completion.....	81
3.4.20.3	Abnormal cases	81
3.5	RR procedures on CCCH related to temporary block flow establishment	81
3.5.1	Packet paging procedure using CCCH.....	82
3.5.1.1	Packet paging initiation by the network	82
3.5.1.2	On receipt of a packet paging request	82
3.5.2	Packet access procedure using CCCH	82

3.5.2.1	Entering the packet transfer mode: packet access procedure	83
3.5.2.1.1	Permission to access the network	83
3.5.2.1.2	Initiation of the packet access procedure: channel request	83
3.5.2.1.3	Packet immediate assignment.....	84
3.5.2.1.3.1	On receipt of a CHANNEL REQUEST message	84
3.5.2.1.3.2	One phase packet access	85
3.5.2.1.3.3	Single block packet access.....	85
3.5.2.1.3.4	Packet access rejection.....	86
3.5.2.1.4	Packet access completion	86
3.5.2.1.5	Abnormal cases	86
3.5.2.2	Sending an RLC/MAC control message: single block packet access procedure	87
3.5.3	Packet downlink assignment procedure using CCCH	87
3.5.3.1	Entering the packet transfer mode: packet downlink assignment procedure.....	87
3.5.3.1.1	Void	87
3.5.3.1.2	Initiation of the packet downlink assignment procedure	87
3.5.3.1.3	Packet downlink assignment completion.....	89
3.5.3.1.4	Abnormal cases	89
3.5.3.2	Sending an RLC/MAC control message: single block packet downlink assignment procedure.....	89
4	Elementary procedures for Mobility Management.....	90
4.1	General	90
4.1.1	MM and GMM procedures	91
4.1.1.1	Types of MM and GMM procedures	91
4.1.1.2	MM-GMM co-ordination for GPRS MS's	92
4.1.1.2.1	GPRS MS operating in mode A or B in a network that operates in mode I	92
4.1.1.2.2	GPRS MS operating in mode A or B in a network that operates in mode II or III.....	92
4.1.2	MM sublayer states.....	93
4.1.2.1	MM sublayer states in the mobile station.....	93
4.1.2.1.1	Main states.....	93
4.1.2.1.2	Substates of the MM IDLE state	96
4.1.2.2	The update Status	97
4.1.2.3	MM sublayer states on the network side.....	98
4.1.3	GPRS mobility management (GMM) sublayer states.....	99
4.1.3.1	GMM states in the MS.....	99
4.1.3.1.1	Main states.....	99
4.1.3.1.1.1	GMM-NULL	99
4.1.3.1.1.2	GMM-DEREGISTERED	99
4.1.3.1.1.3	GMM-REGISTERED-INITIATED.....	99
4.1.3.1.1.4	GMM-REGISTERED	100
4.1.3.1.1.5	GMM-DEREGISTERED-INITIATED	100
4.1.3.1.1.6	GMM-ROUTING-AREA-UPDATING-INITIATED	100
4.1.3.1.2	Substates of state GMM-DEREGISTERED.....	100
4.1.3.1.2.1	GMM-DEREGISTERED.NORMAL-SERVICE	100
4.1.3.1.2.2	GMM-DEREGISTERED.LIMITED-SERVICE	100
4.1.3.1.2.3	GMM-DEREGISTERED.ATTACH-NEEDED	100
4.1.3.1.2.4	GMM-DEREGISTERED.ATTEMPTING-TO-ATTACH	100
4.1.3.1.2.5	GMM-DEREGISTERED.NO-IMSI	100
4.1.3.1.2.6	GMM-DEREGISTERED.NO-CELL-AVAILABLE	100
4.1.3.1.2.7	GMM-DEREGISTERED.PLMN-SEARCH	100
4.1.3.1.2.8	GMM-DEREGISTERED.SUSPENDED.....	101
4.1.3.1.3	Substates of state GMM-REGISTERED.....	101
4.1.3.1.3.1	GMM-REGISTERED.NORMAL-SERVICE.....	101
4.1.3.1.3.2	GMM-REGISTERED.SUSPENDED.....	101
4.1.3.1.3.3	GMM-REGISTERED.UPDATE-NEEDED.....	101
4.1.3.1.3.4	GMM-REGISTERED.ATTEMPTING-TO-UPDATE.....	101
4.1.3.1.3.5	GMM-REGISTERED.NO-CELL-AVAILABLE.....	101
4.1.3.1.3.6	GMM-REGISTERED.LIMITED-SERVICE.....	102
4.1.3.1.3.7	GMM-REGISTERED.ATTEMPTING-TO-UPDATE-MM	102
4.1.3.1.3.8	GMM-REGISTERED.IMSI-DETACH-INITIATED.....	102
4.1.3.2	GPRS update status	102
4.1.3.3	GMM mobility management states on the network side.....	103
4.1.3.3.1	Main States	103

4.1.3.3.1.1	GMM-DEREGISTERED	103
4.1.3.3.1.2	GMM-COMMON-PROCEDURE-INITIATED.....	103
4.1.3.3.1.3	GMM-REGISTERED.....	103
4.1.3.3.1.4	GMM-DEREGISTERED-INITIATED	103
4.1.3.3.2	Substates of state GMM-REGISTERED.....	104
4.1.3.3.2.1	GMM-REGISTERED.NORMAL-SERVICE.....	104
4.1.3.3.2.2	GMM-REGISTERED.SUSPENDED.....	104
4.2	Behaviour of the MS in MM Idle state, GMM-DEREGISTERED state and GMM-REGISTERED state	104
4.2.1	Primary Service State selection	105
4.2.1.1	Selection of the Service State after Power On.....	105
4.2.1.2	Other Cases	105
4.2.2	Detailed Description of the MS behaviour in MM IDLE State	106
4.2.2.1	Service State, NORMAL SERVICE.....	106
4.2.2.2	Service State, ATTEMPTING TO UPDATE	106
4.2.2.3	Service State, LIMITED SERVICE.....	107
4.2.2.4	Service State, NO IMSI.....	107
4.2.2.5	Service State, SEARCH FOR PLMN, NORMAL SERVICE.....	108
4.2.2.6	Service State, SEARCH FOR PLMN	108
4.2.2.7	Service State, RECEIVING GROUP CALL (NORMAL SERVICE).....	108
4.2.2.8	Service State, RECEIVING GROUP CALL (LIMITED SERVICE).....	109
4.2.3	Service state when back to state MM IDLE from another state.....	109
4.2.4	Behaviour in state GMM-DEREGISTERED.....	110
4.2.4.1	Primary substate selection.....	110
4.2.4.1.1	Selection of the substate after power on or enabling the MS's GPRS capability.....	110
4.2.4.1.2	Other Cases.....	110
4.2.4.2	Detailed description of the MS behaviour in state GMM-DEREGISTERED.....	111
4.2.4.2.1	Substate, NORMAL SERVICE.....	111
4.2.4.2.2	Substate, ATTEMPTING-TO-ATTACH.....	111
4.2.4.2.3	Substate, LIMITED SERVICE.....	111
4.2.4.2.4	Substate, NO-IMSI	111
4.2.4.2.5	Substate, NO-CELL	111
4.2.4.2.6	Substate, PLMN-SEARCH.....	112
4.2.4.2.7	Substate, ATTACH-NEEDED.....	112
4.2.4.2.8	Substate, SUSPENDED.....	112
4.2.4.3	Substate when back to state GMM-DEREGISTERED from another GMM state	112
4.2.5	Behaviour in state GMM-REGISTERED.....	112
4.2.5.1	Detailed description of the MS behaviour in state GMM-REGISTERED	113
4.2.5.1.1	Substate, NORMAL-SERVICE	113
4.2.5.1.2	Substate, SUSPENDED	113
4.2.5.1.3	Substate, UPDATE-NEEDED.....	113
4.2.5.1.4	Substate, ATTEMPTING-TO-UPDATE	113
4.2.5.1.5	Substate, NO-CELL-AVAILABLE	113
4.2.5.1.6	Substate, LIMITED-SERVICE	114
4.2.5.1.7	Substate, ATTEMPTING-TO-UPDATE-MM	114
4.3	MM common procedures	114
4.3.1	TMSI reallocation procedure	114
4.3.1.1	TMSI reallocation initiation by the network	114
4.3.1.2	TMSI reallocation completion by the mobile station	115
4.3.1.3	TMSI reallocation completion in the network.....	115
4.3.1.4	Abnormal cases	115
4.3.2	Authentication procedure.....	116
4.3.2.1	Authentication request by the network.....	116
4.3.2.2	Authentication response by the mobile station.....	116
4.3.2.3	Authentication processing in the network	116
4.3.2.4	Ciphering key sequence number	116
4.3.2.5	Unsuccessful authentication.....	116
4.3.2.6	Abnormal cases	117
4.3.3	Identification procedure.....	117
4.3.3.1	Identity request by the network.....	117
4.3.3.2	Identification response by the mobile station.....	118
4.3.3.3	Abnormal cases.....	118
4.3.4	IMSI detach procedure.....	118

4.3.4.1	IMSI detach initiation by the mobile station	118
4.3.4.2	IMSI detach procedure in the network	119
4.3.4.3	IMSI detach completion by the mobile station.....	119
4.3.4.4	Abnormal cases	119
4.3.5	Abort procedure	119
4.3.5.1	Abort procedure initiation by the network	119
4.3.5.2	Abort procedure in the mobile station	119
4.3.6	MM information procedure.....	119
4.3.6.1	MM information procedure initiation by the network.....	120
4.3.6.2	MM information procedure in the mobile station	120
4.4	MM specific procedures	120
4.4.1	Location updating procedure	120
4.4.2	Periodic updating	121
4.4.3	IMSI attach procedure	122
4.4.4	Generic Location Updating procedure.....	122
4.4.4.1	Location updating initiation by the mobile station	122
4.4.4.1a	Network Request for Additional mobile station Capability Information	122
4.4.4.2	Identification request from the network	122
4.4.4.3	Authentication by the network	122
4.4.4.4	Ciphering mode setting by the network	122
4.4.4.5	Attempt Counter.....	123
4.4.4.6	Location updating accepted by the network.....	123
4.4.4.7	Location updating not accepted by the network.....	124
4.4.4.8	Release of RR connection after location updating	124
4.4.4.9	Abnormal cases on the mobile station side	124
4.4.4.10	Abnormal cases on the network side	126
4.5	Connection management sublayer service provision	126
4.5.1	MM connection establishment.....	127
4.5.1.1	MM connection establishment initiated by the mobile station	127
4.5.1.2	Abnormal cases	129
4.5.1.3	MM connection establishment initiated by the network	130
4.5.1.3.1	Mobile Terminating CM Activity	130
4.5.1.3.2	Mobile Originating CM Activity (CCBS)	130
4.5.1.4	Abnormal cases	131
4.5.1.5	MM connection establishment for emergency calls.....	131
4.5.1.6	Call re-establishment.....	132
4.5.1.6.1	Call re-establishment, initiation by the mobile station	132
4.5.1.6.2	Abnormal cases	134
4.5.1.7	Forced release during MO MM connection establishment	134
4.5.2	MM connection information transfer phase.....	135
4.5.2.1	Sending CM messages	135
4.5.2.2	Receiving CM messages	135
4.5.2.3	Abnormal cases	135
4.5.3	MM connection release.....	135
4.5.3.1	Release of associated RR connection	136
4.5.3.2	Uplink release in a voice group call	136
4.6	Receiving a MM STATUS message by a MM entity.....	136
4.7	Elementary mobility management procedures for GPRS services	136
4.7.1	General.....	136
4.7.1.1	Lower layer failure.....	136
4.7.1.2	Ciphering of messages	136
4.7.1.3	P-TMSI signature.....	137
4.7.1.4	Radio resource sublayer address handling	137
4.7.1.5	P-TMSI handling.....	138
4.7.1.6	Change of network mode of operation.....	138
4.7.2	GPRS Mobility management timers	139
4.7.2.1	READY timer behaviour.....	139
4.7.2.2	Periodic routing area updating	140
4.7.3	GPRS attach procedure.....	141
4.7.3.1	GPRS attach procedure for GPRS services	142
4.7.3.1.1	GPRS attach procedure initiation	142
4.7.3.1.2	GMM common procedure initiation.....	142

4.7.3.1.3	GPRS attach accepted by the network.....	142
4.7.3.1.4	GPRS attach not accepted by the network.....	143
4.7.3.1.5	Abnormal cases in the MS.....	144
4.7.3.1.6	Abnormal cases on the network side.....	145
4.7.3.2	Combined GPRS attach procedure for GPRS and non-GPRS services.....	146
4.7.3.2.1	Combined GPRS attach procedure initiation.....	146
4.7.3.2.2	GMM Common procedure initiation.....	146
4.7.3.2.3	Combined GPRS attach accepted by the network.....	147
4.7.3.2.3.1	Combined attach successful for GPRS and non-GPRS services.....	147
4.7.3.2.3.2	Combined attach successful for GPRS services only.....	147
4.7.3.2.4	Combined GPRS attach not accepted by the network.....	148
4.7.3.2.5	Abnormal cases in the MS.....	149
4.7.3.2.6	Abnormal cases on the network side.....	149
4.7.4	GPRS detach procedure.....	149
4.7.4.1	MS initiated GPRS detach procedure.....	149
4.7.4.1.1	MS initiated GPRS detach procedure initiation.....	149
4.7.4.1.2	MS initiated GPRS detach procedure completion for GPRS services only.....	150
4.7.4.1.3	MS initiated combined GPRS detach procedure completion.....	150
4.7.4.1.4	Abnormal cases in the MS.....	150
4.7.4.2	Network initiated GPRS detach procedure.....	151
4.7.4.2.1	Network initiated GPRS detach procedure initiation.....	151
4.7.4.2.2	Network initiated GPRS detach procedure completion by the MS.....	152
4.7.4.2.3	Network initiated GPRS detach procedure completion by the network.....	153
4.7.4.2.4	Abnormal cases on the network side.....	153
4.7.5	Routing area updating procedure.....	154
4.7.5.1	Normal and periodic routing area updating procedure.....	155
4.7.5.1.1	Normal and periodic routing area updating procedure initiation.....	155
4.7.5.1.2	GMM Common procedure initiation.....	155
4.7.5.1.3	Normal and periodic routing area updating procedure accepted by the network.....	155
4.7.5.1.4	Normal and periodic routing area updating procedure not accepted by the network.....	156
4.7.5.1.5	Abnormal cases in the MS.....	157
4.7.5.1.6	Abnormal cases on the network side.....	158
4.7.5.2	Combined routing area updating procedure.....	159
4.7.5.2.1	Combined routing area updating procedure initiation.....	159
4.7.5.2.2	GMM Common procedure initiation.....	160
4.7.5.2.3	Combined routing area updating procedure accepted by the network.....	160
4.7.5.2.3.1	Combined routing area updating successful.....	160
4.7.5.2.3.2	Combined routing area updating successful for GPRS services only.....	161
4.7.5.2.4	Combined routing area updating not accepted by the network.....	161
4.7.5.2.5	Abnormal cases in the MS.....	162
4.7.5.2.6	Abnormal cases on the network side.....	163
4.7.6	P-TMSI reallocation procedure.....	163
4.7.6.1	P-TMSI reallocation initiation by the network.....	163
4.7.6.2	P-TMSI reallocation completion by the MS.....	163
4.7.6.3	P-TMSI reallocation completion by the network.....	163
4.7.6.4	Abnormal cases on the network side.....	164
4.7.7	Authentication and ciphering procedure.....	165
4.7.7.1	Authentication and ciphering initiation by the network.....	165
4.7.7.2	Authentication and ciphering response by the MS.....	165
4.7.7.3	Authentication and ciphering completion by the network.....	166
4.7.7.4	GPRS ciphering key sequence number.....	166
4.7.7.5	Unsuccessful authentication and ciphering.....	167
4.7.7.6	Abnormal cases on the network side.....	167
4.7.8	Identification procedure.....	168
4.7.8.1	Identification initiation by the network.....	168
4.7.8.2	Identification response by the MS.....	168
4.7.8.3	Identification completion by the network.....	168
4.7.8.4	Abnormal cases on the network side.....	168
4.7.9	Paging procedure.....	169
4.7.9.1	Paging for GPRS services.....	169
4.7.9.1.1	Paging for GPRS services using P-TMSI.....	170
4.7.9.1.2	Paging for GPRS services using IMSI.....	170

4.7.9.2	Paging for non-GPRS services	170
4.7.10	Receiving a GMM STATUS message by a GMM entity	170
4.7.11	GMM support for anonymous access	170
4.7.11.1	MS side	171
4.7.11.2	Network side	171
4.7.12	GMM Information procedure	171
4.7.12.1	GMM information procedure initiation by the network	171
4.7.12.2	GMM information procedure in the mobile station	171
5	Elementary procedures for circuit-switched Call Control	172
5.1	Overview	172
5.1.1	General	172
5.1.2	Call Control States	176
5.1.2.1	Call states at the mobile station side of the interface	176
5.1.2.1.1	Null (State U0)	176
5.1.2.1.2	MM Connection pending (U0.1)	176
5.1.2.1.2a	CC prompt present (U0.2) \$(CCBS)\$	177
5.1.2.1.2b	Wait for network information (U0.3) \$(CCBS)\$	177
5.1.2.1.2c	CC-Establishment present (U0.4) \$(CCBS)\$	177
5.1.2.1.2d	CC-Establishment confirmed (U0.5) \$(CCBS)\$	177
5.1.2.1.2e	Recall present (U0.6) \$(CCBS)\$	177
5.1.2.1.3	Call initiated (U1)	177
5.1.2.1.4	Mobile originating call proceeding (U3)	177
5.1.2.1.5	Call delivered (U4)	177
5.1.2.1.6	Call present (U6)	177
5.1.2.1.7	Call received (U7)	177
5.1.2.1.8	Connect Request (U8)	177
5.1.2.1.9	Mobile terminating call confirmed (U9)	178
5.1.2.1.10	Active (U10)	178
5.1.2.1.11	Disconnect request (U11)	178
5.1.2.1.12	Disconnect indication (U12)	178
5.1.2.1.13	Release request (U19)	178
5.1.2.1.14	Mobile originating modify (U26)	178
5.1.2.1.15	Mobile terminating modify (U27)	178
5.1.2.2	Network call states	178
5.1.2.2.1	Null (State N0)	178
5.1.2.2.2	MM connection pending (N0.1)	178
5.1.2.2.2a	CC connection pending (N0.2) \$(CCBS)\$	178
5.1.2.2.2b	Network answer pending (N0.3) \$(CCBS)\$	178
5.1.2.2.2c	CC-Establishment present (N0.4) \$(CCBS)\$	179
5.1.2.2.2d	CC-Establishment confirmed (N0.5) \$(CCBS)\$	179
5.1.2.2.3	Call initiated (N1)	179
5.1.2.2.4	Mobile originating call proceeding (N3)	179
5.1.2.2.5	Call delivered (N4)	179
5.1.2.2.6	Call present (N6)	179
5.1.2.2.7	Call received (N7)	179
5.1.2.2.8	Connect request (N8)	179
5.1.2.2.9	Mobile terminating call confirmed (N9)	179
5.1.2.2.10	Active (N10)	179
5.1.2.2.11	Not used	179
5.1.2.2.12	Disconnect indication (N12)	179
5.1.2.2.13	Release request (N19)	180
5.1.2.2.14	Mobile originating modify (N26)	180
5.1.2.2.15	Mobile terminating modify (N27)	180
5.1.2.2.16	Connect Indication (N28)	180
5.2	Call establishment procedures	180
5.2.1	Mobile originating call establishment	180
5.2.1.1	Call initiation	181
5.2.1.2	Receipt of a setup message	181
5.2.1.3	Receipt of a CALL PROCEEDING message	182
5.2.1.4	Notification of progressing mobile originated call	183
5.2.1.4.1	Notification of interworking in connection with mobile originated call establishment	183

5.2.1.4.2	Call progress in the PLMN/ISDN environment	183
5.2.1.5	Alerting	183
5.2.1.6	Call connected.....	184
5.2.1.7	Call rejection.....	185
5.2.1.8	Transit network selection	185
5.2.1.9	Traffic channel assignment at mobile originating call establishment	185
5.2.1.10	Call queuing at mobile originating call establishment	185
5.2.2	Mobile terminating call establishment.....	185
5.2.2.1	Call indication	185
5.2.2.2	Compatibility checking	186
5.2.2.3	Call confirmation	186
5.2.2.3.1	Response to SETUP	186
5.2.2.3.2	Receipt of CALL CONFIRMED and ALERTING by the network	187
5.2.2.3.3	Call failure procedures	187
5.2.2.3.4	Called mobile station clearing during mobile terminating call establishment.....	187
5.2.2.4	Notification of interworking in connection with mobile terminating call establishment	187
5.2.2.5	Call accept.....	188
5.2.2.6	Active indication	188
5.2.2.7	Traffic channel assignment at mobile terminating call establishment.....	188
5.2.2.8	Call queuing at mobile terminating call establishment	188
5.2.2.9	User connection attachment during a mobile terminating call	189
5.2.3	Network initiated MO call \$(CCBS)\$	189
5.2.3.1	Initiation.....	189
5.2.3.2	CC-Establishment present.....	189
5.2.3.2.1	Recall Alignment Procedure.....	190
5.2.3.3	CC-Establishment confirmation.....	191
5.2.3.4	Recall present.....	191
5.2.3.5	Traffic channel assignment during network initiated mobile originating call establishment	192
5.3	Signalling procedures during the "active" state.....	192
5.3.1	User notification procedure.....	192
5.3.2	Call rearrangements	192
5.3.3	Not used.....	193
5.3.4	Support of Dual Services.....	193
5.3.4.1	Service Description	193
5.3.4.2	Call establishment.....	193
5.3.4.2.1	Mobile Originating Establishment.....	193
5.3.4.2.2	Mobile Terminating Establishment	194
5.3.4.3	Changing the Call Mode	194
5.3.4.3.1	Initiation of in-call modification.....	195
5.3.4.3.2	Successful completion of in-call modification	195
5.3.4.3.3	Change of the channel configuration.....	195
5.3.4.3.4	Failure of in-call modification.....	195
5.3.4.3.4.1	Network rejection of in-call modification.....	195
5.3.4.3.4.2	Mobile station rejection of in-call modification.....	196
5.3.4.3.4.3	Time-out recovery.....	196
5.3.4.4	Abnormal procedures	196
5.3.5	User initiated service level up- and downgrading.....	196
5.3.5.1	Initiation of service level up- and downgrading.....	197
5.3.5.2	Successful completion of service level up- and downgrading	197
5.3.5.3	Rejection of service level up- and downgrading	197
5.3.5.4	Time-out recovery.....	197
5.4	Call clearing	197
5.4.1	Terminology	197
5.4.2	Exception conditions.....	198
5.4.3	Clearing initiated by the mobile station	198
5.4.3.1	Initiation of call clearing	198
5.4.3.2	Receipt of a DISCONNECT message from the mobile station.....	198
5.4.3.3	Receipt of a RELEASE message from the network.....	199
5.4.3.4	Receipt of a RELEASE COMPLETE message from the mobile station	199
5.4.3.5	Abnormal cases	199
5.4.4	Clearing initiated by the network.....	199
5.4.4.1	Clearing initiated by the network: mobile does not support "Prolonged Clearing Procedure"	199

5.4.4.1.1	Clearing when tones/announcements provided	199
5.4.4.1.1.1	Receipt of a DISCONNECT message with progress indicator #8 from the network	199
5.4.4.1.1.2	Expiry of timer T306	200
5.4.4.1.2	Clearing when tones/announcements not provided	200
5.4.4.1.2.1	Receipt of a DISCONNECT message without progress indicator or with progress indicator different from #8 from the network	200
5.4.4.1.2.2	Receipt of a RELEASE message from the mobile station	200
5.4.4.1.2.3	Abnormal cases	200
5.4.4.1.3	Completion of clearing	200
5.4.4.1.3.1	Abnormal cases	200
5.4.4.2	Clearing initiated by the network: mobile supports "Prolonged Clearing Procedure"	200
5.4.4.2.1	Clearing when tones/announcements provided and the network does not indicate that "CCBS activation is possible"	201
5.4.4.2.1.1	Receipt of a DISCONNECT message	201
5.4.4.2.1.2	Expiry of timer T306	201
5.4.4.2.2	Clearing when the network indicates that "CCBS activation is possible"	201
5.4.4.2.2.1	Receipt of a DISCONNECT	201
5.4.4.2.2.2	Expiry of timer T338	202
5.4.4.2.3	Clearing when tones/announcements are not provided and the network does not indicate that "CCBS activation is possible"	202
5.4.4.2.3.1	Receipt of a DISCONNECT message	202
5.4.4.2.3.2	Abnormal cases	203
5.4.4.2.4	Receipt of a RELEASE message from the mobile station	203
5.4.4.2.4.1	Release, CCBS not requested	203
5.4.4.2.4.2	Release, CCBS Requested	203
5.4.4.2.5	Completion of clearing	203
5.4.4.2.5.1	Abnormal cases	203
5.4.5	Clear collision	204
5.5	Miscellaneous procedures	204
5.5.1	In-band tones and announcements	204
5.5.2	Call collisions	204
5.5.3	Status procedures	204
5.5.3.1	Status enquiry procedure	204
5.5.3.2	Reception of a STATUS message by a CC entity	205
5.5.3.2.1	STATUS message with incompatible state	205
5.5.3.2.2	STATUS message with compatible state	205
5.5.4	Call re-establishment, mobile station side	205
5.5.4.1	Indication from the mobility management sublayer	205
5.5.4.2	Reaction of call control	205
5.5.4.3	Completion of re-establishment	206
5.5.4.4	Unsuccessful outcome	206
5.5.5	Call re-establishment, network side	206
5.5.5.1	State alignment	206
5.5.6	Progress	206
5.5.7	DTMF protocol control procedure	206
5.5.7.1	Start DTMF request by the mobile station	207
5.5.7.2	Start DTMF response by the network	207
5.5.7.3	Stop DTMF request by the mobile station	207
5.5.7.4	Stop DTMF response by the network	207
5.5.7.5	Sequencing of subsequent start DTMF requests by the mobile station	207
6	Support for packet services	208
6.1	GPRS Session management	208
6.1.1	General	208
6.1.1.1	Radio resource sublayer address handling for anonymous access	208
6.1.2	Session management states	208
6.1.2.1	Session management states in the MS	208
6.1.2.1.1	PDP-INACTIVE	209
6.1.2.1.2	PDP-ACTIVE-PENDING	209
6.1.2.1.3	PDP-INACTIVE-PENDING	209
6.1.2.1.4	PDP-ACTIVE	209
6.1.2.2	Session management states on the network side	209

6.1.2.2.1	PDP-INACTIVE.....	209
6.1.2.2.2	PDP-ACTIVE-PENDING.....	210
6.1.2.2.3	PDP-INACTIVE-PENDING.....	210
6.1.2.2.4	PDP-ACTIVE.....	210
6.1.2.2.5	PDP-MODIFY-PENDING.....	210
6.1.3	Session Management procedures.....	210
6.1.3.1	PDP context activation.....	210
6.1.3.1.1	Successful PDP context activation initiated by the mobile station.....	211
6.1.3.1.2	Successful PDP context activation requested by the network.....	211
6.1.3.1.3	Unsuccessful PDP context activation initiated by the MS.....	211
6.1.3.1.4	Unsuccessful PDP context activation requested by the network.....	212
6.1.3.1.5	Abnormal cases.....	212
6.1.3.2	PDP context modification procedure.....	213
6.1.3.2.1	Abnormal cases.....	214
6.1.3.3	PDP context deactivation procedure.....	214
6.1.3.3.1	PDP context deactivation initiated by the MS.....	214
6.1.3.3.2	PDP context deactivation initiated by the network.....	214
6.1.3.3.3	Abnormal cases.....	215
6.1.3.4	AA PDP context activation.....	215
6.1.3.4.1	Successful AA PDP context activation initiated by the mobile station.....	216
6.1.3.4.2	Unsuccessful AA PDP context activation.....	216
6.1.3.4.3	Abnormal cases.....	216
6.1.3.5	AA PDP context deactivation.....	217
6.1.3.5.1	Implicit AA PDP context deactivation.....	217
6.1.3.5.2	Explicit AA PDP context deactivation.....	217
6.1.3.5.3	Abnormal cases.....	217
6.1.3.6	Receiving a SM STATUS message by a SM entity.....	218
7	Examples of structured procedures.....	218
7.1	General.....	218
7.1.1	Paging request.....	218
7.1.2	Immediate assignment.....	218
7.1.3	Service request and contention resolution.....	219
7.1.4	Authentication.....	219
7.1.5	Ciphering mode setting.....	220
7.1.6	Transaction phase.....	220
7.1.6.1	Channel mode modify.....	220
7.1.7	Channel release.....	220
7.2	Abnormal cases.....	221
7.3	Selected examples.....	221
7.3.1	Location updating.....	221
7.3.2	Mobile originating call establishment.....	222
7.3.3	Mobile terminating call establishment.....	226
7.3.4	Call clearing.....	228
7.3.5	DTMF protocol control.....	229
7.3.6	Handover.....	230
7.3.7	In-call modification.....	231
7.3.8	Call re-establishment.....	232
7.3.9	Network initiated mobile originating call \$(CCBS)\$.....	233
8	Handling of unknown, unforeseen, and erroneous protocol data.....	238
8.1	General.....	238
8.2	Message too short.....	238
8.3	Unknown or unforeseen transaction identifier.....	239
8.3.1	Call Control.....	239
8.3.2	Session Management.....	240
8.4	Unknown or unforeseen message type.....	240
8.5	Non-semantical mandatory information element errors.....	241
8.5.1	Radio resource management.....	241
8.5.2	Mobility management.....	241
8.5.3	Call control.....	242
8.5.4	GMM mobility management.....	242