



Designation: **F1430/F1430M – 15 F1430/F1430M – 18**

Standard Test Method for Acoustic Emission Testing of Insulated and Non-Insulated Aerial Personnel Devices with Supplemental Load Handling Attachments¹

This standard is issued under the fixed designation F1430/F1430M; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This test method describes a procedure for acoustic emission (AE) testing of aerial personnel devices (APDs) with supplemental load handling attachments.

1.1.1 *Equipment Covered*—This test method covers the following types of vehicle-mounted aerial personnel devices with supplemental load handling attachments:

- 1.1.1.1 Extensible-boom APDs,
- 1.1.1.2 Articulating-boom APDs, and
- 1.1.1.3 Any combination of 1.1.1.1 and 1.1.1.2.

1.1.2 *Equipment Not Covered*—This test method does not cover any of the following equipment:

- 1.1.2.1 Aerial personnel devices without supplemental load handling attachments,
- 1.1.2.2 Digger-derricks with platform,
- 1.1.2.3 Cranes with platform, and
- 1.1.2.4 Aerial devices with load-lifting capabilities located anywhere other than adjacent to the platform.

NOTE 1—This test method is not intended to be a stand-alone NDT method for the verification of the structural integrity of an aerial device. Other NDT methods should be used to supplement the results.

1.2 The AE test method is used to detect and area-locate emission sources. Verification of emission sources may require the use of other nondestructive test (NDT) methods, such as radiography, ultrasonics, magnetic particle, liquid penetrant, and visual inspection. (**Warning**—This test method requires that external loads be applied to the superstructure of the vehicle under test. During the test, caution must be taken to safeguard personnel and equipment against unexpected failure or instability of the vehicle or components.)

1.3 The values stated in either SI units or inch-pound units are to be regarded separately as standard. The values stated in each system may not be exact equivalents; therefore, each system shall be used independently of the other. Combining values from the two systems may result in non-conformance with the standard.

1.4 *This standard does not purport to address all of the safety ~~problems~~, ~~concerns~~, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate ~~safety~~ safety, health, and health ~~environmental~~ environmental practices and determine the applicability of regulatory limitations prior to use.*

1.5 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 *ASTM Standards:*²

- E94 Guide for Radiographic Examination Using Industrial Radiographic Film
- E114 Practice for Ultrasonic Pulse-Echo Straight-Beam Contact Testing
- E164 Practice for Contact Ultrasonic Testing of Weldments

¹ This test method is under the jurisdiction of ASTM Committee F18 on Electrical Protective Equipment for Workers and is the direct responsibility of Subcommittee F18.55 on Inspection and Non-Destructive Test Methods for Aerial Devices.

Current edition approved April 1, 2015; March 1, 2018. Published May 2015; April 2018. Originally approved in 1992. Last previous edition approved in 2014 as F1430/F1430M-14-15. DOI: 10.1520/F1430-F1430M-15.10.1520/F1430_F1430M-18.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

- E569 Practice for Acoustic Emission Monitoring of Structures During Controlled Stimulation
- E650 Guide for Mounting Piezoelectric Acoustic Emission Sensors
- E750 Practice for Characterizing Acoustic Emission Instrumentation
- E976 Guide for Determining the Reproducibility of Acoustic Emission Sensor Response
- E1316 Terminology for Nondestructive Examinations
- E1417/E1417M Practice for Liquid Penetrant Testing
- E1444/E1444M Practice for Magnetic Particle Testing
- F914 Test Method for Acoustic Emission for Insulated and Non-Insulated Aerial Personnel Devices Without Supplemental Load Handling Attachments
- F2174 Practice for Verifying Acoustic Emission Sensor Response

2.2 *Other Standards:*

- ANSI A92.2 Standard for Vehicle-Mounted Elevating and Rotating Aerial Devices³
- ASNT SNT-TC-1A Recommended Practice for Personnel Qualification and Certification in Nondestructive Testing⁴

3. Terminology

3.1 *Definitions:*

3.1.1 *acoustic emission (AE)*—the class of phenomena whereby elastic waves are generated by the rapid release of energy from a localized source or sources within a material, or the transient elastic wave(s) so generated. Acoustic emission is the recommended term for general use. Other terms that have been used in AE literature include (1) stress wave emission, (2) microseismic activity, and (3) emission or acoustic emission with other qualifying modifiers.

3.1.2 *amplitude (acoustic emission signal amplitude)*—the peak voltage of the largest excursion attained by the signal waveform from an emission event.

3.1.3 *amplitude distribution*—a display of the number of acoustic emission events with signals that exceed an arbitrary amplitude as a function of amplitude.

3.1.4 *articulating-boom aerial device*—an aerial device with two or more hinged boom sections.

3.1.5 *attenuation*—the loss of energy per unit distance, typically measured as loss of signal peak amplitude with unit distance from the source of emission.

3.1.6 *channel*—an input to the main AE instrument that accepts a preamplifier output.

3.1.7 *commoned*—two or more sensors interconnected such that the sensor outputs are electronically processed by a single channel without differentiation of sensor origin.

3.1.8 *count also acoustic emission count, n*—the number of times the acoustic emission signal amplitude exceeds a preset threshold during any selected portion of a test.

3.1.9 *decibel (dB)*—the logarithmic expression of a ratio of two single peak amplitudes. A reference scale expresses the logarithmic ratio of a single peak amplitude to a fixed reference amplitude.

$$\text{Signal peak amplitude (dB)} = 20 \log_{10} (A_1/A_0)$$

where:

- A_0 = 1 μ V at the sensor output (before amplification), and
- A_1 = peak voltage of the measured acoustic emission signal.

dB Value	Acoustic Emission Reference Scale	
	Voltage At Sensor Output	Voltage At Integral Preamp Sensor Output (40-dB Gain)
0	1 μ V	100 μ V
20	10 μ V	1 mV
40	100 μ V	10 mV
60	1 mV	100 mV
80	10 mV	1 V
100	100 mV	10 V

3.1.10 *insulated aerial personnel device (IAPD)*—any device (extensible or articulating) which is designed primarily to position personnel and may be equipped with a supplemental load handling attachment.

3.1.11 *event (acoustic emission event)*—a local material change giving rise to acoustic emission.

3.1.12 *event count (N_e)*—the number obtained by counting each discerned acoustic emission event once.

3.1.13 *extensible-boom aerial device*—an aerial device, except the aerial ladder type, with a telescopic or extensible boom.

³ Available from American National Standards Institute (ANSI), 25 W. 43rd St., 4th Floor, New York, NY 10036, <http://www.ansi.org>.

⁴ Available from American Society for Nondestructive Testing (ASNT), P.O. Box 28518, 1711 Arlington Ln., Columbus, OH 43228-0518, <http://www.asnt.org>.