INTERNATIONAL STANDARD



INTERNATIONAL ORGANIZATION FOR STANDARDIZATION ORGANISATION INTERNATIONALE DE NORMALISATION МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ

Conveyor belts - Heat resistance -

Part 2: Specifications

Courroies transporteuses – Résistance à la chaleur ds.iteh.ai)

Partie 2: Spécifications

ISO 4195-2:1988 https://standards.iteh.ai/catalog/standards/sist/3e94e019-3833-4c83-816f-700618c4797b/iso-4195-2-1988

ISO 4195-2

First edition 1988-04-15

Reference number ISO 4195-2:1988 (E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council. They are approved in accordance with ISO procedures requiring at least 75 % approval by the member bodies voting.

International Standard ISO 4195-2 was prepared by Technical Committee ISO/TC 41, Pulleys and belts (including veebelts).

Users should note that all International Standards undergo revision from times to time and that any reference made hereinito sany others international Standard/implies4its19-3833-4c83-816flatest edition, unless otherwise stated. 700618c4797b/iso-4195-2-1988

IEW

© International Organization for Standardization, 1988

Printed in Switzerland

Conveyor belts — Heat resistance — Part 2: Specifications

1 Scope and field of application

2 References

This part of ISO 4195 specifies the permissible variations of hardness, and breaking elongation and strength of conveyor belt covers after exposure to heat as described in ISO 4195-1.

The temperatures selected for the tests are usually not those corresponding to the temperature of the product to be transported; they are generally lower to take account of

a) the possibility of conveyor belt cooling;

b) the fact that contact between the product and the conveyor belt will not equalize the temperature.

	4 Permissible variations	S			
strain properties. iTeh STANDARI) PREVIEW				
ISO 48, Vulcanized rubbers — Determination of hardness		Belt class			
(Hardness between 30 and 85 IRHD). (Standards.)	Characteristics of covers	1	2	3	
			Variation		
ISO 4195-1, Conveyor belts – Heat resistance – Part 1: Test ISO 4195-2:1	888 Hardness				
method. https://standards.iteh.ai/catalog/standards/s 700618c4797b/iso-41		+ 20	+ 20	± 20	
3 Principle	— maximum value	85	85	85	
	Breaking elongation				
Measurement of	 variation in percentage of the initial value 	- 50	- 50	- 55	
 IRHD hardness of covers, according to ISO 48, 		000	000	100	
 breaking elongation of covers, according to ISO 37, 	— minimum value, %	200	200	180	
	Breaking strength				
 breaking strength of covers, according to ISO 37, 	 variation in percentage of the initial value 	- 25	- 30	- 40	
before and after exposure to heat under conditions defined in ISO 4195-1.	— minimum value, MPa	12	10	5	

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 4195-2:1988</u> https://standards.iteh.ai/catalog/standards/sist/3e94e019-3833-4c83-816f-700618c4797b/iso-4195-2-1988

UDC 621.867.2.052 : 620.17

Descriptors : conveyor belts, specifications, thermal resistance.

Price based on 1 page