

ETSI EN 300 113-1 V1.7.1 (2011-11)



**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
Land mobile service;
Radio equipment intended for the transmission
of data (and/or speech) using constant or non-constant
envelope modulation and having an antenna connector;
Part 1: Technical characteristics and
methods of measurement**

Reference

REN/ERM-TGDMR-296-1

Keywords

antenna, data, mobile, PMR, radio, speech

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2011.
All rights reserved.

DECTTM, PLUGTESTSTM, UMTSTM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPPTM and LTETM are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	8
Foreword.....	8
1 Scope	9
2 References	9
2.1 Normative references	9
2.2 Informative references.....	10
3 Definitions, symbols and abbreviations	10
3.1 Definitions.....	10
3.2 Symbols.....	11
3.3 Abbreviations	12
4 General	12
4.1 Presentation of equipment for testing purposes.....	12
4.1.1 Choice of model for testing	12
4.1.1.1 Auxiliary test equipment	13
4.1.1.2 Declarations by the provider	13
4.2 Mechanical and electrical design.....	13
4.2.1 General.....	13
4.2.2 Controls	13
4.2.3 Transmitter shut-off facility	13
4.3 Marking.....	13
4.4 Testing using bit streams or messages.....	13
4.5 Measuring continuous mode equipment.....	13
4.6 Measuring discontinuous mode equipment	14
4.7 Combined full bandwidth analogue speech/full bandwidth digital equipment.....	14
4.8 Constant and non-constant envelope modulation.....	15
5 Test conditions, power sources and ambient temperatures	15
5.1 Normal and extreme test conditions	15
5.2 Test power source.....	15
5.3 Normal test conditions.....	15
5.3.1 Normal temperature and humidity	15
5.3.2 Normal test power source	16
5.3.2.1 Mains voltage	16
5.3.2.2 Regulated lead-acid battery power sources used on vehicles.....	16
5.3.2.3 Other power sources.....	16
5.4 Extreme test conditions	16
5.4.1 Extreme temperatures	16
5.4.2 Extreme test source voltages.....	16
5.4.2.1 Mains voltage	16
5.4.2.2 Regulated lead-acid battery power sources used on vehicles.....	16
5.4.2.3 Power sources using other types of batteries.....	16
5.4.2.4 Other power sources.....	17
5.5 Procedure for tests at extreme temperatures.....	17
5.5.1 Procedure for equipment designed for continuous transmission.....	17
5.5.2 Procedure for equipment designed for intermittent transmission	17
5.5.3 Testing of equipment that does not have an external 50 Ω RF connector (integral antenna equipment).....	17
6 General test conditions	18
6.1 Arrangements for test signals applied to the receiver input.....	18
6.2 Receiver mute or squelch facility	18
6.3 Normal test signals (wanted and unwanted signals).....	18
6.3.1 Equipment measured as constant envelope angle modulation equipment	18
6.3.2 Equipment measured as non-constant envelope modulation equipment.....	19
6.4 Encoder for receiver measurements	19

6.5	Transceiver data interface.....	20
6.6	Impedance	20
6.7	Artificial antenna.....	20
6.8	Tests of equipment with a duplex filter	20
6.9	Facilities for access	20
6.9.1	Analogue access.....	20
6.9.2	Test points for bit stream measurements.....	20
6.9.3	Coupling arrangements	21
6.9.3.1	Arrangements for measurements with continuous bit streams.....	21
6.9.3.2	Arrangements for measurements with messages.....	21
6.10	Test site and general arrangements for measurements involving the use of radiated fields	21
6.11	Modes of operation of the transmitter for constant envelope equipment	21
7	Technical characteristics of the transmitter	22
7.1	Frequency error	22
7.1.1	Definition	22
7.1.2	Method of measurement	22
7.1.3	Limits.....	22
7.2	Transmitter power (conducted)	23
7.2.1	Definitions	23
7.2.1.1	Equipment measured as constant envelope angle modulation equipment.....	23
7.2.1.2	Equipment measured as non-constant envelope modulation equipment	23
7.2.2	Method of measurement	23
7.2.2.1	Equipment measured as constant envelope angle modulation equipment.....	23
7.2.2.2	Equipment measured as non-constant envelope modulation equipment	24
7.2.3	Limits.....	24
7.3	Maximum Effective radiated power	24
7.3.1	Definition	24
7.3.1.1	Equipment measured as constant envelope angle modulation equipment.....	24
7.3.1.2	Equipment measured as non-constant envelope modulation equipment	25
7.3.2	Methods of measurement	25
7.3.2.1	Equipment measured as constant envelope angle modulation equipment.....	26
7.3.2.2	Equipment measured as non-constant envelope modulation equipment	27
7.3.3	Limits.....	28
7.4	Adjacent channel power	29
7.4.1	Definition	29
7.4.2	Method of measurement	29
7.4.3	Limits.....	30
7.5	Unwanted emissions in the spurious domain.....	31
7.5.1	Definition.....	31
7.5.2	Method of measuring the power level	31
7.5.2.1	Equipment measured as constant envelope angle modulation equipment.....	32
7.5.2.2	Equipment measured as non-constant envelope modulation equipment	32
7.5.3	Method of measuring the effective radiated power.....	32
7.5.3.1	Equipment measured as constant envelope angle modulation equipment.....	33
7.5.3.2	Equipment measured as non-constant envelope modulation equipment	33
7.5.4	Limits.....	35
7.6	Intermodulation attenuation.....	36
7.6.1	Definition.....	36
7.6.2	Method of measurement	36
7.6.3	Limits.....	37
7.7	Transmitter attack time.....	37
7.7.1	Definition.....	37
7.7.2	Method of measurement	38
7.7.3	Limit	38
7.8	Transmitter release time	38
7.8.1	Definition.....	38
7.8.2	Method of measurement	39
7.8.3	Limits.....	39
7.9	Transient behaviour of the transmitter.....	39
7.9.1	Definitions	39
7.9.2	Timings, frequencies and powers	41

7.9.3	Methods of measurement.....	44
7.9.3.1	Time domain measurements of power and frequency.....	44
7.9.3.2	Test arrangement and characteristics of the FM modulation meter	45
7.9.3.3	Adjacent channel transient power measurements.....	45
7.9.3.3.1	Definition.....	45
7.9.3.3.2	Measurement method for constant envelope angle modulation equipment.....	45
7.9.3.3.3	Measurement method for non-constant envelope modulation equipment	46
7.9.3.3.4	Alternative measurement method using a spectrum analyser	47
7.9.3.4	Characteristics of the adjacent channel transient power measuring device.....	48
7.9.4	Limits.....	48
7.9.4.1	Time domain analysis of power and frequency for constant envelope transmissions	49
7.9.4.2	Adjacent and alternate channel transient power	49
7.9.4.2.1	Equipment measured as constant envelope angle modulation equipment	49
7.9.4.2.2	Equipment measured as non-constant envelope modulation equipment	49
8	Methods of measurement for receiver parameters	50
8.1	Maximum usable sensitivity (conducted).....	50
8.1.1	Definition.....	50
8.1.2	Method of measurement	50
8.1.2.1	Method of measurement with continuous bit streams	50
8.1.2.2	Method of measurement with messages.....	51
8.1.2.3	Method of measurement with packets.....	51
8.1.3	Limits.....	52
8.2	Average usable sensitivity (field strength)	52
8.2.1	Definition.....	52
8.2.2	Method of measurement	52
8.2.3	Limits.....	53
8.3	Level of the wanted signal for the degradation measurements.....	53
8.4	Error behaviour at high input levels	54
8.4.1	Definition.....	54
8.4.2	Method of measurement	54
8.4.2.1	Method of measurement with continuous bit streams	54
8.4.2.2	Method of measurement with messages.....	54
8.4.2.3	Method of measurement with packets.....	55
8.4.3	Limits.....	55
8.5	Co-channel rejection.....	55
8.5.1	Definition.....	55
8.5.2	Method of measurement	56
8.5.2.1	Method of measurement with continuous bit streams	56
8.5.2.2	Method of measurement with messages.....	57
8.5.2.3	Method of measurement with packets.....	58
8.5.3	Limits.....	58
8.6	Adjacent channel selectivity.....	59
8.6.1	Definition.....	59
8.6.2	Method of measurement	59
8.6.2.1	Method of measurement with continuous bit streams	59
8.6.2.2	Method of measurement with messages.....	60
8.6.2.3	Method of measurement with packets.....	61
8.6.3	Limits.....	62
8.7	Spurious response rejection.....	62
8.7.1	Definition.....	62
8.7.2	Introduction to the method of measurement	62
8.7.3	Method of search over the "limited frequency range"	63
8.7.4	Method of measurement with continuous bit streams.....	64
8.7.5	Method of measurement with messages	64
8.7.6	Method of measurement with packets	65
8.7.7	Limits.....	66
8.8	Intermodulation response rejection	66
8.8.1	Definition.....	66
8.8.2	Method of measurement	67
8.8.2.1	Method of measurement with continuous bit streams	67
8.8.2.2	Method of measurement with messages.....	68

8.8.2.3	Method of measurement with packets.....	69
8.8.3	Limits.....	69
8.9	Blocking or desensitization	70
8.9.1	Definition.....	70
8.9.2	Method of measurement	70
8.9.2.1	Method of measurement with continuous bit streams.....	70
8.9.2.2	Method of measurement with messages.....	71
8.9.2.3	Method of measurement with packets.....	72
8.9.3	Limits.....	72
8.10	Spurious radiations	72
8.10.1	Definition.....	72
8.10.2	Method of measuring the power level	73
8.10.3	Method of measuring the effective radiated power.....	74
8.10.4	Limits.....	75
9	Duplex operation	76
9.1	Receiver desensitization (with simultaneous transmission and reception).....	76
9.1.1	Definition.....	76
9.1.2	Desensitization measured with continuous bit streams.....	77
9.1.2.1	Method of measurement when the equipment has a duplex filter.....	77
9.1.2.2	Method of measurement when the equipment has to operate with two antennas.....	78
9.1.3	Limits.....	79
9.2	Receiver spurious response rejection (with simultaneous transmission and reception)	79
9.2.1	Definition.....	79
9.2.2	Method of measurement	79
9.2.3	Limits.....	81
10	Measurement uncertainty	81

Annex A (normative): Radiated measurement.....83

A.1	Test sites and general arrangements for measurements involving the use of radiated fields.....	83
A.1.1	Anechoic chamber.....	83
A.1.2	Anechoic chamber with a conductive ground plane.....	84
A.1.3	Open Area Test Site (OATS)	85
A.1.4	Test antenna.....	86
A.1.5	Substitution antenna.....	87
A.1.6	Measuring antenna.....	87
A.2	Guidance on the use of radiation test sites	87
A.2.1	Verification of the test site	87
A.2.2	Preparation of the EUT.....	87
A.2.3	Power supplies to the EUT	87
A.2.4	Volume control setting for analogue speech tests	88
A.2.5	Range length.....	88
A.2.6	Site preparation	89
A.3	Coupling of signals.....	89
A.3.1	General	89
A.3.2	Data Signals.....	89
A.3.3	Speech and analogue signals	89
A.3.3.1	Acoustic coupler description.....	90
A.3.3.2	Calibration	90

Annex B (normative): Specification for some particular measurement arrangements.....91

B.1	Power measuring receiver specification.....	91
B.1.1	IF filter	91
B.1.2	Attenuation indicator.....	92
B.1.3	RMS value indicator.....	92
B.1.4	Oscillator and amplifier.....	92
B.2	Spectrum analyser specification.....	93
B.3	Integrating and power summing device	93

Annex C (informative):	Bibliography.....	94
History		95

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI EN 300 113-1 V1.7.1 \(2011-11\)](https://standards.iteh.ai/catalog/standards/etsi/603e554e-bd9f-416f-9150-d23bdd09e0ce/etsi-en-300-113-1-v1-7-1-2011-11)

<https://standards.iteh.ai/catalog/standards/etsi/603e554e-bd9f-416f-9150-d23bdd09e0ce/etsi-en-300-113-1-v1-7-1-2011-11>