

ETSI EN 300 132-3-1 V2.1.1 (2012-02)



**Environmental Engineering (EE);
Power supply interface at the input to telecommunications and
datacom (ICT) equipment;
Part 3: Operated by rectified current source, alternating
current source or direct current source up to 400 V;
Sub-part 1: Direct current source up to 400 V**

<https://standards.iteh.ai/catalog/standards/etsi/7d69bc6c-c2fd-4070-95a2-3fb3c020f698/etsi-en-300-132-3-1-v2-1-1-2012-02>

Reference

REN/EE-02017-1

Keywords

environment, interface, power supply

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2012.
All rights reserved.

DECTTM, PLUGTESTSTM, UMTSTM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPPTM and LTETM are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	5
Foreword.....	5
1 Scope	6
2 References	6
2.1 Normative references	6
2.2 Informative references.....	7
3 Definitions, symbols and abbreviations	7
3.1 Definitions.....	7
3.2 Symbols.....	8
3.3 Abbreviations	8
4 Interface A3.....	9
5 DC interface requirements.....	9
5.1 Nominal voltage	9
5.2 Normal service voltage range at interface A3	10
5.3 Normal operating voltage range at interface A3.....	10
5.4 Reference test voltage (U_T) at interface A3.....	10
5.5 Abnormal service voltage ranges at interface A3.....	10
6 Abnormal conditions: Voltage variations, voltage dips, short interruptions and voltage surges at interface A3.....	11
6.1 Voltage variations.....	11
6.2 Voltages dips	12
6.3 Short interruptions.....	12
6.4 Voltage surges	12
7 DC Supply protection.....	14
8 Maximum steady state current	14
8.1 Maximum steady state current I_m , in the normal service voltage range	14
8.2 Maximum steady state current in the abnormal service voltage range	14
9 Inrush current on connection to interface A3	14
9.1 Limits	14
9.2 Measurements.....	16
10 Earthing and Bonding.....	16
11 Electrical Safety requirements.....	16
12 EMC requirements at the input of telecommunications and datacom (ICT) equipment.....	17
Annex A (informative): Power supply considerations.....	18
Annex B (normative): Identification of interface A3	19
Annex C (informative): Calculation of the extreme DC voltage range at interface A3	20
Annex D (informative): Guide for defining inrush current energy, measuring inrush current and test generator peak inrush current drive capability.....	21
D.1 Measurement	21
D.2 Test generator peak inrush current drive capability	21
D.3 Example of inrush current waveform.....	22
Annex E (informative): Dimensioning of over-current protective devices.....	23

Annex F (informative):	Test generator for voltage dips, short interruptions and voltage variations	24
Annex G (informative):	Details of the voltage transient measurement in the most common case of distribution and protective devices	25
Annex H (informative):	Diagram of voltage ranges and values at the interface A3	27
History		28

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI EN 300 132-3-1 V2.1.1 \(2012-02\)](https://standards.iteh.ai/catalog/standards/etsi/7d69bc6c-c2fd-4070-95a2-3fb3c020f698/etsi-en-300-132-3-1-v2-1-1-2012-02)

<https://standards.iteh.ai/catalog/standards/etsi/7d69bc6c-c2fd-4070-95a2-3fb3c020f698/etsi-en-300-132-3-1-v2-1-1-2012-02>