

ETSI EN 300 175-4 V2.4.1 (2012-04)



Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 4: Data Link Control (DLC) layer

Document Preview

[ETSI EN 300 175-4 V2.4.1 \(2012-04\)](https://standards.iteh.ai/catalog/standards/etsi/6a84acdf-64a3-4525-8619-9bd413d1017b/etsi-en-300-175-4-v2-4-1-2012-04)

<https://standards.iteh.ai/catalog/standards/etsi/6a84acdf-64a3-4525-8619-9bd413d1017b/etsi-en-300-175-4-v2-4-1-2012-04>

Reference

REN/DECT-000260

Keywords

DECT, IMT-2000, mobility, radio, TDD, TDMA

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2012.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	11
Foreword.....	11
1 Scope	12
2 References	13
2.1 Normative references	13
2.2 Informative references.....	14
3 Definitions, symbols and abbreviations	14
3.1 Definitions.....	14
3.2 Symbols and abbreviations.....	14
4 Data Link Control (DLC) layer overview	16
4.1 General	16
4.2 C-plane services	17
4.3 U-plane services	18
4.4 Lower Layer Management Entity (LLME)	21
5 C-plane service characteristics	21
5.1 Data link service (LAPC+Lc).....	21
5.1.1 General.....	21
5.1.2 LAPC types of operation	22
5.1.3 Establishment of information transfer modes	22
5.1.3.1 Data Link Identifier (DLI)	22
5.1.3.2 LAPC states.....	22
5.2 Broadcast service (Lb).....	23
6 Frame structures for C-plane services	24
6.1 Data link service frame structure.....	24
6.1.1 General frame structure	24
6.1.2 Lc frame delimiting and transparency	25
6.1.3 Transmission order	25
6.1.4 Routing to logical channels.....	25
6.1.4.1 C_F/CL_F logical channel.....	25
6.1.4.2 C_S/CL_S logical channel.....	26
6.1.5 Invalid frames	26
6.2 Broadcast service frame structure.....	27
6.2.1 Standard frame structure	27
6.2.2 Extended frame structure	27
7 Elements of procedures and formats of fields for C-plane peer-to-peer communication.....	28
7.1 General	28
7.2 Address field formats	28
7.3 Address field parameters	28
7.3.1 REServed bit (RES).....	28
7.3.2 Command Response (C/R) bit	28
7.3.3 SAPI field	28
7.3.4 New Link Flag (NLF) bit.....	29
7.3.5 LLN-field.....	29
7.3.6 Data Link Identifiers (DLI).....	29
7.4 Control field formats	30
7.5 Control field parameters	30
7.5.1 Poll/Final (P/F) bit	30
7.5.2 Multiple frame operation variables and sequence numbers	30
7.5.2.1 Modulus	30
7.5.2.2 Send state Variable V(S).....	30
7.5.2.3 Acknowledge state Variable V(A)	31
7.5.2.4 Send sequence Number N(S)	31

7.5.2.5	Receive state Variable V(R).....	31
7.5.2.6	Receive sequence Number N(R).....	31
7.5.3	Unacknowledged operation variables and sequence numbers	31
7.5.4	Supervisory and Unnumbered function bits S and U.....	31
7.6	Length indicator field format.....	31
7.7	Length indicator field parameters.....	32
7.7.1	Length indicator field extension bit (N).....	32
7.7.2	More data bit (M).....	32
7.7.3	Length parameter (L _I)	32
7.7.4	Extended length parameter (L _{JJ})	33
7.7.5	Reserved bit (RES)	33
7.8	Fill field format	33
7.9	Checksum field format	33
7.10	Checksum field parameters	33
7.11	Commands and responses	35
7.11.1	Information (I) command.....	35
7.11.2	Receive Ready (RR) command/response.....	35
7.11.3	Receive Not Ready (RNR) command/response.....	36
7.11.4	REJect (REJ) command/response	36
7.11.5	Set Asynchronous Balanced Mode (SABM) command.....	36
7.11.6	Disconnect Mode (DM) response	36
7.11.7	Unnumbered Information (UI) command	36
7.11.8	DISConnect (DISC) command	37
7.11.9	Unnumbered ACK (UA) response	37
8	Primitives	37
8.1	Primitive types.....	37
8.2	Primitives to the MAC layer (lower layer)	37
8.3	Primitives to the NWK layer (higher layer)	37
8.3.1	Parameter definitions	38
8.3.2	S-SAP primitives	39
8.3.2.1	DL_ESTABLISH primitive	39
8.3.2.2	DL_RELEASE primitive	39
8.3.2.3	DL_DATA primitive.....	40
8.3.2.4	DL_UNIT_DATA primitive	40
8.3.2.5	DL_SUSPEND primitive.....	40
8.3.2.6	DL_RESUME primitive.....	40
8.3.2.7	DL_ENC_KEY primitive.....	41
8.3.2.8	DL_ENCRYPT primitive.....	41
8.3.2.9	DL_SERVICE_MOD primitive	41
8.3.3	B-SAP primitives.....	41
8.3.3.1	DL_BROADCAST primitive.....	42
8.3.3.2	DL_EXPEDITED primitive.....	42
8.4	Primitives to the interworking unit.....	42
8.4.1	Parameter definitions	42
8.4.2	LU _x -SAP primitives	43
8.4.2.1	DL_U_DATA primitive.....	43
8.4.2.2	DL_U_UNIT_DATA primitive	43
8.4.2.3	DL_U_ERROR primitive.....	43
9	C-plane peer-to-peer procedures	44
9.1	General	44
9.2	Point to point acknowledged operation	44
9.2.1	Procedure for the use of the P/F bit	44
9.2.1.1	Class A acknowledged information transfer	44
9.2.1.2	Class B acknowledged information transfer	45
9.2.2	Use of LLN	45
9.2.2.1	Class A operation	45
9.2.2.2	Class B operation	45
9.2.3	Link establishment and information transfer in class A operation.....	45
9.2.3.1	Establishing class A operation	45
9.2.3.2	Class A acknowledged information transfer	46

9.2.3.3	Transmission of class A I-frames.....	46
9.2.3.4	Reception of class A I-frames.....	47
9.2.3.5	Receiving acknowledgements.....	47
9.2.3.6	Waiting for acknowledgement.....	47
9.2.3.7	Release of class A operation.....	48
9.2.3.8	Re-establishment of class A operation.....	48
9.2.4	Establishing class B multiple frame operation.....	48
9.2.4.1	Overview.....	48
9.2.4.2	Class B multiple frame establishment procedures.....	49
9.2.4.3	Class B LLN assignment procedures.....	50
9.2.4.3.1	PT establishment.....	50
9.2.4.3.2	FT establishment.....	51
9.2.5	Link maintenance and information transfer in class B multiple frame operation.....	51
9.2.5.1	Transmitting I-frames.....	51
9.2.5.2	Receiving I-frames.....	52
9.2.5.2.1	P bit set to 1.....	52
9.2.5.2.2	P bit set to 0.....	52
9.2.5.3	Sending and receiving acknowledgements.....	52
9.2.5.3.1	Sending acknowledgements.....	52
9.2.5.3.2	Receiving acknowledgements.....	52
9.2.5.4	Receiving REJ-frames.....	53
9.2.5.5	Receiving RNR-frames.....	54
9.2.5.6	LAPC own receiver busy condition.....	55
9.2.5.7	Waiting acknowledgement.....	55
9.2.5.8	Appropriate supervisory frame.....	56
9.2.6	Release of class B multiple frame operation.....	56
9.2.7	Link suspension and resumption.....	57
9.2.7.1	Link suspension.....	57
9.2.7.1.1	Class B acknowledged suspend.....	57
9.2.7.1.2	Unacknowledged suspend.....	58
9.2.7.2	Class B link resumption.....	59
9.2.7.3	Connection handover.....	60
9.2.7.3.1	Class A connection handover.....	61
9.2.7.3.2	Class B connection handover.....	62
9.2.7.3.3	Expiry of connection handover timer.....	62
9.2.8	Re-establishment of class B multi-frame operation.....	62
9.2.8.1	Criteria for re-establishment.....	62
9.2.8.2	Procedure.....	63
9.2.9	Exception handling.....	63
9.2.9.1	General.....	63
9.2.9.2	Class B exception condition reporting and recovery.....	64
9.2.9.2.1	N(S) sequence error.....	64
9.2.9.2.2	N(R) sequence error.....	64
9.2.9.2.3	Timer recovery condition.....	64
9.2.9.2.4	Collision of identical transmitted and received commands.....	64
9.3	Unacknowledged operation.....	65
9.3.1	Use of LLN for unacknowledged information transfer.....	65
9.3.2	Class U link establishment.....	65
9.3.3	Unacknowledged information transfer.....	65
9.3.3.1	Transmission of unacknowledged information.....	65
9.3.3.2	Reception of unacknowledged information.....	65
9.3.4	Unacknowledged release.....	65
9.4	Broadcast operation.....	65
9.4.1	Normal operation.....	65
9.4.1.1	Procedure in the Fixed radio Termination (FT).....	65
9.4.1.2	Procedure in the Portable radio Termination (PT).....	66
9.4.2	Expedited operation.....	66
9.4.2.1	Procedure in the Fixed radio Termination (FT).....	66
9.4.2.2	Procedure in the Portable radio Termination (PT).....	66
9.5	MAC layer interfaces.....	67
9.5.1	MC-SAP.....	67
9.5.1.1	C-plane overview.....	67

9.5.1.2	C-plane service data procedures.....	67
9.5.1.3	U-plane service data.....	68
9.5.2	MB-SAP	68
9.5.2.1	C-plane service data procedures.....	68
9.5.2.2	U-plane service data.....	68
9.5.3	MA-SAP	69
9.5.3.1	Overview	69
9.5.3.2	Service data procedures.....	69
10	Management procedures.....	69
10.1	Lower Layer Management Entity (LLME)	69
10.2	MAC connection management.....	70
10.2.1	MAC connection set-up	70
10.2.2	MAC connection release.....	70
10.2.3	MAC connection modification	70
10.2.4	MAC connection identifiers.....	71
10.2.4.1	Overview	71
10.2.4.2	Advanced MAC Connection Identifiers (AMCI).....	71
10.2.4.3	Basic MAC Connection Identifiers (BMCI)	72
10.2.4.4	MAC Connection Endpoint Identifier (MCEI)	72
10.2.5	Selection of logical channel (C_S or C_F).....	72
10.3	DLC C-plane (LAPC) management	73
10.3.1	Provision of link signature	73
10.3.2	Routing of connection oriented links	73
10.3.3	Routing of connectionless links	74
10.4	DLC U-plane (LUX) management.....	74
10.4.1	U-plane establishment.....	74
10.4.2	U-plane release	74
10.4.3	U-plane suspend and resume	74
10.5	Connection handover management	75
10.6	Ciphering management.....	75
10.6.1	Ciphering management in cases where the NWK layer executes the ciphering related MM procedure	75
10.6.1.1	Providing a key to the MAC layer	75
10.6.1.2	Starting and stopping the ciphering.....	76
10.6.1.3	Connection handover	76
10.6.2	Ciphering management in cases where the NWK layer does not execute the ciphering related MM procedure	76
10.7	Broadband data link management	76
11	U-plane service characteristics.....	77
11.1	General	77
11.2	LU1 TRAnsparent UnProtected service (TRUP)	77
11.3	LU2 Frame RELay service (FREL).....	78
11.3.1	General.....	78
11.3.2	Checksum operation	79
11.3.3	Segmentation and transmission class.....	79
11.3.4	Data transmission.....	80
11.3.4.1	Send side procedure	80
11.3.4.2	Receive side procedure	80
11.4	LU3 Frame SWItching service (FSWI).....	81
11.5	LU4 Forward Error Correction (FEC) service.....	81
11.6	LU5 Basic RATE adaption service (BRAT).....	82
11.6.1	Overview	82
11.6.2	Protected service operation.....	83
11.6.2.1	General.....	83
11.6.2.2	Data buffering and initial rate adaptation.....	83
11.6.2.3	Multi-channel set multiplexing	84
11.6.2.4	Segmentation of Multiplexed Data Units (MDU).....	85
11.6.2.5	Frame sequencing and addition of control and fill octets.....	86
11.6.2.6	Frame transmission	87
11.6.3	Unprotected service operation	88
11.6.3.1	General.....	88

11.6.3.2	Data buffering and initial rate adaption.....	88
11.6.3.3	Multi-channel set multiplexing	88
11.6.3.4	Segmentation of MDUs.....	90
11.6.3.5	Frame transmission	90
11.7	LU6 Secondary RATE adaption (SRAT) service	90
11.7.1	General.....	90
11.8	LU16 ESCape Service (ESC).....	91
11.8.1	General.....	91
11.9	LU7 64 kbit/s data bearer service	92
11.9.1	General.....	92
11.9.2	Physical layer service.....	92
11.9.3	MAC layer service	92
11.9.4	DLC layer service	92
11.9.4.1	Architectural model.....	92
11.9.4.1.1	Transmit (Tx) frame buffering	93
11.9.4.1.2	Receive (Rx) frame buffering	93
11.9.4.2	Automatic-Repeat-Request (ARQ) and Forward Error Control (FEC).....	93
11.9.4.2.1	Control field	94
11.9.4.2.2	Information field.....	96
11.9.4.2.3	ARQ checksum.....	97
11.9.4.3	Procedures for normal operation	97
11.9.4.3.1	Establishment and synchronization procedures	97
11.9.4.3.2	Active phase	99
11.9.4.3.3	Release.....	101
11.9.4.4	Exceptional procedures	101
11.9.4.4.1	Invalid frame condition	101
11.9.4.4.2	Establishment	101
11.9.4.4.3	Transmitting frames.....	101
11.9.4.4.4	Receiving frames.....	101
11.9.4.4.5	Sending acknowledgements	102
11.9.4.4.6	Forwarding of received data	102
11.9.4.4.7	N(R) sequence error	102
11.9.4.4.8	N(O) sequence error	102
11.9.4.4.9	N(S) sequence error	103
11.9.4.4.10	Format error.....	103
11.9.4.4.11	Abnormal release	103
11.9.4.4.12	Implicit reset	103
11.9.5	Network layer service	103
11.9.5.1	LCE service.....	103
11.9.5.2	CC service	103
11.10	LU8 service	104
11.10.1	Physical layer service.....	104
11.10.2	MAC layer service	104
11.10.3	DLC layer service	104
11.11	LU9 - Unprotected Rate Adaption for V series Equipment (RAVE) Service	104
11.11.1	Overview	104
11.11.1.1	FU9 frame structure	105
11.11.1.1.1	General frame structure	105
11.11.1.1.2	FU9 buffering procedures.....	105
11.11.1.1.3	Connection handover	105
11.11.1.1.4	Transmission order	106
11.11.2	Alignment signal management	106
11.11.2.1	General	106
11.11.2.2	Procedures	106
11.11.3	V.24 Signalling	107
11.11.3.1	General	107
11.11.3.2	Transmitter procedures.....	108
11.11.3.3	Receiver procedures	108
11.11.4	Rate Coding	108
11.11.4.1	General	108
11.11.4.2	Transmitter procedures.....	109
11.11.4.3	Receiver procedures	109