



**Digital Enhanced Cordless Telecommunications (DECT);
Common Interface (CI);
Part 4: Data Link Control (DLC) layer**

Document Preview

[ETSI EN 300 175-4 V2.5.1 \(2013-08\)](https://standards.iteh.ai/catalog/standards/etsi/00c72c87-6c95-4bd9-8d93-784acc18d0ef/etsi-en-300-175-4-v2-5-1-2013-08)

<https://standards.iteh.ai/catalog/standards/etsi/00c72c87-6c95-4bd9-8d93-784acc18d0ef/etsi-en-300-175-4-v2-5-1-2013-08>

Reference

REN/DECT-000268-4

KeywordsDECT, DLC, IMT-2000, mobility, radio, TDD,
TDMA**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iteh Standards
(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2013.
All rights reserved.

DECTTM, PLUGTESTSTM, UMTSTM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPPTM and LTETM are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	12
Foreword.....	12
1 Scope	13
2 References	14
2.1 Normative references	14
2.2 Informative references.....	15
3 Definitions, symbols and abbreviations	15
3.1 Definitions.....	15
3.2 Symbols and abbreviations.....	15
4 Data Link Control (DLC) layer overview	18
4.1 General	18
4.2 C-plane services	19
4.3 U-plane services	20
4.4 Lower Layer Management Entity (LLME)	23
5 C-plane service characteristics	23
5.1 Data link service (LAPC+Lc).....	23
5.1.1 General.....	23
5.1.2 LAPC types of operation	24
5.1.3 Establishment of information transfer modes	24
5.1.3.1 Data Link Identifier (DLI)	24
5.1.3.2 LAPC states.....	24
5.2 Broadcast service (Lb).....	25
6 Frame structures for C-plane services	26
6.1 Data link service frame structure.....	26
6.1.1 General frame structure	26
6.1.2 Lc frame delimiting and transparency	27
6.1.3 Transmission order	27
6.1.4 Routing to logical channels.....	27
6.1.4.1 C_F/CL_F logical channel.....	27
6.1.4.2 C_S/CL_S logical channel.....	28
6.1.5 Invalid frames	28
6.2 Broadcast service frame structure.....	29
6.2.1 Standard frame structure	29
6.2.2 Extended frame structure	29
7 Elements of procedures and formats of fields for C-plane peer-to-peer communication.....	30
7.1 General	30
7.2 Address field formats	30
7.3 Address field parameters	30
7.3.1 REserved bit (RES).....	30
7.3.2 Command Response (C/R) bit	30
7.3.3 SAPI field	30
7.3.4 New Link Flag (NLF) bit.....	31
7.3.5 LLN-field.....	31
7.3.6 Data Link Identifiers (DLI).....	31
7.4 Control field formats	32
7.5 Control field parameters	32
7.5.1 Poll/Final (P/F) bit	32
7.5.2 Multiple frame operation variables and sequence numbers	32
7.5.2.1 Modulus	32
7.5.2.2 Send state Variable V(S).....	32
7.5.2.3 Acknowledge state Variable V(A).....	33
7.5.2.4 Send sequence Number N(S)	33

7.5.2.5	Receive state Variable V(R).....	33
7.5.2.6	Receive sequence Number N(R).....	33
7.5.3	Unacknowledged operation variables and sequence numbers	33
7.5.4	Supervisory and Unnumbered function bits S and U	33
7.6	Length indicator field format.....	33
7.7	Length indicator field parameters.....	34
7.7.1	Length indicator field extension bit (N).....	34
7.7.2	More data bit (M).....	34
7.7.3	Length parameter (L _I)	34
7.7.4	Extended length parameter (L _{JJ})	35
7.7.5	Reserved bit (RES)	35
7.8	Fill field format	35
7.9	Checksum field format	35
7.10	Checksum field parameters	35
7.11	Commands and responses	37
7.11.1	Information (I) command.....	37
7.11.2	Receive Ready (RR) command/response.....	37
7.11.3	Receive Not Ready (RNR) command/response.....	38
7.11.4	REJect (REJ) command/response	38
7.11.5	Set Asynchronous Balanced Mode (SABM) command.....	38
7.11.6	Disconnect Mode (DM) response	38
7.11.7	Unnumbered Information (UI) command	38
7.11.8	DISConnect (DISC) command	39
7.11.9	Unnumbered ACK (UA) response	39
8	Primitives	39
8.1	Primitive types.....	39
8.2	Primitives to the MAC layer (lower layer)	39
8.3	Primitives to the NWK layer (higher layer)	39
8.3.1	Parameter definitions	40
8.3.2	S-SAP primitives	41
8.3.2.1	DL_ESTABLISH primitive	41
8.3.2.2	DL_RELEASE primitive	41
8.3.2.3	DL_DATA primitive.....	42
8.3.2.4	DL_UNIT_DATA primitive	42
8.3.2.5	DL_SUSPEND primitive	42
8.3.2.6	DL_RESUME primitive	42
8.3.2.7	DL_ENC_KEY primitive.....	43
8.3.2.8	DL_ENCRYPT primitive.....	43
8.3.2.9	DL_SERVICE_MOD primitive	43
8.3.3	B-SAP primitives.....	43
8.3.3.1	DL_BROADCAST primitive.....	44
8.3.3.2	DL_EXPEDITED primitive	44
8.4	Primitives to the interworking unit	44
8.4.1	Parameter definitions	44
8.4.2	LU _X -SAP primitives	45
8.4.2.1	DL_U_DATA primitive	45
8.4.2.2	DL_U_UNIT_DATA primitive	45
8.4.2.3	DL_U_ERROR primitive.....	45
9	C-plane peer-to-peer procedures	46
9.1	General	46
9.2	Point to point acknowledged operation	46
9.2.1	Procedure for the use of the P/F bit	46
9.2.1.1	Class A acknowledged information transfer	46
9.2.1.2	Class B acknowledged information transfer	47
9.2.2	Use of LLN	47
9.2.2.1	Class A operation	47
9.2.2.2	Class B operation	47
9.2.3	Link establishment and information transfer in class A operation.....	47
9.2.3.1	Establishing class A operation	47
9.2.3.2	Class A acknowledged information transfer	48

9.2.3.3	Transmission of class A I-frames.....	48
9.2.3.4	Reception of class A I-frames.....	49
9.2.3.5	Receiving acknowledgements.....	49
9.2.3.6	Waiting for acknowledgement.....	49
9.2.3.7	Release of class A operation.....	50
9.2.3.8	Re-establishment of class A operation.....	50
9.2.4	Establishing class B multiple frame operation.....	50
9.2.4.1	Overview.....	50
9.2.4.2	Class B multiple frame establishment procedures.....	51
9.2.4.3	Class B LLN assignment procedures.....	52
9.2.4.3.1	PT establishment.....	52
9.2.4.3.2	FT establishment.....	53
9.2.5	Link maintenance and information transfer in class B multiple frame operation.....	53
9.2.5.1	Transmitting I-frames.....	53
9.2.5.2	Receiving I-frames.....	54
9.2.5.2.1	P bit set to 1.....	54
9.2.5.2.2	P bit set to 0.....	54
9.2.5.3	Sending and receiving acknowledgements.....	54
9.2.5.3.1	Sending acknowledgements.....	54
9.2.5.3.2	Receiving acknowledgements.....	54
9.2.5.4	Receiving REJ-frames.....	55
9.2.5.5	Receiving RNR-frames.....	56
9.2.5.6	LAPC own receiver busy condition.....	57
9.2.5.7	Waiting acknowledgement.....	57
9.2.5.8	Appropriate supervisory frame.....	58
9.2.6	Release of class B multiple frame operation.....	58
9.2.7	Link suspension and resumption.....	59
9.2.7.1	Link suspension.....	59
9.2.7.1.1	Class B acknowledged suspend.....	59
9.2.7.1.2	Unacknowledged suspend.....	60
9.2.7.2	Class B link resumption.....	61
9.2.7.3	Connection handover.....	62
9.2.7.3.1	Class A connection handover.....	63
9.2.7.3.2	Class B connection handover.....	64
9.2.7.3.3	Expiry of connection handover timer.....	64
9.2.8	Re-establishment of class B multi-frame operation.....	64
9.2.8.1	Criteria for re-establishment.....	64
9.2.8.2	Procedure.....	65
9.2.9	Exception handling.....	65
9.2.9.1	General.....	65
9.2.9.2	Class B exception condition reporting and recovery.....	66
9.2.9.2.1	N(S) sequence error.....	66
9.2.9.2.2	N(R) sequence error.....	66
9.2.9.2.3	Timer recovery condition.....	66
9.2.9.2.4	Collision of identical transmitted and received commands.....	66
9.3	Unacknowledged operation.....	67
9.3.1	Use of LLN for unacknowledged information transfer.....	67
9.3.2	Class U link establishment.....	67
9.3.3	Unacknowledged information transfer.....	67
9.3.3.1	Transmission of unacknowledged information.....	67
9.3.3.2	Reception of unacknowledged information.....	67
9.3.4	Unacknowledged release.....	67
9.4	Broadcast operation.....	67
9.4.1	Normal operation.....	67
9.4.1.1	Procedure in the Fixed radio Termination (FT).....	67
9.4.1.2	Procedure in the Portable radio Termination (PT).....	68
9.4.2	Expedited operation.....	68
9.4.2.1	Procedure in the Fixed radio Termination (FT).....	68
9.4.2.2	Procedure in the Portable radio Termination (PT).....	68
9.5	MAC layer interfaces.....	69
9.5.1	MC-SAP.....	69
9.5.1.1	C-plane overview.....	69

9.5.1.2	C-plane service data procedures.....	69
9.5.1.3	U-plane service data.....	70
9.5.2	MB-SAP	70
9.5.2.1	C-plane service data procedures.....	70
9.5.2.2	U-plane service data.....	70
9.5.3	MA-SAP	71
9.5.3.1	Overview	71
9.5.3.2	Service data procedures.....	71
10	Management procedures.....	71
10.1	Lower Layer Management Entity (LLME)	71
10.2	MAC connection management	72
10.2.1	MAC connection set-up	72
10.2.2	MAC connection release.....	72
10.2.3	MAC connection modification	72
10.2.4	MAC connection identifiers.....	73
10.2.4.1	Overview	73
10.2.4.2	Advanced MAC Connection Identifiers (AMCI).....	73
10.2.4.3	Basic MAC Connection Identifiers (BMCI)	74
10.2.4.4	MAC Connection Endpoint Identifier (MCEI)	74
10.2.5	Selection of logical channel (C _S or C _F).....	74
10.3	DLC C-plane (LAPC) management	75
10.3.1	Provision of link signature	75
10.3.2	Routing of connection oriented links	75
10.3.3	Routing of connectionless links	76
10.4	DLC U-plane (LUX) management	76
10.4.1	U-plane establishment.....	76
10.4.2	U-plane release	76
10.4.3	U-plane suspend and resume	76
10.5	Connection handover management	77
10.6	Ciphering management.....	77
10.6.1	Ciphering management in cases where the NWK layer executes the ciphering related MM procedure	77
10.6.1.1	Providing a key to the MAC layer	77
10.6.1.2	Starting and stopping the ciphering.....	78
10.6.1.3	Connection handover	78
10.6.2	Ciphering management in cases where the NWK layer does not execute the ciphering related MM procedure	78
10.7	Broadband data link management	78
11	U-plane service characteristics.....	79
11.1	General	79
11.2	LU1 TRAnsparent UnProtected service (TRUP)	79
11.3	LU2 Frame RELay service (FREL).....	80
11.3.1	General.....	80
11.3.2	Checksum operation	81
11.3.3	Segmentation and transmission class.....	81
11.3.4	Data transmission.....	82
11.3.4.1	Send side procedure	82
11.3.4.2	Receive side procedure	82
11.4	LU3 Frame SWItching service (FSWI).....	83
11.5	LU4 Forward Error Correction (FEC) service.....	83
11.6	LU5 Basic RATE adaption service (BRAT).....	84
11.6.1	Overview	84
11.6.2	Protected service operation.....	85
11.6.2.1	General.....	85
11.6.2.2	Data buffering and initial rate adaptation.....	85
11.6.2.3	Multi-channel set multiplexing	86
11.6.2.4	Segmentation of Multiplexed Data Units (MDU).....	87
11.6.2.5	Frame sequencing and addition of control and fill octets.....	88
11.6.2.6	Frame transmission	89
11.6.3	Unprotected service operation	90
11.6.3.1	General.....	90

11.6.3.2	Data buffering and initial rate adaption.....	90
11.6.3.3	Multi-channel set multiplexing	90
11.6.3.4	Segmentation of MDUs.....	92
11.6.3.5	Frame transmission	92
11.7	LU6 Secondary RATE adaption (SRAT) service	92
11.7.1	General.....	92
11.8	LU16 ESCape Service (ESC).....	93
11.8.1	General.....	93
11.9	LU7 64 kbit/s data bearer service	94
11.9.1	General.....	94
11.9.2	Physical layer service.....	94
11.9.3	MAC layer service	94
11.9.4	DLC layer service	94
11.9.4.1	Architectural model.....	94
11.9.4.1.1	Transmit (Tx) frame buffering	95
11.9.4.1.2	Receive (Rx) frame buffering	95
11.9.4.2	Automatic-Repeat-Request (ARQ) and Forward Error Control (FEC).....	95
11.9.4.2.1	Control field	96
11.9.4.2.2	Information field.....	98
11.9.4.2.3	ARQ checksum.....	99
11.9.4.3	Procedures for normal operation	99
11.9.4.3.1	Establishment and synchronization procedures	99
11.9.4.3.2	Active phase	101
11.9.4.3.3	Release.....	103
11.9.4.4	Exceptional procedures	103
11.9.4.4.1	Invalid frame condition	103
11.9.4.4.2	Establishment	103
11.9.4.4.3	Transmitting frames.....	103
11.9.4.4.4	Receiving frames.....	103
11.9.4.4.5	Sending acknowledgements	104
11.9.4.4.6	Forwarding of received data	104
11.9.4.4.7	N(R) sequence error	104
11.9.4.4.8	N(O) sequence error	104
11.9.4.4.9	N(S) sequence error	105
11.9.4.4.10	Format error.....	105
11.9.4.4.11	Abnormal release	105
11.9.4.4.12	Implicit reset	105
11.9.5	Network layer service	105
11.9.5.1	LCE service.....	105
11.9.5.2	CC service	105
11.10	LU8 service	106
11.10.1	Physical layer service.....	106
11.10.2	MAC layer service	106
11.10.3	DLC layer service	106
11.11	LU9 - Unprotected Rate Adaption for V series Equipment (RAVE) Service	106
11.11.1	Overview	106
11.11.1.1	FU9 frame structure	107
11.11.1.1.1	General frame structure	107
11.11.1.1.2	FU9 buffering procedures.....	107
11.11.1.1.3	Connection handover	107
11.11.1.1.4	Transmission order	108
11.11.2	Alignment signal management	108
11.11.2.1	General	108
11.11.2.2	Procedures	108
11.11.3	V.24 Signalling	109
11.11.3.1	General	109
11.11.3.2	Transmitter procedures.....	110
11.11.3.3	Receiver procedures	110
11.11.4	Rate Coding	110
11.11.4.1	General	110
11.11.4.2	Transmitter procedures.....	111
11.11.4.3	Receiver procedures	111