

ETSI EN 300 175-5 V2.4.1 (2012-04)



Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 5: Network (NWK) layer

(<https://standards.iteh.ai>)
Document Preview

[ETSI EN 300 175-5 V2.4.1 \(2012-04\)](https://standards.iteh.ai/catalog/standards/etsi/62ca91f6-0b25-41be-acc9-1abca1bca427/etsi-en-300-175-5-v2-4-1-2012-04)

<https://standards.iteh.ai/catalog/standards/etsi/62ca91f6-0b25-41be-acc9-1abca1bca427/etsi-en-300-175-5-v2-4-1-2012-04>

ReferenceREN/DECT-000261

Keywords

DECT, IMT-2000, mobility, radio, TDD, TDMA

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iteh Standards
(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2012.
All rights reserved.

DECTTM, PLUGTESTSTM, UMTSTM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPPTM and LTETM are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	16
Foreword.....	16
1 Scope	17
2 References	17
2.1 Normative references	18
2.2 Informative references.....	21
3 Definitions, symbols and abbreviations	22
3.1 Definitions.....	22
3.2 Symbols and abbreviations.....	23
4 Overview of the NWK layer	26
5 Overview of procedures	28
5.1 General	28
5.2 Overview of Call Control (CC)	28
5.2.1 General.....	28
5.2.2 Call establishment.....	28
5.2.2.1 Call setup	28
5.2.2.2 Service negotiation.....	29
5.2.3 Call connect	29
5.2.4 Call information.....	29
5.2.5 Service change	30
5.2.6 Call release.....	30
5.3 Overview of Supplementary Services (SS)	30
5.3.1 General.....	30
5.3.2 Keypad protocol.....	31
5.3.3 Feature key management protocol	31
5.3.4 Functional protocol	31
5.4 Overview of Connection Oriented Message Service (COMS)	31
5.4.1 General.....	31
5.4.2 COMS establishment	32
5.4.3 Service negotiation	32
5.4.4 COMS connect.....	32
5.4.5 COMS data transfer	32
5.4.6 COMS suspend and resume	32
5.4.7 COMS release	33
5.5 Overview of ConnectionLess Message Service (CLMS)	33
5.5.1 Fixed length message service.....	33
5.5.2 Variable length message service.....	33
5.6 Overview of Mobility Management (MM)	33
5.6.1 General.....	33
5.6.2 Identity procedures	34
5.6.3 Authentication procedures	34
5.6.4 Location procedures.....	35
5.6.5 Access rights procedures	35
5.6.6 Key allocation procedure	35
5.6.7 Parameter retrieval procedure	36
5.6.8 Ciphering related procedure.....	36
5.6.9 External protocol information procedure.....	36
5.7 Overview of Link Control Entity (LCE)	36
5.7.1 General.....	36
5.7.2 Data Link Endpoint Identifier (DLEI)	36
5.7.3 Data link establishment.....	37
5.7.4 Data link re-establishment	37
5.7.5 Data link release	37

5.7.6	Data link suspend and resume.....	38
5.7.7	Queuing of messages	38
5.7.8	Request paging.....	38
6	Message functional definitions.....	38
6.1	Overview of message structures	38
6.1.1	Messages.....	38
6.1.2	Information elements	39
6.2	Message summaries.....	40
6.2.1	Summary of CC messages	40
6.2.2	Summary of CISS messages	40
6.2.3	Summary of COMS messages	41
6.2.4	Summary of CLMS messages.....	41
6.2.5	Summary of MM messages	42
6.2.6	Summary of LCE messages	42
6.3	S-FORMAT message functional contents.....	43
6.3.1	S-FORMAT message overview	43
6.3.2	CC-messages.....	43
6.3.2.1	{CC-SETUP}	43
6.3.2.2	{CC-INFO}	45
6.3.2.3	{CC-SETUP-ACK}	46
6.3.2.4	{CC-CALL-PROC}	47
6.3.2.5	{CC-ALERTING}	48
6.3.2.6	{CC-CONNECT}	49
6.3.2.7	{CC-CONNECT-ACK}	50
6.3.2.8	{CC-RELEASE}	50
6.3.2.9	{CC-RELEASE-COM}	52
6.3.2.10	{CC-SERVICE-CHANGE}	53
6.3.2.11	{CC-SERVICE-ACCEPT}	54
6.3.2.12	{CC-SERVICE-REJECT}	54
6.3.2.13	{CC-NOTIFY}	55
6.3.2.14	{IWU-INFO}	55
6.3.3	SS-messages (call related and call independent)	56
6.3.3.1	{FACILITY}.....	56
6.3.3.2	{HOLD}	57
6.3.3.3	{HOLD-ACK}	57
6.3.3.4	{HOLD-REJECT}	58
6.3.3.5	{RETRIEVE}	58
6.3.3.6	{RETRIEVE-ACK}	59
6.3.3.7	{RETRIEVE-REJECT}	59
6.3.3.8	{CISS-REGISTER}	60
6.3.3.9	{CISS-RELEASE-COM}	61
6.3.4	COMS-messages.....	61
6.3.4.1	{COMS-SETUP}	61
6.3.4.2	{COMS-INFO}	62
6.3.4.3	{COMS-ACK}	63
6.3.4.4	{COMS-CONNECT}	63
6.3.4.5	{COMS-RELEASE}	64
6.3.4.6	{COMS-RELEASE-COM}	64
6.3.4.7	{COMS-NOTIFY}.....	65
6.3.5	CLMS-message.....	65
6.3.5.1	{CLMS-VARIABLE}	65
6.3.6	MM-messages.....	66
6.3.6.1	{ACCESS-RIGHTS-ACCEPT}	66
6.3.6.2	{ACCESS-RIGHTS-REJECT}.....	66
6.3.6.3	{ACCESS-RIGHTS-REQUEST}	67
6.3.6.4	{ACCESS-RIGHTS-TERMINATE-ACCEPT}	67
6.3.6.5	{ACCESS-RIGHTS-TERMINATE-REJECT}	68
6.3.6.6	{ACCESS-RIGHTS-TERMINATE-REQUEST}.....	68
6.3.6.7	{AUTHENTICATION-REJECT}	69
6.3.6.8	{AUTHENTICATION-REPLY}	70
6.3.6.9	{AUTHENTICATION-REQUEST}	71

6.3.6.10	{CIPHER-REJECT}	71
6.3.6.11	{CIPHER-REQUEST}	72
6.3.6.12	{CIPHER-SUGGEST}	72
6.3.6.13	{DETACH}	72
6.3.6.14	{IDENTITY-REPLY}	73
6.3.6.15	{IDENTITY-REQUEST}	74
6.3.6.16	{KEY-ALLOCATE}	74
6.3.6.17	{LOCATE-ACCEPT}	75
6.3.6.18	{LOCATE-REJECT}	75
6.3.6.19	{LOCATE-REQUEST}	76
6.3.6.20	{MM-INFO-ACCEPT}	77
6.3.6.21	{MM-INFO-REJECT}	77
6.3.6.22	{MM-INFO-REQUEST}	78
6.3.6.23	{MM-INFO-SUGGEST}	79
6.3.6.24	{TEMPORARY-IDENTITY-ASSIGN}	79
6.3.6.25	{TEMPORARY-IDENTITY-ASSIGN-ACK}	80
6.3.6.26	{TEMPORARY-IDENTITY-ASSIGN-REJ}	80
6.3.6.27	{MM-IWU}	81
6.3.6.28	{MM-NOTIFY}	81
6.3.7	LCE-messages	82
6.3.7.1	{LCE-PAGE-RESPONSE}	82
6.3.7.2	{LCE-PAGE-REJECT}	82
6.4	B-FORMAT message functional contents	83
6.4.1	B-FORMAT message overview	83
6.4.2	{LCE-REQUEST-PAGE}	83
6.4.3	{CLMS-FIXED}	84
7	S-FORMAT message structures	84
7.1	Overview	84
7.2	Protocol Discrimination (PD) element	85
7.3	Transaction Identifier (TI) element	85
7.4	Message type element	86
7.4.1	Messages for CC	87
7.4.2	Messages for SS	87
7.4.3	Messages for COMS	87
7.4.4	Messages for CLMS	88
7.4.5	Messages for MM	88
7.4.6	Messages for LCE	88
7.5	Other information elements	89
7.5.1	Coding rules	89
7.5.2	Extensions of codesets	91
7.5.3	Locking shift procedure	91
7.5.4	Non-locking shift procedure	92
7.5.5	Display and keypad elements	92
7.5.6	Repeated elements	92
7.6	Fixed length information elements	93
7.6.1	Summary	93
7.6.2	Sending complete, delimiter request and use TPUI	93
7.6.3	Repeat indicator	94
7.6.4	Basic service	94
7.6.5	Single display	95
7.6.6	Single keypad	95
7.6.7	Release reason	96
7.6.8	Signal	97
7.6.9	Timer restart	98
7.6.10	Test hook control	98
7.7	Variable length information elements	98
7.7.1	Summary	98
7.7.2	Allocation type	100
7.7.3	Alphanumeric	100
7.7.4	Auth type	102
7.7.5	Call attributes	103

7.7.6	Call identity	106
7.7.7	Called party number.....	106
7.7.8	Called party subaddress	107
7.7.9	Calling party number	108
7.7.10	Cipher info	109
7.7.11	Connection attributes	110
7.7.12	Connection identity.....	113
7.7.13	Duration	114
7.7.14	End-to-end compatibility	115
7.7.15	Facility	118
7.7.16	Feature activate	118
7.7.17	Feature indicate.....	120
7.7.18	Fixed identity.....	122
7.7.19	Identity type.....	123
7.7.20	Info type.....	124
7.7.21	InterWorking Unit (IWU) attributes	125
7.7.22	IWU packet.....	130
7.7.23	IWU to IWU	131
7.7.24	Key.....	133
7.7.25	Location area	133
7.7.26	Multi-display.....	134
7.7.27	Multi-keypad.....	135
7.7.28	NetWorK (NWK) assigned identity.....	135
7.7.29	Network parameter	136
7.7.30	Portable identity.....	138
7.7.31	Progress indicator	142
7.7.32	RAND	143
7.7.33	Rate parameters	143
7.7.34	Reject reason.....	144
7.7.35	RES	145
7.7.36	RS	146
7.7.37	Segmented info	146
7.7.38	Service change info.....	147
7.7.39	Service class.....	148
7.7.40	Setup capability	149
7.7.41	Terminal capability.....	150
7.7.42	Transit delay	156
7.7.43	Window size	156
7.7.44	ZAP field	157
7.7.45	Escape to proprietary	157
7.7.46	Model identifier	158
7.7.47	MMS Generic Header.....	159
7.7.48	MMS Object Header.....	159
7.7.49	MMS Extended header	159
7.7.50	Time-Date	160
7.7.51	Ext h/o indicator	162
7.7.52	Called party Name	162
7.7.53	Calling party Name.....	163
7.7.54	Codec List.....	164
7.7.55	Events notification	165
7.7.56	Call information.....	169
8	B-FORMAT message structures	172
8.1	General	172
8.2	LCE request paging messages	172
8.2.1	Short format message.....	173
8.2.2	Full format message.....	174
8.2.3	Long format message.....	175
8.2.4	Message elements	176
8.2.4.1	LCE paging header.....	176
8.2.4.2	Info fields (Full format)	177
8.2.4.3	Default setup behaviour	178

8.2.4.4	Address elements in collective or group ringing.....	180
8.3	CLMS-FIXED messages.....	180
8.3.1	General message structure	180
8.3.2	Message elements	181
8.3.3	Standard message structures	183
8.3.3.1	General	183
8.3.3.2	Messages using 4-bit characters	183
8.3.3.3	Messages using 8-bit characters	183
9	Call Control (CC) procedures.....	183
9.1	General	183
9.2	Call Control (CC) states	186
9.2.1	States at PT	186
9.2.1.1	State T-00: "NULL"	186
9.2.1.2	State T-19: "RELEASE PENDING"	186
9.2.1.3	State T-10: "ACTIVE"	186
9.2.1.4	State T-01: "CALL INITIATED"	186
9.2.1.5	State T-02: "OVERLAP SENDING"	186
9.2.1.6	State T-03: "CALL PROCEEDING"	186
9.2.1.7	State T-04: "CALL DELIVERED"	186
9.2.1.8	State T-06: "CALL PRESENT"	186
9.2.1.9	State T-07: "CALL RECEIVED"	186
9.2.1.10	State T-08: "CONNECT PENDING"	186
9.2.2	States at FT	187
9.2.2.1	State F-00: "NULL"	187
9.2.2.2	State F-19: "RELEASE PENDING"	187
9.2.2.3	State F-10: "ACTIVE"	187
9.2.2.4	State F-01: "CALL-INITIATED"	187
9.2.2.5	State F-02: "OVERLAP SENDING"	187
9.2.2.6	State F-03: "CALL PROCEEDING"	187
9.2.2.7	State F-04: "CALL DELIVERED"	187
9.2.2.8	State F-06: "CALL PRESENT"	187
9.2.2.9	State F-07: "CALL RECEIVED"	187
9.2.3	Optional states (PT and FT).....	188
9.2.3.1	States T-22 and F-22: "OVERLAP RECEIVING"	188
9.2.3.2	States T-23 and F-23: "INCOMING CALL PROCEEDING"	188
9.3	Call establishment procedures.....	188
9.3.1	PT initiated call establishment (outgoing call).....	188
9.3.1.1	Call request	188
9.3.1.2	Call accept or reject.....	189
9.3.1.3	Selection of lower layer resources	189
9.3.1.4	Connection of U-plane	190
9.3.1.5	Overlap sending	190
9.3.1.6	Call proceeding	191
9.3.1.7	Call confirmation	191
9.3.1.8	Call connection	192
9.3.1.9	Expiry of timer <CC.04>	192
9.3.2	FT initiated call establishment (incoming call).....	192
9.3.2.1	Call request	192
9.3.2.2	Call accept or reject.....	193
9.3.2.3	Selection of lower layer resources	193
9.3.2.4	Connection of U-plane	194
9.3.2.5	Overlap receiving	194
9.3.2.6	Call proceeding	194
9.3.2.7	Call confirmation	194
9.3.2.8	Call connection	194
9.3.2.9	Sending of <<TERMINAL-CAPABILITY>>	195
9.3.2.10	Expiry of timer <CC.04>	195
9.4	Call information procedures	195
9.5	Call release procedures.....	195
9.5.1	Normal call release	195
9.5.2	Abnormal call release	196