

ETSI EN 300 175-5 V2.5.1 (2013-08)



Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 5: Network (NWK) layer

Document Preview

[ETSI EN 300 175-5 V2.5.1 \(2013-08\)](https://standards.iteh.ai/catalog/standards/etsi/65fc3cd6-f2af-40b9-b951-687c5f25f846/etsi-en-300-175-5-v2-5-1-2013-08)

<https://standards.iteh.ai/catalog/standards/etsi/65fc3cd6-f2af-40b9-b951-687c5f25f846/etsi-en-300-175-5-v2-5-1-2013-08>

ReferenceREN/DECT-000268-5

Keywords

DECT, IMT-2000, mobility, radio, TDD, TDMA

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iteh Standards
(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2013.
All rights reserved.

DECTTM, PLUGTESTSTM, UMTSTM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPPTM and LTETM are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	16
Foreword.....	16
1 Scope	17
2 References	18
2.1 Normative references	18
2.2 Informative references.....	22
3 Definitions, symbols and abbreviations	23
3.1 Definitions.....	23
3.2 Symbols and abbreviations.....	23
4 Overview of the NWK layer	27
5 Overview of procedures	29
5.1 General	29
5.2 Overview of Call Control (CC)	29
5.2.1 General.....	29
5.2.2 Call establishment.....	30
5.2.2.1 Call setup	30
5.2.2.2 Service negotiation.....	30
5.2.3 Call connect	30
5.2.4 Call information.....	31
5.2.5 Service change	31
5.2.6 Call release.....	31
5.3 Overview of Supplementary Services (SS)	31
5.3.1 General.....	31
5.3.2 Keypad protocol.....	32
5.3.3 Feature key management protocol	32
5.3.4 Functional protocol.....	32
5.4 Overview of Connection Oriented Message Service (COMS)	33
5.4.1 General.....	33
5.4.2 COMS establishment	33
5.4.3 Service negotiation	33
5.4.4 COMS connect.....	33
5.4.5 COMS data transfer	33
5.4.6 COMS suspend and resume	34
5.4.7 COMS release	34
5.5 Overview of ConnectionLess Message Service (CLMS)	34
5.5.1 Fixed length message service.....	34
5.5.2 Variable length message service	34
5.6 Overview of Mobility Management (MM)	35
5.6.1 General.....	35
5.6.2 Identity procedures	35
5.6.3 Authentication procedures	35
5.6.4 Location procedures.....	36
5.6.5 Access rights procedures	36
5.6.6 Key allocation procedure	37
5.6.7 Parameter retrieval procedure	37
5.6.8 Ciphering related procedure.....	37
5.6.9 External protocol information procedure.....	37
5.7 Overview of Link Control Entity (LCE)	37
5.7.1 General.....	37
5.7.2 Data Link Endpoint Identifier (DLEI)	38
5.7.3 Data link establishment.....	38
5.7.4 Data link re-establishment	38
5.7.5 Data link release	39

5.7.6	Data link suspend and resume.....	39
5.7.7	Queuing of messages	39
5.7.8	Request paging.....	39
6	Message functional definitions.....	40
6.1	Overview of message structures	40
6.1.1	Messages.....	40
6.1.2	Information elements	40
6.2	Message summaries.....	41
6.2.1	Summary of CC messages	41
6.2.2	Summary of CISS messages	41
6.2.3	Summary of COMS messages	42
6.2.4	Summary of CLMS messages.....	42
6.2.5	Summary of MM messages	43
6.2.6	Summary of LCE messages	43
6.3	S-FORMAT message functional contents.....	44
6.3.1	S-FORMAT message overview	44
6.3.2	CC-messages.....	44
6.3.2.1	{CC-SETUP}	44
6.3.2.2	{CC-INFO}	46
6.3.2.3	{CC-SETUP-ACK}	47
6.3.2.4	{CC-CALL-PROC}	48
6.3.2.5	{CC-ALERTING}	49
6.3.2.6	{CC-CONNECT}	50
6.3.2.7	{CC-CONNECT-ACK}	51
6.3.2.8	{CC-RELEASE}	51
6.3.2.9	{CC-RELEASE-COM}	53
6.3.2.10	{CC-SERVICE-CHANGE}	54
6.3.2.11	{CC-SERVICE-ACCEPT}	55
6.3.2.12	{CC-SERVICE-REJECT}	55
6.3.2.13	{CC-NOTIFY}	56
6.3.2.14	{IWU-INFO}	56
6.3.3	SS-messages (call related and call independent)	57
6.3.3.1	{FACILITY}	57
6.3.3.2	{HOLD}	58
6.3.3.3	{HOLD-ACK}	58
6.3.3.4	{HOLD-REJECT}	59
6.3.3.5	{RETRIEVE}	59
6.3.3.6	{RETRIEVE-ACK}	60
6.3.3.7	{RETRIEVE-REJECT}	60
6.3.3.8	{CISS-REGISTER}	61
6.3.3.9	{CISS-RELEASE-COM}	62
6.3.4	COMS-messages.....	62
6.3.4.1	{COMS-SETUP}	62
6.3.4.2	{COMS-INFO}	63
6.3.4.3	{COMS-ACK}	64
6.3.4.4	{COMS-CONNECT}	64
6.3.4.5	{COMS-RELEASE}	65
6.3.4.6	{COMS-RELEASE-COM}	65
6.3.4.7	{COMS-NOTIFY}	66
6.3.5	CLMS-message.....	66
6.3.5.1	{CLMS-VARIABLE}	66
6.3.6	MM-messages.....	67
6.3.6.1	{ACCESS-RIGHTS-ACCEPT}	67
6.3.6.2	{ACCESS-RIGHTS-REJECT}	67
6.3.6.3	{ACCESS-RIGHTS-REQUEST}	68
6.3.6.4	{ACCESS-RIGHTS-TERMINATE-ACCEPT}	68
6.3.6.5	{ACCESS-RIGHTS-TERMINATE-REJECT}	69
6.3.6.6	{ACCESS-RIGHTS-TERMINATE-REQUEST}	69
6.3.6.7	{AUTHENTICATION-REJECT}	70
6.3.6.8	{AUTHENTICATION-REPLY}	71
6.3.6.9	{AUTHENTICATION-REQUEST}	72

6.3.6.10	{CIPHER-REJECT}	72
6.3.6.11	{CIPHER-REQUEST}	73
6.3.6.12	{CIPHER-SUGGEST}	73
6.3.6.13	{DETACH}	73
6.3.6.14	{IDENTITY-REPLY}	74
6.3.6.15	{IDENTITY-REQUEST}	75
6.3.6.16	{KEY-ALLOCATE}	75
6.3.6.17	{LOCATE-ACCEPT}	76
6.3.6.18	{LOCATE-REJECT}	76
6.3.6.19	{LOCATE-REQUEST}	77
6.3.6.20	{MM-INFO-ACCEPT}	78
6.3.6.21	{MM-INFO-REJECT}	78
6.3.6.22	{MM-INFO-REQUEST}	79
6.3.6.23	{MM-INFO-SUGGEST}	80
6.3.6.24	{TEMPORARY-IDENTITY-ASSIGN}	80
6.3.6.25	{TEMPORARY-IDENTITY-ASSIGN-ACK}	81
6.3.6.26	{TEMPORARY-IDENTITY-ASSIGN-REJ}	81
6.3.6.27	{MM-IWU}	82
6.3.6.28	{MM-NOTIFY}	82
6.3.7	LCE-messages	83
6.3.7.1	{LCE-PAGE-RESPONSE}	83
6.3.7.2	{LCE-PAGE-REJECT}	83
6.4	B-FORMAT message functional contents	84
6.4.1	B-FORMAT message overview	84
6.4.2	{LCE-REQUEST-PAGE}	84
6.4.3	{CLMS-FIXED}	85
7	S-FORMAT message structures	85
7.1	Overview	85
7.2	Protocol Discrimination (PD) element	86
7.3	Transaction Identifier (TI) element	86
7.4	Message type element	87
7.4.1	Messages for CC	88
7.4.2	Messages for SS	88
7.4.3	Messages for COMS	88
7.4.4	Messages for CLMS	89
7.4.5	Messages for MM	89
7.4.6	Messages for LCE	89
7.5	Other information elements	90
7.5.1	Coding rules	90
7.5.2	Extensions of codesets	92
7.5.3	Locking shift procedure	92
7.5.4	Non-locking shift procedure	93
7.5.5	Display and keypad elements	93
7.5.6	Repeated elements	93
7.6	Fixed length information elements	94
7.6.1	Summary	94
7.6.2	Sending complete, delimiter request and use TPUI	94
7.6.3	Repeat indicator	95
7.6.4	Basic service	95
7.6.5	Single display	96
7.6.6	Single keypad	96
7.6.7	Release reason	97
7.6.8	Signal	98
7.6.9	Timer restart	99
7.6.10	Test hook control	99
7.7	Variable length information elements	99
7.7.1	Summary	99
7.7.2	Allocation type	101
7.7.3	Alphanumeric	101
7.7.4	Auth type	103
7.7.5	Call attributes	104

7.7.6	Call identity	108
7.7.7	Called party number.....	109
7.7.8	Called party subaddress	110
7.7.9	Calling party number	110
7.7.10	Cipher info	111
7.7.11	Connection attributes	112
7.7.12	Connection identity.....	116
7.7.13	Duration	117
7.7.14	End-to-end compatibility	118
7.7.15	Facility	121
7.7.16	Feature activate	121
7.7.17	Feature indicate.....	123
7.7.18	Fixed identity.....	125
7.7.19	Identity type.....	126
7.7.20	Info type.....	127
7.7.21	InterWorking Unit (IWU) attributes	128
7.7.22	IWU packet.....	133
7.7.23	IWU to IWU	134
7.7.24	Key.....	136
7.7.25	Location area	136
7.7.26	Multi-display.....	137
7.7.27	Multi-keypad.....	138
7.7.28	NetWorK (NWK) assigned identity.....	138
7.7.29	Network parameter	139
7.7.30	Portable identity.....	141
7.7.31	Progress indicator	145
7.7.32	RAND	146
7.7.33	Rate parameters	146
7.7.34	Reject reason.....	147
7.7.35	RES	148
7.7.36	RS	149
7.7.37	Segmented info	149
7.7.38	Service change info.....	150
7.7.39	Service class.....	151
7.7.40	Setup capability	152
7.7.41	Terminal capability.....	153
7.7.42	Transit delay	159
7.7.43	Window size	160
7.7.44	ZAP field	160
7.7.45	Escape to proprietary	161
7.7.46	Model identifier	161
7.7.47	MMS Generic Header.....	162
7.7.48	MMS Object Header.....	162
7.7.49	MMS Extended header	163
7.7.50	Time-Date	163
7.7.51	Ext h/o indicator	165
7.7.52	Called party Name	165
7.7.53	Calling party Name	166
7.7.54	Codec List.....	167
7.7.55	Events notification	168
7.7.55.1	General structure	168
7.7.55.2	Event types	170
7.7.56	Call information.....	174
7.7.57	List change details	177
7.7.58	ULE MAC Configuration Info.....	179
8	B-FORMAT message structures	180
8.1	General	180
8.2	LCE request paging messages	180
8.2.1	Short format message.....	180
8.2.2	Full format message.....	182
8.2.3	Long format message.....	183

8.2.4	Message elements	183
8.2.4.1	LCE paging header.....	183
8.2.4.2	Info fields (Full format)	185
8.2.4.3	Default setup behaviour	186
8.2.4.4	Address elements in collective or group ringing.....	187
8.3	CLMS-FIXED messages.....	187
8.3.1	General message structure	187
8.3.2	Message elements	188
8.3.3	Standard message structures	190
8.3.3.1	General	190
8.3.3.2	Messages using 4-bit characters	190
8.3.3.3	Messages using 8-bit characters	190
9	Call Control (CC) procedures.....	190
9.1	General	190
9.2	Call Control (CC) states	193
9.2.1	States at PT	193
9.2.1.1	State T-00: "NULL"	193
9.2.1.2	State T-19: "RELEASE PENDING"	193
9.2.1.3	State T-10: "ACTIVE"	193
9.2.1.4	State T-01: "CALL INITIATED"	193
9.2.1.5	State T-02: "OVERLAP SENDING"	193
9.2.1.6	State T-03: "CALL PROCEEDING"	193
9.2.1.7	State T-04: "CALL DELIVERED"	193
9.2.1.8	State T-06: "CALL PRESENT"	193
9.2.1.9	State T-07: "CALL RECEIVED"	193
9.2.1.10	State T-08: "CONNECT PENDING"	193
9.2.2	States at FT	194
9.2.2.1	State F-00: "NULL"	194
9.2.2.2	State F-19: "RELEASE PENDING"	194
9.2.2.3	State F-10: "ACTIVE"	194
9.2.2.4	State F-01: "CALL-INITIATED"	194
9.2.2.5	State F-02: "OVERLAP SENDING"	194
9.2.2.6	State F-03: "CALL PROCEEDING"	194
9.2.2.7	State F-04: "CALL DELIVERED"	194
9.2.2.8	State F-06: "CALL PRESENT"	194
9.2.2.9	State F-07: "CALL RECEIVED"	194
9.2.3	Optional states (PT and FT).....	195
9.2.3.1	States T-22 and F-22: "OVERLAP RECEIVING"	195
9.2.3.2	States T-23 and F-23: "INCOMING CALL PROCEEDING"	195
9.3	Call establishment procedures.....	195
9.3.1	PT initiated call establishment (outgoing call).....	195
9.3.1.1	Call request	195
9.3.1.2	Call accept or reject.....	196
9.3.1.3	Selection of lower layer resources	196
9.3.1.4	Connection of U-plane	197
9.3.1.5	Overlap sending	197
9.3.1.6	Call proceeding	198
9.3.1.7	Call confirmation	198
9.3.1.8	Call connection	199
9.3.1.9	Expiry of timer <CC.04>	199
9.3.2	FT initiated call establishment (incoming call).....	199
9.3.2.1	Call request	199
9.3.2.2	Call accept or reject.....	200
9.3.2.3	Selection of lower layer resources	200
9.3.2.4	Connection of U-plane	201
9.3.2.5	Overlap receiving.....	201
9.3.2.6	Call proceeding	201
9.3.2.7	Call confirmation	201
9.3.2.8	Call connection	202
9.3.2.9	Sending of <<TERMINAL-CAPABILITY>>	202
9.3.2.10	Expiry of timer <CC.04>	202