



**Terrestrial Trunked Radio (TETRA);
Voice plus Data (V+D);
Part 3: Interworking at the Inter-System Interface (ISI);
Sub-part 12: Transport layer independent
Additional Network Feature Individual Call (ANF-ISIIC)**

ReferenceREN/TCCE-03279

KeywordsANF, interworking, TETRA, V+D

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed,
this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.
In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part of this document may be reproduced in any form, by any means and in any media, without the prior written authorization of ETSI and except as expressly permitted below.

By way of exception and when the document is a normative deliverable (European Standard (EN), Technical Specification (TS), Group Specification (GS) or ETSI Standard (ES)), ETSI authorizes to reproduce and incorporate into products, services and technical documentation only those extracts (e.g. templates) that are strictly necessary for the technical implementation of the normative deliverable, to ensure compliance with the latter. Nothing in this notice shall be construed as limiting any mandatory exceptions to copyright provided by applicable law.

© ETSI 2026.
All rights reserved.

Contents

Intellectual Property Rights	8
Foreword.....	8
Modal verbs terminology.....	10
1 Scope	11
2 References	11
2.1 Normative references	11
2.2 Informative references.....	12
3 Definition of terms, symbols and abbreviations.....	13
3.1 Terms.....	13
3.2 Symbols.....	14
3.3 Abbreviations	14
4 ANF-ISIIC stage 1 specification	16
4.1 Description	16
4.1.1 General description.....	16
4.1.2 Qualifications on applicability to telecommunication services.....	16
4.2 Procedures	16
4.2.1 Provision/withdrawal.....	16
4.2.2 Normal procedures.....	16
4.2.2.1 Activation/deactivation/registration/interrogation	16
4.2.2.2 Invocation and operation.....	17
4.2.2.2.1 General	17
4.2.2.2.2 Call routing	17
4.2.2.2.3 Control of call time-out timers	17
4.2.2.2.4 Transmission control	17
4.2.2.2.5 Setup modification.....	17
4.2.2.2.6 Call modification.....	18
4.2.2.2.7 Call restoration after migration.....	18
4.2.2.2.8 Call clearing	18
4.2.2.2.9 Interaction between ANF-ISIICs	19
4.2.2.2.10 Resource queuing and allocation policies.....	19
4.2.3 Exceptional procedures.....	19
4.2.3.1 Activation/deactivation/registration/interrogation	19
4.2.3.2 Invocation and operation.....	19
4.3 Interactions with other TETRA supplementary services and ANFs.....	20
4.3.1 Introduction.....	20
4.3.2 Calling Line Identification Presentation (SS-CLIP)	20
4.3.3 Connected Line identification Presentation (SS-COLP).....	20
4.3.4 Calling/connected Line Identification Restriction (SS-CLIR).....	20
4.3.5 Call Report (SS-CR)	20
4.3.6 Talking Party Identification (SS-TPI).....	20
4.3.7 Call Forwarding Unconditional (SS-CFU)	20
4.3.8 Call Forwarding on Busy (SS-CFB)	22
4.3.9 Call Forwarding on No Reply (SS-CFNRY)	23
4.3.10 Call Forwarding on Not Reachable (SS-CFNRC)	24
4.3.11 List Search Call (SS-LSC)	24
4.3.12 Call Authorized by Dispatcher (SS-CAD).....	24
4.3.13 Short Number Addressing (SS-SNA)	25
4.3.14 Area Selection (SS-AS)	25
4.3.15 Access Priority (SS-AP)	25
4.3.16 Priority Call (SS-PC)	26
4.3.17 Call Waiting (SS-CW)	26
4.3.18 Call Hold (SS-HOLD)	26
4.3.19 Call Completion to Busy Subscriber (SS-CCBS)	26
4.3.20 Late Entry (SS-LE)	26

4.3.21	Pre-emptive Priority Call (SS-PPC).....	26
4.3.22	Include Call (SS-IC)	26
4.3.23	Barring of Outgoing Calls (SS-BOC)	27
4.3.24	Barring of Incoming Calls (SS-BIC)	27
4.3.25	Discreet Listening (SS-DL)	27
4.3.26	Ambience Listening (SS-AL)	28
4.3.27	Dynamic Group Number Assignment (SS-DGNA).....	28
4.3.28	Call Completion on No Reply (SS-CCNR)	28
4.3.29	Call Retention (SS-CRT)	28
4.3.30	Additional Network Feature - Inter System Interface Group Call (ANF-ISIGC).....	28
4.3.31	Additional Network Feature - Inter System Interface Short Data Service (ANF-ISISDS).....	28
4.3.32	Additional Network Feature - Inter System Interface Mobility Management (ANF-ISIMM)	28
4.3.33	Additional Network Feature - Inter System Interface Supplementary service (ANF-ISISS)	29
4.4	Interworking considerations	29
5	ANF-ISIIC stage 2 specification	29
5.1	Functional model.....	29
5.1.1	Functional model description.....	29
5.1.2	Description of functional entities.....	34
5.1.2.1	Originating/Controlling SwMI individual call control application functional entity, FE1	34
5.1.2.2	Originating/Controlling SwMI ISI individual call originating functional entity, FE2	34
5.1.2.3	Called/Forward Switching SwMI call control functional entity, FE3	35
5.1.2.4	Called/Forward Switching SwMI ISI individual call functional entity, FE4	36
5.1.2.5	Terminating SwMI individual call control functional entity, FE5	36
5.1.2.6	ISI individual call terminating functional entity, FE6	37
5.1.2.7	New terminating SwMI call restoring functional entity, FE7	37
5.1.2.8	New terminating SwMI ISI call restoring functional entity (ANF-ISIIC), FE8.....	37
5.2	Information flow	38
5.2.1	Examples of information flow sequences	38
5.2.1.1	Introduction.....	38
5.2.1.2	Successful call set-up when the called user is registered in SwMI B and uses on/off hook signalling.....	38
5.2.1.3	Successful call set up when the called user is registered in SwMI B and uses direct set-up signalling.....	39
5.2.1.4	ANF-ISIIC set-up to a called user having migrated from SwMI B, using forward switching	41
5.2.1.5	ANF-ISIIC set-up to a called user having migrated from SwMI B, using re-routeing	41
5.2.1.6	Loop avoidance in case of intra-TETRA call.....	42
5.2.1.7	Unsuccessful ANF-ISIIC call set-up.....	43
5.2.1.8	Transmission control.....	44
5.2.1.9	Call modify	47
5.2.1.10	Call restoration after migration	47
5.2.1.11	Call clearing	50
5.2.1.12	Resource queuing and allocation.....	51
5.2.2	Definition of information flows	52
5.2.2.1	General	52
5.2.2.2	CALL RESTORE	52
5.2.2.3	CALL RESTORE PREPARE	53
5.2.2.4	CHARACTERISTIC CHANGE	54
5.2.2.5	COMPLETE.....	54
5.2.2.6	MIGRATION.....	54
5.2.2.7	MODIFY	55
5.2.2.8	RELEASE	55
5.2.2.9	SETUP	56
5.2.2.10	SETUP PROLONGATION	57
5.2.2.11	TROMBONE	57
5.2.2.12	TX-CEASED	57
5.2.2.12.1	TX-CEASED 1.....	57
5.2.2.12.2	TX-CEASED 2.....	58
5.2.2.13	TX-CONTINUE 1.....	58
5.2.2.14	TX-CONTINUE 2.....	58
5.2.2.15	TX-DEMAND	58
5.2.2.16	TX-GRANTED	59

5.2.2.17	TX-INTERRUPT	59
5.2.2.18	TX-WAIT	59
5.3	Functional entity actions	60
5.4	Allocation of functional entities to physical equipment/SwMIs.....	60
6	ANF-ISIIC stage 3 specification	62
6.1	ANF-ISIIC coding requirements	62
6.1.1	General.....	62
6.1.2	TETRA PDUs	62
6.1.2.1	General encoding rule	62
6.1.2.2	ISI-SETUP PDU message sent by the originating or the forward switching SwMI	62
6.1.2.3	ISI-PROGRESS PDU used to give information about the call progress.....	64
6.1.2.4	ISI-REDIRECT PDU sent by the called SwMI when it is not the terminating SwMI because of migration or SS-CF invocation	64
6.1.2.5	ISI-FORWARD SWITCH PDU sent by the originating or the forward switching SwMI to request forward switching	66
6.1.2.6	ISI-ALERTING PDU sent by the terminating or the forward switching SwMI to give information about the connected party alerted	66
6.1.2.7	ISI-CONNECT PDU sent by the terminating or the forward switching SwMI to give information that the connected party has answered the call.....	66
6.1.2.8	ISI-CALL PROCEEDING sent by the terminating SwMI before the ISI-ALERTING or ISI-CONNECT message	68
6.1.2.9	ISI-SETUP PROLONGATION PDU sent to prolong the call setup time	68
6.1.2.10	ISI CONNECT ACKNOWLEDGE PDU sent by the originating SwMI.....	68
6.1.2.11	Transmission control PDUs sent by the controlling SwMI	69
6.1.2.12	ISI-TX WAIT PDU possibly sent by either the controlling or the terminating SwMI.....	70
6.1.2.13	ISI-INFO DEMAND and ISI-INFO REPLY PDU possibly sent by either the originating or the terminating SwMI	70
6.1.2.14	Transmission control PDUs sent by the terminating SwMI	71
6.1.2.15	TETRA PDUs to restore the call after the calling or the connected user has migrated in a new SwMI.....	72
6.1.2.15.1	Case where no connection between the old SwMI and the new SwMI already exists or has not been identified	72
6.1.2.15.2	Cases where no new connection is needed between the old SwMI and the new SwMI	74
6.1.2.16	ISI-DISCONNECT PDU sent by a SwMI in case of call clearing or call rejection.....	76
6.1.2.17	TETRA PDUs specific for interaction with supplementary service protocol sent to the originating SwMI	76
6.1.2.18	ISI-QUEUEING PDUs sent towards the terminating SwMI	77
6.1.2.19	ISI-RESOURCE PDU sent towards the Terminating SwMI	78
6.1.2.20	ISI-RESOURCE RESPONSE PDUs sent towards the Called or Originating SwMI after the call has connected	78
6.1.3	TETRA PDU information element coding	78
6.1.3.1	Introduction.....	78
6.1.3.2	Specific ISI definition of some information elements already defined for air interface messages	79
6.1.3.2.1	Basic service information	79
6.1.3.2.2	Call status	79
6.1.3.2.3	Call time-out, set-up phase	79
6.1.3.2.4	Disconnect cause information element	80
6.1.3.2.5	PDU type	81
6.1.3.3	New information elements used at the ISI	81
6.1.3.3.1	Call diverted to a dispatcher	81
6.1.3.3.2	Call has been forward switched.....	82
6.1.3.3.3	Call identified as fleet call	82
6.1.3.3.4	Called/forwarded-to external subscriber number.....	82
6.1.3.3.5	Called/forwarded-to party extension	82
6.1.3.3.6	Called/forwarded-to party SSI.....	82
6.1.3.3.7	Called/forwarded-to party fleet number SSI.....	82
6.1.3.3.8	Called/forwarded-to user having migrated	82
6.1.3.3.9	Calling external subscriber number	83
6.1.3.3.10	Calling external subscriber number parameters.....	83
6.1.3.3.11	Calling party fleet number SSI	83
6.1.3.3.12	Calling party presentation indicator.....	83

6.1.3.3.13	Cause for PDU addressed to originating SwMI.....	83
6.1.3.3.14	Connected external subscriber number.....	83
6.1.3.3.15	Connected external subscriber number parameters	84
6.1.3.3.16	Connected party presentation indicator	84
6.1.3.3.17	Connected party extension.....	84
6.1.3.3.18	Connected party SSI.....	84
6.1.3.3.19	Connected party fleet number SSI.....	84
6.1.3.3.20	Controlling SwMI.....	84
6.1.3.3.21	Incoming call barring status	84
6.1.3.3.22	Forwarded-to external subscriber number	85
6.1.3.3.23	Forwarded-to user extension	85
6.1.3.3.24	Forwarded-to user SSI.....	85
6.1.3.3.25	Last Forwarding SwMI MNI.....	85
6.1.3.3.26	Modify accepted	85
6.1.3.3.27	Modify request	85
6.1.3.3.28	MSISDN present as external subscriber number	85
6.1.3.3.29	New SwMI MNI.....	85
6.1.3.3.30	Number of digits in called/forwarded-to external subscriber number	86
6.1.3.3.31	Number of digits in calling external subscriber number.....	86
6.1.3.3.32	Number of digits in connected external subscriber number	86
6.1.3.3.33	Number of digits in forwarded-to external subscriber number.....	86
6.1.3.3.34	Number of digits in visited/forwarded-to SwMI PISN number.....	86
6.1.3.3.35	Originating SwMI MNI.....	86
6.1.3.3.36	Other end SwMI MNI	86
6.1.3.3.37	Override SS-CAD invocation.....	87
6.1.3.3.38	PDU addressed to originating SwMI.....	87
6.1.3.3.39	Possible ISI trombone or loop connection detected.....	87
6.1.3.3.40	Restoring party extension	87
6.1.3.3.41	Restoring party SSI.....	87
6.1.3.3.42	Resource release permission.....	87
6.1.3.3.43	Resource release signalling support.....	88
6.1.3.3.44	Resource indicator.....	88
6.1.3.3.45	Routeing method choice	88
6.1.3.3.46	Routeing method response.....	88
6.1.3.3.47	Security level at air interface	89
6.1.3.3.48	Setup resource allocation.....	89
6.1.3.3.49	Speech service requested/chosen/used	89
6.1.3.3.50	Speech services supported.....	89
6.1.3.3.51	SS-CF invocation counter.....	89
6.1.3.3.52	SS-CF invoked	90
6.1.3.3.53	SS-CLIR invoked for other party	90
6.1.3.3.54	Terminating SwMI MNI.....	90
6.1.3.3.55	Visited/forwarded-to SwMI MNI.....	90
6.1.3.3.56	Visited/forwarded-to SwMI PISN number	90
6.2	ANF-ISIIC state definitions	90
6.3	ANF-ISIIC signalling procedures.....	90
6.3.1	General.....	90
6.3.2	Call establishment.....	90
6.3.2.1	Call request and call proceeding	90
6.3.2.2	Called user migration	91
6.3.2.2.1	Introduction	91
6.3.2.2.2	Called user having migrated in SwMI C different from SwMI A	91
6.3.2.2.3	Called user having migrated in SwMI C coinciding with SwMI A.....	93
6.3.2.3	Call characteristics and set-up time negotiation by the terminating SwMI.....	94
6.3.2.4	Call through connection	95
6.3.2.4.1	Call confirmation indication by the terminating SwMI.....	95
6.3.2.4.2	Resource queuing and different resource allocation policies when no forward switching SwMIs involved.....	96
6.3.2.4.3	Resource queuing and different resource allocation policies if forward switching SwMIs are involved.....	97
6.3.2.5	Failure of call establishment	99
6.3.3	Call maintenance procedures	99

6.3.3.1	Transmission control procedures	99
6.3.3.2	Call modification.....	100
6.3.3.3	Call restoration.....	101
6.3.3.3.1	General call restoration procedure.....	101
6.3.3.3.2	Specific call restoration procedure in a SwMI already on the path of the call	102
6.3.4	DTMF procedures.....	103
6.3.5	ANF-ISIIC clearing	103
6.4	ANF-ISIIC impact of interworking with ISDN/PISN/PSTN	104
6.5	Protocol interactions between ANF-ISIIC and supplementary services and other ANFs	104
6.5.1	Interaction with SS-CLIR	104
6.5.2	Interactions with SS-CF	105
6.5.2.1	Interaction with SS-CF at call establishment	105
6.5.2.2	Specific interaction with SS-CFNRY at call establishment	106
6.5.2.3	Interaction with SS-CF at call restoration	106
6.5.3	Interaction with SS-CAD.....	106
6.5.3.1	Invocation of a specific ANF-ISIIC.....	106
6.5.3.2	Interception of an already invoked ANF-ISIIC.....	106
6.5.3.3	Call authorization by a distant dispatcher	107
6.5.3.4	Completion of call establishment	107
6.5.3.4.1	Call not diverted to dispatcher.....	107
6.5.3.4.2	Call diverted to dispatcher.....	107
6.5.4	Interactions with SS-PC, SS-PPC and SS-CRT.....	108
6.5.5	Interaction with SS-CW.....	108
6.5.6	Interaction with SS-HOLD	108
6.5.7	Interaction with SS-CCBS and SS-CCNR.....	108
6.5.8	Interaction with SS-BIC.....	108
6.5.9	Area Selection (SS-AS) and selected area number	109
6.5.10	Interactions with other supplementary services	109
6.6	ANF-ISIIC parameter values (timers)	109
Annex A (informative):	Interactions of SS-CFU with ANF-ISIIC.....	110
A.1	Possible SS-CFU activation	110
A.2	Invocation and operation	110
A.2.1	Invocation.....	110
A.2.2	Called user home SwMI being SwMI A	110
A.2.3	Called user home SwMI being SwMI B.....	111
A.2.3.1	Introduction.....	111
A.2.3.2	Forwarded-to user with home SwMI being SwMI B, being registered in its home SwMI	111
A.2.3.3	Forwarded-to user with home SwMI being SwMI B, having migrated	112
A.2.3.4	Forwarded-to user with home SwMI different from SwMI B, being registered in its home SwMI	112
A.2.3.5	Forwarded-to user with home SwMI different from SwMI B, having migrated	112
Annex B (informative):	Change Requests.....	115
History		116

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables (European Standard (EN), Technical Specification (TS), Group Specification (GS) or ETSI Standard (ES)) may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Foreword

This European Standard (EN) has been produced by ETSI Technical Committee TETRA and Critical Communications Evolution (TCCE).

National transposition dates	
Date of adoption of this EN:	23 June 2026
Date of latest announcement of this EN (doa):	30 September 2026
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 March 2027
Date of withdrawal of any conflicting National Standard (dow):	31 March 2027

The present document is part 3, sub-part 12 of a multi-part deliverable covering the Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D), as identified below:

Part 1: "General network design";

Part 2: "Air Interface (AI)";

Part 3: "Interworking at the Inter-System Interface (ISI)":

Sub-part 1: "General design";

Sub-part 2: "Additional Network Feature Individual Call (ANF-ISIIC)";

Sub-part 3: "Additional Network Feature Group Call (ANF-ISIGC)";

- Sub-part 4: "Additional Network Feature Short Data Service (ANF-ISISDS)";
- Sub-part 5: "Additional Network Feature for Mobility Management (ANF-ISIMM)";
- Sub-part 6: "Speech format implementation for circuit mode transmission";
- Sub-part 7: "Speech Format Implementation for Packet Mode Transmission";
- Sub-part 8: "Generic Speech Format Implementation";
- Sub-part 9: "Transport layer independent, General design";
- Sub-part 10: "General design, PSS1 over E.1";
- Sub-part 11: "General design, SIP/IP";
- Sub-part 12: "Transport layer independent Additional Network Feature Individual Call (ANF-ISIIC)";**
- Sub-part 13: "Transport layer independent Additional Network Feature Group Call (ANF-ISIGC)";
- Sub-part 14: "Transport layer independent Additional Network Feature Short Data Service (ANF-ISISDS)";
- Sub-part 15: "Transport layer independent Additional Network Feature, Mobility Management (ANF-ISIMM)";

- Part 4: "Gateways basic operation";
- Part 5: "Peripheral Equipment Interface (PEI)";
- Part 7: "Security";
- Part 9: "General requirements for supplementary services";
- Part 10: "Supplementary services stage 1";
- Part 11: "Supplementary services stage 2";
- Part 12: "Supplementary services stage 3";
- Part 13: "SDL model of the Air Interface (AI)";
- Part 14: "Protocol Implementation Conformance Statement (PICS) proforma specification";
- Part 15: "TETRA frequency bands, duplex spacings and channel numbering";
- Part 16: "Network Performance Metrics";
- Part 17: "TETRA V+D and DMO specifications";
- Part 18: "Air interface optimized applications";
- Part 19: "Interworking between TETRA and Broadband systems".

NOTE 1: Part 3, sub-parts 6 and 7 (Speech format implementation), part 4, sub-part 3 (Data networks gateway), part 10, sub-part 15 (Transfer of control), part 13 (SDL) and part 14 (PICS) of this multi-part deliverable are in status "historical" and are not maintained.

NOTE 2: Some parts are also published as Technical Specifications such as ETSI TS 100 392-2 and those may be the latest version of the document.

The present document is based on ETSI EN 300 392-3-2 [i.9] "Interworking at the Inter-System Interface, Sub-part 2 Additional Network Feature for Individual Call (ANF-ISIIC)". The main changes are:

- Removal of any reference to the bearer protocol.
- Clean up of stage 2 descriptions.

For all sub-parts in the TETRA specification ETSI EN 300 392-3, "Interworking at the Inter-System Interface (ISI)", the terms ISI and TETRA ISI are equivalent.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Sample Document

get full document from standards.iteh.ai

1 Scope

The present document defines the Terrestrial Trunked Radio (TETRA) system supporting Voice plus Data (V+D). It specifies:

- the interworking of individual calls between TETRA networks;
- the supplementary services interaction with individual calls between TETRA networks.

The TETRA V+D interworking - basic operation part defines the interworking between TETRA networks over the corresponding interface: the Inter-System Interface (ISI). It comprises the following sub-parts:

- Transport layer independent General design [2];
- General Design, PSS1 over E.1 [i.10];
- General Design, SIP/IP [i.11];
- Transport layer independent Additional Network Feature - ISI Individual Call (ANF-ISIIC) (the present document);
- Transport layer independent Additional Network Feature - ISI Group Call (ANF-ISIGC) [5];
- Transport layer independent Additional Network Feature - ISI Short Data service (ANF-ISISDS) [i.8];
- Transport layer independent Additional Network Feature - ISI Mobility Management (ANF-ISIMM) [6];
- Generic Speech Format Implementation [i.7].

The present document is the ANF-ISIIC sub-part.

Like all other Additional Network Feature (ANF) specifications, those of ANF-ISIIC are produced in three stages, according to the method described in Recommendation ITU-T I.130 [i.4]. The present document contains the stage 1 and 2 descriptions of ANF-ISIIC, and stage 3 description. The stage 1 description specifies the ANF as seen by its users, which are essentially the individual call control entities in both TETRA networks. The stage 2 description identifies the functional entities involved in the ANF and the information flows between them. And the stage 3 description of ANF-ISIIC specifies its protocol.

NOTE 1: According to Recommendation ITU-T I.130 [i.4], the stage 3 description of a bearer or tele-service addresses the network implementation aspects. Consequently, it comprises two steps: the specifications of all protocols at the various reference points involved in any of the service procedures (notably the service operation) are the first step of the stage 3 description, and the specifications of the functions of the corresponding network entities are its second step.

NOTE 2: The SDL diagrams have not been provided since they can be derived from the specification of the functional entity actions in the stage 2 description.

The present document applies to TETRA networks which support inter-TETRA individual calls. More specifically, it applies to their Circuit Mode Control Entities (CMCE), as defined in clause 14.2 of ETSI EN 300 392-2 [1], and to their ANF-ISIIC entities defined in the stage 2 description.

The relation between the ANF-ISIIC and the transport layer protocol is described in the General Design documents [2], [i.10] and [i.11].

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found in the [ETSI docbox](#).

NOTE 1: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long-term validity.

NOTE 2: Note that for the TETRA standards, the reference is always to a European Standard (ETSI EN 300 xxx) if such has been published, but the latest version of that standard can be either an EN or a Technical Specification (ETSI TS 100 xxx), even if this is not visible in the reference list.

The following referenced documents are necessary for the application of the present document.

- [1] [ETSI EN 300 392-2](#): "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (AI)".
- [2] [ETSI EN 300 392-3-9](#): "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 9: Transport layer independent, General design".
- [3] Void.
- [4] Void.
- [5] [ETSI EN 300 392-3-13](#): "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 13: Transport layer independent Additional Network Feature Group Call (ANF-ISIGC)".
- [6] [ETSI EN 300 392-3-15](#): "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 15: Transport layer independent Additional Network Feature, Mobility Management (ANF-ISIMM)".
- [7] [ETSI EN 300 392-9](#): "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 9: General requirements for supplementary services".
- [8] [ETSI EN 300 392-12-4](#): "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 12: Supplementary services stage 3; Sub-part 4: Call Forwarding (CF)".
- [9] [ISO/IEC 11572](#): "Information technology — Telecommunications and information exchange between systems — Private Integrated Services Network — Circuit mode bearer services — Inter-exchange signalling procedures and protocol".
- [10] [ETSI EN 300 392-12-8](#): "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 12: Supplementary services stage 3; Sub-part 8: Area Selection (AS)".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE 1: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long-term validity.

NOTE 2: Note that for the TETRA standards, the reference is always to a European Standard (ETSI EN 300 xxx) if such has been published, but the latest version of that standard can be either an EN or a Technical Specification (ETSI TS 100 xxx), even if this is not visible in the reference list.

The following referenced documents may be useful in implementing an ETSI deliverable or add to the reader's understanding, but are not required for conformance to the present document.

- [i.1] ETSI EN 300 392-7: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 7: Security".
- [i.2] ETSI EN 300 392-10-19: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 10: Supplementary services stage 1; Sub-part 19: Barring of Incoming Calls (BIC)".

- [i.3] ETSI EN 300 395-2: "Terrestrial Trunked Radio (TETRA); Speech codec for full-rate traffic channel; Part 2: TETRA codec".
- [i.4] Recommendation ITU-T I.130: "Method for the characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN".
- [i.5] ETSI TR 102 300-5: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Designers' guide; Part 5: Guidance on numbering and addressing".
- [i.6] Void.
- [i.7] ETSI EN 300 392-3-8: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 8: Generic Speech Format Implementation".
- [i.8] ETSI EN 300 392-3-14: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 14: Transport layer independent Additional Network Feature Short Data Service (ANF-ISISDS)".
- [i.9] ETSI EN 300 392-3-2: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 2: Additional Network Feature Individual Call (ANF-ISIIC)".
- [i.10] [ETSI EN 300 392-3-10](#): "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 10: General design, PSS1 over E.1".
- [i.11] [ETSI EN 300 392-3-11](#): "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 11: General design, SIP/IP".

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the terms given in ETSI EN 300 392-3-9 [2] and the following apply:

called SwMI: Switching and Management Infrastructure to which ANF-ISIIC routes the first call attempt

controlling SwMI: Switching and Management Infrastructure responsible of the speech item management in half duplex individual calls

NOTE: During the call setup the originating SwMI is also the controlling SwMI. When the calling party migrates during a call the control of the call is transferred to that SwMI.

fleet call: call to a closed user group using a Fleet Specific Short Number

NOTE: Refer to ETSI TR 102 300-5 [i.5], clause 5.4.3.

forward switching: network routing algorithm which performs the routing from SwMI A to SwMI C by joining together the first connection, from SwMI A to SwMI B, and a second connection from SwMI B to SwMI C

home SwMI: SwMI which is the home of the MS (or LS) ITSI, i.e. to which the Mobile Network Identity (MNI) which is part of the ITSI belongs

loop connection: ISI connection which has both its ends in the same SwMI

originating SwMI: Switching and Management Infrastructure in which the calling user has registered when the call is set up

re-routing: network routing algorithm which performs the routing from SwMI A to SwMI C by replacing the connection from SwMI A to SwMI B by another connection from SwMI A to SwMI C

SwMI A: Switching and Management Infrastructure in which the calling user has registered or in case of call forwarding SS where the call forwarding is performed

SwMI B: Switching and Management Infrastructure to which ANF-ISIIC of SwMI A routes the call attempt

SwMI C: Switching and Management Infrastructure in which the called user or the forwarded-to user has registered after having migrated from SwMI B, in the case where its home SwMI is SwMI B

terminating SwMI: Switching and Management Infrastructure in which the connected user is registered

NOTE: Unless an interaction with one or more supplementary services which modify the routing of the call (e.g. call forwarding) has occurred, the connected user will be the called user; and the terminating SwMI will be the SwMI where the called user is registered, i.e. SwMI B or SwMI C.

transit SwMI: TETRA SwMI involved in a call but not being controlling or terminating SwMI

NOTE: A SwMI performing forward switching becomes a transit SwMI. Also in case of call restoration the old visited SwMI becomes a transit SwMI.

trombone connection: two inter-SwMI connections between two SwMIs for the same call

visited SwMI: TETRA network which MNI is not equal to the user's MNI

NOTE: In the present document the term visited SwMI follows the definition of the Air Interface standard ETSI EN 300 392-2 [1].

3.2 Symbols

Void.

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AL	Ambience Listening
ANF	Additional Network Feature
AP	Access Priority
APDU	Application Packet Data Unit
AS	Area Selection
BIC	Barring of Incoming Calls
BOC	Barring of Outgoing Calls
CAD	Call Authorized by Dispatcher
CC	Call Control

NOTE: PISN functional entity.

CCAp Call Control Application

NOTE: SwMI functional entity.

CCBS	Call Completion to Busy Subscriber
CCNR	Call Completion on No Reply
CF	Call Forwarding
CFB	Call Forwarding on Busy
CFNRc	Call Forwarding on Not Reachable
CFNRy	Call Forwarding on No Reply
CFU	Call Forwarding Unconditional
CLIP	Calling Line Identification Presentation
CLIR	Calling/connected Line Identification Restriction
CMCE	Circuit Mode Control Entities
COLP	COConnected Line identification Presentation
CR	Call Report
CRT	Call ReTention
CRV	Call Retention Value
CW	Call Waiting
DGNA	Dynamic Group Number Assignment

DL	Discreet Listening
DTMF	Dual Tone Multi Frequency
FE	Functional Entity
GTSI	Group TETRA Subscriber Identity
GW	GateWay
HOLD	call Hold
IC	Include Call
IE	Information Element
ISDN	Integrated Services Digital Network
ISI	Inter System Interface
ISIGC	Inter System Interface Group Call
ISIIC	Inter System Interface Individual Call
ISIMM	Inter System Interface Mobility Management
ISISDS	Inter System Interface Short Data Service
ISSS	Inter System Interface Supplementary Service
ITSI	Individual TETRA Subscriber Identity
LE	Late Entry
LS	Line Station
LSC	List Search Call
MLE	Mobile Link Entity
MM	Mobility Management
MNI	Mobile Network Identity
MS	Mobile Station
MSC	Message Sequence Chart
MSISDN	Mobile Station Integrated Services Digital Network
PABX	Private Automatic Branch eXchange
PC	Priority Call
PDU	Protocol Data Unit
PEI	Peripheral Equipment Interface
PISN	Private Integrated Services Network
PPC	Pre-emptive Priority Call
PSS1	Private integrated Signalling System number 1
PSTN	Public Switched Telephone Network
RSI	Removal of Subscriber Information
SDL	Specification and Description Language
SNA	Short Number Addressing
SS	Supplementary Service
SSI	Short Subscriber Identity
SwMI	Switching and Management Infrastructure
TNCC	TETRA Network layer Call Control
TPI	Talking Party Identification
TX	Transmission