

ETSI EN 300 392-3-2 V1.4.1 (2010-08)

European Standard (Telecommunications series)

**Terrestrial Trunked Radio (TETRA);
Voice plus Data (V+D);
Part 3: Interworking at the Inter-System Interface (ISI);
Sub-part 2: Additional Network Feature
Individual Call (ANF-ISIIC)**

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI EN 300 392-3-2 V1.4.1 \(2010-08\)](https://standards.iteh.ai/catalog/standards/etsi/ec49af3e-00d3-426d-a43f-60655e902ae6/etsi-en-300-392-3-2-v1-4-1-2010-08)

<https://standards.iteh.ai/catalog/standards/etsi/ec49af3e-00d3-426d-a43f-60655e902ae6/etsi-en-300-392-3-2-v1-4-1-2010-08>



Reference

REN/TETRA-03193

Keywords

air interface, TETRA, V+D

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2010.
All rights reserved.

DECTTM, PLUGTESTSTM, UMTSTM, TIPHONTM, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPPTM is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTETM is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	8
Foreword.....	8
1 Scope	10
2 References	11
2.1 Normative references	11
2.2 Informative references.....	12
3 Definitions and abbreviations.....	12
3.1 Definitions.....	12
3.2 Abbreviations	13
4 ANF-ISIIC stage 1 specification	14
4.1 Description	14
4.1.1 General description.....	14
4.1.2 Qualifications on applicability to telecommunication services.....	14
4.2 Procedures	15
4.2.1 Provision/withdrawal.....	15
4.2.2 Normal procedures.....	15
4.2.2.1 Activation/deactivation/registration/interrogation	15
4.2.2.2 Invocation and operation.....	15
4.2.2.2.1 Call routing	15
4.2.2.2.2 Control of call time-out timers	16
4.2.2.2.3 Transmission control	16
4.2.2.2.3a Setup modification.....	16
4.2.2.2.4 Call modification.....	16
4.2.2.2.5 Call restoration after migration.....	16
4.2.2.2.6 Call clearing	17
4.2.2.2.7 Interaction between ANF-ISIICs.....	17
4.2.2.2.8 Radio traffic channel resource queuing and allocation policies	18
4.2.3 Exceptional procedures.....	18
4.2.3.1 Activation/deactivation/registration/interrogation	18
4.2.3.2 Invocation and operation.....	18
4.3 Interactions with other TETRA supplementary services and ANFs.....	19
4.3.1 Calling Line Identification Presentation (SS-CLIP)	19
4.3.2 Connected Line identification Presentation (SS-COLP).....	19
4.3.3 Calling/connected Line Identification Restriction (SS-CLIR).....	19
4.3.4 Call Report (SS-CR)	19
4.3.5 Talking Party Identification (SS-TPI).....	19
4.3.6 Call Forwarding Unconditional (SS-CFU)	19
4.3.7 Call Forwarding on Busy (SS-CFB).....	21
4.3.8 Call Forwarding on No Reply (SS-CFNRy)	22
4.3.9 Call Forwarding on Not Reachable (SS-CFNRC)	22
4.3.10 List Search Call (SS-LSC).....	23
4.3.11 Call Authorized by Dispatcher (SS-CAD).....	23
4.3.12 Short Number Addressing (SS-SNA)	24
4.3.13 Area Selection (SS-AS)	24
4.3.14 Access Priority (SS-AP)	24
4.3.15 Priority Call (SS-PC)	25
4.3.16 Call Waiting (SS-CW).....	25
4.3.17 Call Hold (SS-HOLD).....	25
4.3.18 Call Completion to Busy Subscriber (SS-CCBS).....	25
4.3.19 Late Entry (SS-LE)	25
4.3.20 Void	25
4.3.21 Pre-emptive Priority Call (SS-PPC).....	25
4.3.22 Include Call (SS-IC)	26
4.3.23 Advice of Charge (SS-AoC)	26

4.3.24	Barring of Outgoing Calls (SS-BOC)	26
4.3.25	Barring of Incoming Calls (SS-BIC)	26
4.3.26	Discreet Listening (SS-DL)	27
4.3.27	Ambience Listening (SS-AL)	27
4.3.28	Dynamic Group Number Assignment (SS-DGNA)	27
4.3.29	Call Completion on No Reply (SS-CCNR)	27
4.3.30	Call Retention (SS-CRT)	27
4.3.31	Additional Network Feature - Inter System Interface Group Call (ANF-ISIGC)	28
4.3.32	Additional Network Feature - Inter System Interface Short Data Service (ANF-ISISDS)	28
4.3.33	Additional Network Feature - Inter System Interface Mobility Management (ANF-ISIMM)	28
4.3.34	Additional Network Feature - Inter System Interface Supplementary service (ANF-ISISS)	28
4.4	Interworking considerations	28
4.5	Static description of ANF-ISIIC using attributes	30
4.6	Overall SDL	32
5	ANF-ISIIC stage 2 specification	37
5.1	Functional model	37
5.1.1	Functional model description	37
5.1.2	Description of functional entities	38
5.1.2.1	SwMI A individual call control application functional entity, FE1	38
5.1.2.2	ISI individual call originating functional entity, FE2	39
5.1.2.3	ISI individual outgoing call route determining functional entity, FE3	39
5.1.2.4	ISI individual call migration handling functional entity, FE4	39
5.1.2.5	ISI information provision functional entity, FE5	40
5.1.2.6	ISI individual call migrated called user routeing functional entity, FE6	40
5.1.2.7	ISI individual call terminating functional entity, FE7	40
5.1.2.8	Terminating SwMI call control functional entity, FE8	41
5.1.3	Relationship of functional model to basic call functional model	41
5.2	Information flow	42
5.2.1	Examples of information flow sequences	42
5.2.1.1	Successful call set-up when the called user is registered in SwMI B and uses on/off hook signalling	43
5.2.1.2	Successful call set-up when the called user is registered in SwMI B and uses direct set-up signalling	45
5.2.1.3	ANF-ISIIC set-up to a called user having migrated from SwMI B, using forward switching	46
5.2.1.4	ANF-ISIIC set-up to a called user having migrated from SwMI B, using re-routeing	46
5.2.1.5	Loop avoidance in case of intra-TETRA call	49
5.2.1.6	Unsuccessful ANF-ISIIC call set-up	50
5.2.1.7	Transmission control	52
5.2.1.8	Call modify	53
5.2.1.9	Call restoration after migration	54
5.2.1.10	Call clearing	56
5.2.1.11	Radio traffic channel resource queuing and allocation	56
5.2.2	Definition of information flows	57
5.2.2.1	CALL RESTORE	57
5.2.2.2	CALL RESTORE PREPARE	58
5.2.2.3	CHARACTERISTIC CHANGE	59
5.2.2.4	COMPLETE	59
5.2.2.5	INFORM 1	60
5.2.2.6	INFORM 2	60
5.2.2.7	INFORM 3	60
5.2.2.8	MIGRATION	61
5.2.2.9	MODIFY	61
5.2.2.10	RELEASE	62
5.2.2.11	SETUP	62
5.2.2.12	SETUP PROLONGATION	63
5.2.2.13	TROMBONE	64
5.2.2.14	TX-CEASED	64
5.2.2.14.1	TX-CEASED 1	64
5.2.2.14.2	TX-CEASED 2	64
5.2.2.15	TX-CONTINUE 1	65
5.2.2.16	TX-CONTINUE 2	65

5.2.2.17	TX-DEMAND	65
5.2.2.18	TX-GRANTED	66
5.2.2.19	TX-INTERRUPT	66
5.2.2.20	TX-WAIT	66
5.2.3	Relationship of information flows to basic call information flows	66
5.3	Functional entity actions	67
5.4	Allocation of functional entities to physical equipment/SwMIs	67
6	ANF-ISIIC stage 3 specification	69
6.1	ANF-ISIIC description	69
6.2	ANF-ISIIC operational requirements	69
6.2.1	Requirements on the originating SwMI	69
6.2.2	Requirements on the terminating SwMI	70
6.2.3	Requirements on a called SwMI when it is different from the terminating SwMI	70
6.2.4	Requirements on a routeing SwMI	71
6.2.5	Requirements on a SwMI with PSTN/ISDN/PISN incoming gateway	71
6.2.6	Requirements on a SwMI with PSTN/ISDN/PISN outgoing gateways	72
6.3	ANF-ISIIC coding requirements	73
6.3.1	TETRA PDUs	73
6.3.1.1	TETRA PDU giving complementary information in the PSS1 SETUP message sent by the originating or the incoming gateway SwMI	74
6.3.1.2	TETRA PDU giving complementary information in a PSS1 PROGRESS message	77
6.3.1.3	TETRA message sent by the called SwMI in a PSS1 FACILITY message when it is not the terminating SwMI because of migration or SS-CF invocation	77
6.3.1.4	TETRA message sent by the originating SwMI in a PSS1 FACILITY message to request forward switching	79
6.3.1.5	TETRA PDU giving complementary information in the PSS1 ALERTING message	80
6.3.1.6	TETRA PDU giving complementary information in the PSS1 CONNECT message	80
6.3.1.7	TETRA information sent by the terminating SwMI in PSS1 FACILITY messages before the PSS1 ALERTING or CONNECT message	82
6.3.1.8	TETRA information sent by the terminating SwMI in a PSS1 FACILITY message during call establishment after the PSS1 ALERTING or CONNECT message	83
6.3.1.9	TETRA information sent by the originating SwMI in a PSS1 FACILITY message before the call has been established	83
6.3.1.10	TETRA CONNECT ACKNOWLEDGE sent by the originating SwMI in a PSS1 FACILITY message	83
6.3.1.11	Other TETRA messages possibly sent by the originating SwMI in PSS1 FACILITY messages	83
6.3.1.12	TETRA messages possibly sent by either the originating or the terminating SwMI in a PSS1 FACILITY message	85
6.3.1.13	TETRA messages possibly sent by the terminating SwMI in PSS1 FACILITY messages	86
6.3.1.14	TETRA PDUs giving complementary information in PSS1 messages to restore the call after the calling or the connected user has migrated in a new SwMI	87
6.3.1.14.1	Case where no connection between the old SwMI and the new SwMI already exists or has been identified	88
6.3.1.14.2	Cases where no new connection is needed between the old SwMI and the new SwMI	89
6.3.1.15	TETRA PDUs giving complementary information in PSS1 DISCONNECT messages	92
6.3.1.16	TETRA PDU giving complementary information in a PSS1 RELEASE message	93
6.3.1.17	TETRA PDUs giving complementary information in a PSS1 RELEASE COMPLETE message	93
6.3.1.18	TETRA PDUs specific for interaction with supplementary service protocol sent to the originating SwMI in a PSS1 FACILITY message	93
6.3.1.19	TETRA PDUs sent towards the Called or Visited SwMI in a PSS1 FACILITY after the PSS1 call has been connected	94
6.3.1.20	TETRA PDUs sent towards the Called or Originating SwMI in a PSS1 FACILITY after the PSS1 call has connected	96
6.3.2	TETRA PDU information element coding	97
6.3.2.1	Specific ISI definition of some information elements already defined for air interface messages	97
6.3.2.1.1	Basic service information	97
6.3.2.1.2	Call status	97
6.3.2.1.3	Call time-out, set-up phase	97
6.3.2.1.4	Disconnect cause information element	98
6.3.2.1.5	PDU type	99
6.3.2.2	New information elements used at the ISI	100

6.3.2.2.1	Call diverted to a dispatcher	100
6.3.2.2.2	Call has been forward switched	100
6.3.2.2.3	Call identified as fleet call	100
6.3.2.2.4	Called/forwarded-to external subscriber number	100
6.3.2.2.5	Called/forwarded-to party extension	100
6.3.2.2.6	Called/forwarded-to party SSI	100
6.3.2.2.7	Called/forwarded-to party fleet number SSI	100
6.3.2.2.8	Called/forwarded-to user having migrated	101
6.3.2.2.9	Calling external subscriber number	101
6.3.2.2.10	Calling external subscriber number parameters	101
6.3.2.2.11	Calling party fleet number SSI	101
6.3.2.2.12	Calling party presentation indicator	101
6.3.2.2.13	Cause for PDU addressed to originating SwMI	102
6.3.2.2.14	Connected external subscriber number	102
6.3.2.2.15	Connected external subscriber number parameters	102
6.3.2.2.16	Connected party presentation indicator	102
6.3.2.2.17	Connected party extension	102
6.3.2.2.18	Connected party SSI	102
6.3.2.2.19	Connected party fleet number SSI	103
6.3.2.2.20	Controlling SwMI	103
6.3.2.2.21	Incoming call barring status	103
6.3.2.2.22	Forwarded-to external subscriber number	103
6.3.2.2.23	Forwarded-to user extension	103
6.3.2.2.24	Forwarded-to user SSI	103
6.3.2.2.25	Last Forwarding SwMI MNI	103
6.3.2.2.26	Modify accepted	103
6.3.2.2.27	Modify request	104
6.3.2.2.28	MSISDN present as external subscriber number	104
6.3.2.2.29	New SwMI MNI	104
6.3.2.2.30	Number of digits in called/forwarded-to external subscriber number	104
6.3.2.2.31	Number of digits in calling external subscriber number	104
6.3.2.2.32	Number of digits in connected external subscriber number	104
6.3.2.2.33	Number of digits in forwarded-to external subscriber number	105
6.3.2.2.34	Number of digits in visited/forwarded-to SwMI PISN number	105
6.3.2.2.35	Originating SwMI MNI	105
6.3.2.2.36	Other end SwMI MNI	105
6.3.2.2.37	Override SS-CAD invocation	105
6.3.2.2.38	PDU addressed to originating SwMI	105
6.3.2.2.39	Possible ISI trombone or loop connection detected	105
6.3.2.2.40	Restoring party extension	106
6.3.2.2.41	Restoring party SSI	106
6.3.2.2.41a	Radio traffic channel release permission	106
6.3.2.2.41b	Radio traffic channel release signalling supported	107
6.3.2.2.41c	Resource indicator	107
6.3.2.2.42	Routeing method choice	107
6.3.2.2.43	Routeing method response	108
6.3.2.2.44	Security level at calling user air interface	108
6.3.2.2.44a	Setup resource allocation	108
6.3.2.2.45	Speech service requested/chosen/used	108
6.3.2.2.46	Speech services supported	109
6.3.2.2.47	SS-CF invocation counter	109
6.3.2.2.48	SS-CF invoked	109
6.3.2.2.49	SS-CLIR invoked for other party	109
6.3.2.2.50	Terminating SwMI MNI	109
6.3.2.2.51	Visited/forwarded-to SwMI MNI	109
6.3.2.2.52	Visited/forwarded-to SwMI PISN number	109
6.3.3	PSS1 facility information element	110
6.4	ANF-ISIIC state definitions	111
6.5	ANF-ISIIC signalling procedures	111
6.5.1	Call establishment	111
6.5.1.1	Call request, information channel selection, PISN called number sending and call proceeding	111
6.5.1.2	Called user migration	111

6.5.1.2.1	Called user having migrated in SwMI C different from SwMI A	112
6.5.1.2.2	Called user having migrated in SwMI C coinciding with SwMI A	115
6.5.1.3	Call characteristics and set-up time negotiation by the terminating SwMI	115
6.5.1.4	Call confirmation indication and call connected by the terminating SwMI	116
6.5.1.5	Failure of call establishment	117
6.5.2	Call maintenance procedures	118
6.5.2.1	Transmission control procedures	118
6.5.2.2	Call modification and/or continuation	118
6.5.2.3	Call restoration	118
6.5.2.3.1	General call restoration procedure	118
6.5.2.3.2	Specific call restoration procedure in a SwMI already on the path of the call	120
6.5.3	DTMF procedures	123
6.5.4	ANF-ISIIC clearing	123
6.5.5	Call collisions	124
6.6	ANF-ISIIC impact of interworking with ISDN/PISN/PSTN	125
6.7	Protocol interactions between ANF-ISIIC and supplementary services and other ANFs	125
6.7.1	Interaction with SS-CLIR	125
6.7.2	Interactions with SS-CF	126
6.7.2.1	Interaction with SS-CF at call establishment	126
6.7.2.2	Specific interaction with SS-CFNry at call establishment	126
6.7.2.3	Interaction with SS-CF at call restoration	126
6.7.3	Interaction with SS-CAD	127
6.7.3.1	Invocation of a specific ANF-ISIIC	127
6.7.3.2	Interception of an already invoked ANF-ISIIC	127
6.7.3.3	Call authorization by a distant dispatcher	127
6.7.3.4	Completion of call establishment	127
6.7.3.4.1	Call not diverted to dispatcher	127
6.7.3.4.2	Call diverted to dispatcher	128
6.7.4	Interactions with SS-PC, SS-PPC and SS-CRT	128
6.7.5	Interaction with SS-CW	129
6.7.6	Interaction with SS-HOLD	129
6.7.7	Interaction with SS-CCBS and SS-CCNR	129
6.7.8	Interaction with SS-BIC	129
6.7.9	Interactions with SS-AoC	129
6.7.10	Area Selection (SS-AS) and selected area number	130
6.7.11	Interactions with other supplementary services	130
6.8	ANF-ISIIC parameter values (timers)	130

Annex A (informative):	Static description of the TETRA individual call bearer service, using attributes	131
-------------------------------	---	------------

Annex B (informative):	Definition of the ISI ROSE operation	132
-------------------------------	---	------------

Annex C (informative):	Interactions of SS-CFU with ANF-ISIIC	133
-------------------------------	--	------------

C.1	Possible SS-CFU activation	133
C.2	Invocation and operation	133
C.2.1	Called user home SwMI being SwMI A	133
C.2.2	Called user home SwMI being SwMI B	133
C.2.2.1	Forwarded-to user with home SwMI being SwMI B, being registered in its home SwMI	134
C.2.2.2	Forwarded-to user with home SwMI being SwMI B, having migrated	135
C.2.2.3	Forwarded-to user with home SwMI different from SwMI B, being registered in its home SwMI	135
C.2.2.4	Forwarded-to user with home SwMI different from SwMI B, having migrated	135

Annex D (informative):	Change Requests	138
-------------------------------	------------------------------	------------

History	139
---------------	-----