



**Terrestrial Trunked Radio (TETRA);
Conformance testing specification;
Part 1: Radio**

(<https://standards.iteh.ai>)

Document Preview

[ETSI EN 300 394-1 V3.2.1 \(2012-10\)](https://standards.iteh.ai/catalog/standards/etsi/d1cd43af-ce3f-4abc-b396-16828765dff8/etsi-en-300-394-1-v3-2-1-2012-10)

<https://standards.iteh.ai/catalog/standards/etsi/d1cd43af-ce3f-4abc-b396-16828765dff8/etsi-en-300-394-1-v3-2-1-2012-10>

Reference

REN/TETRA-03201

Keywords

DMO, testing, TETRA, V+D

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2012.
All rights reserved.

DECTTM, PLUGTESTSTM, UMTSTM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPPTM and LTETM are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	10
Foreword.....	10
Introduction	10
1 Scope	11
2 References	11
2.1 Normative references	11
2.2 Informative references.....	12
3 Definitions, symbols and abbreviations	12
3.1 Definitions.....	12
3.2 Symbols.....	12
3.3 Abbreviations	13
4 General	13
4.1 Presentation of equipment for testing purposes.....	13
4.1.1 Facilities and information required for testing.....	14
4.1.2 Choice of radio frequency channels to be tested.....	14
4.1.3 Interpretation of the measurement results.....	15
4.2 Mechanical and electrical design.....	15
4.2.1 General.....	15
4.2.2 Controls	15
4.2.3 Marking	15
5 Radio test configuration, test signals and test modes	15
5.1 General functional radio test configuration.....	16
5.2 Radio test modes	16
5.2.1 Test receive mode	16
5.2.1.1 MS test receive mode for phase modulation	17
5.2.1.2 BS test receive mode for phase modulation	17
5.2.1.3 MS test receive mode for QAM (where supported)	18
5.2.1.4 BS test receive mode for QAM (where supported)	18
5.2.2 Test transmit mode.....	19
5.2.2.1 MS testing for phase modulation	19
5.2.2.2 Void.....	19
5.2.2.3 BS testing for phase modulation	19
5.2.2.4 MS testing for QAM (where supported)	20
5.2.2.5 BS testing for QAM (where supported)	20
5.3 Radio test signals.....	21
5.3.1 General.....	21
5.3.2 Test signal T1 (TETRA wanted signal, phase modulation)	21
5.3.2.1 MS testing	21
5.3.2.2 BS testing	22
5.3.2.3 Void.....	23
5.3.2.4 Void.....	23
5.3.3 Test signal T2 (TETRA interferer)	23
5.3.4 Test signal T3 (unmodulated interferer)	23
5.3.5 Test signal T4 (TETRA wanted signal, QAM).....	23
5.3.5.1 MS testing	23
5.3.5.1.1 Use of synchronization burst in frame 18 when testing CA MSs.....	25
5.3.5.1.1a Use of frequency correction burst in frame 18 when testing DA MSs	27
5.3.5.2 BS testing	28
6 Test conditions	29
6.1 General	29
6.2 Power sources and ambient conditions.....	29
6.2.1 Normal test conditions	29

6.2.2	Extreme test conditions.....	30
6.3	Procedure for tests at extreme temperatures.....	31
6.3.1	Equipment designed for continuous operation.....	31
6.3.2	Equipment designed for intermittent operation.....	31
7	Technical characteristics	31
7.1	Transmitter parameter definitions and limits.....	31
7.1.1	Transmitter output power.....	31
7.1.1.1	Definition	31
7.1.1.2	Limit values for phase modulation and QAM.....	32
7.1.2	Unwanted output power in non-active transmit state.....	32
7.1.2.1	Definition	32
7.1.2.2	Limit values.....	32
7.1.3	Adjacent channel power due to modulation.....	32
7.1.3.1	Definition	32
7.1.3.2	Limit values for phase modulation.....	32
7.1.3.3	Limit values for QAM.....	33
7.1.4	Adjacent channel power due to switching transients	34
7.1.4.1	Definition	34
7.1.4.2	Limit values for phase modulation.....	34
7.1.4.3	Limit values for QAM.....	34
7.1.5	Unwanted emissions far from the carrier	35
7.1.5.1	Definition	35
7.1.5.2	Limit values for phase modulation.....	35
7.1.5.3	Limit values for QAM.....	36
7.1.6	Unwanted radiated emissions	37
7.1.6.1	Definition	37
7.1.6.2	Limit values.....	37
7.1.7	Unwanted emissions during the BLCH/CLCH (linearization)	37
7.1.7.1	Definition	37
7.1.7.2	Limit values for phase modulation.....	37
7.1.7.3	Limit values for QAM.....	37
7.1.8	Transmitter intermodulation attenuation	38
7.1.8.1	Definition	38
7.1.8.2	Limit values for phase modulation and QAM.....	38
7.1.8.2.1	MS Limit values	38
7.1.8.2.2	Limit values for single BS transmitter.....	38
7.1.8.2.3	Limit values for intra BS intermodulation.....	38
7.2	Receiver parameter definitions and limits.....	39
7.2.1	General.....	39
7.2.2	Nominal error rates	39
7.2.2.1	Definition	39
7.2.2.2	Limit values for phase modulation.....	39
7.2.2.3	Limit values for QAM.....	39
7.2.3	Reference sensitivity performance.....	39
7.2.3.1	Definition	39
7.2.3.2	Limit values for phase modulation.....	40
7.2.3.3	Limit values for QAM.....	40
7.2.4	Reference interference performance	42
7.2.4.1	Definition	42
7.2.4.2	Limit values for phase modulation.....	42
7.2.4.3	Limit values for QAM.....	43
7.2.4.3.1	Adjacent channel interference	43
7.2.4.3.2	Co-channel interference.....	43
7.2.5	Blocking characteristics	44
7.2.5.1	Definition	44
7.2.5.2	Limit values for phase modulation.....	44
7.2.5.3	Limit values for QAM.....	44
7.2.6	Spurious response rejection	45
7.2.6.1	Definition	45
7.2.6.2	Limit values for phase modulation.....	45
7.2.6.3	Limit values for QAM.....	45

7.2.7	Intermodulation response rejection.....	46
7.2.7.1	Definition	46
7.2.7.2	Limit values.....	46
7.2.8	Unwanted conducted emissions	47
7.2.8.1	Definition	47
7.2.8.2	Limit values.....	47
7.2.9	Unwanted radiated emissions	47
7.2.9.1	Definition	47
7.2.9.2	Limit values.....	47
7.3	Transmitter/receiver parameter definitions and limits.....	47
7.3.1	Modulation accuracy.....	47
7.3.1.1	Definition	47
7.3.1.2	Limit values for phase modulation.....	47
7.3.1.3	Limit values for QAM.....	47
7.3.2	Carrier frequency accuracy.....	48
7.3.2.1	Definition	48
7.3.2.2	Limit values.....	48
7.3.3	MS receiver performance for synchronization burst acquisition	48
7.3.3.1	Definition for phase modulation	48
7.3.3.2	Limit values for phase modulation.....	48
7.3.3.3	Definition for QAM modulation	48
7.3.3.4	Limit values for QAM modulation.....	48
7.3.4	MS Frame alignment performance	49
7.3.4.1	Definition	49
7.3.4.2	Limit values.....	49
7.3.5	MS link control	49
7.3.5.1	Definition	49
7.3.5.2	Limit values.....	49
8	Methods of measurement for transmitter parameters	50
8.1	Transmitter output power	50
8.1.1	Transmitter output power for phase modulation.....	50
8.1.1.1	MS transmitter output power for phase modulation.....	50
8.1.1.2	BS transmitter output power for phase modulation.....	51
8.1.2	Transmitter output power for QAM.....	52
8.1.2.1	MS transmitter output power for QAM.....	52
8.1.2.2	BS transmitter output power for QAM.....	52
8.2	Unwanted output power in non active transmit state.....	53
8.3	Adjacent channel power due to modulation	53
8.4	Adjacent channel power due to switching transients.....	54
8.5	Unwanted emissions far from the carrier	54
8.6	Unwanted radiated emissions	56
8.7	Unwanted emissions during the BLCH/CLCH and BLCH-Q/CLCH-Q (linearization)	56
8.7.1	MS unwanted emissions during the CLCH (linearization)	56
8.7.2	BS unwanted emissions during the BLCH (linearization)	57
8.7.3	MS unwanted emissions during the CLCH-Q (linearization).....	57
8.7.4	BS unwanted emissions during the BLCH-Q (linearization).....	57
8.8	Transmitter intermodulation attenuation	58
8.8.1	MS Transmitter intermodulation attenuation	58
8.8.2	BS Transmitter intermodulation attenuation.....	58
8.8.3	Intra BS transmitter intermodulation attenuation.....	58
9	Methods of measurement for receiver parameters	59
9.1	General	59
9.2	Nominal error rates for phase modulation.....	59
9.2.1	MS nominal error rate.....	59
9.2.2	BS nominal error rate.....	59
9.3	Reference sensitivity performance	59
9.3.1	MS reference sensitivity performance for phase modulation.....	59
9.3.2	BS reference sensitivity performance for phase modulation	60
9.3.3	MS reference sensitivity performance for QAM	60
9.3.4	BS reference sensitivity performance for QAM	60

9.3.5	PUEM performance	60
9.4	Reference interference performance	61
9.4.1	MS reference interference performance for phase modulation	61
9.4.2	BS reference interference performance for phase modulation	61
9.4.3	MS reference interference performance for QAM	61
9.4.4	BS reference interference performance for QAM	62
9.5	Blocking characteristics	62
9.5.1	MS blocking for phase modulation	62
9.5.2	BS blocking for phase modulation	63
9.5.3	MS blocking for QAM	63
9.5.4	BS blocking for QAM	63
9.6	Spurious response rejection	63
9.6.1	Phase Modulation	63
9.6.2	QAM	64
9.7	Intermodulation response rejection	64
9.7.1	MS intermodulation response rejection for phase modulation	64
9.7.2	BS intermodulation response rejection for phase modulation	64
9.7.3	MS intermodulation response rejection for QAM	65
9.7.4	BS intermodulation response rejection for QAM	65
9.8	Unwanted emissions	65
9.9	Unwanted radiated emissions	66
10	Methods of measurement for transmitter/receiver parameters	66
10.1	Modulation accuracy	66
10.1.1	MS modulation accuracy for phase modulation	66
10.1.2	BS modulation accuracy for phase modulation	67
10.1.3	Vector error magnitude at symbol time for phase modulation	67
10.1.4	MS modulation accuracy for QAM	67
10.1.5	BS modulation accuracy for QAM	67
10.1.6	Vector error magnitude at symbol time for QAM	67
10.2	Carrier frequency accuracy	68
10.2.1	MS carrier frequency accuracy for phase modulation	68
10.2.2	BS carrier frequency accuracy for phase modulation	68
10.2.3	MS carrier frequency accuracy for QAM	69
10.2.4	BS carrier frequency accuracy for QAM	69
10.3	MS receiver performance for synchronization acquisition	70
10.3.1	CA MS receiver performance for synchronization burst acquisition	70
10.3.2	DA MS receiver performance for frequency correction burst acquisition	70
10.4	MS Frame alignment performance	70
10.5	MS link control	71
11	Measurement uncertainty	72
11.1	Transmitter	72
11.2	Receiver	76
11.3	Transmitter/receiver parameter definitions and limits	77
11.4	Interpretation of measurement results	78
Annex A (normative):	TETRA receiver testing	79
A.1	Frequencies of spurious response	79
A.2	Test cases and test conditions for BS and MS receivers	79
A.3	Test signal T1/T4, content of BSCH, BSCH-Q/T, BNCH/T and BNCH-Q/T	108
Annex B (normative):	Radio test system functions	115
B.1	Test transmitter and receiver	115
B.1.1	General	115
B.1.2	Sampling system	115
B.1.2.1	General	115
B.1.2.2	TETRA filter	115
B.1.2.3	Adjacent channel power measurements	116
B.1.2.4	Modulation accuracy measurements	116

B.1.2.5	Measurement of unwanted output power in the non-active transmit state	116
B.1.3	Spectrum analyser	116
B.1.4	Error rate tester	116
B.1.5	Test signal requirements	117
B.1.5.1	On channel test signal T1	117
B.1.5.2	Interfering test signal T2	117
B.1.5.2.1	Phase Modulated	117
B.1.5.2.2	QAM Modulated	117
B.1.5.3	Interfering test signal T3	117
B.1.5.4	On channel test signal T4	118
B.1.6	Propagation simulators	118
B.1.7	Timing measurement unit	118
B.1.8	Passive test system components	118
B.1.9	Test system controller	118

Annex C (normative): TETRA Test Connector Interface (TTCI)119

C.1	General	119
C.2	Formal aspects	119
C.3	TTCI, layer 1	119
C.3.1	Mechanical and electrical characteristics	119
C.3.2	Transmission and reception characteristics	120
C.4	TTCI, Layer 2	120
C.4.1	General structure	120
C.4.2	Frame structure	120
C.4.3	Flow of I-frames on layer 2	121
C.4.3.1	Transmission of frames	121
C.4.3.2	Reception of frames	121
C.4.3.3	Parameters on layer 2	122
C.5	TTCI, Layer 3	122
C.5.1	Message structure	122
C.5.2	Definitions of the messages	122
C.5.2.1	DATO	122
C.5.2.1.1	Test equipment error handling	124
C.5.2.2	Bi-directional operation of the TTCI	124
C.5.2.3	Codec conformance testing	125
C.5.2.4	ST indicator	125
C.6	Control of MS/BS	126
C.6.1	Manual intervention of MS/BS	126
C.6.2	Bi-directional operation of the test interface	126
C.6.3	MS controlled by T1	126
C.7	Characteristics of the interface	126
C.7.1	Mechanical characteristics of the interface	126
C.7.2	Electric characteristics of the interface	126
C.8	Codec conformance testing using the TTCI	127
C.8.1	Codec conformance test methodology using the TTCI	127

Annex D (normative): RF test facility using RF loop back128

D.1	Introduction to the TETRA Test (TT) protocol for RF loop back test	129
D.1.1	Outline requirements	129
D.1.2	Test modes	130
D.1.3	Switching for loop back test mode	131
D.2	TETRA test entity	131
D.3	TETRA RF loop back test protocol	132
D.3.1	Setting the TETRA MS into TETRA test mode	132
D.3.2	TETRA test protocol	133