

# ETSI EN 300 394-1 V3.2.1 (2012-10)



## **Terrestrial Trunked Radio (TETRA); Conformance testing specification; Part 1: Radio**

(<https://standards.iteh.ai>)

### **Document Preview**

[ETSI EN 300 394-1 V3.2.1 \(2012-10\)](https://standards.iteh.ai/catalog/standards/etsi/d1cd43af-ce3f-4abc-b396-16828765dff8/etsi-en-300-394-1-v3-2-1-2012-10)

<https://standards.iteh.ai/catalog/standards/etsi/d1cd43af-ce3f-4abc-b396-16828765dff8/etsi-en-300-394-1-v3-2-1-2012-10>

---

ReferenceREN/TETRA-03201

---

Keywords

---

DMO, testing, TETRA, V+D

---

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

**(<https://standards.iteh.ai>)**  
**Document Preview**

---

**Important notice**

---

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

[http://portal.etsi.org/chaicor/ETSI\\_support.asp](http://portal.etsi.org/chaicor/ETSI_support.asp)

---

**Copyright Notification**

---

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2012.  
All rights reserved.

DECT<sup>TM</sup>, PLUGTESTS<sup>TM</sup>, UMTS<sup>TM</sup> and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.  
3GPP<sup>TM</sup> and LTE<sup>TM</sup> are Trade Marks of ETSI registered for the benefit of its Members and  
of the 3GPP Organizational Partners.  
GSM<sup>®</sup> and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

|                                                                                    |    |
|------------------------------------------------------------------------------------|----|
| Intellectual Property Rights .....                                                 | 10 |
| Foreword.....                                                                      | 10 |
| Introduction .....                                                                 | 10 |
| 1 Scope .....                                                                      | 11 |
| 2 References .....                                                                 | 11 |
| 2.1 Normative references .....                                                     | 11 |
| 2.2 Informative references.....                                                    | 12 |
| 3 Definitions, symbols and abbreviations .....                                     | 12 |
| 3.1 Definitions.....                                                               | 12 |
| 3.2 Symbols.....                                                                   | 12 |
| 3.3 Abbreviations .....                                                            | 13 |
| 4 General .....                                                                    | 13 |
| 4.1 Presentation of equipment for testing purposes.....                            | 13 |
| 4.1.1 Facilities and information required for testing.....                         | 14 |
| 4.1.2 Choice of radio frequency channels to be tested.....                         | 14 |
| 4.1.3 Interpretation of the measurement results.....                               | 15 |
| 4.2 Mechanical and electrical design.....                                          | 15 |
| 4.2.1 General.....                                                                 | 15 |
| 4.2.2 Controls .....                                                               | 15 |
| 4.2.3 Marking .....                                                                | 15 |
| 5 Radio test configuration, test signals and test modes.....                       | 15 |
| 5.1 General functional radio test configuration.....                               | 16 |
| 5.2 Radio test modes .....                                                         | 16 |
| 5.2.1 Test receive mode .....                                                      | 16 |
| 5.2.1.1 MS test receive mode for phase modulation .....                            | 17 |
| 5.2.1.2 BS test receive mode for phase modulation .....                            | 17 |
| 5.2.1.3 MS test receive mode for QAM (where supported) .....                       | 18 |
| 5.2.1.4 BS test receive mode for QAM (where supported) .....                       | 18 |
| 5.2.2 Test transmit mode.....                                                      | 19 |
| 5.2.2.1 MS testing for phase modulation .....                                      | 19 |
| 5.2.2.2 Void.....                                                                  | 19 |
| 5.2.2.3 BS testing for phase modulation .....                                      | 19 |
| 5.2.2.4 MS testing for QAM (where supported) .....                                 | 20 |
| 5.2.2.5 BS testing for QAM (where supported) .....                                 | 20 |
| 5.3 Radio test signals.....                                                        | 21 |
| 5.3.1 General.....                                                                 | 21 |
| 5.3.2 Test signal T1 (TETRA wanted signal, phase modulation) .....                 | 21 |
| 5.3.2.1 MS testing .....                                                           | 21 |
| 5.3.2.2 BS testing .....                                                           | 22 |
| 5.3.2.3 Void.....                                                                  | 23 |
| 5.3.2.4 Void.....                                                                  | 23 |
| 5.3.3 Test signal T2 (TETRA interferer) .....                                      | 23 |
| 5.3.4 Test signal T3 (unmodulated interferer) .....                                | 23 |
| 5.3.5 Test signal T4 (TETRA wanted signal, QAM).....                               | 23 |
| 5.3.5.1 MS testing .....                                                           | 23 |
| 5.3.5.1.1 Use of synchronization burst in frame 18 when testing CA MSs.....        | 25 |
| 5.3.5.1.1a Use of frequency correction burst in frame 18 when testing DA MSs ..... | 27 |
| 5.3.5.2 BS testing .....                                                           | 28 |
| 6 Test conditions .....                                                            | 29 |
| 6.1 General .....                                                                  | 29 |
| 6.2 Power sources and ambient conditions.....                                      | 29 |
| 6.2.1 Normal test conditions.....                                                  | 29 |

|           |                                                               |    |
|-----------|---------------------------------------------------------------|----|
| 6.2.2     | Extreme test conditions.....                                  | 30 |
| 6.3       | Procedure for tests at extreme temperatures.....              | 31 |
| 6.3.1     | Equipment designed for continuous operation.....              | 31 |
| 6.3.2     | Equipment designed for intermittent operation.....            | 31 |
| 7         | Technical characteristics .....                               | 31 |
| 7.1       | Transmitter parameter definitions and limits.....             | 31 |
| 7.1.1     | Transmitter output power.....                                 | 31 |
| 7.1.1.1   | Definition .....                                              | 31 |
| 7.1.1.2   | Limit values for phase modulation and QAM.....                | 32 |
| 7.1.2     | Unwanted output power in non-active transmit state.....       | 32 |
| 7.1.2.1   | Definition .....                                              | 32 |
| 7.1.2.2   | Limit values.....                                             | 32 |
| 7.1.3     | Adjacent channel power due to modulation.....                 | 32 |
| 7.1.3.1   | Definition .....                                              | 32 |
| 7.1.3.2   | Limit values for phase modulation.....                        | 32 |
| 7.1.3.3   | Limit values for QAM.....                                     | 33 |
| 7.1.4     | Adjacent channel power due to switching transients .....      | 34 |
| 7.1.4.1   | Definition .....                                              | 34 |
| 7.1.4.2   | Limit values for phase modulation.....                        | 34 |
| 7.1.4.3   | Limit values for QAM.....                                     | 34 |
| 7.1.5     | Unwanted emissions far from the carrier .....                 | 35 |
| 7.1.5.1   | Definition .....                                              | 35 |
| 7.1.5.2   | Limit values for phase modulation.....                        | 35 |
| 7.1.5.3   | Limit values for QAM.....                                     | 36 |
| 7.1.6     | Unwanted radiated emissions .....                             | 37 |
| 7.1.6.1   | Definition .....                                              | 37 |
| 7.1.6.2   | Limit values.....                                             | 37 |
| 7.1.7     | Unwanted emissions during the BLCH/CLCH (linearization) ..... | 37 |
| 7.1.7.1   | Definition .....                                              | 37 |
| 7.1.7.2   | Limit values for phase modulation.....                        | 37 |
| 7.1.7.3   | Limit values for QAM.....                                     | 37 |
| 7.1.8     | Transmitter intermodulation attenuation .....                 | 38 |
| 7.1.8.1   | Definition .....                                              | 38 |
| 7.1.8.2   | Limit values for phase modulation and QAM.....                | 38 |
| 7.1.8.2.1 | MS Limit values .....                                         | 38 |
| 7.1.8.2.2 | Limit values for single BS transmitter.....                   | 38 |
| 7.1.8.2.3 | Limit values for intra BS intermodulation.....                | 38 |
| 7.2       | Receiver parameter definitions and limits.....                | 39 |
| 7.2.1     | General.....                                                  | 39 |
| 7.2.2     | Nominal error rates .....                                     | 39 |
| 7.2.2.1   | Definition .....                                              | 39 |
| 7.2.2.2   | Limit values for phase modulation.....                        | 39 |
| 7.2.2.3   | Limit values for QAM.....                                     | 39 |
| 7.2.3     | Reference sensitivity performance.....                        | 39 |
| 7.2.3.1   | Definition .....                                              | 39 |
| 7.2.3.2   | Limit values for phase modulation.....                        | 40 |
| 7.2.3.3   | Limit values for QAM.....                                     | 40 |
| 7.2.4     | Reference interference performance .....                      | 42 |
| 7.2.4.1   | Definition .....                                              | 42 |
| 7.2.4.2   | Limit values for phase modulation.....                        | 42 |
| 7.2.4.3   | Limit values for QAM.....                                     | 43 |
| 7.2.4.3.1 | Adjacent channel interference .....                           | 43 |
| 7.2.4.3.2 | Co-channel interference.....                                  | 43 |
| 7.2.5     | Blocking characteristics .....                                | 44 |
| 7.2.5.1   | Definition .....                                              | 44 |
| 7.2.5.2   | Limit values for phase modulation.....                        | 44 |
| 7.2.5.3   | Limit values for QAM.....                                     | 44 |
| 7.2.6     | Spurious response rejection .....                             | 45 |
| 7.2.6.1   | Definition .....                                              | 45 |
| 7.2.6.2   | Limit values for phase modulation.....                        | 45 |
| 7.2.6.3   | Limit values for QAM.....                                     | 45 |

|         |                                                                                 |    |
|---------|---------------------------------------------------------------------------------|----|
| 7.2.7   | Intermodulation response rejection.....                                         | 46 |
| 7.2.7.1 | Definition .....                                                                | 46 |
| 7.2.7.2 | Limit values.....                                                               | 46 |
| 7.2.8   | Unwanted conducted emissions .....                                              | 47 |
| 7.2.8.1 | Definition .....                                                                | 47 |
| 7.2.8.2 | Limit values.....                                                               | 47 |
| 7.2.9   | Unwanted radiated emissions .....                                               | 47 |
| 7.2.9.1 | Definition .....                                                                | 47 |
| 7.2.9.2 | Limit values.....                                                               | 47 |
| 7.3     | Transmitter/receiver parameter definitions and limits.....                      | 47 |
| 7.3.1   | Modulation accuracy.....                                                        | 47 |
| 7.3.1.1 | Definition .....                                                                | 47 |
| 7.3.1.2 | Limit values for phase modulation.....                                          | 47 |
| 7.3.1.3 | Limit values for QAM.....                                                       | 47 |
| 7.3.2   | Carrier frequency accuracy.....                                                 | 48 |
| 7.3.2.1 | Definition .....                                                                | 48 |
| 7.3.2.2 | Limit values.....                                                               | 48 |
| 7.3.3   | MS receiver performance for synchronization burst acquisition .....             | 48 |
| 7.3.3.1 | Definition for phase modulation .....                                           | 48 |
| 7.3.3.2 | Limit values for phase modulation.....                                          | 48 |
| 7.3.3.3 | Definition for QAM modulation .....                                             | 48 |
| 7.3.3.4 | Limit values for QAM modulation.....                                            | 48 |
| 7.3.4   | MS Frame alignment performance .....                                            | 49 |
| 7.3.4.1 | Definition .....                                                                | 49 |
| 7.3.4.2 | Limit values.....                                                               | 49 |
| 7.3.5   | MS link control.....                                                            | 49 |
| 7.3.5.1 | Definition .....                                                                | 49 |
| 7.3.5.2 | Limit values.....                                                               | 49 |
| 8       | Methods of measurement for transmitter parameters .....                         | 50 |
| 8.1     | Transmitter output power .....                                                  | 50 |
| 8.1.1   | Transmitter output power for phase modulation .....                             | 50 |
| 8.1.1.1 | MS transmitter output power for phase modulation.....                           | 50 |
| 8.1.1.2 | BS transmitter output power for phase modulation.....                           | 51 |
| 8.1.2   | Transmitter output power for QAM.....                                           | 52 |
| 8.1.2.1 | MS transmitter output power for QAM.....                                        | 52 |
| 8.1.2.2 | BS transmitter output power for QAM.....                                        | 53 |
| 8.2     | Unwanted output power in non active transmit state.....                         | 53 |
| 8.3     | Adjacent channel power due to modulation .....                                  | 53 |
| 8.4     | Adjacent channel power due to switching transients.....                         | 54 |
| 8.5     | Unwanted emissions far from the carrier .....                                   | 54 |
| 8.6     | Unwanted radiated emissions .....                                               | 56 |
| 8.7     | Unwanted emissions during the BLCH/CLCH and BLCH-Q/CLCH-Q (linearization) ..... | 56 |
| 8.7.1   | MS unwanted emissions during the CLCH (linearization) .....                     | 56 |
| 8.7.2   | BS unwanted emissions during the BLCH (linearization) .....                     | 57 |
| 8.7.3   | MS unwanted emissions during the CLCH-Q (linearization).....                    | 57 |
| 8.7.4   | BS unwanted emissions during the BLCH-Q (linearization).....                    | 57 |
| 8.8     | Transmitter intermodulation attenuation .....                                   | 58 |
| 8.8.1   | MS Transmitter intermodulation attenuation .....                                | 58 |
| 8.8.2   | BS Transmitter intermodulation attenuation.....                                 | 58 |
| 8.8.3   | Intra BS transmitter intermodulation attenuation.....                           | 58 |
| 9       | Methods of measurement for receiver parameters .....                            | 59 |
| 9.1     | General .....                                                                   | 59 |
| 9.2     | Nominal error rates for phase modulation.....                                   | 59 |
| 9.2.1   | MS nominal error rate.....                                                      | 59 |
| 9.2.2   | BS nominal error rate.....                                                      | 59 |
| 9.3     | Reference sensitivity performance .....                                         | 59 |
| 9.3.1   | MS reference sensitivity performance for phase modulation.....                  | 59 |
| 9.3.2   | BS reference sensitivity performance for phase modulation .....                 | 60 |
| 9.3.3   | MS reference sensitivity performance for QAM .....                              | 60 |
| 9.3.4   | BS reference sensitivity performance for QAM .....                              | 60 |

|                             |                                                                             |            |
|-----------------------------|-----------------------------------------------------------------------------|------------|
| 9.3.5                       | PUEM performance .....                                                      | 60         |
| 9.4                         | Reference interference performance .....                                    | 61         |
| 9.4.1                       | MS reference interference performance for phase modulation .....            | 61         |
| 9.4.2                       | BS reference interference performance for phase modulation .....            | 61         |
| 9.4.3                       | MS reference interference performance for QAM .....                         | 61         |
| 9.4.4                       | BS reference interference performance for QAM .....                         | 62         |
| 9.5                         | Blocking characteristics .....                                              | 62         |
| 9.5.1                       | MS blocking for phase modulation .....                                      | 62         |
| 9.5.2                       | BS blocking for phase modulation .....                                      | 63         |
| 9.5.3                       | MS blocking for QAM .....                                                   | 63         |
| 9.5.4                       | BS blocking for QAM .....                                                   | 63         |
| 9.6                         | Spurious response rejection .....                                           | 63         |
| 9.6.1                       | Phase Modulation .....                                                      | 63         |
| 9.6.2                       | QAM .....                                                                   | 64         |
| 9.7                         | Intermodulation response rejection .....                                    | 64         |
| 9.7.1                       | MS intermodulation response rejection for phase modulation .....            | 64         |
| 9.7.2                       | BS intermodulation response rejection for phase modulation .....            | 64         |
| 9.7.3                       | MS intermodulation response rejection for QAM .....                         | 65         |
| 9.7.4                       | BS intermodulation response rejection for QAM .....                         | 65         |
| 9.8                         | Unwanted emissions .....                                                    | 65         |
| 9.9                         | Unwanted radiated emissions .....                                           | 66         |
| 10                          | Methods of measurement for transmitter/receiver parameters .....            | 66         |
| 10.1                        | Modulation accuracy .....                                                   | 66         |
| 10.1.1                      | MS modulation accuracy for phase modulation .....                           | 66         |
| 10.1.2                      | BS modulation accuracy for phase modulation .....                           | 67         |
| 10.1.3                      | Vector error magnitude at symbol time for phase modulation .....            | 67         |
| 10.1.4                      | MS modulation accuracy for QAM .....                                        | 67         |
| 10.1.5                      | BS modulation accuracy for QAM .....                                        | 67         |
| 10.1.6                      | Vector error magnitude at symbol time for QAM .....                         | 67         |
| 10.2                        | Carrier frequency accuracy .....                                            | 68         |
| 10.2.1                      | MS carrier frequency accuracy for phase modulation .....                    | 68         |
| 10.2.2                      | BS carrier frequency accuracy for phase modulation .....                    | 68         |
| 10.2.3                      | MS carrier frequency accuracy for QAM .....                                 | 69         |
| 10.2.4                      | BS carrier frequency accuracy for QAM .....                                 | 69         |
| 10.3                        | MS receiver performance for synchronization acquisition .....               | 70         |
| 10.3.1                      | CA MS receiver performance for synchronization burst acquisition .....      | 70         |
| 10.3.2                      | DA MS receiver performance for frequency correction burst acquisition ..... | 70         |
| 10.4                        | MS Frame alignment performance .....                                        | 70         |
| 10.5                        | MS link control .....                                                       | 71         |
| 11                          | Measurement uncertainty .....                                               | 72         |
| 11.1                        | Transmitter .....                                                           | 72         |
| 11.2                        | Receiver .....                                                              | 76         |
| 11.3                        | Transmitter/receiver parameter definitions and limits .....                 | 77         |
| 11.4                        | Interpretation of measurement results .....                                 | 78         |
| <b>Annex A (normative):</b> | <b>TETRA receiver testing .....</b>                                         | <b>79</b>  |
| A.1                         | Frequencies of spurious response .....                                      | 79         |
| A.2                         | Test cases and test conditions for BS and MS receivers .....                | 79         |
| A.3                         | Test signal T1/T4, content of BSCH, BSCH-Q/T, BNCH/T and BNCH-Q/T .....     | 108        |
| <b>Annex B (normative):</b> | <b>Radio test system functions .....</b>                                    | <b>115</b> |
| B.1                         | Test transmitter and receiver .....                                         | 115        |
| B.1.1                       | General .....                                                               | 115        |
| B.1.2                       | Sampling system .....                                                       | 115        |
| B.1.2.1                     | General .....                                                               | 115        |
| B.1.2.2                     | TETRA filter .....                                                          | 115        |
| B.1.2.3                     | Adjacent channel power measurements .....                                   | 116        |
| B.1.2.4                     | Modulation accuracy measurements .....                                      | 116        |

|           |                                                                             |     |
|-----------|-----------------------------------------------------------------------------|-----|
| B.1.2.5   | Measurement of unwanted output power in the non-active transmit state ..... | 116 |
| B.1.3     | Spectrum analyser .....                                                     | 116 |
| B.1.4     | Error rate tester .....                                                     | 116 |
| B.1.5     | Test signal requirements .....                                              | 117 |
| B.1.5.1   | On channel test signal T1 .....                                             | 117 |
| B.1.5.2   | Interfering test signal T2 .....                                            | 117 |
| B.1.5.2.1 | Phase Modulated .....                                                       | 117 |
| B.1.5.2.2 | QAM Modulated .....                                                         | 117 |
| B.1.5.3   | Interfering test signal T3 .....                                            | 117 |
| B.1.5.4   | On channel test signal T4 .....                                             | 118 |
| B.1.6     | Propagation simulators .....                                                | 118 |
| B.1.7     | Timing measurement unit .....                                               | 118 |
| B.1.8     | Passive test system components .....                                        | 118 |
| B.1.9     | Test system controller .....                                                | 118 |

## **Annex C (normative): TETRA Test Connector Interface (TTCI) .....119**

|           |                                                         |     |
|-----------|---------------------------------------------------------|-----|
| C.1       | General .....                                           | 119 |
| C.2       | Formal aspects .....                                    | 119 |
| C.3       | TTCI, layer 1 .....                                     | 119 |
| C.3.1     | Mechanical and electrical characteristics .....         | 119 |
| C.3.2     | Transmission and reception characteristics .....        | 120 |
| C.4       | TTCI, Layer 2 .....                                     | 120 |
| C.4.1     | General structure .....                                 | 120 |
| C.4.2     | Frame structure .....                                   | 120 |
| C.4.3     | Flow of I-frames on layer 2 .....                       | 121 |
| C.4.3.1   | Transmission of frames .....                            | 121 |
| C.4.3.2   | Reception of frames .....                               | 121 |
| C.4.3.3   | Parameters on layer 2 .....                             | 122 |
| C.5       | TTCI, Layer 3 .....                                     | 122 |
| C.5.1     | Message structure .....                                 | 122 |
| C.5.2     | Definitions of the messages .....                       | 122 |
| C.5.2.1   | DATO .....                                              | 122 |
| C.5.2.1.1 | Test equipment error handling .....                     | 124 |
| C.5.2.2   | Bi-directional operation of the TTCI .....              | 124 |
| C.5.2.3   | Codec conformance testing .....                         | 125 |
| C.5.2.4   | ST indicator .....                                      | 125 |
| C.6       | Control of MS/BS .....                                  | 126 |
| C.6.1     | Manual intervention of MS/BS .....                      | 126 |
| C.6.2     | Bi-directional operation of the test interface .....    | 126 |
| C.6.3     | MS controlled by T1 .....                               | 126 |
| C.7       | Characteristics of the interface .....                  | 126 |
| C.7.1     | Mechanical characteristics of the interface .....       | 126 |
| C.7.2     | Electric characteristics of the interface .....         | 126 |
| C.8       | Codec conformance testing using the TTCI .....          | 127 |
| C.8.1     | Codec conformance test methodology using the TTCI ..... | 127 |

## **Annex D (normative): RF test facility using RF loop back .....128**

|       |                                                                          |     |
|-------|--------------------------------------------------------------------------|-----|
| D.1   | Introduction to the TETRA Test (TT) protocol for RF loop back test ..... | 129 |
| D.1.1 | Outline requirements .....                                               | 129 |
| D.1.2 | Test modes .....                                                         | 130 |
| D.1.3 | Switching for loop back test mode .....                                  | 131 |
| D.2   | TETRA test entity .....                                                  | 131 |
| D.3   | TETRA RF loop back test protocol .....                                   | 132 |
| D.3.1 | Setting the TETRA MS into TETRA test mode .....                          | 132 |
| D.3.2 | TETRA test protocol .....                                                | 133 |