

ETSI EN 300 396-2 V1.4.1 (2011-12)



Terrestrial Trunked Radio (TETRA); Technical requirements for Direct Mode Operation (DMO); Part 2: Radio aspects

Document Preview

[ETSI EN 300 396-2 V1.4.1 \(2011-12\)](https://standards.iteh.ai/catalog/standards/etsi/a97726d5-675d-4531-b1a8-8f9cff994fa4/etsi-en-300-396-2-v1-4-1-2011-12)

<https://standards.iteh.ai/catalog/standards/etsi/a97726d5-675d-4531-b1a8-8f9cff994fa4/etsi-en-300-396-2-v1-4-1-2011-12>

Reference

REN/TETRA-08192

Keywords

TETRA, DMO, radio, repeater, gateway, air interface

ETSI650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iteh Standards
(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2011.
All rights reserved.

DECTTM, PLUGTESTSTM, UMTSTM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPPTM and LTETM are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	7
Foreword.....	7
1 Scope	8
2 References	8
2.1 Normative references	8
2.2 Informative references.....	9
3 Definitions, symbols and abbreviations	9
3.1 Definitions.....	9
3.2 Symbols.....	11
3.3 Abbreviations	11
4 Radio aspects.....	12
4.1 Introduction	12
4.2 Set of logical channels.....	12
4.3 Reference configuration	12
4.4 Error control schemes.....	13
4.5 Timeslot structure.....	13
4.5.1 Framing structure	13
4.5.2 Timeslots and bursts	14
4.5.3 Mapping of logical channels onto physical channels.....	14
4.6 Coding, interleaving and scrambling.....	14
4.7 Modulation	14
4.8 Transmission and reception.....	14
4.9 Other radio-related functions.....	14
4.10 Performance	14
5 Modulation	15
5.1 Introduction	15
5.2 Modulation type	15
5.3 Modulation rate	15
5.4 Modulation symbol definition	15
5.5 Modulated signal definition.....	16
5.6 Modulation filter definition	16
5.7 Modulation block diagram	17
6 Radio transmission and reception.....	17
6.1 Introduction	17
6.2 Frequency bands and channel arrangement.....	17
6.3 Reference test planes	17
6.4 Transmitter characteristics.....	18
6.4.1 Output power	18
6.4.2 Power classes	18
6.4.3 Unwanted conducted emissions.....	18
6.4.3.1 Definitions.....	18
6.4.3.2 Unwanted emissions close to the carrier	19
6.4.3.2.1 Emissions during the useful part of the burst	19
6.4.3.2.2 Emissions during the switching transients.....	19
6.4.3.3 Unwanted emissions far from the carrier	20
6.4.3.3.1 Discrete spurious	20
6.4.3.3.2 Wideband noise	20
6.4.3.4 Unwanted emissions during the Linearization Channel (LCH)	21
6.4.3.5 Unwanted emissions in the non-transmit state	21
6.4.4 Unwanted radiated emissions	21
6.4.5 Radio frequency tolerance	21
6.4.6 RF output power time mask.....	21
6.4.7 Transmitter intermodulation attenuation.....	23

6.4.7.1	Definition	23
6.4.7.2	Specification.....	23
6.4.7.3	Intra-gateway transmitter intermodulation attenuation	23
6.5	Receiver characteristics	23
6.5.1	Blocking characteristics	23
6.5.1.1	Definition	23
6.5.1.2	Specification.....	23
6.5.2	Spurious response rejection	24
6.5.2.1	Definition	24
6.5.2.2	Specification.....	24
6.5.3	Intermodulation response rejection.....	24
6.5.3.1	Definition	24
6.5.3.2	Specification.....	24
6.5.4	Unwanted conducted emissions	25
6.5.4.1	Definition	25
6.5.4.2	Specification.....	25
6.5.5	Unwanted radiated emissions	25
6.6	Transmitter/receiver performance	25
6.6.1	Modulation accuracy.....	25
6.6.1.1	Ideal case.....	25
6.6.1.2	Vector error magnitude requirement at symbol time	26
6.6.2	Receiver performance	26
6.6.2.1	Nominal error rates	26
6.6.2.2	Dynamic reference sensitivity.....	27
6.6.2.3	Receiver performance at reference interference ratios	27
6.6.2.4	Static reference sensitivity	28
6.6.2.5	Receiver performance for acquisition of synchronization burst.....	28
6.6.3	Propagation conditions	29
6.6.3.1	Tap-gain process types	29
6.6.3.2	DM propagation models.....	29
7	Radio sub-system synchronization.....	30
7.1	Introduction	30
7.2	Definitions and general requirements for synchronization of DM device.....	30
7.2.1	Synchronisation of DM-MS to DM-MS communication	30
7.2.2	Synchronisation of DM-MS communication through a type 1 DM-REP	31
7.2.3	Synchronisation of DM-MS communication using a DM-GATE	32
7.2.4	Definitions and general requirements for synchronization of DM-REPs	32
7.2.5	Definitions and general requirements for synchronization of DM-GATEs	33
7.3	Timebase counters.....	33
7.3.1	Definition of counters	33
7.3.2	Relationship between the counters.....	33
7.4	Requirements for the frequency reference source of DM devices.....	34
7.5	Requirements for the synchronization of a slave or idle DM-MS	34
7.6	Synchronization requirements for a master DM-MS operating on channel B in frequency efficient mode.....	34
7.7	Requirements for the synchronization of a type 1 DM-REP	35
7.8	Requirements for the synchronization of a DM-GATE.....	35
8	Channel coding and scrambling	35
8.1	Introduction	35
8.2	General	36
8.2.1	Interfaces in the error control structure.....	36
8.2.2	Notation	37
8.2.3	Definition of error control codes.....	37
8.2.3.1	16-state Rate-Compatible Punctured Convolutional (RCPC) codes	37
8.2.3.1.1	Encoding by the 16-state mother code of rate 1/4	38
8.2.3.1.2	Puncturing of the mother code.....	38
8.2.3.1.3	Puncturing scheme of the RCPC code of rate 2/3.....	38
8.2.3.1.4	Puncturing scheme of the RCPC code of rate 292/432.....	38
8.2.3.1.5	Puncturing scheme of the RCPC code of rate 148/432.....	39
8.2.3.2	($K_1 + 16$, K_1) block code	39
8.2.4	Definition of interleaving schemes	39

8.2.4.1	Block interleaving	39
8.2.4.2	Interleaving over N blocks	39
8.2.5	Definition of scrambling	40
8.2.5.1	Scrambling method	40
8.2.5.2	Scrambling sequence	40
8.3	Error control schemes	40
8.3.1	Signalling channels	41
8.3.1.1	Synchronization Signalling Channel (SCH/S)	41
8.3.1.2	Half-slot Signalling Channel (SCH/H) and Stealing Channel (STCH)	42
8.3.1.3	Full-slot Signalling Channel (SCH/F)	42
8.3.2	Traffic channels in circuit switched mode	43
8.3.2.1	Traffic channel, net rate = 7,2 kbit/s (TCH/7,2)	43
8.3.2.2	Traffic channel, net rate = 4,8 kbit/s (TCH/4,8)	44
8.3.2.3	Traffic channel, net rate = 2,4 kbit/s (TCH/2,4)	45
8.3.2.4	Speech Traffic Channel, full slot (TCH/S)	45
8.3.2.5	Speech Traffic Channel, half slot (TCH/S)	46
9	Channel multiplexing for DM	46
9.1	Introduction	46
9.2	Logical channels	46
9.2.1	Logical channels hierarchy	46
9.2.2	Traffic channels	46
9.2.3	Control channels	47
9.2.3.1	General	47
9.2.3.2	Linearization Channel (LCH)	47
9.2.3.3	Signalling Channel (SCH)	47
9.2.3.4	Stealing Channel (STCH)	47
9.3	The physical resource	47
9.3.1	General	47
9.3.2	Timeslots	48
9.3.3	DM frame	48
9.3.4	Multiframe	48
9.4	Physical channels	48
9.4.1	General	48
9.4.2	Bursts	49
9.4.2.1	General	49
9.4.2.2	Modulation symbol numbering	49
9.4.2.3	Modulation bit numbering	49
9.4.2.4	Burst timing	49
9.4.3	Type of bursts	49
9.4.3.1	General	49
9.4.3.2	Modulation bits allocation	50
9.4.3.2.1	DM Normal Burst (DNB)	50
9.4.3.2.2	DM Linearization Burst (DLB)	51
9.4.3.2.3	DM Synchronization Burst (DSB)	51
9.4.3.3	Burst fields	51
9.4.3.3.1	Frequency correction field	51
9.4.3.3.2	Inter-slot frequency correction field	51
9.4.3.3.3	Normal training sequence and preamble	52
9.4.3.3.4	Synchronization training sequence	52
9.4.3.3.5	Phase adjustment bits	52
9.4.3.3.6	Tail bits	53
9.4.4	DM device multiple slot transmission	53
9.4.5	General mapping of logical channels	53
10	Radio subsystem link control	54
10.1	Introduction	54
10.2	RF power control	54
10.3	Radio link measurements	54
10.3.1	Signal strength	54
10.3.2	Signal quality	54
Annex A (informative):	Bibliography	55

Annex B (informative):	Change requests	56
History		57

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI EN 300 396-2 V1.4.1 \(2011-12\)](https://standards.iteh.ai/catalog/standards/etsi/a97726d5-675d-4531-b1a8-8f9cff994fa4/etsi-en-300-396-2-v1-4-1-2011-12)

<https://standards.iteh.ai/catalog/standards/etsi/a97726d5-675d-4531-b1a8-8f9cff994fa4/etsi-en-300-396-2-v1-4-1-2011-12>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (EN) has been produced by ETSI Technical Committee Terrestrial Trunked Radio (TETRA).

The present document is part 2 of a multi-part deliverable covering the Technical requirements for Direct Mode Operation (DMO), as identified below:

Part 1: "General network design";

Part 2: "Radio aspects";

Part 3: "Mobile Station to Mobile Station (MS-MS) Air Interface (AI) protocol";

Part 4: "Type 1 repeater air interface";

Part 5: "Gateway air interface";

Part 6: "Security";

Part 7: "Type 2 repeater air interface"; (Historical)

Part 8: "Protocol Implementation Conformance Statement (PICS) proforma specification"; (Historical)

Part 10: "Managed Direct Mode Operation (M-DMO)". (Historical)

NOTE: Part 7, part 8 and part 10 of this multi-part deliverable are of status "historical" and will not be updated according to this version of the standard.

National transposition dates

Date of adoption of this EN:	22 December 2011
Date of latest announcement of this EN (doa):	31 March 2012
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 September 2012
Date of withdrawal of any conflicting National Standard (dow):	30 September 2012