



**Terrestrial Trunked Radio (TETRA);
Technical requirements for Direct Mode Operation (DMO);
Part 2: Radio aspects**

(<http://standards.iteh.ai>)
Document Preview

ETSI EN 300 396-2 V1.4.1 (2011-12)

<https://standards.iteh.ai/catalog/standards/etsi/a97726d5-675d-4531-b1a8-8f9cff994fa4/etsi-en-300-396-2-v1-4-1-2011-12>

Reference

REN/TETRA-08192

Keywords

TETRA, DMO, radio, repeater, gateway, air interface

ETSI650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iteh Standards
(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2011.
All rights reserved.

DECTTM, PLUGTESTSTM, UMTSTM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPPTM and LTETM are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	7
Foreword.....	7
1 Scope	8
2 References	8
2.1 Normative references	8
2.2 Informative references.....	9
3 Definitions, symbols and abbreviations	9
3.1 Definitions.....	9
3.2 Symbols.....	11
3.3 Abbreviations	11
4 Radio aspects.....	12
4.1 Introduction	12
4.2 Set of logical channels.....	12
4.3 Reference configuration	12
4.4 Error control schemes.....	13
4.5 Timeslot structure.....	13
4.5.1 Framing structure	13
4.5.2 Timeslots and bursts	14
4.5.3 Mapping of logical channels onto physical channels.....	14
4.6 Coding, interleaving and scrambling.....	14
4.7 Modulation	14
4.8 Transmission and reception.....	14
4.9 Other radio-related functions.....	14
4.10 Performance	14
5 Modulation	15
5.1 Introduction	15
5.2 Modulation type	15
5.3 Modulation rate	15
5.4 Modulation symbol definition	15
5.5 Modulated signal definition.....	16
5.6 Modulation filter definition	16
5.7 Modulation block diagram	17
6 Radio transmission and reception.....	17
6.1 Introduction	17
6.2 Frequency bands and channel arrangement.....	17
6.3 Reference test planes	17
6.4 Transmitter characteristics.....	18
6.4.1 Output power	18
6.4.2 Power classes	18
6.4.3 Unwanted conducted emissions.....	18
6.4.3.1 Definitions.....	18
6.4.3.2 Unwanted emissions close to the carrier	19
6.4.3.2.1 Emissions during the useful part of the burst	19
6.4.3.2.2 Emissions during the switching transients.....	20
6.4.3.3 Unwanted emissions far from the carrier	20
6.4.3.3.1 Discrete spurious	20
6.4.3.3.2 Wideband noise	20
6.4.3.4 Unwanted emissions during the Linearization Channel (LCH)	21
6.4.3.5 Unwanted emissions in the non-transmit state	21
6.4.4 Unwanted radiated emissions	21
6.4.5 Radio frequency tolerance	21
6.4.6 RF output power time mask.....	22
6.4.7 Transmitter intermodulation attenuation.....	23

6.4.7.1	Definition	23
6.4.7.2	Specification.....	23
6.4.7.3	Intra-gateway transmitter intermodulation attenuation	23
6.5	Receiver characteristics	23
6.5.1	Blocking characteristics	23
6.5.1.1	Definition	23
6.5.1.2	Specification.....	24
6.5.2	Spurious response rejection	24
6.5.2.1	Definition	24
6.5.2.2	Specification.....	24
6.5.3	Intermodulation response rejection.....	25
6.5.3.1	Definition	25
6.5.3.2	Specification.....	25
6.5.4	Unwanted conducted emissions	25
6.5.4.1	Definition	25
6.5.4.2	Specification.....	25
6.5.5	Unwanted radiated emissions	25
6.6	Transmitter/receiver performance	25
6.6.1	Modulation accuracy.....	25
6.6.1.1	Ideal case.....	26
6.6.1.2	Vector error magnitude requirement at symbol time	26
6.6.2	Receiver performance	27
6.6.2.1	Nominal error rates	27
6.6.2.2	Dynamic reference sensitivity.....	27
6.6.2.3	Receiver performance at reference interference ratios	28
6.6.2.4	Static reference sensitivity	28
6.6.2.5	Receiver performance for acquisition of synchronization burst.....	29
6.6.3	Propagation conditions	29
6.6.3.1	Tap-gain process types	29
6.6.3.2	DM propagation models.....	30
7	Radio sub-system synchronization.....	30
7.1	Introduction	30
7.2	Definitions and general requirements for synchronization of DM device.....	30
7.2.1	Synchronisation of DM-MS to DM-MS communication	30
7.2.2	Synchronisation of DM-MS communication through a type 1 DM-REP	31
7.2.3	Synchronisation of DM-MS communication using a DM-GATE	32
7.2.4	Definitions and general requirements for synchronization of DM-REPs	33
7.2.5	Definitions and general requirements for synchronization of DM-GATEs	33
7.3	Timebase counters.....	33
7.3.1	Definition of counters	33
7.3.2	Relationship between the counters.....	34
7.4	Requirements for the frequency reference source of DM devices.....	34
7.5	Requirements for the synchronization of a slave or idle DM-MS	34
7.6	Synchronization requirements for a master DM-MS operating on channel B in frequency efficient mode.....	35
7.7	Requirements for the synchronization of a type 1 DM-REP	35
7.8	Requirements for the synchronization of a DM-GATE.....	36
8	Channel coding and scrambling	36
8.1	Introduction	36
8.2	General	37
8.2.1	Interfaces in the error control structure.....	37
8.2.2	Notation	38
8.2.3	Definition of error control codes.....	38
8.2.3.1	16-state Rate-Compatible Punctured Convolutional (RCPC) codes	38
8.2.3.1.1	Encoding by the 16-state mother code of rate 1/4	39
8.2.3.1.2	Puncturing of the mother code.....	39
8.2.3.1.3	Puncturing scheme of the RCPC code of rate 2/3.....	39
8.2.3.1.4	Puncturing scheme of the RCPC code of rate 292/432.....	39
8.2.3.1.5	Puncturing scheme of the RCPC code of rate 148/432.....	40
8.2.3.2	($K_1 + 16$, K_1) block code	40
8.2.4	Definition of interleaving schemes	40

8.2.4.1	Block interleaving	40
8.2.4.2	Interleaving over N blocks	40
8.2.5	Definition of scrambling	41
8.2.5.1	Scrambling method	41
8.2.5.2	Scrambling sequence	41
8.3	Error control schemes	41
8.3.1	Signalling channels	42
8.3.1.1	Synchronization Signalling Channel (SCH/S)	42
8.3.1.2	Half-slot Signalling Channel (SCH/H) and Stealing Channel (STCH)	43
8.3.1.3	Full-slot Signalling Channel (SCH/F)	43
8.3.2	Traffic channels in circuit switched mode	44
8.3.2.1	Traffic channel, net rate = 7,2 kbit/s (TCH/7,2)	44
8.3.2.2	Traffic channel, net rate = 4,8 kbit/s (TCH/4,8)	45
8.3.2.3	Traffic channel, net rate = 2,4 kbit/s (TCH/2,4)	46
8.3.2.4	Speech Traffic Channel, full slot (TCH/S)	46
8.3.2.5	Speech Traffic Channel, half slot (TCH/S)	47
9	Channel multiplexing for DM	47
9.1	Introduction	47
9.2	Logical channels	47
9.2.1	Logical channels hierarchy	47
9.2.2	Traffic channels	47
9.2.3	Control channels	48
9.2.3.1	General	48
9.2.3.2	Linearization Channel (LCH)	48
9.2.3.3	Signalling Channel (SCH)	48
9.2.3.4	Stealing Channel (STCH)	48
9.3	The physical resource	48
9.3.1	General	48
9.3.2	Timeslots	49
9.3.3	DM frame	49
9.3.4	Multiframe	49
9.4	Physical channels	49
9.4.1	General	49
9.4.2	Bursts	50
9.4.2.1	General	50
9.4.2.2	Modulation symbol numbering	50
9.4.2.3	Modulation bit numbering	50
9.4.2.4	Burst timing	50
9.4.3	Type of bursts	50
9.4.3.1	General	50
9.4.3.2	Modulation bits allocation	51
9.4.3.2.1	DM Normal Burst (DNB)	51
9.4.3.2.2	DM Linearization Burst (DLB)	52
9.4.3.2.3	DM Synchronization Burst (DSB)	52
9.4.3.3	Burst fields	52
9.4.3.3.1	Frequency correction field	52
9.4.3.3.2	Inter-slot frequency correction field	52
9.4.3.3.3	Normal training sequence and preamble	53
9.4.3.3.4	Synchronization training sequence	53
9.4.3.3.5	Phase adjustment bits	53
9.4.3.3.6	Tail bits	54
9.4.4	DM device multiple slot transmission	54
9.4.5	General mapping of logical channels	54
10	Radio subsystem link control	55
10.1	Introduction	55
10.2	RF power control	55
10.3	Radio link measurements	55
10.3.1	Signal strength	55
10.3.2	Signal quality	55

Annex A (informative):	Bibliography	56
-------------------------------	---------------------------	-----------

Annex B (informative):	Change requests	57
History		58

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI EN 300 396-2 V1.4.1 \(2011-12\)](https://standards.iteh.ai/catalog/standards/etsi/a97726d5-675d-4531-b1a8-8f9cff994fa4/etsi-en-300-396-2-v1-4-1-2011-12)

<https://standards.iteh.ai/catalog/standards/etsi/a97726d5-675d-4531-b1a8-8f9cff994fa4/etsi-en-300-396-2-v1-4-1-2011-12>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This final draft European Standard (EN) has been produced by ETSI Technical Committee Terrestrial Trunked Radio (TETRA), and is now submitted for the ETSI standards One-step Approval Procedure.

The present document is part 2 of a multi-part deliverable covering the Technical requirements for Direct Mode Operation (DMO), as identified below:

Part 1: "General network design";

Part 2: "Radio aspects";

Part 3: "Mobile Station to Mobile Station (MS-MS) Air Interface (AI) protocol";

Part 4: "Type 1 repeater air interface";

Part 5: "Gateway air interface";

Part 6: "Security";

Part 7: "Type 2 repeater air interface"; (Historical)

Part 8: "Protocol Implementation Conformance Statement (PICS) proforma specification"; (Historical)

Part 10: "Managed Direct Mode Operation (M-DMO)". (Historical)

NOTE: Part 7, part 8 and part 10 of this multi-part deliverable are of status "historical" and will not be updated according to this version of the standard.

Proposed national transposition dates

Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa