



**Terrestrial Trunked Radio (TETRA);
Technical requirements for Direct Mode Operation (DMO);
Part 3: Mobile Station to Mobile Station (MS-MS)
Air Interface (AI) protocol**

[ETSI EN 300 396-3 V1.4.1 \(2011-12\)](https://standards.iteh.ai/catalog/standards/etsi/d3c9a94d-34f1-4ea3-89cc-6e5aae05319a/etsi-en-300-396-3-v1-4-1-2011-12)

<https://standards.iteh.ai/catalog/standards/etsi/d3c9a94d-34f1-4ea3-89cc-6e5aae05319a/etsi-en-300-396-3-v1-4-1-2011-12>

ReferenceREN/TETRA-08193

Keywordsair interface, protocol, radio, TETRA

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iteh Standards
(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2011.
All rights reserved.

DECTTM, PLUGTESTSTM, UMTSTM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPPTM and LTETM are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	11
Foreword.....	11
1 Scope	12
2 References	12
2.1 Normative references	12
2.2 Informative references.....	13
3 Definitions and abbreviations.....	13
3.1 Definitions.....	13
3.2 Abbreviations	16
4 Overview of protocol.....	17
4.1 General	17
4.2 The DM channel.....	18
4.3 DM call procedures	18
4.3.1 Constraints on the frame structure	19
4.3.2 Setting up a call	19
4.3.2.1 Call set-up without presence check	20
4.3.2.1.1 Basic procedure	20
4.3.2.1.2 Procedure in frequency efficient mode.....	20
4.3.2.2 Call set-up with presence check.....	21
4.3.3 Changeover in a call	21
4.3.4 Pre-emption of a DM call	23
4.3.5 Terminating a call.....	23
4.3.6 DM short data call	23
4.3.6.1 Unacknowledged short data message.....	24
4.3.6.2 Acknowledged short data message	24
4.4 DM protocol layering.....	25
5 Layer 3 service description.....	25
5.1 Introduction	25
5.2 Services offered.....	26
5.3 Primitive description	26
5.3.1 DMCC-COMPLETE primitive.....	27
5.3.2 DMCC-RELEASE primitive	27
5.3.3 DMCC-REPORT primitive	27
5.3.4 DMCC-SDS DATA primitive	27
5.3.5 DMCC-SDS REPORT primitive	28
5.3.6 DMCC-SDS UNITDATA primitive.....	28
5.3.7 DMCC-SETUP primitive	29
5.3.8 DMCC-TPNI primitive.....	30
5.3.9 DMCC-TX CEASED primitive.....	30
5.4 Parameter description	30
5.5 States for DMCC-SAP	35
6 Layer 3 protocol	36
6.1 Introduction	36
6.1.1 DMCC protocol states	36
6.1.1.1 IDLE	36
6.1.1.2 CALL SETUP NORMAL ORIGINATING.....	36
6.1.1.3 CALL SETUP NORMAL TERMINATING	36
6.1.1.4 CALL SETUP PRES_CHECK ORIGINATING.....	36
6.1.1.5 CALL SETUP PRES_CHECK TERMINATING.....	36
6.1.1.6 PRE-EMPTION	36
6.1.1.7 CALL ACTIVE TX OCCUPATION.....	36
6.1.1.8 CALL ACTIVE TX RESERVATION.....	37
6.1.1.9 CALL ACTIVE RX OCCUPATION.....	37

6.1.1.10	CALL ACTIVE RX RESERVATION.....	37
6.1.1.11	WAIT RSP OCCUPATION	37
6.1.1.12	WAIT RSP RESERVATION.....	37
6.1.1.13	ACK'D SHORT DATA INITIATED.....	37
6.1.1.14	UNACK'D SHORT DATA INITIATED.....	37
6.2	Circuit mode calls.....	37
6.2.1	Procedures for call set-up without presence check	38
6.2.1.1	Outgoing call.....	38
6.2.1.2	Incoming call.....	40
6.2.1.3	Temporary group address.....	41
6.2.2	Procedures for call set-up with presence check	41
6.2.2.1	Outgoing call.....	41
6.2.2.2	Incoming call.....	43
6.2.3	Usage of DM-OCCUPIED PDU	44
6.2.3.1	Sending of DM-OCCUPIED PDU by master DM-MS.....	44
6.2.3.2	Late entry by slave DM-MS.....	44
6.2.4	Procedures during occupation.....	44
6.2.4.1	Master DM-MS	44
6.2.4.2	Slave DM-MS	45
6.2.4.3	Transmitting Party Number Identification (TPNI).....	47
6.2.5	Procedures during reservation.....	47
6.2.5.1	Master DM-MS	47
6.2.5.2	Slave DM-MS	49
6.2.5.3	Pre-emption of short data sent as a transaction within a circuit mode call.....	51
6.2.6	Procedures to set up a new call by pre-emption.....	51
6.3	Short Data Service (SDS) procedures	52
6.3.1	Sending short data.....	53
6.3.1.1	Sending short data on a free channel	53
6.3.1.1.1	Sending unacknowledged short data on a free channel	53
6.3.1.1.2	Sending acknowledged short data on a free channel	55
6.3.1.2	Sending short data by pre-emption.....	57
6.3.1.3	Sending short data during circuit mode transmission.....	58
6.3.1.4	Sending short data as a transaction within a circuit mode call.....	59
6.3.1.4.1	Pre-emption to send short data as a transaction within a circuit mode call	59
6.3.1.4.2	Changeover to send short data as a transaction within a circuit mode call.....	60
6.3.1.4.3	Sending the short data as master of the circuit mode call	60
6.3.2	Receiving short data.....	60
6.3.2.1	Receiving unacknowledged short data	60
6.3.2.2	Receiving acknowledged short data	61
6.3.3	Additional addressing	61
6.3.4	Extended error protection	61
6.3.5	SDS-TL service in DMO	62
6.3.5.1	Service primitives at the DMTL-SDS-SAP	62
6.3.5.2	DMTL-SDS primitives' parameters	65
6.3.5.3	DMTL-SDS PDUs	67
6.3.5.4	DMTL-SDS procedures	67
6.4	Usage of DMA-UNITDATA primitive	70
7	Layer 2 service description.....	71
7.1	Introduction	71
7.2	Layer 2 architecture.....	72
7.2.1	Lower layer management in layer 2.....	73
7.3	Service descriptions.....	73
7.3.1	Services at the DMA-SAP	73
7.3.1.1	Services provided to layer 3.....	73
7.3.1.2	Service primitives at the DMA-SAP	74
7.3.1.2.1	DMA-REPORT primitive.....	74
7.3.1.2.2	DMA-UNITDATA primitive	74
7.3.2	Services at the DMC-SAP	75
7.3.2.1	Services provided to layer 3.....	75
7.3.2.2	Service primitives at the DMC-SAP	75
7.3.2.2.1	DMC-CONFIGURE primitive	76

7.3.2.2.2	DMC-REPORT primitive.....	76
7.3.3	Services at the DMD-SAP	76
7.3.3.1	Services provided to the U-plane application.....	76
7.3.3.2	Service primitives at the DMD-SAP	76
7.3.3.2.1	DMD-REPORT primitive.....	77
7.3.3.2.2	DMD-UNITDATA primitive	77
7.4	Parameter listing.....	77
7.4.1	Air interface encryption information	77
7.4.2	Air interface encryption state.....	77
7.4.2A	Called party in ongoing call.....	78
7.4.3	Call release.....	78
7.4.4	Call set-up after pre-emption or changeover.....	78
7.4.5	Changeover request held during occupation.....	78
7.4.5A	Channel selection information	78
7.4.6	Circuit mode information.....	78
7.4.7	Circuit mode type	78
7.4.8	Communication type.....	78
7.4.9	Destination address	78
7.4.10	Destination address type	79
7.4.10A	DM channel	79
7.4.11	DM-SDU	79
7.4.12	DM-SDU length.....	79
7.4.12A	Dual watch information	79
7.4.13	FCS flag.....	79
7.4.14	Half slot condition	79
7.4.15	Half slot content.....	79
7.4.16	Half slot importance.....	79
7.4.17	Half slot position.....	79
7.4.18	Half slot synchronization	80
7.4.19	Handle to the request	80
7.4.20	Immediate retransmission.....	80
7.4.21	Incomplete DM-SDS DATA/ACK received	80
7.4.21A	Lower layer quality information	80
7.4.21B	Master of ongoing call	80
7.4.22	Message type	80
7.4.23	New call pre-emption.....	80
7.4.24	Number of repeats.....	81
7.4.25	Priority	81
7.4.26	Priority of ongoing call	81
7.4.27	Recent user changeover request.....	81
7.4.28	Recent user priority.....	81
7.4.29	Report	81
7.4.30	Reservation time	81
7.4.31	SDS transaction type.....	81
7.4.32	Source address	81
7.4.33	Source address type	81
7.4.34	Stealing priority	82
7.4.35	Stolen indication.....	82
7.4.36	Type of pre-emption	82
7.4.37	Valid addresses	82
8	Layer 2 protocol	82
8.1	Introduction	82
8.1.1	Functions of lower MAC	82
8.1.2	Functions of upper MAC	83
8.2	Interface between lower and upper MAC.....	83
8.2.1	Logical channels defined at the DMV-SAP.....	83
8.2.2	Service primitives at the DMV-SAP.....	84
8.2.3	PDU mapping of the logical channels at the DMV-SAP	85
8.2.4	Scrambling mechanism.....	85
8.2.5	PDU error detection.....	86
8.2.6	Modes of operation	86

8.2.6.1	DM-MS modes of operation	86
8.2.6.1.1	Idle mode.....	86
8.2.6.1.2	Signalling mode.....	87
8.2.6.1.3	Traffic mode.....	87
8.2.6.2	Operation in traffic mode.....	88
8.2.6.2.1	Traffic transmission.....	88
8.2.6.2.2	Stealing mechanism.....	89
8.2.6.3	Selection of the mode of operation	89
8.3	Basic capabilities of the Physical Layer (PL).....	90
8.3.1	DM-MS capabilities.....	90
8.3.1.1	DM only and dual mode capable MS operation.....	90
8.3.1.2	Dual watch capable MS operation	91
8.3.1.2.1	Full Dual Watch Mobile Station (F-DW-MS).....	91
8.3.1.2.2	Idle Dual Watch Mobile Station (I-DW-MS)	91
8.4	Usage of DM channel.....	91
8.4.1	Definition of DM channel.....	91
8.4.1.1	DM channel arrangement.....	91
8.4.1.2	DM channel A operation.....	91
8.4.1.3	DM channel B operation	92
8.4.2	DM-MAC states.....	93
8.4.2.1	DM-MAC state definitions	93
8.4.2.2	DM-MS channel surveillance procedures	94
8.4.2.2.1	Initial determination of DM channel state	94
8.4.2.2.2	Fast call set-up surveillance in idle mode.....	96
8.4.2.2.3	DM-MS channel surveillance at call set-up.....	99
8.4.2.3	Master DM-MS channel maintenance procedures during a call	101
8.4.2.4	Slave DM-MS channel maintenance procedures during a call.....	101
8.4.2.4.1	Slave MS channel maintenance during call transaction	102
8.4.2.4.2	Slave MS signal quality measurement during call transaction	102
8.4.2.4.3	Slave MS channel maintenance during reservation	102
8.4.2.5	Additional master MS procedures in frequency efficient mode.....	102
8.4.2.5.1	Channel A master MS procedures	103
8.4.2.5.2	Channel B master MS procedures	103
8.4.3	Criteria for changing DM-MAC state.....	103
8.4.3.1	Criteria for changing DM-MAC state for master DM-MS.....	103
8.4.3.2	Criteria for changing DM-MAC state for slave DM-MS.....	104
8.4.3.3	Criteria for changing DM-MAC state for idle DM-MS	105
8.4.4	DM-MS channel monitoring procedures	107
8.4.4.1	DM channel during call set-up with presence check.....	108
8.4.4.2	DM channel in occupation during a circuit mode call.....	108
8.4.4.3	DM channel in reservation during a circuit mode call	108
8.4.4.4	DM channel in occupation during an SDS call	108
8.4.4.5	DM channel usage during pre-emption signalling	109
8.4.4.6	DM channel usage during timing change request signalling.....	109
8.4.5	Transmission of layer 3 messages by DM-MAC.....	109
8.4.5.1	Transmission of C-plane messages by DM-MAC.....	109
8.4.5.1.1	Transmitting DM-SETUP.....	109
8.4.5.1.2	Transmitting DM-SETUP PRES	110
8.4.5.1.3	Transmitting DM-CONNECT	111
8.4.5.1.4	Transmitting DM-DISCONNECT.....	111
8.4.5.1.5	Transmitting DM-CONNECT ACK.....	111
8.4.5.1.6	Transmitting DM-RELEASE	111
8.4.5.1.7	Transmitting DM-OCCUPIED.....	112
8.4.5.1.8	Transmitting DM-TX CEASED.....	112
8.4.5.1.9	Transmitting DM-TX REQUEST.....	113
8.4.5.1.10	Transmitting response to DM-TX REQUEST.....	113
8.4.5.1.11	Transmitting DM-PREEMPT	114
8.4.5.1.12	Transmitting response to DM-PREEMPT	114
8.4.5.1.13	Transmitting DM-SDS UDATA and DM-SDS DATA.....	115
8.4.5.1.14	Transmitting response to DM-SDS DATA	116
8.4.5.1.15	Transmitting DM-INFO	116
8.4.5.2	Transmission of U-plane messages by DM-MAC	116

8.4.6	Transmission of layer 2 messages generated by DM-MAC	116
8.4.6.1	Transmitting DM-RESERVED.....	117
8.4.6.2	Transmitting DM-SDS OCCUPIED	117
8.4.6.3	Transmitting DM-TIMING REQUEST	118
8.4.6.4	Transmitting DM-TIMING ACK.....	118
8.4.7	General DM-MAC procedures	118
8.4.7.1	DM-MAC repeat transmissions	118
8.4.7.2	DM-MAC frame countdown procedure	118
8.4.7.3	Use of timers	119
8.4.7.4	Linearization	119
8.4.7.5	Fragmentation	119
8.4.7.6	Fill bit indication	119
8.4.7.7	Selection of pseudo address	119
8.4.7.8	Slot flag indication	120
8.4.7.9	Requests bitmap	120
8.4.7.10	DM aspects of dual watch operation	120
8.4.7.10.1	Full and idle dual watch operation.....	120
8.4.7.10.2	DM aspects of full dual watch operation	120
8.4.7.10.3	DM aspects of idle dual watch operation	124
8.4.7.11	Air interface encryption	126
8.4.7.12	Channel A or B operation	126
8.4.7.13	Sending short data as a transaction within a circuit mode call	126
8.4.7.14	SDS time remaining	127
8.4.7.15	Timing change procedure.....	127
8.4.7.16	Timing change at changeover or pre-emption.....	129
8.5	MAC procedures for transfer of signalling messages.....	129
8.5.1	Formation of MAC PDU	129
8.5.2	Addressing	130
8.5.2.1	Transmission of message	130
8.5.2.1.1	Addressing in synchronization burst	130
8.5.2.1.2	Addressing in normal burst.....	132
8.5.2.2	Reception of message.....	132
8.5.3	Use of air interface encryption.....	133
8.5.4	Fragmentation and reconstruction.....	134
8.5.4.1	Fragmentation	134
8.5.4.2	Reconstruction	135
8.5.5	Fill bit addition and deletion	136
8.5.5.1	Fill bit addition.....	136
8.5.5.2	Fill bit deletion	137
8.5.5.3	Null PDU	137
8.5.6	Transmission and reception of messages by layer 2 unacknowledged service	137
8.5.6.1	Transmission of message	138
8.5.6.2	Reception of message.....	139
8.5.7	Random access protocol	141
8.5.7.1	Introduction	141
8.5.7.2	Procedures for master DM-MS	141
8.5.7.2.1	Indicating frames available for requests	141
8.5.7.2.2	Monitoring frames available for requests	141
8.5.7.2.3	Response to pre-emption or changeover request	142
8.5.7.2.4	Response to timing change request.....	143
8.5.7.3	Procedures for requesting DM-MS	144
8.5.7.3.1	Preparing for random access.....	144
8.5.7.3.2	First transmission of request.....	144
8.5.7.3.3	Valid access slots.....	145
8.5.7.3.4	Waiting for response.....	146
8.5.7.3.5	Subsequent transmission of request.....	146
8.5.7.3.6	Abandoning random access attempt	146
8.6	MAC procedures in traffic mode.....	148
8.6.1	Introduction.....	148
8.6.2	Criteria for transmission and reception of traffic	148
8.6.3	Change of U-plane mode	149
8.6.3.1	Call set-up without presence check.....	149