

ETSI EN 300 396-5 V1.3.1 (2011-12)



Terrestrial Trunked Radio (TETRA); Technical requirements for Direct Mode Operation (DMO); Part 5: Gateway air interface

Document Preview

[ETSI EN 300 396-5 V1.3.1 \(2011-12\)](https://standards.iteh.ai/catalog/standards/etsi/d27b6773-d9cb-4769-af34-199d45422575/etsi-en-300-396-5-v1-3-1-2011-12)

<https://standards.iteh.ai/catalog/standards/etsi/d27b6773-d9cb-4769-af34-199d45422575/etsi-en-300-396-5-v1-3-1-2011-12>

Reference

REN/TETRA-08195

Keywords

air interface, gateway, protocol, radio, TETRA

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2011.
All rights reserved.

DECTTM, PLUGTESTSTM, UMTSTM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPPTM and LTETM are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	15
Foreword.....	15
1 Scope	16
2 References	16
2.1 Normative references	16
2.2 Informative references.....	17
3 Definitions and abbreviations.....	17
3.1 Definitions.....	17
3.2 Abbreviations	21
4 Overview of protocol.....	22
4.1 General	22
4.2 The DM channel.....	24
4.3 DM call procedures for operation with a gateway.....	25
4.3.1 Constraints on the frame structure	26
4.3.2 Setting up a call through a DM-GATE	27
4.3.2.1 Group call from TMO to DM-MS via a DM-GATE.....	27
4.3.2.2 Group call from DM-MS via a DM-GATE.....	29
4.3.2.3 Individual call from TM-MS to DM-MS via a DM-GATE	31
4.3.2.4 Individual call from DM-MS to TM-MS via a DM-GATE	34
4.3.3 Changeover in a call via a DM-GATE.....	36
4.3.4 Pre-emption of a direct mode call through a DM-GATE.....	38
4.3.5 Short Data Service through a gateway.....	39
4.3.6 Group call from DM-MS via DM-REP/GATE.....	40
5 DM-MS layer 3 service description (for operation with a gateway).....	41
5.1 Introduction	41
5.2 Services offered at the DMCC-SAP	41
5.3 Description of primitives at the DMCC-SAP.....	41
5.4 Description of parameters at the DMCC-SAP.....	42
5.5 States for DMCC-SAP	43
5.6 Services offered at the DMMM-SAP	43
5.7 Description of primitives at the DMMM-SAP	43
5.7.1 DMMM-REGISTRATION primitive	44
5.7.2 DMMM-REPORT primitive.....	44
5.8 Description of parameters at the DMMM-SAP.....	44
6 DM-MS layer 3 protocol (for operation with a gateway).....	45
6.1 Introduction	45
6.1.1 DMCC protocol states	45
6.1.2 DMMM protocol states.....	45
6.1.2.1 NOT-REGISTERED.....	45
6.1.2.2 WAIT-REGISTRATION.....	46
6.1.2.3 REGISTRATION-ACCEPTED.....	46
6.1.2.4 REGISTRATION-REJECTED.....	46
6.2 Circuit mode calls.....	46
6.2.1 Procedures for outgoing call set-up through a gateway	47
6.2.1.1 Outgoing call set-up	47
6.2.1.2 Temporary group address.....	49
6.2.1.3 Layer 3 addressing in DM-GSETUP PDU.....	49
6.2.1.3.1 Called party address	49
6.2.1.3.2 Area selection.....	49
6.2.1.3.3 Calls to external subscribers	49
6.2.1.3.4 Calling party address	49
6.2.2 Procedures for incoming call set-up.....	49
6.2.2.1 Incoming call set-up without presence check.....	49

6.2.2.2	Incoming call set-up with presence check.....	50
6.2.2.3	Transmitting Party Number Identification (TPNI) during incoming call set-up	50
6.2.3	Usage of DM-OCCUPIED PDU	50
6.2.3.1	Sending of DM-OCCUPIED PDU by master DM-MS.....	50
6.2.3.2	Late entry by slave DM-MS.....	50
6.2.4	Procedures during occupation.....	51
6.2.4.1	Master DM-MS	51
6.2.4.2	Slave DM-MS	51
6.2.4.3	Transmitting Party Number Identification (TPNI) during occupation	53
6.2.4.3.1	Master DM-MS	53
6.2.4.3.2	Slave DM-MS.....	53
6.2.5	Procedures during reservation.....	53
6.2.5.1	Master DM-MS	53
6.2.5.2	Slave DM-MS	54
6.2.5.3	Pre-emption of short data sent as a transaction within a circuit mode call.....	54
6.2.6	Procedures to set up a new call by pre-emption.....	55
6.3	Short Data Service (SDS) procedures	55
6.3.1	Sending short data.....	56
6.3.1.1	Sending short data on a free channel.....	56
6.3.1.1.1	Sending unacknowledged short data on a free channel	56
6.3.1.1.2	Sending acknowledged short data on a free channel	56
6.3.1.2	Sending short data by pre-emption.....	56
6.3.1.3	Sending short data during circuit mode transmission.....	56
6.3.1.4	Sending short data as a transaction within a circuit mode call.....	57
6.3.1.4.1	Pre-emption to send short data as a transaction within a circuit mode call	57
6.3.1.4.2	Changeover to send short data as a transaction within a circuit mode call.....	57
6.3.1.4.3	Sending the short data as master of the circuit mode call.....	57
6.3.2	Receiving short data.....	57
6.3.2.1	Receiving unacknowledged short data	57
6.3.2.2	Receiving acknowledged short data	58
6.3.3	Additional addressing	58
6.3.3.1	DM-MS sending short data	58
6.3.3.2	DM-MS receiving short data	58
6.3.4	Extended error protection	58
6.3.5	SDS-TL service in DMO	58
6.3.5.1	Service primitives at the DMTL-SAP	58
6.3.5.2	DMTL-SDS primitives' parameters	59
6.3.5.3	DMTL-SDS PDUs	59
6.3.5.4	DMTL-SDS procedures	59
6.4	Procedures for mobility management.....	59
6.4.1	Solicited registration	59
6.4.2	Unsolicited registration.....	60
6.4.3	Cancellation of registration by gateway.....	60
6.4.4	Other criteria for DMMM state change	60
6.4.5	Action on entering state REGISTRATION-REJECTED.....	61
6.4.6	Layer 3 addressing in DM-GREGISTER REQUEST PDU.....	61
6.5	Usage of DMA-UNITDATA primitive	61
6.5.1	Sending a DMCC PDU	61
6.5.2	Sending a DMMM PDU	61
6.5.3	Protocol control function for delivery of received message	61
6.6	General procedures.....	62
6.6.1	Usage restriction type and validity time	62
7	DM-MS layer 2 service description (for operation with a gateway).....	62
7.1	Introduction	62
7.2	Layer 2 architecture.....	63
7.3	Service descriptions.....	63
7.3.1	Services at the DMA-SAP	63
7.3.1.1	Services provided to layer 3.....	63
7.3.1.2	Service primitives at the DMA-SAP	63
7.3.1.2.1	DMA-REPORT primitive.....	63
7.3.1.2.2	DMA-UNITDATA primitive	63

7.3.2	Services at the DMC-SAP	64
7.3.2.1	Services provided to layer 3	64
7.3.2.2	Service primitives at the DMC-SAP	64
7.3.2.2.1	DMC-CONFIGURE primitive	64
7.3.2.2.2	DMC-REPORT primitive	64
7.3.3	Services at the DMD-SAP	64
7.3.3.1	Services provided to the U-plane application	64
7.3.3.2	Service primitives at the DMD-SAP	64
7.4	Parameter listing	65
8	DM-MS layer 2 protocol (for operation with a gateway)	66
8.1	Introduction	66
8.1.1	Functions of lower MAC	66
8.1.2	Functions of upper MAC	66
8.2	Interface between lower and upper MAC	66
8.2.1	Logical channels defined at the DMV-SAP	66
8.2.2	Service primitives at the DMV-SAP	66
8.2.3	PDU mapping of the logical channels at the DMV-SAP	66
8.2.4	Scrambling mechanism	67
8.2.5	PDU error detection	67
8.2.6	Modes of operation	67
8.3	Basic capabilities of the physical layer	68
8.3.1	DM-MS capabilities	68
8.3.1.1	DM only and dual mode capable MS operation	68
8.3.1.2	Dual watch capable MS operation	68
8.4	Usage of DM channel with gateway	68
8.4.1	Definition of DM channel	69
8.4.1.1	DM channel arrangement	69
8.4.1.1.1	DM channel arrangement for operation with a DM-GATE	69
8.4.1.1.2	DM channel arrangement for operation with a type 1A DM-REP/GATE	69
8.4.1.1.3	DM channel arrangement for operation with a type 1B DM-REP/GATE	69
8.4.1.2	DM channel operation	70
8.4.2	DM-MAC states	70
8.4.2.1	DM-MAC state definitions	71
8.4.2.2	DM-MS channel surveillance procedures	72
8.4.2.2.1	Initial determination of DM channel state	72
8.4.2.2.1.1	Initial determination of state of carrier	72
8.4.2.2.1.2	Determination of state of one DM channel when other DM channel is busy	73
8.4.2.2.2	Fast call set-up surveillance in idle mode	73
8.4.2.2.2.1	Fast call set-up surveillance when idle on a free carrier	73
8.4.2.2.2.2	Fast call set-up surveillance when idle on a carrier that is not free	74
8.4.2.2.3	DM-MS channel surveillance at call set-up (circuit mode call or short data message)	74
8.4.2.2.4	DM-MS channel surveillance for registration outside the registration phase	74
8.4.2.3	Master DM-MS channel maintenance procedures during a call transaction	75
8.4.2.4	Slave DM-MS channel maintenance procedures during a call	76
8.4.2.4.1	Slave MS channel maintenance during call transaction	76
8.4.2.4.2	Slave MS signal quality measurement during call transaction	76
8.4.2.4.3	Slave MS channel maintenance during reservation	76
8.4.3	Criteria for changing DM-MAC states	76
8.4.3.1	Criteria for changing DM-MAC state for master DM-MS	76
8.4.3.2	Criteria for changing DM-MAC state for slave DM-MS	76
8.4.3.3	Criteria for changing DM-MAC state for idle DM-MS	77
8.4.4	DM-MS channel monitoring procedures	78
8.4.4.1	DM channel when setting up a circuit mode call through a gateway	78
8.4.4.2	DM channel when receiving a circuit mode call set-up from a gateway	79
8.4.4.3	DM channel in occupation during a circuit mode call	79
8.4.4.4	DM channel in reservation during a circuit mode call	79
8.4.4.5	DM channel in occupation during an SDS call	79
8.4.4.6	DM channel during pre-emption signalling	80
8.4.4.7	DM channel during registration phase	80
8.4.4.8	DM channel in occupation for an unsolicited registration	80
8.4.5	Transmission of layer 3 messages by DM-MAC	81

8.4.5.1	Transmission of C-plane messages by DM-MAC.....	81
8.4.5.1.1	Transmitting DM-SETUP.....	81
8.4.5.1.2	Transmitting DM-SETUP PRES	81
8.4.5.1.3	Transmitting DM-CONNECT	81
8.4.5.1.4	Transmitting DM-DISCONNECT.....	81
8.4.5.1.5	Transmitting DM-CONNECT ACK.....	81
8.4.5.1.6	Transmitting DM-RELEASE	82
8.4.5.1.7	Transmitting DM-OCCUPIED.....	82
8.4.5.1.8	Transmitting DM-TX CEASED.....	82
8.4.5.1.9	Transmitting DM-TX REQUEST.....	82
8.4.5.1.10	Transmitting response to DM-TX REQUEST.....	82
8.4.5.1.11	Transmitting DM-PREEMPT	83
8.4.5.1.12	Transmitting response to DM-PREEMPT	83
8.4.5.1.13	Transmitting DM-SDS UDATA and DM-SDS DATA.....	83
8.4.5.1.14	Transmitting response to DM-SDS DATA	83
8.4.5.1.15	Transmitting DM-INFO	83
8.4.5.1.16	Transmitting DM-GSETUP.....	84
8.4.5.1.17	Transmitting DM-GTX REQUEST.....	84
8.4.5.1.18	Transmitting DM-GPREEMPT	85
8.4.5.1.19	Transmitting DM-GREGISTER REQUEST	85
8.4.5.1.20	Transmitting DM-GCANCEL ACK.....	86
8.4.5.2	Transmission of U-plane messages by DM-MAC	86
8.4.6	Transmission of layer 2 messages generated by DM-MAC	86
8.4.6.1	Transmitting DM-RESERVED.....	86
8.4.6.2	Transmitting DM-SDS OCCUPIED	86
8.4.6.3	Transmitting DM-TIMING REQUEST	86
8.4.6.4	Transmitting DM-TIMING ACK.....	86
8.4.7	General DM-MAC procedures	87
8.4.7.1	DM-MAC repeat transmissions	87
8.4.7.2	DM-MAC frame countdown procedure	87
8.4.7.3	Use of timers	87
8.4.7.4	Linearization	87
8.4.7.5	Fragmentation	88
8.4.7.6	Fill bit indication	88
8.4.7.7	Selection of pseudo address	88
8.4.7.8	Slot flag indication	88
8.4.7.9	Requests bitmap	88
8.4.7.10	Dual watch operation	88
8.4.7.11	Air interface encryption	88
8.4.7.12	Channel A or B operation	89
8.4.7.13	Sending short data as a transaction within a circuit mode call.....	89
8.4.7.14	SDS and registration transaction time remaining.....	89
8.4.7.14.1	SDS time remaining	89
8.4.7.14.2	Registration transaction time remaining.....	89
8.4.7.15	Timing change procedure.....	89
8.4.7.16	Timing change at changeover or pre-emption.....	89
8.4.7.17	Modification of slot/frame numbering by gateway	90
8.4.7.18	Modification of channel timing by gateway.....	90
8.5	MAC procedures for transfer of signalling messages.....	90
8.5.1	Formation of MAC PDU	90
8.5.2	Addressing	91
8.5.2.1	Transmission of message	91
8.5.2.1.1	Addressing in synchronization burst carrying gateway-specific message	91
8.5.2.1.2	Addressing in synchronization burst carrying non-gateway-specific message.....	91
8.5.2.1.3	Lifetime of pseudo SSI.....	92
8.5.2.1.4	Additional elements in synchronization burst	93
8.5.2.1.5	Addressing in normal burst.....	93
8.5.2.2	Reception of message.....	93
8.5.2.3	Usage of MNI.....	94
8.5.3	Use of air interface encryption.....	94
8.5.4	Fragmentation and reconstruction.....	95
8.5.4.1	Fragmentation by a DM-MS	95

8.5.4.2	Reconstruction by a DM-MS	96
8.5.5	Fill bit addition and deletion	97
8.5.6	Transmission and reception of messages by layer 2 unacknowledged service	97
8.5.6.1	Transmission of message	98
8.5.6.2	Reception of message	99
8.5.7	Random access protocol during occupation and reservation periods	101
8.5.7.1	Introduction	101
8.5.7.2	Procedures for master DM-MS	101
8.5.7.2.1	Indicating frames available for requests	102
8.5.7.2.2	Monitoring frames available for requests	102
8.5.7.2.3	Response to pre-emption request	102
8.5.7.2.4	Response to timing change request	103
8.5.7.2.5	Response to DM-GRELEASE message	103
8.5.7.3	Procedures for requesting DM-MS	103
8.5.8	Procedures for sending messages during registration phase	105
8.5.8.1	Procedures for registering DM-MS during registration phase	105
8.5.8.1.1	Preparing for registration access	105
8.5.8.1.2	First transmission of solicited registration request	105
8.5.8.1.3	Valid access slots	105
8.5.8.1.4	Waiting for response	105
8.5.8.1.5	Subsequent transmission of request	105
8.5.8.1.6	Abandoning registration access attempt	106
8.5.8.2	Procedures for pre-empting DM-MS during registration phase	106
8.5.8.2.1	Preparing for random access	106
8.5.8.2.2	First transmission of pre-emption request	106
8.5.8.2.3	Valid slots for pre-emption	106
8.5.8.2.4	Waiting for response	106
8.5.8.2.5	Subsequent transmission of request	107
8.5.8.2.6	Abandoning random access attempt	107
8.6	MAC procedures in traffic mode	107
8.6.1	Introduction	107
8.6.2	Criteria for transmission and reception of traffic	108
8.6.3	Change of U-plane mode	108
8.6.3.1	Call set-up by DM-MS	108
8.6.3.2	Incoming call set-up	108
8.6.3.2.1	Incoming call set-up without presence check	108
8.6.3.2.2	Incoming call set-up with presence check	109
8.6.3.3	Late entry	109
8.6.3.4	End of traffic transmission	109
8.6.3.4.1	Master DM-MS	109
8.6.3.4.2	Slave DM-MS	109
8.6.4	Exchange of information at the DMD-SAP	109
8.6.5	Stealing from circuit mode capacity	109
9	Gateway layer 3 call control procedures	110
9.1	Introduction	110
9.2	Gateway call control states	110
9.2.1	Gateway TMO call control states	110
9.2.1.1	IDLE	110
9.2.1.2	MO-CALL-SETUP	110
9.2.1.3	MT-CALL-SETUP	110
9.2.1.4	CALL ACTIVE	110
9.2.1.5	CALL DISCONNECT	110
9.2.1.6	WAIT	111
9.2.2	Gateway DM call control states	111
9.2.2.1	IDLE	111
9.2.2.2	CALL SETUP NORMAL ORIGINATING	111
9.2.2.3	CALL SETUP PRES_CHECK ORIGINATING	111
9.2.2.4	CALL SETUP TERMINATING	111
9.2.2.5	PRE-EMPTION	111
9.2.2.6	CALL ACTIVE TX OCCUPATION	111
9.2.2.7	CALL ACTIVE TX RESERVATION	111