Final draft ETSI EN 300 422-1 V1.4.2 (2011-06)

European Standard

Electromagnetic compatibility and Radio spectrum Matters (ERM); Wireless microphones in the 25 MHz to 3 GHz frequency range; Part 1: Technical characteristics and methods of measurement

Reference
REN/ERM-TG17WG3-014-1

Keywords
audio, radio, radio MIC, testing

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:
 http://www.etsi.org

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at
http://portal.etsi.org/tb/status/status.asp

If you find errors in the present document, please send your comment to one of the following services:
http://portal.etsi.org/chaircor/ETSI_support.asp

Copyright Notification

Contents

Intellectual Property Rights 7
Foreword 7
Introduction 8
1 Scope 9
2 References 10
2.1 Normative references 10
2.2 Informative references 10
3 Definitions, symbols and abbreviations 11
3.1 Definitions 11
3.2 Symbols 13
3.3 Abbreviations 13
Part I: Radio microphones 14
4 Functional characteristics 14
4.1 Radio microphone descriptions 14
4.2 In ear monitoring 14
4.3 Tour Guide systems 14
5 General 14
5.1 Presentation of equipment for testing purposes 14
5.1.1 Choice of model for testing 15
5.1.2 Definitions of alignment and switching ranges 15
5.1.3 Choice of frequencies 15
5.1.4 Testing of single channel equipment 16
5.1.5 Testing of two channel equipment 16
5.1.6 Testing of multi-channel equipment (more than two channels) 16
5.1.7 Testing of equipment without a permanent external RF port 16
5.1.7.1 Equipment with a permanent internal RF port 16
5.1.7.2 Equipment with a temporary RF port 16
5.2 Mechanical and electrical design 16
5.2.1 General 16
5.2.2 Controls 16
5.2.3 Performance testing with Integral antenna 16
5.2.4 Marking (equipment identification) 17
5.3 Interpretation of the measurement results 17
6 Test conditions, power sources and ambient conditions 17
6.1 Normal and extreme test-conditions 17
6.2 Test power source 17
6.3 Normal test conditions 18
6.3.1 Normal temperature and humidity 18
6.3.2 Normal test power source voltage 18
6.3.2.1 Mains voltage 18
6.3.2.2 Other power sources 18
6.4 Extreme test conditions 18
6.4.1 Extreme temperatures 18
6.4.1.1 Procedures for tests at extreme temperatures 18
6.4.2 Extreme test power source voltages 19
6.4.2.1 Mains voltage 19
6.4.2.2 Other power sources 19
7 General conditions 19
7.1 Normal test modulation 19
7.1.1 Analogue systems 19
7.1.2 Digital systems 20

7.2 Artificial antenna 21
7.3 Test fixture 21
7.4 Test site and general arrangements for radiated measurements 21
7.5 Modes of operation of the transmitter 21
7.6 Arrangement for test signals at the input of the transmitter 21

8 Methods of measurement and limits for transmitter parameters 22
8.1 Frequency stability 22
8.1.1 Method of measurement (analogue) 22
8.1.2 Method of measurement (digital) 22
8.1.3 Limit 22
8.2 Rated output power 22
8.2.1 Method of measurement for equipment without integral antenna 22
8.2.2 Method of measurement for equipment with integral antenna 22
8.2.2.1 Method of measurement under normal test conditions 22
8.2.3 Limit 23
8.3 Necessary bandwidth 23
8.3.1 Necessary Bandwidth (BN) for Analogue Systems 23
8.3.1.1 Method of Measurement 23
8.3.1.2 Limits 24
8.3.2 Necessary Bandwidth (BN) for Digital Systems 24
8.3.2.1 Method of Measurement 24
8.3.2.2 Limits 26
8.4 Spurious emissions 27
8.4.1 Definition 27
8.4.2 Method of measurement 27
8.4.3 Limits 28
8.4.4 Measuring receiver 28

9 Receiver 28
9.1 Spurious emissions 28
9.1.1 Definitions 28
9.1.2 Method of measuring the power level in a specified load 28
9.1.3 Method of measuring the effective radiated power of the enclosure 29
9.1.4 Method of measuring the effective radiated power 29
9.1.5 Limits 29

Part II: Assistive listening devices 30

10 Functional characteristics 30
10.1 Assistive Listening Devices (Aids for the handicapped) 30

11 General 30
11.1 Presentation of equipment for testing purposes 30
11.1.1 Choice of model for testing 31
11.1.2 Definitions of alignment and switching ranges 31
11.1.3 Choice of frequencies 31
11.1.4 Testing of single channel equipment 32
11.1.5 Testing of two channel equipment 32
11.1.6 Testing of multi-channel equipment (more than two channels) 32
11.1.7 Testing of equipment without a permanent external RF port 32
11.1.7.1 Equipment with a permanent internal RF port 32
11.1.7.2 Equipment with a temporary RF port 32
11.2 Mechanical and electrical design 32
11.2.1 General 32
11.2.2 Controls 32
11.2.3 Performance testing with Integral antenna 32
11.2.4 Marking (equipment identification) 33
11.3 Interpretation of the measurement results 33

12 Test conditions, power sources and ambient conditions 33
12.1 Normal and extreme test-conditions 33
12.2 Test power source 33
12.3 Normal test conditions 34

12.3.1 Normal temperature and humidity 34
12.3.2 Normal test power source voltage 34
12.3.2.1 Mains voltage 34
12.3.2.2 Other power sources 34
12.4 Extreme test conditions 34
12.4.1 Extreme temperatures 34
12.4.1.1 Procedures for tests at extreme temperatures 34
12.4.2 Extreme test power source voltages 35
12.4.2.1 Mains voltage 35
12.4.2.2 Other power sources 35

13 General conditions 35
13.1 Normal test modulation 35
13.1.1 Analogue systems 35
13.1.2 Digital systems 35
13.2 Artificial antenna 36
13.3 Test fixture 36
13.4 Test site and general arrangements for radiated measurements 36
13.5 Modes of operation of the transmitter 36
13.6 Arrangement for test signals at the input of the transmitter 36

14 Methods of measurement and limits for transmitter parameters 37
14.1 Frequency stability 37
14.1.1 Method of measurement (analogue) 37
14.1.2 Method of measurement (digital) 37
14.1.3 Limit 37
14.2 Rated output power 37
14.2.1 Method of measurement for equipment without integral antenna 37
14.2.2 Method of measurement for equipment with integral antenna 37
14.2.2.1 Method of measurement under normal test conditions 37
14.2.3 Limit 38
14.3 Necessary bandwidth 38
14.3.1 Necessary Bandwidth (BN) for Analogue Systems 38
14.3.1.1 Method of Measurement 38
14.3.1.2 Limits 39
14.3.2 Necessary Bandwidth (BN) for Digital Systems 40
14.3.2.1 Method of Measurement 40
14.3.2.2 Limits 41
14.4 Spurious emissions 41
14.4.1 Definition 41
14.4.2 Method of measurement 41
14.4.3 Limits 41
14.4.4 Measuring receiver 42

15 Receiver 42
15.1 Spurious emissions 42
15.1.1 Definitions 42
15.1.2 Method of measuring the power level in a specified load 42
15.1.3 Method of measuring the effective radiated power of the enclosure 43
15.1.4 Method of measuring the effective radiated power 43
15.1.5 Limits 43

16 Measurement uncertainty 44

Annex A (normative): Radiated measurement 45

A.1 Test sites and general arrangements for measurements involving the use of radiated fields 45
A.1.1 Anechoic Chamber 45
A.1.2 Anechoic Chamber with a conductive ground plane 46
A.1.3 Open Area Test Site (OATS) 47
A.1.4 Test antenna 48
A.1.5 Substitution antenna 48
A.1.6 Measuring antenna 49
A.1.7 Stripline arrangement 49

A.1.7.1 General 49
A.1.7.2 Description 49
A.1.7.3 Calibration 49
A.1.7.4 Mode of use 49

A.2 Guidance on the use of radiation test sites 49
A.2.1 Verification of the test site 49
A.2.2 Preparation of the EUT 49
A.2.3 Power supplies to the EUT 50
A.2.4 Volume control setting for analogue speech tests 50
A.2.5 Range length 50
A.2.6 Site preparation 51

A.3 Coupling of signals 51
A.3.1 General 51
A.3.2 Data Signals 51
A.3.3 Speech and analogue signals 51
A.3.3.1 Acoustic coupler description 52
A.3.3.2 Calibration 52

A.4 Standard test position 52

A.5 Test fixture 53
A.5.1 Description 53
A.5.2 Calibration 53
A.5.3 Mode of use 54

Annex B (normative): Measurement of Necessary Bandwidth (BN) for analogue systems 55

Annex C (informative): Bibliography 56

History 57

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (http://webapp.etsi.org/IPR/home.asp).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This final draft European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the Vote phase of the ETSI standards Two-step Approval Procedure.

The present document has been updated in line with the advances in radio microphone technology in the digital field and the increased use of wireless applications for Assistive listening Devices, also with changes generated within CEPT and the EC in the former ERMES band for aids for the handicapped.

The present document is part 1 of a multi-part deliverable covering the Electromagnetic compatibility and Radio spectrum Matters (ERM); Wireless microphones in the 25 MHz to 3 GHz frequency range, as identified below:

Part 1: "Technical characteristics and methods of measurement";

Part 2: "Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive".

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa