

ETSI EN 300 440-1 V1.6.1 (2010-08)

European Standard (Telecommunications series)

**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
Short range devices;
Radio equipment to be used
in the 1 GHz to 40 GHz frequency range;
Part 1: Technical characteristics and
test methods**

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI EN 300 440-1 V1.6.1 \(2010-08\)](https://standards.iteh.ai/catalog/standards/etsi/5390cbc1-9d15-4497-8314-f22ed466a0dd/etsi-en-300-440-1-v1-6-1-2010-08)

<https://standards.iteh.ai/catalog/standards/etsi/5390cbc1-9d15-4497-8314-f22ed466a0dd/etsi-en-300-440-1-v1-6-1-2010-08>



Reference

REN/ERM-TG28-045-1

Keywords

radio, SRD, testing

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2010.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTE™ is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	7
Foreword.....	7
1 Scope	8
2 References	9
2.1 Normative references	9
2.2 Informative references.....	9
3 Definitions, symbols and abbreviations	10
3.1 Definitions.....	10
3.2 Symbols.....	12
3.3 Abbreviations	12
4 Technical requirements specifications	12
4.1 General requirements	12
4.1.1 Receiver category	12
4.1.2 General performance criteria	13
4.2 Presentation of equipment for testing purposes.....	13
4.2.1 Choice of model for testing	14
4.2.2 Testing of equipment with alternative power levels	14
4.2.3 Testing of equipment that does not have an external 50 Ω RF connector (integral antenna equipment)	14
4.2.3.1 Equipment with an internal permanent or temporary antenna connector or using a dedicated test fixture	14
4.2.3.2 Equipment with a temporary antenna connector	14
4.3 Mechanical and electrical design.....	14
4.3.1 General.....	14
4.3.2 Controls	15
4.3.3 Transmitter shut-off facility	15
4.3.4 Receiver mute or squelch.....	15
4.3.5 Marking (equipment identification)	15
4.3.5.1 Equipment identification	15
4.3.5.2 Marking.....	15
4.4 Auxiliary test equipment	15
5 Test conditions, power sources and ambient temperatures	15
5.1 Normal and extreme test conditions	15
5.2 Test power source.....	15
5.2.1 External test power source	16
5.2.2 Internal test power source	16
5.3 Normal test conditions.....	16
5.3.1 Normal temperature and humidity	16
5.3.2 Normal test power source	16
5.3.2.1 Mains voltage	16
5.3.2.2 Regulated lead-acid battery power sources	16
5.3.2.3 Other power sources.....	16
5.4 Extreme test conditions	17
5.4.1 Extreme temperatures	17
5.4.1.1 Procedure for tests at extreme temperatures.....	17
5.4.1.1.1 Procedure for equipment designed for continuous operation	17
5.4.1.1.2 Procedure for equipment designed for intermittent operation	17
5.4.1.2 Extreme temperature ranges.....	17
5.4.2 Extreme test source voltages.....	18
5.4.2.1 Mains voltage	18
5.4.2.2 Regulated lead-acid battery power sources	18
5.4.2.3 Power sources using other types of batteries.....	18
5.4.2.4 Other power sources.....	18

6	General conditions.....	18
6.1	Normal test signals and test modulation.....	18
6.1.1	Normal test signals for data	19
6.2	Artificial antenna.....	19
6.3	Test fixture	19
6.3.1	Validation of the test-fixture in the temperature chamber	21
6.3.2	Mode of use	22
6.4	Test sites and general arrangements for radiated measurements	23
6.5	Measuring receiver	23
7	Methods of measurement and limits for transmitter parameters	23
7.1	Equivalent isotropically radiated power (e.i.r.p.)	24
7.1.1	Definition.....	24
7.1.2	Method of measurement	24
7.1.2.1	Non spread spectrum transmitters with a -6 dB bandwidth of up to 20 MHz and spread spectrum transmitters with channel bandwidth of up to 1 MHz	24
7.1.2.1.1	Equipment measured as constant envelope modulation equipment.....	24
7.1.2.1.2	Equipment measured as non-constant envelope modulation equipment	25
7.1.2.2	Other transmitters than defined in clause 7.1.2.1	25
7.1.3	Limits.....	26
7.2	Permitted range of operating frequencies	27
7.2.1	Definition.....	27
7.2.2	Method of measurement	27
7.2.3	Method of measurement for equipment using FHSS modulation.....	28
7.2.4	Limit	28
7.3	Unwanted emissions in the spurious domain.....	28
7.3.1	Definition.....	28
7.3.2	Method of measurement - conducted spurious emission.....	29
7.3.3	Method of measurement - cabinet spurious radiation.....	29
7.3.4	Method of measurement - radiated spurious emission.....	30
7.3.5	Additional requirements for equipment employing FHSS modulation.....	31
7.3.6	Limits.....	31
7.4	Duty cycle	31
7.4.1	Definitions	31
7.4.2	Declaration.....	31
7.4.3	Duty cycle limits.....	32
7.5	Additional requirements for FHSS equipment.....	32
7.5.1	FHSS modulation.....	32
8	Receiver.....	32
8.1	Adjacent channel selectivity.....	32
8.1.1	Definition.....	32
8.1.2	Method of measurement	33
8.1.3	Limits.....	33
8.2	Blocking or desensitization	34
8.2.1	Definition.....	34
8.2.2	Methods of measurement.....	34
8.2.3	Limits.....	34
8.3	Spurious emissions	35
8.3.1	Definition.....	35
8.3.2	Method of measurement conducted spurious components	35
8.3.3	Method of measurement cabinet radiation.....	36
8.3.4	Method of measurement radiated spurious components	37
8.3.5	Limits.....	37
9	Spectrum access techniques	37
9.1	Principle for Listen Before Talk (LBT).....	37
9.1.1	LBT timing parameters.....	38
9.1.1.1	Minimum transmitter off-time	38
9.1.1.1.1	Definition.....	38
9.1.1.1.2	Limit.....	38
9.1.1.2	LBT minimum listening time	38
9.1.1.2.1	Definition.....	38

9.1.1.2.2	Limit for minimum listening time	38
9.1.1.3	Acknowledge transmissions	39
9.1.1.4	Maximum transmitter on-time	39
9.1.1.4.1	Definition.....	39
9.1.1.4.2	Limit	39
9.1.1.5	Declaration of LBT parameters.....	39
9.1.1.6	Equipment with or without LBT using transmitter time-out-timer	39
9.2	Receiver LBT threshold and transmitter max on-time	39
9.2.1	Definitions	40
9.2.2	Method of measurements	40
9.2.3	Limits.....	40
9.3	Detect And Avoid techniques (DAA)	41
9.4	Adaptive Frequency Agility (AFA).....	41
9.4.1	Introduction.....	41
10	Measurement uncertainty	41
10.1	Measurement uncertainty is greater than maximum acceptable uncertainty	42

Annex A (normative): Radiated measurements43

A.1	General requirements for measurements involving the use of radiated fields.....	43
A.2	Test Sites	44
A.2.1	Outdoor test site	44
A.2.2	Indoor test site	45
A.2.3	Shielded anechoic test site.....	46
A.2.3.1	Influence of parasitic reflections in anechoic chambers	46
A.2.3.2	Calibration of the shielded RF anechoic chamber	46
A.3	Antennas.....	48
A.3.1	Test antenna.....	48
A.3.2	Substitution antenna	48
A.3.3	Artificial antenna.....	48
A.4	Test Practice and Auxiliary Test Equipment.....	49
A.5	Measuring distance.....	49
A.5.1	Standard position.....	49
A.5.2	Auxiliary cables.....	49

Annex B (normative): General description of measurement methods.....50

B.1	Conducted measurements.....	50
B.2	Radiated measurements.....	50

Annex C (normative): Power limits for RFID systems operating in the 2,45 GHz ISM band.....52

C.1	Power limits and frequency band	52
C.1.1	Additional requirements for 2,45 GHz 4 W e.i.r.p. indoor RFID equipment	52
C.1.2	Spectrum mask	53

Annex D (informative): Example of implementation for restriction of 4 W RFID to in-building use only.....54

Annex E (normative): Limits for GBSAR operating in the frequency range 17,1 GHz to 17,3 GHz56

E.1	Introduction	56
E.2	Effective radiated power (e.i.r.p.).....	56
E.2.1	Definition	56
E.2.2	Method of measurement	56
E.2.3	Limits	56
E.3	Permitted range of operating frequencies.....	56
E.3.1	Definition	56

E.3.2	Method of measurement	56
E.3.3	Limits	57
E.4	Principles of Detection And Avoid (DAA)	57
E.4.1	General DAA test set-up	57
E.4.2	Test signals	58
E.4.3	DAA threshold	58
E.4.3.1	Definition	58
E.4.3.2	Method of measurement	58
E.4.3.3	Limit	59
E.4.4	DAA timing parameters	59
E.4.4.1	Minimum listen Time	59
E.4.4.1.1	Definition	59
E.4.4.1.2	Method of measurement	59
E.4.4.1.3	Limit for minimum listen time	60
E.4.4.2	Minimum listen time after detection	60
E.4.4.2.1	Definition	60
E.4.4.2.2	Method of measurement	60
E.4.4.2.3	Limit	61
E.4.4.3	Maximum transmitter on-time	61
E.4.4.3.1	Definition	61
E.4.4.3.2	Method of measurement	61
E.4.4.3.3	Limit	62
E.4.4.4	Minimum transmitter off-time	62
E.4.4.4.1	Definition	62
E.4.4.4.2	Method of measurement	62
E.4.4.4.3	Limit	63
E.5	Antenna pattern	63
E.5.1	Definition	63
E.5.2	Method of measurements	63
E.5.3	Limits	65
Annex F (informative):	Bibliography	66
History		67

ETSI EN 300 440-1 V1.6.1 (2010-08)

<https://standards.iteh.ai/catalog/standards/etsi/5390cbc1-9d15-4497-8314-f22ed466a0dd/etsi-en-300-440-1-v1-6-1-2010-08>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

For non EU countries the present document may be used for regulatory (Type Approval) purposes.

The present document includes improvements to the previous version of the standard that take advantage of technical developments within the SRD industry. In particular this includes optional features such as Listen Before Talk (LBT) and Detect And Avoid (DAA).

The present document is part 1 of a multi-part deliverable covering Electromagnetic compatibility and Radio spectrum Matters (ERM); Short range devices; Radio equipment to be used in the 1 GHz to 40 GHz frequency range, as identified below:

Part 1: "Technical characteristics and test methods";

Part 2: "Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive".

National transposition dates

Date of adoption of this EN:	17 August 2010
Date of latest announcement of this EN (doa):	30 November 2010
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 May 2011
Date of withdrawal of any conflicting National Standard (dow):	31 May 2011