



Digital Video Broadcasting (DVB); Specification for Service Information (SI) in DVB systems

Sample Document

get full document from standards.iteh.ai

EBU DVB[®]

Reference

REN/JTC-DVB-419

Keywords

broadcasting, digital, DVB, MPEG, service, TV,
video

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed,
this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.
In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part of this document may be reproduced in any form, by any means and in any media, without the prior written authorization of ETSI and except as expressly permitted below.

By way of exception and when the document is a normative deliverable (European Standard (EN), Technical Specification (TS), Group Specification (GS) or ETSI Standard (ES)), ETSI authorizes to reproduce and incorporate into products, services and technical documentation only those extracts (e.g. templates) that are strictly necessary for the technical implementation of the normative deliverable, to ensure compliance with the latter. Nothing in this notice shall be construed as limiting any mandatory exceptions to copyright provided by applicable law.

© ETSI 2026.
© European Broadcasting Union 2026.
All rights reserved.

Contents

Intellectual Property Rights	8
Foreword.....	8
Modal verbs terminology.....	9
1 Scope	10
2 References	10
2.1 Normative references	10
2.2 Informative references.....	13
3 Definition of terms, symbols and abbreviations.....	14
3.1 Terms.....	14
3.2 Symbols.....	17
3.3 Abbreviations	17
4 Service information description	21
5 Service information tables.....	23
5.1 Service information table mechanism	23
5.1.1 Use of table sections	23
5.1.2 Mapping of sections into DVB transport stream packets.....	24
5.1.3 Coding of PID and table_id fields	24
5.1.4 Repetition rates and random access	25
5.1.4.1 Rates for DVB PSI and SI.....	25
5.1.4.2 Rates for Satellite Access Tables	25
5.1.5 Scrambling.....	26
5.1.6 Bit order and transmission order.....	26
5.2 Table definitions.....	28
5.2.0 Introduction.....	28
5.2.1 Network Information Table	29
5.2.2 Bouquet Association Table.....	30
5.2.3 Service Description Table.....	32
5.2.4 Event Information Table.....	34
5.2.5 Time and Date Table.....	36
5.2.6 Time Offset Table.....	37
5.2.7 Running Status Table.....	38
5.2.8 Stuffing Table	38
5.2.9 Discontinuity Information Table.....	39
5.2.10 Selection Information Table	39
5.2.11 Satellite Access Tables	39
5.2.11.1 Definition	39
5.2.11.2 Satellite Position v2 info	41
5.2.11.3 Cell Fragment info	43
5.2.11.4 Time Association info	45
5.2.11.5 Beamhopping Time Plan info	46
5.2.11.6 Satellite Position v3 info	49
6 Descriptors	52
6.0 Introduction	52
6.1 Descriptor identification and location	52
6.2 Descriptor coding	54
6.2.0 General principles.....	54
6.2.1 Adaptation field data descriptor.....	54
6.2.2 Ancillary data descriptor.....	55
6.2.3 Announcement support descriptor	55
6.2.4 Bouquet name descriptor	57
6.2.5 CA identifier descriptor	57
6.2.6 Cell frequency link descriptor.....	57
6.2.7 Cell list descriptor.....	58

6.2.8	Component descriptor.....	59
6.2.9	Content descriptor.....	67
6.2.10	Country availability descriptor	70
6.2.11	Data broadcast descriptor.....	71
6.2.12	Data broadcast id descriptor.....	72
6.2.13	Delivery system descriptors	72
6.2.13.1	Cable delivery system descriptor	72
6.2.13.2	Satellite delivery system descriptor.....	74
6.2.13.3	S2 satellite delivery system descriptor	75
6.2.13.4	Terrestrial delivery system descriptor	76
6.2.14	DSNG descriptor	79
6.2.15	Extended event descriptor.....	79
6.2.16	Extension descriptor	80
6.2.17	Frequency list descriptor.....	81
6.2.18	FTA content management descriptor.....	81
6.2.18.1	Semantics and syntax of the FTA content management descriptor.....	81
6.2.18.2	Scope of the FTA content management descriptor	84
6.2.19	Linkage descriptor	84
6.2.19.1	Semantics and syntax of the linkage descriptor	84
6.2.19.2	Mobile hand-over linkage	86
6.2.19.3	Event linkage.....	87
6.2.19.4	Extended event linkage	87
6.2.20	Local time offset descriptor	90
6.2.21	Mosaic descriptor.....	91
6.2.22	Multilingual bouquet name descriptor.....	94
6.2.23	Multilingual component descriptor.....	95
6.2.24	Multilingual network name descriptor.....	95
6.2.25	Multilingual service name descriptor.....	96
6.2.26	NVOD reference descriptor	96
6.2.27	Network name descriptor.....	97
6.2.28	Parental rating descriptor	97
6.2.29	Partial TS descriptor	98
6.2.30	PDC descriptor.....	98
6.2.31	Private data specifier descriptor.....	99
6.2.32	Scrambling descriptor	99
6.2.33	Service descriptor	100
6.2.34	Service availability descriptor.....	101
6.2.35	Service list descriptor.....	102
6.2.36	Service move descriptor.....	102
6.2.37	Short event descriptor	103
6.2.38	Short smoothing buffer descriptor	104
6.2.39	Stream identifier descriptor.....	106
6.2.40	Stuffing descriptor	106
6.2.41	Subtitling descriptor.....	106
6.2.42	Telephone descriptor.....	107
6.2.43	Teletext descriptor	109
6.2.44	Time shifted event descriptor.....	109
6.2.45	Time shifted service descriptor	110
6.2.46	Transport stream descriptor	110
6.2.47	VBI data descriptor.....	111
6.2.48	VBI teletext descriptor.....	112
6.3	Extended descriptor identification and location	112
6.4	Extended descriptor coding	113
6.4.0	General principles	113
6.4.1	Audio preselection descriptor	114
6.4.2	CID ancillary data descriptor.....	117
6.4.3	CP descriptor	117
6.4.4	CP identifier descriptor	118
6.4.5	CPCM delivery signalling descriptor.....	118
6.4.6	Delivery system descriptors	118
6.4.6.1	C2 delivery system descriptor.....	118
6.4.6.2	SH delivery system descriptor.....	120

6.4.6.3	T2 delivery system descriptor	124
6.4.6.4	C2 bundle delivery system descriptor	127
6.4.6.5	S2X satellite delivery system descriptors	128
6.4.6.5.1	Introduction	128
6.4.6.5.2	S2X satellite delivery system descriptor (version 1)	128
6.4.6.5.3	S2Xv2 satellite delivery system descriptor (version 2)	131
6.4.7	Image icon descriptor	135
6.4.8	Message descriptor	137
6.4.9	Network change notify descriptor	138
6.4.10	Service relocated descriptor	140
6.4.11	Supplementary audio descriptor	141
6.4.12	Target region descriptor	143
6.4.13	Target region name descriptor	145
6.4.14	T2-MI descriptor	146
6.4.15	URI linkage descriptor	147
6.4.16	Video depth range descriptor	147
6.4.16.1	Semantics and syntax of the video depth range descriptor	147
6.4.16.2	Production disparity hint	148
6.4.17	VVC subpictures descriptor	149
6.4.18	Service Prominence Descriptor	150
6.5	Scoping rules for scoping descriptors	152
7	Storage Media Interoperability measures	153
7.0	Introduction	153
7.1	SMI tables	153
7.1.0	General principles	153
7.1.1	Discontinuity Information Table	153
7.1.2	Selection Information Table	154
7.2	SMI descriptors	155
7.2.0	Introduction	155
7.2.1	Partial transport stream descriptor	155
Annex A (normative):	Coding of text characters	156
A.0	General principles	156
A.1	Control codes	156
A.2	Selection of character table	156
Annex B (informative):	Void	170
Annex C (informative):	Conversion between time and date conventions	171
Annex D (normative):	Service information implementation of AC-3, Enhanced AC-3, and AC-4 audio in DVB systems	173
D.0	Introduction	173
D.1	AC-3 and Enhanced AC-3 component types	173
D.2	AC-3 descriptor	174
D.3	AC-3 descriptor syntax and semantics	174
D.4	Enhanced AC-3 descriptor	175
D.5	Enhanced AC-3 descriptor syntax and semantics	176
D.6	AC-4 descriptor	178
D.7	AC-4 descriptor syntax and semantics	178
D.8	Use of the supplementary audio descriptor with AC-4	180
Annex E (normative):	Usage of the scrambling descriptor	181

Annex F (informative):	ISO 639 language descriptor for "original audio" soundtrack	182
Annex G (normative):	Service information implementation of DTS coded audio in DVB systems	183
G.0	Introduction	183
G.1	DTS and DTS-HD descriptors	183
G.2	DTS descriptor	183
G.2.0	Use of the DTS descriptor	183
G.2.1	Syntax and semantics for the DTS descriptor	183
G.3	DTS-HD descriptor	186
G.3.1	DTS-HD descriptor syntax	186
G.3.2	Substream information	187
G.3.3	Asset information	189
G.3.4	Component type	190
G.4	Use of DTS-HD in Receiver Mixed Applications for Single PID and Multiple PID Implementations	191
G.5	DTS-UHD descriptors	192
G.5.1	DTS-UHD descriptor	192
G.5.2	DTS-UHD and the audio preselection descriptor	193
G.5.2.1	The DTS-UHD Broadcast Chunk and audio preselections	193
G.6	Use of the supplementary audio descriptor with DTS-UHD	194
Annex H (normative):	Service information implementation of AAC coded audio in DVB systems	195
H.0	Introduction	195
H.1	AAC Audio descriptor	195
H.2	AAC descriptor	195
H.2.0	Use of the AAC descriptor	195
H.2.1	Syntax and semantics for the AAC descriptor	195
Annex I (normative):	Assignment and interpretation of the service_type field	197
I.1	Background	197
I.2	Assignment of service_type	197
I.2.0	General principles	197
I.2.1	service_type "digital television service" (0x01)	197
I.2.2	service_type "H.264/AVC" (various)	198
I.2.3	service_type "H.264/AVC frame compatible stereoscopic HD" (various)	198
I.2.4	service_type "advanced codec digital radio sound service" (0x0A)	199
I.2.5	service_type "HEVC digital television service" (0x1F)	199
I.2.5.0	General principles	199
I.2.5.1	Signalling for service frame compatible plano-stereoscopic 3DTV for HEVC coded services	200
I.2.5.2	Signalling for HDR and/or frame rate of 100 Hz, 120 0001 001 Hz, or 120 Hz, but with a HEVC half frame rate temporal video sub-bitstream frame rate lower than or equal to 60 Hz	201
I.2.5.3	Spatial, temporal, and dynamic range characteristics	202
I.2.5.4	Summary of signalling for different bitstream profiles using service_type 0x1F	202
I.2.6	service_type "HEVC UHD digital television service" (0x20)	203
I.2.6.1	General principles	203
I.2.6.2	Summary of signalling for different bitstream profiles using service_type 0x20	205
I.2.7	Summary of signalling for HEVC bitstream profiles using service_type 0x1F or 0x20	207
I.2.8	service_type "VVC digital television service" (0x21)	210
I.2.8.1	General principles	210
I.2.8.2	Spatial, temporal and dynamic range characteristics	211
I.2.8.3	Examples of signalling for different bitstream profiles using service_type 0x21	212
I.2.9	service_type "AVS3 digital television service" (0x22)	214

I.2.9.1	General principles	214
I.2.9.2	Spatial, temporal and dynamic range characteristics	214
I.2.9.3	Examples of signalling for different bitstream profiles using service_type 0x22	215
Annex J (normative):	Signalling of supplementary audio	218
J.1	Overview	218
J.2	Receiver-mix supplementary audio	218
J.2.1	Introduction	218
J.2.2	PSI PMT signalling	219
J.2.3	EIT signalling	219
J.2.3.1	General principles	219
J.2.3.2	Visually impaired audio description	219
J.3	Broadcast-mix supplementary audio	220
J.3.1	Introduction	220
J.3.2	PSI PMT signalling	220
J.3.3	EIT signalling	220
J.3.3.1	General principles	220
J.3.3.2	Visually impaired audio description	220
J.4	PSI signalling of audio purpose	221
J.5	SAOC-DE parametric data streams	221
J.5.1	Introduction	221
J.5.2	PSI PMT signalling	221
J.5.3	EIT signalling	222
Annex K (normative):	Use of the extended_event_linkage_info	223
Annex L (normative):	Service information implementation of DTS Neural™ Surround coded audio in DVB systems	225
L.0	Introduction	225
L.1	DTS Neural descriptor	225
Annex M (normative):	Signalling of next-generation audio	227
M.1	Overview	227
M.2	PSI PMT signalling	227
M.3	Mapping of codec-specific values to the audio preselection descriptor (informative)	227
Annex N (informative):	Examples for using multiple component descriptors	230
Annex O (normative):	Signalling of AVS3-P3 Audio	231
Annex P (informative):	Bibliography	232
Annex Q (informative):	Change history	233
History		235

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables (European Standard (EN), Technical Specification (TS), Group Specification (GS) or ETSI Standard (ES)) may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Foreword

This European Standard (EN) has been produced by Joint Technical Committee (JTC) Broadcast of the European Broadcasting Union (EBU), Comité Européen de Normalisation ELECTrotechnique (CENELEC) and the European Telecommunications Standards Institute (ETSI).

NOTE: The EBU/ETSI JTC Broadcast was established in 1990 to co-ordinate the drafting of standards in the specific field of broadcasting and related fields. Since 1995 the JTC Broadcast became a tripartite body by including in the Memorandum of Understanding also CENELEC, which is responsible for the standardization of radio and television receivers. The EBU is a professional association of broadcasting organizations whose work includes the co-ordination of its members' activities in the technical, legal, programme-making and programme-exchange domains. The EBU has active members in about 60 countries in the European broadcasting area; its headquarters is in Geneva.

European Broadcasting Union
CH-1218 GRAND SACONNEX (Geneva)
Switzerland
Tel: +41 22 717 21 11
Fax: +41 22 717 24 81

The DVB® Project is an industry-led consortium of broadcasters, manufacturers, network operators, software developers, regulators and others from around the world committed to designing open, interoperable technical specifications for the global delivery of digital media and broadcast services. DVB® specifications cover all aspects of digital television from transmission through interfacing, conditional access and interactivity for digital video, audio and data. The consortium came together in 1993.

National transposition dates	
Date of adoption of this EN:	14 September 2026
Date of latest announcement of this EN (doa):	31 December 2026
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 June 2027
Date of withdrawal of any conflicting National Standard (dow):	30 June 2027

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Sample Document

get full document from standards.iteh.ai

1 Scope

The present document specifies the Service Information (SI) data which forms a part of Digital Video Broadcasting (DVB) bitstreams, in order that the user can be provided with information to assist in selection of services and/or events within the bitstream, and so that the Integrated Receiver Decoder (IRD) can automatically configure itself for the selected service. SI data for automatic configuration is mostly specified within ISO/IEC 13818-1 [1] as Program Specific Information (PSI).

The present document specifies additional data which complements the PSI by providing data to aid automatic tuning of IRDs, and additional information intended for display to the user. The manner of presentation of the information is not specified in the present document, and IRD manufacturers have freedom to choose appropriate presentation methods.

It is expected that Electronic Programme Guide (EPG) will be a feature of Digital TeleVision (TV) transmissions.

The definition of an EPG is outside the scope of the present document (i.e. the SI specification), but the data contained within the SI specified in the present document may be used as the basis for an EPG.

Rules of operation for the implementation of the present document are specified in ETSI TS 101 211 [i.1].

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found in the [ETSI docbox](#).

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long-term validity.

The following referenced documents are necessary for the application of the present document.

- [1] [ISO/IEC 13818-1](#): "Information technology — Generic coding of moving pictures and associated audio information — Part 1: Systems".
- [2] [ETSI EN 300 743](#): "Digital Video Broadcasting (DVB); Subtitling systems".
- [3] [ETSI EN 301 192](#): "Digital Video Broadcasting (DVB); DVB specification for data broadcasting".
- [4] [ETSI EN 301 210](#): "Digital Video Broadcasting (DVB); Framing structure, channel coding and modulation for Digital Satellite News Gathering (DSNG) and other contribution applications by satellite".
- [5] [ETSI EN 301 775](#): "Digital Video Broadcasting (DVB); Specification for the carriage of Vertical Blanking Information (VBI) data in DVB bitstreams".
- [6] [ETSI EN 301 790](#): "Digital Video Broadcasting (DVB); Interaction channel for satellite distribution systems".
- [7] [ETSI EN 302 307-1](#): "Digital Video Broadcasting (DVB); Second generation framing structure, channel coding and modulation systems for Broadcasting, Interactive Services, News Gathering and other broadband satellite applications; Part 1: DVB-S2".
- [8] [ETSI EN 302 307-2](#): "Digital Video Broadcasting (DVB); Second generation framing structure, channel coding and modulation systems for Broadcasting, Interactive Services, News Gathering and other broadband satellite applications; Part 2: DVB-S2 Extensions (DVB-S2X)".

- [9] [ETSI EN 302 769](#): "Digital Video Broadcasting (DVB); Frame structure channel coding and modulation for a second generation digital transmission system for cable systems (DVB-C2)".
- [10] [ETSI EN 302 583](#): "Digital Video Broadcasting (DVB); Framing Structure, channel coding and modulation for Satellite Services to Handheld devices (SH) below 3 GHz".
- [11] [ETSI EN 302 755](#): "Digital Video Broadcasting (DVB); Frame structure channel coding and modulation for a second generation digital terrestrial television broadcasting system (DVB-T2)".
- [12] [ETSI EN 303 560](#): "Digital Video Broadcasting (DVB); TTML subtitling systems".
- [13] [ETSI ES 201 812](#): "Digital Video Broadcasting (DVB); Multimedia Home Platform (MHP) Specification 1.0.3".
- [14] [ETSI TS 101 154](#): "Digital Video Broadcasting (DVB); Specification for the use of Video and Audio Coding in Broadcast and Broadband Applications".
- [15] [ETSI TS 101 162](#): "Digital Video Broadcasting (DVB); Allocation of identifiers and codes for Digital Video Broadcasting (DVB) systems".
- [16] [ETSI TS 101 547-2](#): "Digital Video Broadcasting (DVB); Plano-stereoscopic 3DTV; Part 2: Frame Compatible Plano-stereoscopic 3DTV".
- [17] [ETSI TS 101 547-3](#): "Digital Video Broadcasting (DVB); Plano-stereoscopic 3DTV; Part 3: HDTV Service Compatible Plano-stereoscopic 3DTV".
- [18] [ETSI TS 101 547-4](#): "Digital Video Broadcasting (DVB); Plano-stereoscopic 3DTV; Part 4: Service frame compatible Plano-stereoscopic 3DTV for HEVC coded services".
- [19] [ETSI TS 102 005](#): "Digital Video Broadcasting (DVB); Specification for the use of Video and Audio Coding in DVB services delivered directly over IP protocols".
- [20] [ETSI TS 102 006](#): "Digital Video Broadcasting (DVB); Specification for System Software Update in DVB Systems".
- [21] [ETSI TS 102 323](#): "Digital Video Broadcasting (DVB); Carriage and signalling of TV-Anytime information in DVB transport streams".
- [22] [ETSI TS 102 770](#): "Digital Video Broadcasting (DVB); System Renewability Messages (SRM) in DVB Systems".
- [23] [ETSI TS 102 772](#): "Digital Video Broadcasting (DVB); Specification of Multi-Protocol Encapsulation - inter-burst Forward Error Correction (MPE-iFEC)".
- [24] [ETSI TS 102 773](#): "Digital Video Broadcasting (DVB); Modulator Interface (T2-MI) for a second generation digital terrestrial television broadcasting system (DVB-T2)".
- [25] [ETSI TS 102 809](#): "Digital Video Broadcasting (DVB); Signalling and carriage of interactive applications and services in Hybrid Broadcast/Broadband environments".
- [26] [ETSI TS 102 812](#): "Digital Video Broadcasting (DVB); Multimedia Home Platform (MHP) Specification 1.1.3".
- [27] [ETSI TS 102 825](#) (parts 1 to 5, 7, 9 and 10): "Digital Video Broadcasting (DVB); Content Protection and Copy Management (DVB-CPCM)".
- [28] [ETSI EN 300 231](#): "Television systems; Specification of the domestic video Programme Delivery Control system (PDC)".
- [29] [ETSI EN 300 401](#): "Radio Broadcasting Systems; Digital Audio Broadcasting (DAB) to mobile, portable and fixed receivers".
- [30] [ETSI EN 300 706](#): "Enhanced Teletext specification".
- [31] [EN 50221](#): "Common interface specification for conditional access and other digital video broadcasting decoder applications", (produced by CENELEC).

- [32] [IETF RFC 2045](#): "Multipurpose Internet Mail Extensions (MIME) Part One: Format of Internet Message Bodies".
- [33] [IETF RFC 3986](#): "Uniform Resource Identifiers (URI): Generic Syntax".
- [34] [ISO 3166 \(all parts\)](#): "Codes for the representation of names of countries and their subdivisions".
- [35] [ISO 639](#): "Code for individual languages and language groups".
- [36] Void.
- [37] [ISO/IEC 6937](#): "Information technology — Coded graphic character set for text communication — Latin alphabet".
- [38] [ISO/IEC 8859-1](#): "Information technology — 8-bit single-byte coded graphic character sets — Part 1: Latin alphabet No. 1".
- [39] [ISO/IEC 8859-2](#): "Information technology — 8-bit single-byte coded graphic character sets — Part 2: Latin alphabet No. 2".
- [40] [ISO/IEC 8859-3](#): "Information technology — 8-bit single-byte coded graphic character sets — Part 3: Latin alphabet No. 3".
- [41] [ISO/IEC 8859-4](#): "Information technology — 8-bit single-byte coded graphic character sets — Part 4: Latin alphabet No. 4".
- [42] [ISO/IEC 8859-5](#): "Information technology — 8-bit single-byte coded graphic character sets — Part 5: Latin/Cyrillic alphabet".
- [43] [ISO/IEC 8859-6](#): "Information technology — 8-bit single-byte coded graphic character sets — Part 6: Latin/Arabic alphabet".
- [44] [ISO/IEC 8859-7](#): "Information technology — 8-bit single-byte coded graphic character sets — Part 7: Latin/Greek alphabet".
- [45] [ISO/IEC 8859-8](#): "Information technology — 8-bit single-byte coded graphic character sets — Part 8: Latin/Hebrew alphabet".
- [46] [ISO/IEC 8859-9](#): "Information technology — 8-bit single-byte coded graphic character sets — Part 9: Latin alphabet No. 5".
- [47] [ISO/IEC 8859-10](#): "Information technology — 8-bit single-byte coded graphic character sets — Part 10: Latin alphabet No. 6".
- [48] [ISO/IEC 8859-11](#): "Information technology — 8-bit single-byte coded graphic character sets — Part 11: Latin/Thai alphabet".
- [49] [ISO/IEC 8859-13](#): "Information technology — 8-bit single-byte coded graphic character sets — Part 13: Latin alphabet No. 7".
- [50] [ISO/IEC 8859-14](#): "Information technology — 8-bit single-byte coded graphic character sets — Part 14: Latin alphabet No. 8 (Celtic)".
- [51] [ISO/IEC 8859-15](#): "Information technology — 8-bit single-byte coded graphic character sets — Part 15: Latin alphabet No. 9".
- [52] [ISO/IEC 10646](#): "Information technology — Universal Coded Character Set (UCS)".
- [53] [GB-2312-1980](#): "Code of Chinese graphic character set for information interchange -- primary set".
- [54] [KS X 1001-2014](#): "Code for Information Interchange (Hangeul and Hanja)", Korean Agency for Technology and Standards, 2014.

NOTE: See <https://standard.go.kr/KSCI/standardIntro/getStandardSearchView.do?ksNo=KSX1001>. This document has been published in Korean only.

- [55] Void.
- [56] [ETSI EN 301 545-2](#): "Digital Video Broadcasting (DVB); Second Generation DVB Interactive Satellite System (DVB-RCS2); Part 2: Lower Layers for Satellite standard".
- [57] [DVB BlueBook A180](#): "Native IP Broadcasting".
- [58] [TA/I 109.3](#): "Information Technology - Intelligent Media Coding (AVS3) Part 3: Immersive Audio".
- [59] [T/AI 109.7](#): "Information Technology - Intelligent Media Coding (AVS3) Part 7: Audio Encapsulation and Transport".
- [60] [Recommendation ITU-R BS.2076-2](#): "Audio definition model".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long-term validity.

The following referenced documents may be useful in implementing an ETSI deliverable or add to the reader's understanding, but are not required for conformance to the present document.

- [i.1] ETSI TS 101 211: "Digital Video Broadcasting (DVB); Implementation and usage of Service Information (SI)".
- [i.2] ETSI TS 102 727: "Digital Video Broadcasting (DVB); Multimedia Home Platform (MHP) Specification 1.2.2".
- [i.3] ETSI TS 103 205: "Digital Video Broadcasting (DVB); Extensions to the CI Plus™ Specification".
- [i.4] ETSI TS 103 286-2: "Digital Video Broadcasting (DVB); Companion Screens and Streams; Part 2: Content Identification and Media Synchronization".
- [i.5] ETSI TR 102 825 (parts 6, 8, 11 to 13): "Digital Video Broadcasting (DVB); Content Protection and Copy Management (DVB-CPCM)".
- [i.6] ATIS 0800006: "IIF Default Scrambling Algorithm (IDSA) IPTV Interoperability Specification".
- [i.7] IEC 61883 (parts 1 and 4): "Consumer audio/video equipment — Digital interface".
- [i.8] IEEE 1394.1™: "IEEE Standard for High Performance Serial Bus Bridges".
- [i.9] [Directive \(EU\) 2018/1808](#) of the European Parliament and of the Council of 14 November 2018 amending Directive 2010/13/EU on the coordination of certain provisions laid down by law, regulation or administrative action in Member States concerning the provision of audiovisual media services (Audiovisual Media Services Directive) in view of changing market realities".
- [i.10] AIAA 2006-6753-Rev1: "[Revisiting Space track Report #3](#)", American Institute of Aeronautics and Astronautics.
- [i.11] NGA.STND.0036-1.0.0-WGS84: "Department of Defense World Geodetic System 1984: Its Definition and Relationships with Local Geodetic Systems", Version 1.0.0, 8 July 2014.
- [i.12] [ISO 8601-1](#): "Date and time — Representations for information interchange — Part 1: Basic rules".
- [i.13] [IEEE 754™-2019](#): "IEEE Standard for Floating-Point Arithmetic".

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the following terms apply:

AC-3: coding of audio using the Dolby AC-3 audio compression method as defined in ETSI TS 101 154 [14], clause 6.2

NOTE: The service information requirements for AC-3 streams carried in DVB systems are described in annex D. The carriage of AC-3 elementary streams as private data within MPEG systems is described in ETSI TS 101 154 [14], clause 6.2.

AC-4: coding of audio using the Dolby AC-4 audio compression method as defined in clause 6.6 and clause 6.7 of ETSI TS 101 154 [14]

NOTE: The Service Information requirements for AC-4 streams carried in DVB systems are described in annex D. The carriage of AC-4 elementary streams as private data within MPEG systems is described in clause 6.6 and clause 6.7 of ETSI TS 101 154 [14].

audio preselection: set of audio programme components representing a version of the audio programme that may be selected by a user for simultaneous decoding

NOTE: An audio preselection is a sub-selection from all available audio programme components of one audio programme. An audio preselection can be considered the NGA equivalent of audio services in predecessor systems, which each utilized complete mixes.

audio programme: complete collection of all audio programme components and a set of accompanying audio preselections

NOTE: Not all audio programme components of an audio programme are necessarily meant to be presented at the same time. An audio programme may contain audio programme components that are always presented, and it may include optional audio programme components.

audio programme component: the smallest addressable unit of an audio programme

auxiliary NGA stream: NGA stream delivered using NGA multi-stream delivery, and containing additional audio programme components not contained in the main NGA stream

AVS3-P3: Audio Codec as defined in TA/I 109.3 [58]

bouquet: collection of services marketed as a single entity

broadcaster: organization which assembles a sequence of events or data streams to be delivered to the viewer; the delivery can be based upon a schedule

cell: geographical area that is covered with DVB signals delivering one or more particular transport or other DVB streams throughout the area by means of one or more transmitters

NOTE: The cell may in addition contain repeaters. Two neighbouring cells may be intersecting, or fully overlapping. The *cell_id* that is used to uniquely identify a cell is unique within each *original_network_id*. For hand-over purposes it is more convenient if the transport streams associated with the cell cover exactly the same area, or only one transport stream per cell is used.

component: one or more entities which together make up an event

EXAMPLE: Video, audio, teletext.

conditional access system: system to control subscriber access to services, data streams and events

EXAMPLE: Videoguard, Eurocrypt.

delivery system: physical medium by which one or more DVB transport streams are transmitted

EXAMPLE: Satellite system, wide-band coaxial cable, fibre optics, terrestrial channel of one emitting point.

dependent stream: stream or component which relies on another stream or component in order to be rendered as intended

EXAMPLE: A dependent view of a 3D video, or a receiver-mix audio description stream.

DTS: coding of audio using the DTS audio compression method as defined in ETSI TS 101 154 [14], clause 6.3

NOTE: The service information requirements for DTS are found in annex G.

DTS-HD: coding of audio using the DTS-HD audio compression method as defined in ETSI TS 101 154 [14], clause 6.3

NOTE: The service information requirements for DTS-HD are found in annex G. Note that DTS-HD is a superset of DTS.

DTS-UHD: coding of audio using the DTS-UHD audio compression method as defined in ETSI TS 101 154 [14], clause 6.9

NOTE: The service information requirements for DTS-UHD are found in annex G.

DVB transport stream: MPEG-2 transport stream (ISO/IEC 13818-1 [1]) containing the mandatory service information signalling as defined in the present document

NOTE: It is recommended that the service information implementation specification ETSI TS 101 211 [i.1] is additionally followed. It defines further requirements for the signalling to help improve the quality of experience for viewers.

event: grouping of elementary broadcast data streams with a defined start time and duration belonging to a common service

EXAMPLE: First half of a football match, News Flash, first part of an entertainment show.

HEVC_UHDTV_IRD: initial ultra high definition IRD profile defined in ETSI TS 101 154 [14]

main NGA stream: NGA stream delivered using NGA multi-stream delivery, and containing at least all the audio programme components corresponding to at least one audio preselection

MPEG-2: ISO/IEC 13818 set of standards

NOTE: Systems coding is defined in part 1 [1], video coding is defined in part 2, and audio coding is defined in part 3 of ISO/IEC 13818.

MPEG-4: coding of video using the H.264/AVC video compression method as defined in clause 5.6 and clause 5.7 of ETSI TS 101 154 [14], or coding of audio using the AAC, HE-AAC, and HE-AAC v2 audio compression methods as defined in clause 6.4 and clause 6.5 of ETSI TS 101 154 [14]

NOTE: The service information requirements for MPEG-4 streams carried in DVB systems are described in annex H.

MPEG-H: coding of audio using the audio compression method as defined in clause 6.8 of ETSI TS 101 154 [14]

multi-stream delivery: method for carrying audio programme components in several NGA streams

NOTE: E.g. when audio programme components offering additional languages are carried in separate elementary streams to facilitate remultiplexing or service aggregation.

network: managed and navigable collection of DVB transport streams transmitted on one or more delivery systems generally based on the same physical medium

NOTE 1: It is possible to operate both, first and second generation delivery systems in the same network (e.g. DVB-T and DVB-T2).

NOTE 2: A network is identified by its *network_id*. It might be composed of one or more emitting sites.