



**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
Technical characteristics and methods of measurement
for shipborne watchkeeping receivers
for reception of Digital Selective Calling (DSC)
in the maritime MF, MF/HF and VHF bands**

[ETSI EN 301 033 V1.3.6 \(2013-07\)](https://standards.iteh.ai/catalog/standards/etsi/71806a91-da9f-45a9-a38b-623359136481/etsi-en-301-033-v1-3-6-2013-07)

<https://standards.iteh.ai/catalog/standards/etsi/71806a91-da9f-45a9-a38b-623359136481/etsi-en-301-033-v1-3-6-2013-07>

ReferenceREN/ERM-TG26-098

Keywords

DSC, maritime, radio, receiver

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iteh Standards
(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2012.
All rights reserved.

DECTTM, PLUGTESTSTM, UMTSTM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPPTM and LTETM are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	7
Foreword.....	7
1 Scope	8
2 References	8
2.1 Normative references	8
2.2 Informative references.....	9
3 Definitions and abbreviations.....	9
3.1 Definitions.....	9
3.2 Abbreviations	10
4 General and operational requirements.....	10
4.1 General	10
4.2 Construction	10
4.2.1 General.....	10
4.2.2 Design.....	10
4.2.3 Accessibility	11
4.2.4 Calibration and maintenance.....	11
4.2.5 Antenna static protection	11
4.2.6 Digital input panels.....	11
4.3 Controls and indicators.....	11
4.3.1 General.....	11
4.3.2 Identification.....	11
4.3.3 Protection against possible maladjustment	11
4.3.4 Light sources.....	11
4.3.5 Operation	11
4.4 Software	12
4.5 Memory	12
4.6 Interfaces (applicable to non-integrated equipment)	12
4.6.1 Audio Frequency	12
4.6.2 Digital interfaces.....	12
4.7 Marking and identification	12
4.8 Instructions.....	13
4.9 Warming-up period	13
4.10 Safety precautions	13
4.10.1 Excessive current and voltage.....	13
4.10.2 Earthing	13
4.10.3 Protection.....	13
4.11 Compass safe distance.....	13
5 Technical requirements	14
5.1 Frequency bands and channels	14
5.2 Mode of reception	14
5.3 Scanning receivers.....	15
5.3.1 Scanning sequence.....	15
5.3.2 Scanning frequencies	15
5.3.2.1 DSC distress frequencies.....	15
5.3.2.2 DSC frequencies for general communication.....	15
5.3.3 Stop/start of scanning.....	15
5.3.4 Frequency information.....	15
6 General test conditions	15
6.1 General	15
6.2 Test power source.....	15
6.3 Normal test conditions.....	16
6.3.1 Normal temperature and humidity	16
6.3.2 Normal test power source	16

6.3.2.1	ac voltage and frequency.....	16
6.3.2.2	Secondary battery power sources.....	16
6.3.2.3	Other power sources.....	16
6.4	Extreme test conditions	16
6.4.1	Extreme temperature tests.....	16
6.4.2	Extreme values of test power source	16
6.4.2.1	a.c. voltage and frequency.....	16
6.4.2.2	Secondary battery power sources.....	16
6.4.2.3	Other power sources.....	17
6.5	Connection of test signals to the receiver	17
6.5.1	Sources.....	17
6.5.2	Levels.....	17
6.6	Testing frequencies.....	17
6.6.1	General test frequencies.....	17
6.6.2	Additional test frequencies for HF equipment.....	17
6.7	Test signals.....	18
6.7.1	Reference to standard DSC signals.....	18
6.7.2	Standard DSC test signal 1	18
6.7.3	Standard DSC test signal 2	18
6.8	Measurement of symbol error rate	18
6.9	Measurement uncertainty and interpretation of the measuring results	18
6.9.1	Measurement uncertainty.....	18
6.9.2	Interpretation of measurement results.....	19
7	Environmental tests	19
7.1	Procedure.....	19
7.2	Performance check	19
7.3	Vibration test	19
7.3.1	Definition.....	19
7.3.2	Method of measurement	19
7.3.3	Requirement.....	20
7.4	Temperature tests	20
7.4.1	Dry heat	20
7.4.1.1	Definition	20
7.4.1.2	Method of measurement.....	20
7.4.1.3	Requirement	20
7.4.2	Damp heat	21
7.4.2.1	Definition	21
7.4.2.2	Method of measurement.....	21
7.4.2.3	Requirement	21
7.4.3	Low temperature.....	21
7.4.3.1	Definition	21
7.4.3.2	Method of measurement.....	21
7.4.3.3	Requirement	21
7.5	Corrosion test	22
7.5.1	General.....	22
7.5.2	Definition.....	22
7.5.3	Method of measurement	22
7.5.4	Requirements	22
8	MF/HF watchkeeping receiver	22
8.1	General	22
8.2	Calling sensitivity	22
8.2.1	Definition.....	22
8.2.2	Method of measurement	22
8.2.3	Limits.....	23
8.3	Adjacent channel selectivity.....	23
8.3.1	Definition.....	23
8.3.2	Method of measurement	23
8.3.3	Limits.....	23
8.4	Co-channel rejection.....	23
8.4.1	Definition.....	23

8.4.2	Method of measurements	23
8.4.3	Limits	24
8.5	RF intermodulation response	24
8.5.1	Definition	24
8.5.2	Method of measurement	24
8.5.3	Limits	24
8.6	Spurious response rejection	24
8.6.1	Definition	24
8.6.2	Method of measurement	24
8.6.3	Limits	25
8.7	Blocking immunity	25
8.7.1	Definition	25
8.7.2	Method of measurement	25
8.7.3	Limits	26
8.8	Dynamic range	26
8.8.1	Definition	26
8.8.2	Method of measurement	26
8.8.3	Limits	26
8.9	Conducted spurious emissions into the antenna	26
8.9.1	Definition	26
8.9.2	Method of measurement	26
8.9.3	Limits	26
8.10	Radiated spurious emissions	27
8.10.1	Definition	27
8.10.2	Method of measurements	27
8.10.3	Limit	28
8.11	Protection of receiver antenna input circuits	28
8.11.1	Definition	28
8.11.2	Method of measurement	28
8.11.3	Limits	28
8.12	Scanning efficiency	28
8.12.1	Definition	28
8.12.2	Method of measurement	28
8.12.3	Limits	29
9	VHF watchkeeping receiver	29
9.1	General	29
9.2	Calling sensitivity	29
9.2.1	Definition	29
9.2.2	Method of measurement	29
9.2.3	Limits	29
9.3	Adjacent channel selectivity	29
9.3.1	Definition	29
9.3.2	Method of measurement	29
9.3.3	Limits	30
9.4	Co-channel rejection	30
9.4.1	Definition	30
9.4.2	Method of measurement	30
9.4.3	Limits	30
9.5	Intermodulation response	30
9.5.1	Definition	30
9.5.2	Method of measurement	30
9.5.3	Limits	31
9.6	Spurious response rejection	31
9.6.1	Definition	31
9.6.2	Method of measurement	31
9.6.3	Limits	32
9.7	Blocking immunity	32
9.7.1	Definition	32
9.7.2	Method of measurement	32
9.7.3	Limits	32
9.8	Dynamic range	32

9.8.1	Definition	32
9.8.2	Method of measurement	32
9.8.3	Limit	32
9.9	Conducted spurious emissions into the antenna	33
9.9.1	Definition	33
9.9.2	Method of measurement	33
9.9.3	Limit	33
9.10	Radiated spurious emission	33
9.10.1	Definition	33
9.10.2	Method of measurements	33
9.10.3	Limit	34

Annex A (normative): Radiated measurements35

A.1	Test sites and general arrangements for measurements involving the use of radiated fields	35
A.1.1	Outdoor test site	35
A.1.2	Test antenna	36
A.1.3	Substitution antenna	36
A.1.4	Optional additional indoor site	36
A.2	Guidance on the use of radiation test sites	37
A.2.1	Measuring distance	37
A.2.2	Test antenna	37
A.2.3	Substitution antenna	37
A.2.4	Artificial antenna	38
A.2.5	Auxiliary cables	38
A.2.6	Acoustic measuring arrangement	38
A.3	Further optional alternative indoor test site using an anechoic chamber	38
A.3.1	Example of the construction of a shielded anechoic chamber	39
A.3.2	Influence of parasitic reflections in anechoic chambers	39
A.3.3	Calibration of the shielded anechoic chamber	40

Annex B (informative): Bibliography42

History	43
---------------	----

ETSI EN 301 033 V1.3.6 (2013-07)

<https://standards.iteh.ai/catalog/standards/etsi/71806a91-da9f-45a9-a38b-623359136481/etsi-en-301-033-v1-3-6-2013-07>