

ETSI EN 301 178-1 V1.4.1 (2011-11)



**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
Portable Very High Frequency (VHF) radiotelephone
equipment for the maritime mobile service operating
in the VHF bands (for non-GMDSS applications only);
Part 1: Technical characteristics and
methods of measurement**

Reference

REN/ERM-TG26-095-1

Keywords

maritime, radio, VHF

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2011.
All rights reserved.

DECTTM, PLUGTESTSTM, UMTSTM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPPTM and LTETM are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	7
Foreword.....	7
1 Scope	8
2 References	8
2.1 Normative references	8
2.2 Informative references.....	9
3 Definitions, symbols and abbreviations	9
3.1 Definitions.....	9
3.2 Symbols.....	9
3.3 Abbreviations	9
4 General and operational requirements.....	10
4.1 Construction	10
4.2 Controls and indicators.....	10
4.3 Microphone and loudspeaker	11
4.4 Safety precautions	11
4.5 Labelling.....	11
5 Technical requirements	12
5.1 Switching time.....	12
5.2 Class of emission and modulation characteristics	12
6 General conditions of measurement	12
6.1 Arrangements for RF connections to the equipment	12
6.1.1 RF connections to integral antenna equipment	12
6.1.2 RF connection to equipment with a detachable antenna	12
6.2 Arrangements for test signals applied to the receiver input.....	12
6.3 Squelch.....	12
6.4 Normal test modulation	12
6.5 Artificial antenna.....	13
6.6 Arrangements for test signals applied to the transmitter input	13
6.7 Test channels	13
6.8 Measurement uncertainty and interpretation of the measured results	13
6.8.1 Measurement uncertainty.....	13
6.8.2 Interpretation of the measurement results	13
6.9 Test conditions, power sources and ambient temperatures.....	14
6.9.1 Normal and extreme test conditions.....	14
6.9.2 Test power source	14
6.10 Normal test conditions.....	14
6.10.1 Normal temperature and humidity	14
6.10.2 Normal power sources	14
6.10.2.1 Battery power source.....	14
6.10.2.2 Other power sources.....	14
6.11 Extreme test conditions	14
6.11.1 Extreme temperatures	15
6.11.2 Extreme values of test power sources	15
6.11.2.1 Battery power source.....	15
6.11.2.2 Other power sources.....	15
6.12 Procedure for tests at extreme temperatures	15
7 Environmental tests	15
7.1 Procedure.....	15
7.2 Performance check	15
7.3 Drop test.....	16
7.3.1 Definition.....	16
7.3.2 Method of measurement	16

7.3.3	Requirement.....	16
7.4	Temperature tests	16
7.4.1	Definition.....	16
7.4.2	Dry heat	16
7.4.2.1	Definition	16
7.4.2.2	Method of measurement.....	16
7.4.2.3	Requirement	16
7.4.3	Damp heat.....	17
7.4.3.1	Definition	17
7.4.3.2	Method of measurement.....	17
7.4.3.3	Requirement	17
7.4.4	Low temperature cycle.....	17
7.4.4.1	Definition	17
7.4.4.2	Method of measurement.....	17
7.4.4.3	Requirement	17
8	Transmitter	17
8.1	Frequency error	17
8.1.1	Definition.....	17
8.1.2	Method of measurement	18
8.1.3	Limits.....	18
8.2	Carrier power.....	18
8.2.1	Definitions	18
8.2.2	Method of measurement	18
8.2.3	Limits, Normal and extreme test conditions	18
8.3	Frequency deviation	18
8.3.1	Definition.....	18
8.3.2	Maximum permissible frequency deviation.....	18
8.3.2.1	Method of measurement.....	18
8.3.2.2	Limits	19
8.3.3	Reduction of frequency deviation at modulation frequencies above 3 kHz.....	19
8.3.3.1	Method of measurement.....	19
8.3.3.2	Limits	19
8.4	Sensitivity of the modulator, including microphone	20
8.4.1	Definition.....	20
8.4.2	Method of measurement	20
8.4.3	Limits.....	20
8.5	Audio frequency response	20
8.5.1	Definition.....	20
8.5.2	Method of measurement	21
8.5.3	Limit	21
8.6	Audio frequency harmonic distortion of the emission.....	22
8.6.1	Definition.....	22
8.6.2	Method of measurement	22
8.6.2.1	Normal test conditions	22
8.6.2.2	Extreme test conditions	22
8.6.3	Limits.....	22
8.7	Adjacent channel power	22
8.7.1	Definition.....	22
8.7.2	Method of measurement	22
8.7.3	Limits.....	23
8.8	Conducted spurious emissions conveyed to the antenna	23
8.8.1	Definition.....	23
8.8.2	Method of measurement	23
8.8.3	Limit	23
8.9	Cabinet radiation and conducted spurious emissions other than those conveyed to the antenna	23
8.9.1	Definitions	23
8.9.2	Method of measurement	24
8.9.3	Limits.....	25
8.10	Residual modulation of the transmitter	25
8.10.1	Definition.....	25
8.10.2	Method of measurement	25

8.10.3	Limit	25
8.11	Transient frequency behaviour of the transmitter.....	25
8.11.1	Definitions	25
8.11.2	Method of measurement	26
8.11.3	Limits.....	27
9	Receiver.....	29
9.1	Harmonic distortion and rated audio frequency output power	29
9.1.1	Definition.....	29
9.1.2	Methods of measurement.....	29
9.1.3	Limits.....	29
9.2	Audio frequency response	29
9.2.1	Definition.....	29
9.2.2	Method of measurement	29
9.2.3	Limits.....	30
9.3	Maximum usable sensitivity.....	30
9.3.1	Definition.....	30
9.3.2	Method of measurement	31
9.3.3	Limits.....	31
9.4	Co-channel rejection.....	31
9.4.1	Definition.....	31
9.4.2	Method of measurement	31
9.4.3	Limit	31
9.5	Adjacent channel selectivity.....	32
9.5.1	Definition.....	32
9.5.2	Method of measurement	32
9.5.3	Limits.....	32
9.6	Spurious response rejection.....	32
9.6.1	Definition.....	32
9.6.2	Method of measurement	32
9.6.3	Limit	33
9.7	Intermodulation response	33
9.7.1	Definition.....	33
9.7.2	Method of measurement	33
9.7.3	Limit	33
9.8	Blocking or desensitization	33
9.8.1	Definition.....	33
9.8.2	Method of measurement	33
9.8.3	Limit	34
9.9	Conducted spurious emissions	34
9.9.1	Definition.....	34
9.9.2	Method of measurement	34
9.9.3	Limit	34
9.10	Radiated spurious emissions.....	34
9.10.1	Definition.....	34
9.10.2	Method of measurements.....	34
9.10.3	Limit	35
9.11	Receiver noise and hum level.....	35
9.11.1	Definition.....	35
9.11.2	Method of measurement	35
9.11.3	Limit	36
9.12	Squelch operation.....	36
9.12.1	Definition.....	36
9.12.2	Method of measurement	36
9.12.3	Limits.....	36
9.13	Squelch hysteresis	37
9.13.1	Definition.....	37
9.13.2	Method of measurement	37
9.13.3	Limit	37

Annex A (normative): Measuring receiver for adjacent channel power measurement.....38

A.1 Power measuring receiver specification.....38

A.1.1	IF filter	38
A.1.2	Attenuation indicator	39
A.1.3	Rms value indicator	39
A.1.4	Oscillator and amplifier	39
Annex B (normative): Radiated measurement.....		40
B.1	Test sites and general arrangements for measurements involving the use of radiated fields	40
B.1.1	Anechoic chamber	40
B.1.2	Anechoic chamber with a ground plane	41
B.1.3	OATS	42
B.1.4	Test antenna.....	43
B.1.5	Substitution antenna	43
B.1.6	Measuring antenna	44
B.2	Guidance on the use of radiation test sites	44
B.2.1	Verification of the test site	44
B.2.2	Preparation of the EUT.....	44
B.2.3	Power supplies to the EUT	44
B.2.4	Volume control setting for analogue speech tests	44
B.2.5	Range length.....	45
B.2.6	Site preparation	45
B.3	Coupling of signals.....	46
B.3.1	General	46
B.3.2	Data signals	46
B.3.3	Speech and analogue signals	46
B.3.3.1	Acoustic coupler description.....	46
B.3.3.2	Calibration	47
History		48

<https://standards.iteh.ai>
 Document Preview

[ETSI EN 301 178-1 V1.4.1 \(2011-11\)](https://standards.iteh.ai/catalog/standards/etsi/638ee1cc-1ed4-4422-bf81-a397e8ca393b/etsi-en-301-178-1-v1-4-1-2011-11)

<https://standards.iteh.ai/catalog/standards/etsi/638ee1cc-1ed4-4422-bf81-a397e8ca393b/etsi-en-301-178-1-v1-4-1-2011-11>