

ETSI EN 301 406-1 V3.2.0 (2026-01)



**Digital Enhanced Cordless Telecommunications (DECT);
Harmonised Standard for access to radio spectrum;
Part 1: DECT, DECT Evolution and DECT ULE**

Document Preview

[ETSI EN 301 406-1 V3.2.0 \(2026-01\)](https://standards.iteh.ai/catalog/standards/etsi/110c1282-4dab-4565-9010-27226f2c8539/etsi-en-301-406-1-v3-2-0-2026-01)

<https://standards.iteh.ai/catalog/standards/etsi/110c1282-4dab-4565-9010-27226f2c8539/etsi-en-301-406-1-v3-2-0-2026-01>

Reference

REN/DECT-00411

Keywords

DECT, digital, generic, radio, regulation, testing

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed,
this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.
In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2026.
All rights reserved.

Contents

Intellectual Property Rights	11
Foreword.....	11
Modal verbs terminology.....	12
1 Scope	13
2 References	14
2.1 Normative references	14
2.2 Informative references.....	14
3 Definition of terms, symbols and abbreviations.....	16
3.1 Terms.....	16
3.2 Symbols.....	19
3.3 Abbreviations	19
4 Technical requirements specifications	20
4.1 Environmental profile.....	20
4.2 Overview	20
4.2.0 General.....	20
4.2.1 Test suites	20
4.2.2 Test groups.....	20
4.2.3 Test cases	21
4.3 Product information for testing	21
4.3.1 Information on capabilities and options implemented	21
4.3.2 Additional information on implementation for testing	22
4.4 Applicability of tests	22
4.4.0 Introduction.....	22
4.4.1 Equipment that includes only a DECT RF receiver.....	22
4.4.2 Equipment that includes a radio transmitter	22
4.4.3 Void	22
4.4.4 Equipment with combined FT and PT functionality.....	22
4.4.4.0 General	22
4.4.4.1 Wireless Relay Station	23
4.4.4.2 Direct PP to PP communication	23
4.4.4.3 Distributed Communications.....	23
4.4.5 Equipment that is capable of using higher level modulation	23
4.5 Conformance requirements	23
4.5.1 Accuracy and stability of RF carriers	23
4.5.1.1 Designation of RF carriers	23
4.5.1.2 Limits	24
4.5.1.3 Conformance.....	24
4.5.2 Accuracy and stability of timing parameters	24
4.5.2.0 General	24
4.5.2.1 Definitions.....	24
4.5.2.1.1 Slot structure.....	24
4.5.2.1.2 Definition of the position of p0	24
4.5.2.1.3 Definition of reference timer	25
4.5.2.2 Limits	25
4.5.2.2.1 Reference timer accuracy and stability.....	25
4.5.2.2.2 RFP transmission jitter	25
4.5.2.2.3 PP reference timer synchronization.....	25
4.5.2.3 Conformance.....	26
4.5.3 Transmission burst.....	26
4.5.3.1 Definitions.....	26
4.5.3.1.0 Introduction	26
4.5.3.1.1 Physical packets.....	26
4.5.3.1.2 Transmitted power.....	26
4.5.3.1.3 Normal Transmitted Power (NTP)	27

4.5.3.1.4	Transmitter attack time.....	27
4.5.3.1.5	Transmitter release time	27
4.5.3.1.6	Minimum power	27
4.5.3.1.7	Maximum power	27
4.5.3.1.8	Maintenance of transmission after packet end.....	27
4.5.3.1.9	Transmitter idle power output	27
4.5.3.2	Limits	27
4.5.3.2.1	Transmitter attack time.....	27
4.5.3.2.2	Transmitter release time	27
4.5.3.2.3	Minimum power	27
4.5.3.2.4	Maximum power	27
4.5.3.2.5	Maintenance of transmission after packet end.....	28
4.5.3.2.6	Transmitter idle power output	28
4.5.3.3	Conformance.....	28
4.5.4	Transmitted power	28
4.5.4.1	Definitions.....	28
4.5.4.1.0	Transceiver and P_{NTP} definitions.....	28
4.5.4.2	Limits	29
4.5.4.2.0	P_{NTP} Limit	29
4.5.4.2.1	PP and RFP with an integral antenna	29
4.5.4.2.2	PP and RFP with external connections for all antennas	29
4.5.4.2.3	PP and RFP with both integral and external antennas	29
4.5.4.3	Conformance.....	29
4.5.4.4	Multi-transceiver systems	29
4.5.5	RF carrier modulation.....	29
4.5.5.1	Definition	29
4.5.5.1.1	GFSK modulation.....	29
4.5.5.1.2	Non-constant envelope modulation.....	30
4.5.5.2	Limit.....	30
4.5.5.2.1	GFSK modulation.....	30
4.5.5.2.2	Non-constant envelope modulation.....	30
4.5.5.3	Conformance.....	31
4.5.6	Unwanted RF power radiation.....	31
4.5.6.1	General	31
4.5.6.2	Emissions due to modulation	31
4.5.6.2.1	Definition.....	31
4.5.6.2.2	Limits	31
4.5.6.2.3	Conformance	31
4.5.6.3	Emissions due to transmitter transients.....	31
4.5.6.3.1	Definition.....	31
4.5.6.3.2	Limits	31
4.5.6.3.3	Conformance	32
4.5.6.4	Emissions due to intermodulation	32
4.5.6.4.1	Definition.....	32
4.5.6.4.2	Limits	32
4.5.6.4.3	Conformance	32
4.5.6.5	Spurious emissions when allocated a transmit channel.....	32
4.5.6.5.1	Definition.....	32
4.5.6.5.2	Limits	32
4.5.6.5.3	Conformance	33
4.5.7	Radio receiver requirements	33
4.5.7.1	Radio receiver sensitivity	33
4.5.7.1.1	Definition.....	33
4.5.7.1.2	Limits	33
4.5.7.1.3	Conformance	33
4.5.7.2	Radio receiver reference BER and FER.....	33
4.5.7.2.1	Definition.....	33
4.5.7.2.2	Limits	33
4.5.7.2.3	Conformance	34
4.5.7.3	Radio receiver interference performance	34
4.5.7.3.1	Definition.....	34

4.5.7.3.2	Limits	34
4.5.7.3.3	Conformance	34
4.5.7.4	Radio receiver blocking case 1: owing to signals occurring at the same time but on other frequencies	34
4.5.7.4.1	Definition.....	34
4.5.7.4.2	Limits	34
4.5.7.4.3	Conformance	35
4.5.7.5	Radio receiver blocking case 2: owing to signals occurring at a different time.....	35
4.5.7.5.1	Definition.....	35
4.5.7.5.2	Limits	35
4.5.7.5.3	Conformance	35
4.5.7.6	Receiver intermodulation performance.....	35
4.5.7.6.1	Definition.....	35
4.5.7.6.2	Limits	35
4.5.7.6.3	Conformance	35
4.5.7.7	Spurious emissions when the PP has no allocated transmit channel.....	35
4.5.7.7.1	Definition.....	35
4.5.7.7.2	Limits	35
4.5.7.7.3	Conformance	36
4.5.8	Channel access.....	36
4.5.8.1	Channel selection	36
4.5.8.2	Channel confirmation.....	36
4.5.8.2.1	For the PT.....	36
4.5.8.2.2	For the FT.....	36
4.5.8.3	Channel release	37
4.5.8.4	General.....	37
4.5.8.5	Channel selection and confirmation for DECT ULE.....	37
4.5.8.5.1	General	37
4.5.8.5.2	For the PT.....	37
4.5.8.5.3	For the FT.....	37
4.5.9	WRS.....	37
4.5.9.0	General requirements	37
4.5.9.1	PP operation	38
4.5.9.2	RFP operation	38
4.5.9.3	Additional requirements	38
4.5.9.4	Conformance.....	39
4.5.10	Direct PP to PP communication.....	39
4.5.10.1	General requirements	39
4.5.10.2	Conformance.....	39
4.5.11	Distributed communications	39
4.5.11.0	General requirements	39
4.5.11.1	PP operation	39
4.5.11.2	RFP operation	39
4.5.11.3	Conformance.....	40
4.5.12	Higher level modulation options.....	40
4.5.12.0	Requirements	40
4.5.12.1	Conformance.....	40
5	Testing for compliance with technical requirements.....	41
5.0	Environmental conditions for testing	41
5.1	General test requirements	41
5.1.1	Test philosophy.....	41
5.1.1.1	General	41
5.1.1.2	Lower Tester (LT).....	41
5.1.1.3	Non-signalling test mode	42
5.1.1.4	Test environment.....	43
5.1.1.4.1	General	43
5.1.1.4.2	Conducted test	43
5.1.1.4.3	Radiated test	43
5.1.2	Test site.....	43
5.1.2.1	Open air test site.....	43
5.1.2.1.1	Description	43

5.1.2.2	Anechoic chamber.....	44
5.1.2.2.1	General	44
5.1.3	Standard position	44
5.1.4	Test antenna of the LT.....	44
5.1.5	Substitution antenna.....	44
5.1.6	Test fixture.....	44
5.1.7	Equipment with a temporary or internal permanent antenna connector.....	45
5.1.7.1	General	45
5.1.7.2	Equipment with a temporary antenna connector.....	45
5.1.8	Void	45
5.1.9	Lower Tester (LT)	45
5.1.9.1	Description	45
5.1.9.2	Connections between the EUT and the LT	46
5.1.9.3	Functions and abilities.....	46
5.1.9.4	Signal generation uncertainty.....	47
5.1.9.5	Modulated DECT-like carrier	47
5.1.9.6	CW interferers.....	47
5.1.9.7	DECT RF signal.....	47
5.1.9.8	Test modulation signals.....	47
5.1.10	Upper Tester (UT)	47
5.1.10.1	Description of the UT.....	47
5.1.10.2	The Test Standby Mode (TSM)	48
5.1.10.3	Test messages.....	48
5.1.10.4	Dummy setting when EUT is an RFP and is in Test Standby Mode (TSM).....	48
5.1.11	Description of the lower tester FT and PT	48
5.1.12	General test methods.....	49
5.1.12.1	General	49
5.1.12.2	Sampling the RF signal	49
5.1.12.2.1	Introduction	49
5.1.12.2.2	Sampling method.....	49
5.1.12.3	Determining the reference position	49
5.1.12.3.0	General	49
5.1.12.3.1	Case 1: EUTs that cannot transmit	49
5.1.12.3.2	Case 2: EUTs that can transmit	49
5.1.12.4	Bit Error Ratio (BER) and Frame Error Ratio (FER) measurements.....	49
5.1.13	Test setup	50
5.1.13.1	General	50
5.1.13.2	Test setup 1	50
5.1.13.3	Test setup 2	50
5.1.13.4	Test setup 3	51
5.1.13.5	Test setup 4	51
5.1.14	Test arrangements for intermodulation measurements	52
5.1.14.1	PT to PT arrangement	52
5.1.14.2	FT to FT arrangement	52
5.1.14.3	FT to PT arrangement	53
5.1.15	Test conditions, power supply and ambient temperatures	53
5.1.15.1	General	53
5.1.15.2	Nominal test conditions.....	53
5.1.15.3	Extreme test conditions.....	54
5.1.15.4	Test power source - general requirements.....	55
5.1.15.5	Nominal test power source.....	55
5.1.15.5.1	Mains voltage	55
5.1.15.5.2	Regulated lead acid battery power sources.....	55
5.1.15.5.3	Nickel cadmium or nickel metal hydride battery.....	55
5.1.15.5.4	Other power sources	55
5.1.15.6	Extreme test power source	55
5.1.15.6.1	Mains voltage	55
5.1.15.6.2	Regulated lead acid battery power sources.....	55
5.1.15.6.3	Nickel cadmium or nickel metal hydride battery.....	55
5.1.15.6.4	Other power sources	56
5.2	Interpretation of the measurement results	56
5.3	Radio test suites.....	56

5.3.1	Accuracy and stability of RF carriers	56
5.3.1.1	Test environment.....	56
5.3.1.2	Method of measurement.....	56
5.3.1.3	Verdict criteria when the EUT is an RFP	57
5.3.1.4	Verdict criteria when the EUT is a PP	57
5.3.2	Accuracy and stability of timing parameters	57
5.3.2.1	Measurement of packet timing jitter	57
5.3.2.1.1	Test environment.....	57
5.3.2.1.2	Method of measurement	57
5.3.2.1.3	Verdict criteria.....	58
5.3.2.2	Measurement of the reference timing accuracy of an RFP	58
5.3.2.2.1	Test environment.....	58
5.3.2.2.2	Method of measurement	58
5.3.2.2.3	Verdict criteria.....	58
5.3.2.3	Measurement of packet transmission accuracy of a PP.....	59
5.3.2.3.1	Test environment.....	59
5.3.2.3.2	Method of measurement	59
5.3.2.3.3	Verdict criteria.....	59
5.3.3	Transmission burst.....	60
5.3.3.1	Test environment.....	60
5.3.3.2	Method of measurement.....	60
5.3.3.3	Verdict criteria	60
5.3.4	Transmitted power	61
5.3.4.1	PP and RFP with an integral antenna	61
5.3.4.1.1	Test environment.....	61
5.3.4.1.2	Method of measurement	61
5.3.4.1.3	Verdict criteria for all EUTs.....	62
5.3.4.2	PP and RFP with external antenna connection(s).....	62
5.3.4.2.1	Test environment.....	62
5.3.4.2.2	Method of measurement	63
5.3.4.2.3	Verdict criteria for all EUTs.....	63
5.3.5	RF carrier modulation.....	63
5.3.5.1	Test environment.....	63
5.3.5.2	Method of measurement, GFSK parts 1 and 2	63
5.3.5.2.1	Introduction	63
5.3.5.2.2	Part 1	64
5.3.5.2.3	Part 2	64
5.3.5.3	Method of measurement, GFSK parts 3 and 4	64
5.3.5.3.0	General	64
5.3.5.3.1	Part 3	65
5.3.5.3.2	Part 4	65
5.3.5.4	Verdict criteria for GFSK part 1	65
5.3.5.5	Verdict criteria for GFSK part 2	65
5.3.5.6	Verdict criteria for GFSK part 3	65
5.3.5.7	Verdict criteria for GFSK part 4	66
5.3.5.8	Method of measurement for non-constant envelope modulation	67
5.3.5.9	Verdict criteria for non-constant envelope modulation.....	67
5.3.6	Unwanted RF power radiation.....	67
5.3.6.1	General test conditions.....	67
5.3.6.2	Emissions due to modulation	68
5.3.6.2.1	Test environment.....	68
5.3.6.2.2	Method of measurement	68
5.3.6.2.3	Verdict criteria.....	69
5.3.6.3	Emissions due to transmitter transients.....	69
5.3.6.3.1	Test environment.....	69
5.3.6.3.2	Method of measurement	69
5.3.6.3.3	Verdict criteria.....	69
5.3.6.4	Emissions due to intermodulation	70
5.3.6.4.1	Test environment.....	70
5.3.6.4.2	Method of measurement	70
5.3.6.4.3	Verdict criteria.....	71
5.3.6.5	Spurious emissions when allocated a transmit channel.....	71