



**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
ElectroMagnetic Compatibility (EMC)
standard for radio equipment and services;
Part 35: Specific requirements for Low Power Active Medical
Implants (LP-AMI) operating
in the 2 483,5 MHz to 2 500 MHz bands**

Reference

DEN/ERM-EMC-313

Keywords

EMC, health, radio, regulation

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2012.
All rights reserved.

DECTTM, PLUGTESTSTM, UMTSTM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPPTM and LTETM are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	5
Foreword.....	5
1 Scope	6
2 References	6
2.1 Normative references	6
2.2 Informative references.....	6
3 Definitions and abbreviations.....	7
3.1 Definitions.....	7
3.2 Abbreviations	8
4 Test conditions	8
4.1 General	8
4.2 Arrangements for test signals	9
4.2.1 Arrangements for test signals at the input of the transmitter	9
4.2.2 Arrangements for test signals at the output of the transmitter	9
4.2.2.1 LP-AMI transmitters	9
4.2.2.2 LP-AMI-P transmitters.....	9
4.2.3 Arrangements for test signals at the input of the receiver	9
4.2.4 Arrangements for test signals at the output of the receiver	10
4.2.5 Arrangements for testing transmitter and receiver together (as a system: LP-AMI together with an associated LP-AMI-P)	10
4.3 Exclusion bands.....	10
4.3.1 Exclusion bands for receivers	10
4.3.2 Exclusion band for transmitters	11
4.4 Narrow band responses of receivers.....	11
4.5 Normal test modulation	11
5 Performance assessment.....	11
5.1 General	11
5.2 Equipment which can provide a continuous communications link	12
5.3 Equipment which does not provide a continuous communications link.....	12
5.4 Ancillary equipment	12
5.5 Equipment's type classification	12
6 Performance criteria	12
6.1 Sub-classification of LP-AMI and LP-AMI-P devices.....	12
6.2 General performance criteria	13
6.3 Performance criteria and table.....	13
6.4 Performance criteria for continuous phenomena applied to transmitters	14
6.5 Performance criteria for transient phenomena applied to transmitters	14
6.6 Performance criteria for continuous phenomena applied to receivers.....	15
6.7 Performance criteria for transient phenomena applied to receivers.....	15
7 Applicability overview	15
7.1 Emission	15
7.1.1 General.....	15
7.1.2 Special conditions	15
7.2 Immunity	16
7.2.1 General.....	16
7.2.2 Special conditions	16
Annex A (normative): Definitions of types of LP-AMI and LP-AMI-P devices in the scope of the present document.....	20
A.1 LP-AMI and LP-AMI-P devices intended for operation in the frequency range 2 483,5 MHz to 2 500 MHz.....	20

Annex B (normative):	Test fixture for LP-AMI devices (Simulated man)	21
Annex C (informative):	Bibliography	23
History		24

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI EN 301 489-35 V1.1.2 \(2013-08\)](https://standards.iteh.ai/catalog/standards/etsi/d74f98fc-31ee-49fc-adc4-99bdd50f32e6/etsi-en-301-489-35-v1-1-2-2013-08)

<https://standards.iteh.ai/catalog/standards/etsi/d74f98fc-31ee-49fc-adc4-99bdd50f32e6/etsi-en-301-489-35-v1-1-2-2013-08>