



**Global System for Mobile communications (GSM);
Harmonized EN for Base Station Equipment covering the
essential requirements of article 3.2 of the R&TTE Directive**

[ETSI EN 301 502 V10.2.1 \(2012-11\)](https://standards.iteh.ai/catalog/standards/etsi/0437dcb9-8f7b-42f3-8511-5bb1a6983aa6/etsi-en-301-502-v10-2-1-2012-11)

<https://standards.iteh.ai/catalog/standards/etsi/0437dcb9-8f7b-42f3-8511-5bb1a6983aa6/etsi-en-301-502-v10-2-1-2012-11>

Reference

REN/MSG-0006

Keywords

base station, cellular, GSM

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2012.
All rights reserved.

DECTTM, PLUGTESTSTM, UMTSTM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPPTM and LTETM are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	7
Foreword.....	7
Introduction	7
1 Scope	8
2 References	8
2.1 Normative references	8
2.2 Informative references.....	10
3 Definitions and abbreviations.....	10
3.1 Definitions	10
3.2 Abbreviations	12
4 Technical requirements specifications	13
4.1 Environmental profile.....	13
4.2 Conformance requirements	14
4.2.1 Modulation accuracy.....	14
4.2.1.1 Definition	14
4.2.1.2 Limit.....	15
4.2.1.3 Conformance.....	16
4.2.2 Mean transmitted RF carrier power	16
4.2.2.1 Definition	16
4.2.2.2 Limit.....	16
4.2.2.3 Conformance	17
4.2.3 Transmitted RF carrier power versus time.....	17
4.2.3.1 Definition	17
4.2.3.2 Limit.....	17
4.2.3.3 Conformance	21
4.2.4 Adjacent channel power.....	21
4.2.4.1 Spectrum due to modulation and wideband noise.....	21
4.2.4.1.1 Definition.....	21
4.2.4.1.2 Limit	21
4.2.4.1.3 Conformance	23
4.2.4.2 Switching transients spectrum.....	23
4.2.4.2.1 Definition.....	23
4.2.4.2.2 Limit	23
4.2.4.2.3 Conformance	24
4.2.5 Spurious emissions from the transmitter antenna connector.....	24
4.2.5.1 Conducted spurious emissions from the transmitter antenna connector, inside the BTS transmit band.....	24
4.2.5.1.1 Definition.....	24
4.2.5.1.2 Limit	24
4.2.5.1.3 Conformance	24
4.2.5.2 Conducted spurious emissions from the transmitter antenna connector, outside the BTS transmit band.....	24
4.2.5.2.1 Definition.....	24
4.2.5.2.2 Limit	24
4.2.5.2.3 Conformance	25
4.2.5.3 Conducted spurious emissions from the transmitter antenna connector, in 3G bands outside the BTS transmit band	25
4.2.5.3.1 Definition.....	25
4.2.5.3.2 Limit	25
4.2.5.3.3 Conformance	26
4.2.6 Intermodulation attenuation	26
4.2.6.1 Definition	26
4.2.6.2 Limit.....	26

4.2.6.2.1	For all BTSs except multicarrier BTS	26
4.2.6.2.2	For multicarrier BTS	26
4.2.6.3	Conformance.....	26
4.2.7	Intra Base Station System intermodulation attenuation	26
4.2.7.1	Definition	26
4.2.7.2	Limit.....	27
4.2.7.2.1	For all BTSs except multicarrier BTS	27
4.2.7.2.2	For multicarrier BTS	27
4.2.7.3	Conformance.....	27
4.2.8	Wideband noise and intra BSS intermodulation attenuation in multicarrier operation.....	27
4.2.8.1	Definition	27
4.2.8.2	Limit.....	27
4.2.9	Static Reference Sensitivity Level	29
4.2.9.1	Definition	29
4.2.9.2	Limit.....	29
4.2.9.3	Conformance.....	31
4.2.10	Multipath Reference Sensitivity Level	31
4.2.10.1	Definition	31
4.2.10.2	Limit.....	31
4.2.10.3	Conformance.....	41
4.2.11	Reference Interference Level.....	41
4.2.11.1	Definition	41
4.2.11.2	Limit.....	41
4.2.11.3	Conformance.....	57
4.2.12	Blocking Characteristics	57
4.2.12.1	Definition	57
4.2.12.2	Limit.....	57
4.2.12.2.1	Blocking	57
4.2.12.2.2	Spurious response	58
4.2.12.3	Conformance.....	58
4.2.13	Intermodulation characteristics.....	58
4.2.13.1	Definition	58
4.2.13.2	Limit.....	58
4.2.13.3	Conformance.....	58
4.2.14	AM suppression	59
4.2.14.1	Definition	59
4.2.14.2	Limit.....	59
4.2.14.3	Conformance.....	59
4.2.15	Spurious emissions from the receiver antenna connector	59
4.2.15.1	Definition	59
4.2.15.2	Limit.....	59
4.2.15.3	Conformance.....	59
4.2.16	Radiated spurious emissions	59
4.2.16.1	Definition	59
4.2.16.2	Limit.....	60
4.2.16.3	Conformance.....	60
5	Testing for compliance with technical requirements.....	60
5.1	Environmental conditions for testing	60
5.2	Interpretation of the measurement results	60
5.3	Essential radio test suites.....	61
5.3.1	Modulation accuracy.....	62
5.3.1.1	Test case.....	62
5.3.1.2	Test Environment.....	63
5.3.2	Mean transmitted RF carrier power	63
5.3.2.1	Test case.....	63
5.3.2.2	Test Environment.....	64
5.3.3	Transmitted RF carrier power versus time.....	64
5.3.3.1	Test case.....	64
5.3.3.2	Test Environment.....	65
5.3.4	Adjacent channel power.....	65
5.3.4.1	Spectrum due to modulation and wideband noise	65

5.3.4.1.1	Test case	65
5.3.4.1.2	Test Environment	65
5.3.4.2	Switching transients spectrum.....	66
5.3.4.2.1	Test case	66
5.3.4.2.2	Test Environment	67
5.3.5	Spurious emissions from the transmitter antenna connector.....	67
5.3.5.1	Conducted spurious emissions from the transmitter antenna connector, inside the BTS transmit band.....	67
5.3.5.1.1	Test case	67
5.3.5.1.2	Test Environment	68
5.3.5.2	Conducted spurious emissions from the transmitter antenna connector, outside the BTS transmit band.....	68
5.3.5.2.1	All base stations except multicarrier BTS	68
5.3.5.2.2	Multicarrier BTS	69
5.3.5.3	Conducted spurious emissions from the transmitter antenna connector, in 3G bands outside the BTS transmit band	71
5.3.5.3.1	Test case	71
5.3.5.3.2	Test Environment	71
5.3.6	Intermodulation attenuation	72
5.3.6.1	Test case.....	72
5.3.6.2	Test Environment.....	73
5.3.7	Intra Base Station System intermodulation attenuation	74
5.3.7.1	Test case.....	74
5.3.7.2	Test Environment.....	75
5.3.8	Wideband noise and intra BSS intermodulation attenuation in multicarrier operation.....	75
5.3.8.1	Test case.....	75
5.3.8.2	Test Environment.....	77
5.3.9	Static reference sensitivity level	77
5.3.9.1	Test case.....	77
5.3.9.2	Test Environment.....	79
5.3.10	Multipath Reference Sensitivity Level	80
5.3.10.1	Test case.....	80
5.3.10.2	Test Environment.....	85
5.3.11	Reference Interference Level.....	85
5.3.11.1	Test case.....	85
5.3.11.2	Test Environment.....	95
5.3.12	Blocking Characteristics	95
5.3.12.1	Test case.....	95
5.3.12.2	Test Environment.....	99
5.3.13	Intermodulation characteristics	99
5.3.13.1	Test case.....	99
5.3.13.2	Test Environment.....	101
5.3.14	AM suppression	101
5.3.14.1	Test case.....	101
5.3.14.2	Test Environment.....	103
5.3.15	Spurious emissions from the receiver antenna connector	103
5.3.15.1	Test case.....	103
5.3.15.2	Test Environment.....	104
5.3.16	Radiated spurious emissions	104
5.3.16.1	Test case.....	104
5.3.16.2	Test Environment.....	106

Annex A (normative):	HS Requirements and conformance Test specifications Table (HS-RTT).....	107
-----------------------------	--	------------

Annex B (normative):	General test conditions and declarations.....	109
-----------------------------	--	------------

B.1	Declaration by manufacturer	109
B.1.1	Output power and determination of power class	109
B.1.2	Specified frequency range	109
B.1.3	Frequency hopping	110
B.1.4	RF power control.....	110

B.1.5	Downlink discontinuous transmission (DTX)	110
B.2	BTS Configurations.....	110
B.2.1	Receiver diversity	111
B.2.2	Duplexers	111
B.2.3	Power supply options	112
B.2.4	Ancillary RF amplifiers.....	112
B.2.5	BSS using antenna arrays	112
B.2.6	BTS supporting 8-PSK modulation.....	114
B.2.7	BTS supporting additional modulations in EGPRS2.....	114
B.2.8	Supported Symbol Rate.....	114
B.2.9	Support of RTTI and/or FANR	114
B.2.10	Multicarrier BTS	114
B.2.11	BTS supporting VAMOS	116
Annex C (normative):	Test environments.....	117
C.1	Normal test environment.....	117
C.2	Extreme test environment.....	117
C.2.1	Extreme temperature	118
C.3	Vibration.....	118
C.4	Power supply	118
Annex D (informative):	The EN title in the official languages	119
Annex E (informative):	Bibliography.....	120
History		121

ITeH Standards
 (https://standards.iteh.ai)
 Document Preview

ETSI EN 301 502 V10.2.1 (2012-11)

<https://standards.iteh.ai/catalog/standards/etsi/0437dcb9-8f7b-42f3-8511-5bb1a6983aa6/etsi-en-301-502-v10-2-1-2012-11>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This draft Harmonized European Standard (EN) has been produced by ETSI Technical Committee Mobile Standards Group (MSG), and is now submitted for the Public Enquiry phase of the ETSI standards Two-step Approval Procedure.

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Directive 98/34/EC [i.1] as amended by Directive 98/48/EC [i.7].

The title and reference to the present document are intended to be included in the publication in the Official Journal of the European Union of titles and references of Harmonized Standard under the Directive 1999/5/EC [i.2].

See article 5.1 of Directive 1999/5/EC [i.2] for information on presumption of conformity and Harmonised Standards or parts thereof the references of which have been published in the Official Journal of the European Union.

The requirements relevant to Directive 1999/5/EC [i.2] are summarised in annex A.

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive [i.2]. The modular structure is shown in EG 201 399 [i.3].

Figure 1: Void