

**Satellite Earth Stations and Systems (SES);
Harmonized EN for Mobile Earth Stations (MESs) of
Geostationary mobile satellite systems, including handheld
earth stations, for Satellite Personal Communications
Networks (S-PCN) in the 1,5/1,6 GHz bands under the Mobile
Satellite Service (MSS) covering the essential requirements
of article 3.2 of the R&TTE Directive**

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ETSI EN 301 681 V1.4.1 (2011-11)

<https://standards.iteh.ai/catalog/standards/etsi/c2232edd-3797-4dea-83dd-c0412947956c/etsi-en-301-681-v1-4-1-2011-11>



Reference

REN/SES-00320

Keywordsearth station, MES, mobile, MSS, radio, satellite,
S-PCN**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iteh Standards
(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2011.
All rights reserved.

DECTTM, PLUGTESTSTM, UMTSTM, TIPPHONTM, the TIPPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPPTM is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTETM is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	6
Foreword.....	6
Introduction	6
1 Scope	8
2 References	8
2.1 Normative references	8
2.2 Informative references.....	9
3 Definitions and abbreviations.....	9
3.1 Definitions.....	9
3.2 Abbreviations	11
4 Technical requirement specifications.....	11
4.1 Environment profile	11
4.2 Conformance requirements	11
4.2.1 Unwanted emissions outside the band 1 626,5 MHz to 1 660,5 MHz and outside the band 1 668,0 MHz to 1 675,0 MHz (carrier-on state)	11
4.2.1.1 Justification	11
4.2.1.2 Technical requirements	12
4.2.1.3 Conformance test	14
4.2.2 Unwanted emissions within the bands 1 626,5 MHz to 1 660,5 MHz and 1 660,5 MHz to 1 662,5 MHz and within the bands 1 666,0 MHz to 1 668,0 MHz, 1 668,0 MHz to 1 675,0 MHz and 1 675,0 MHz to 1 677,0 MHz (carrier-on state)	14
4.2.2.1 Justification	14
4.2.2.2 Technical requirements	15
4.2.2.3 Conformance test	16
4.2.3 Unwanted emissions in carrier-off state.....	16
4.2.3.1 Justification	16
4.2.3.2 Technical requirements.....	17
4.2.3.3 Conformance test	17
4.2.4 MES Control and Monitoring Functions (CMF)	17
4.2.4.1 Self-monitoring functions/Processor monitoring	17
4.2.4.1.1 Justification	17
4.2.4.1.2 Technical requirements.....	17
4.2.4.1.3 Conformance test.....	17
4.2.4.2 Self-monitoring functions/Transmit frequency generation sub-system monitoring.....	18
4.2.4.2.1 Justification	18
4.2.4.2.2 Technical requirements.....	18
4.2.4.2.3 Conformance test.....	18
4.2.4.3 Network control authorization	18
4.2.4.3.1 Justification	18
4.2.4.3.2 Technical requirements.....	18
4.2.4.3.3 Conformance test.....	18
4.2.4.4 Network control reception.....	18
4.2.4.4.1 Transmission disable/enable.....	18
4.2.4.4.2 Transmit frequency control	19
4.2.4.5 Fellow radio stations in a dual-mode or multimode terminal.....	19
4.2.4.5.1 Justification	19
4.2.4.5.2 Technical requirements.....	19
4.2.4.5.3 Conformance test.....	19
4.2.5 Equipment identity.....	20
4.2.5.1 Justification	20
4.2.5.2 Technical requirements	20
4.2.5.3 Conformance test	20

4.2.6	Protection of the radio astronomy service operation in the band 1 660 MHz to 1 660,5 MHz and in the band 1 668,0 MHz to 1 670,0 MHz	20
4.2.6.1	Purpose.....	20
4.2.6.2	Technical requirements	20
4.2.6.3	Conformance test	20
5	Testing for compliance with technical requirements.....	20
5.1	Environmental conditions for testing	20
5.2	Essential radio test suites.....	21
5.2.1	General.....	21
5.2.1.1	Description of equipment.....	21
5.2.1.2	Testing of host-connected equipment and plug-in modules	22
5.2.1.2.1	Alternative approaches	22
5.2.1.2.2	Alternative A: combined equipment.....	22
5.2.1.2.3	Alternative B: use of a test jig	22
5.2.1.3	CMF/Special Test Equipment (STE)	22
5.2.1.4	General test requirements.....	22
5.2.1.4.1	MES test modes	22
5.2.1.4.2	Special Test Equipment (STE)	23
5.2.1.4.3	Laboratory Test Equipment (LTE)	24
5.2.1.4.4	Methods of test for MES RF emissions according to the equipment type.....	24
5.2.1.4.5	Procedures for measurement of radiated emissions.....	24
5.2.1.4.6	Procedures for measurement of conducted emissions	29
5.2.1.4.7	Interpretation of the measurement results.....	31
5.2.1.4.8	Test report.....	31
5.2.2	Unwanted emissions outside the band 1 626,5 MHz to 1 660,5 MHz and outside the band 1 668,0 MHz to 1 675,0 MHz (carrier-on state)	31
5.2.2.1	Method of test	31
5.2.2.2	Peak measurement.....	32
5.2.2.3	Average measurement	32
5.2.2.4	Test requirements.....	33
5.2.3	Unwanted emissions within the band 1 626,5 MHz to 1 660,5 MHz and the band 1 624,5 MHz to 1 626,5 MHz and 1 660,5 MHz to 1 662,5 MHz and within the band 1 668,0 MHz to 1 675,0 MHz and the band 1 666,0 MHz to 1 668,0 MHz and 1 675,0 MHz to 1 677,0 MHz (carrier-on state)	33
5.2.3.1	Method of test	33
5.2.3.2	Measurement method	33
5.2.3.3	Test requirements	34
5.2.4	Unwanted emissions in carrier-off state.....	34
5.2.4.1	Method of test	34
5.2.4.2	Measurement method	34
5.2.4.3	Test requirements.....	35
5.2.5	MES Control and Monitoring Functions (CMF)	35
5.2.5.1	Self-monitoring functions/Processor monitoring	35
5.2.5.2	Self-monitoring functions/Transmit frequency generation sub-system monitoring.....	35
5.2.5.3	Network control authorization	35
5.2.5.3.1	Method of test.....	35
5.2.5.3.2	Test procedure	35
5.2.5.3.3	Test requirements	36
5.2.5.4	Network control reception.....	36
5.2.5.4.1	Transmission disable/enable.....	36
5.2.5.4.2	Transmit frequency control	37
5.2.5.5	Fellow radio stations in a dual-mode or multimode terminal.....	38
5.2.5.5.1	Method of test.....	38
5.2.5.5.2	Test procedure	38
5.2.5.5.3	Test requirements	38
5.2.6	Equipment identity.....	38
5.2.6.1	Method of test	38
5.2.6.2	Test procedure.....	38
5.2.6.3	Test requirements.....	38

Annex A (normative):	HS Requirements and conformance Test specifications	
	Table (HS-RTT)	39

Annex B (informative):	The EN title in the official languages	42
Annex C (informative):	Bibliography	43
History		44

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI EN 301 681 V1.4.1 \(2011-11\)](#)

<https://standards.iteh.ai/catalog/standards/etsi/c2232edd-3797-4dea-83dd-c0412947956c/etsi-en-301-681-v1-4-1-2011-11>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonized European Standard (EN) has been produced by ETSI Technical Committee Satellite Earth Stations and Systems (SES), and is now submitted for the Public Enquiry phase of the ETSI standards Two-step Approval Procedure.

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Council Directive 98/34/EC [7] (as amended) laying down a procedure for the provision of information in the field of technical standards and regulations.

The present document is intended to become a Harmonized Standard, the reference of which will be published in the Official Journal of the European Communities referencing the Directive 1999/5/EC [1] of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity ("the R&TTE Directive").

The requirements relevant to Directive 1999/5/EC [1] are summarised in annex A.

Proposed national transposition dates

Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive. The modular structure is shown in EG 201 399 [i.1]. The determination of the parameters of the user earth stations using a given satellite for the protection of the spectrum allocated to that satellite, is considered to be under the responsibility of the satellite operator or the satellite network operators.

The present document specifies new emission requirements for MESs that are capable of transmitting in the frequency band from 1 668,0 MHz to 1 675,0 MHz. Following the WRC-03 decision to allocate to MSS the bands 1 518 MHz to 1 525 MHz (space to Earth) and 1 668 MHz to 1 675 MHz (Earth to space) and the conclusions of WRC-07, the present document specifies the necessary requirements to harmonise the use of these extended frequency bands by MESs.

The present document treats the two parts of the L-band frequency allocation (as extended) as two sub-bands which may be used separately or in any combination. The original L-band allocation is referenced in the present document as "sub-band 1" and the extended L-band is referenced as "sub-band 2".