

**VHF air-ground Digital Link (VDL) Mode 4 radio equipment;
Technical characteristics and methods of measurement
for ground-based equipment;
Part 2: General description and data link layer**

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI EN 301 842-2 V1.6.1 \(2011-09\)](https://standards.iteh.ai/catalog/standards/etsi/1fe001f9-f089-4860-b282-43d776245b96/etsi-en-301-842-2-v1-6-1-2011-09)

<https://standards.iteh.ai/catalog/standards/etsi/1fe001f9-f089-4860-b282-43d776245b96/etsi-en-301-842-2-v1-6-1-2011-09>



Reference

REN/AERO-00006-2

Keywords

aeronautical, digital, radio, testing, VHF

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2010.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTE™ is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	8
Foreword.....	8
Introduction	8
1 Scope	10
2 References	12
2.1 Normative references	12
2.2 Informative references.....	12
3 Definitions and abbreviations.....	13
3.1 General definitions	13
3.2 Definition of bit order.....	16
3.3 Abbreviations	16
4 General description of VDL Mode 4 ground station link layer.....	18
4.1 General	18
4.1.1 Overview of VDL Mode 4	18
4.1.2 Relationship to OSI reference model.....	18
4.1.3 VDL Mode 4 services.....	20
4.1.4 ADS-B Function.....	20
4.1.5 Operational scenarios	21
4.1.6 VDL Mode 4 fundamentals	21
4.1.7 Possible configuration of ground equipment.....	22
4.1.8 Overall structure of specifications for VDL Mode 4.....	22
4.1.9 Equipment performance verification	24
4.2 Ground quarantine	25
4.3 System timing.....	25
4.4 Net entry	25
4.5 Autotune capability	25
4.6 Autonomous and fixed access	26
5 Minimum performance specification under standard test conditions.....	26
5.1 MAC sublayer	26
5.1.1 Services.....	26
5.1.2 MAC sublayer services	26
5.1.3 MAC sublayer parameters	26
5.1.3.1 General	26
5.1.3.2 Parameter M1 (number of slots per superframe).....	27
5.1.4 Time synchronization	27
5.1.4.1 Primary.....	27
5.1.4.2 Secondary.....	27
5.1.4.3 Alignment to UTC second.....	27
5.1.4.4 Data quality level	27
5.1.5 Slot idle/busy notification.....	28
5.1.5.1 Slot idle detection.....	28
5.1.5.2 Slot busy detection	28
5.1.5.3 Slot occupied detection	28
5.1.5.4 Signal level indication.....	28
5.1.6 Transmission processing.....	28
5.1.7 Received transmission processing	28
5.2 VSS sublayer	29
5.2.1 Services.....	29
5.2.1.1 Error detection.....	29
5.2.1.2 Channel congestion	29
5.2.2 Burst format.....	29
5.2.2.1 VSS burst structure	29
5.2.2.2 Version number	30

5.2.2.3	Source address.....	30
5.2.2.4	Message ID	30
5.2.2.5	Information field	31
5.2.2.6	Reservation fields.....	31
5.2.2.7	Autonomous/directed flag.....	32
5.2.3	VSS sublayer parameters	32
5.2.3.1	General	32
5.2.3.2	Parameter VS1 (number of ground quarantined slots)	33
5.2.3.3	Parameter VS2 (minimum CCI performance).....	33
5.2.3.4	Parameter VS4 (quarantine slot re-use range).....	33
5.2.3.5	Parameter VS5 (maximum burst length).....	34
5.2.4	VSS quality of service parameters	34
5.2.4.1	General	34
5.2.4.2	Parameter Q1 (priority)	34
5.2.4.3	Parameters Q2a to Q2d (slot selection range constraint for level n)	35
5.2.4.4	Parameter Q3 (replace queued data)	36
5.2.4.5	Parameter Q4 (number of available slots).....	36
5.2.5	Received transmission processing	37
5.2.6	Reserved access protocol specification.....	37
5.2.6.1	Reservation table	37
5.2.6.2	Selecting slots for transmission or reservation.....	38
5.2.6.3	Reserved transmissions	39
5.2.6.4	Reservation conflicts.....	40
5.2.7	Random access protocol specification	41
5.2.7.1	General	41
5.2.7.2	Random access parameters.....	41
5.2.7.3	Random access procedures.....	42
5.2.8	Fixed access protocol specification	42
5.2.8.1	General	42
5.2.8.2	Recommendation	43
5.2.9	Null reservation protocol specification	43
5.2.9.1	Null reservation burst format	43
5.2.10	Periodic broadcast protocol specification	43
5.2.10.1	Periodic broadcast reservation burst format.....	43
5.2.10.2	Periodic broadcast timers	44
5.2.10.3	Periodic broadcast parameters.....	44
5.2.10.4	Periodic broadcast reception procedures.....	46
5.2.10.5	Periodic broadcast transmission procedures.....	47
5.2.11	Incremental broadcast protocol specification	49
5.2.11.1	Incremental broadcast reservation burst format	49
5.2.11.2	Incremental broadcast parameters	50
5.2.11.3	Incremental broadcast reception procedures	51
5.2.11.4	Incremental broadcast transmission procedures	51
5.2.12	Combined periodic broadcast and incremental broadcast protocol specification	51
5.2.12.1	Combined periodic broadcast and incremental broadcast reservation burst.....	51
5.2.13	Big Negative Dither (BND) broadcast protocol specifications.....	52
5.2.13.1	BND reservation burst format	52
5.2.13.2	BND broadcast parameters.....	52
5.2.13.3	BND broadcast reception procedures.....	52
5.2.14	Unicast request protocol specification	53
5.2.14.1	Unicast request reservation burst format.....	53
5.2.14.1a	Unicast request parameters.....	54
5.2.14.2	Unicast request reception procedures.....	54
5.2.14.3	Unicast request transmission procedures	55
5.2.15	Information transfer request protocol specification	55
5.2.15.1	Information transfer request reservation burst format.....	55
5.2.15.2	Information transfer request reception procedures.....	56
5.2.16	Directed request protocol specification.....	57
5.2.16.1	Directed request reservation burst format	57
5.2.16.2	Directed request parameters	60
5.2.16.3	Directed request reception procedures	61
5.2.16.4	Directed request transmission procedures	62

5.2.17	Block reservation protocols specification	63
5.2.17.1	Superframe block reservation burst format	63
5.2.17.2	Second frame block reservation burst format	64
5.2.17.3	Superframe block reservation parameters	65
5.2.17.4	Superframe block reservation reception procedures	65
5.2.17.5	Second frame block reservation parameters	66
5.2.17.6	Second frame block reservation reception procedures	66
5.2.17.7	Superframe block reservation transmission procedures	67
5.2.17.8	Second frame block reservation transmission procedures	67
5.2.18	Response protocol specification	68
5.2.18.1	Response burst format	68
5.2.19	General request protocol specification	68
5.2.19.1	General request burst format	68
5.2.19.2	General request procedures	69
5.2.20	General response protocol specification	69
5.2.20.1	General response burst format	69
5.2.20.2	General response procedures	71
5.2.21	Retransmission procedures	71
5.3	DLS sublayer	72
5.3.1	Services	72
5.3.1.1	General	72
5.3.1.2	Data transfer	72
5.3.1.3	Station address encoding	72
5.3.1.4	DLS burst formats	73
5.3.2	DLS system parameters	74
5.3.2.1	Parameter ND4 (maximum length of a UDATA burst)	75
5.3.3	DLS procedures	75
5.3.3.1	Broadcast	75
5.3.3.2	DLS not supported	75
5.3.3.3	User data packet reception	75
5.4	Link Management Entity sublayer	75
5.4.1	Services	75
5.4.2	Synchronization burst format	76
5.4.2.1	General	76
5.4.2.2	Fixed and variable data fields	76
5.4.2.3	Fixed data field format	76
5.4.2.4	Variable data field format	80
5.4.2.5	Synchronization burst request	80
5.4.2.6	Link management burst	80
5.4.3	Control (CTRL) parameter formats	81
5.4.3.1	Encoding	81
5.4.3.2	VDL Mode 4 parameter identification	81
5.4.3.3	Ground-initiated modification parameters	81
5.4.3.4	Ground-initiated information parameters	84
5.4.3a	LME timers and parameters	87
5.4.3a.1	General	87
5.4.3a.2	Counter L1 (maximum number of missed reservations) and Timer TL3 (inter miss timer)	88
5.4.4	LME procedures	88
5.4.4.1	Synchronization burst procedures	88
5.4.4.2	Peer Entity Contact Table (PECT)	90
5.4.4.3	Network entry protocol specifications	90
5.4.5	Additional material for ADS-B applications	91
5.4.5.1	Information field formats	91
5.4.5.2	ADS-B request format	91
5.5	Additional requirements for ground stations	92
5.5.1	System timing requirements	92
5.5.1.1	Maintenance of Primary time	92
5.5.2	Ground station interface requirements	92
5.5.2.1	Ground station coordination	92
5.5.2.2	Network timing requirements	92
5.5.2.3	Application interface requirements	93
5.5.2.4	Transmission control requirements	93

5.5.2.5	Superframe block reservation rebroadcast procedures.....	93
5.5.2.6	Fixed transmission parameters	93
5.5.2.7	Protection of fixed access protocol transmissions by ground quarantine	94
5.5.2.8	Protection of fixed access protocol transmissions by use of appropriate reservation protocols.....	94
5.5.2.9	Restriction of autotune reservations	94
5.5.2.10	Transmission time for autotune reservations.....	94
5.5.2.11	Reporting of channel usage	95
5.6	Definitions for compact position reporting	95
5.6.1	Introduction.....	95
5.6.2	Parameter symbols, data types, constants and variables	95
5.6.2.1	Parameter symbols	95
5.6.2.2	Data types.....	95
5.6.2.3	Constants.....	95
5.6.2.4	Variables	95
5.6.2.5	Functions.....	96
5.6.2.6	Patch constants.....	96
5.6.3	Fixed data field position encoding	96
5.6.4	Fixed data field position local decoding	96
5.6.5	Fixed data field position global decoding	96
5.6.6	Position report processing.....	96
6	General design requirements	96
6.1	Controls and indicators.....	96
6.2	Operation of controls.....	96
6.3	Warm up	96
6.4	Effects of tests	96
6.5	Software management	97
6.6	Recovery from failure	97
6.6.1	Failure of the VDL equipment.....	97
6.7	Monitoring of proper operation	97
7	Protocol test procedures	97
7.1	General	97
7.1.1	Input voltage	97
7.1.2	Power input frequency	97
7.1.3	Adjustment of equipment.....	98
7.1.4	Equipment configuration	98
7.1.5	Test equipment.....	98
7.1.6	Test equipment precautions	98
7.1.7	Ambient conditions.....	98
7.1.8	Connected loads.....	98
7.1.9	Warm-up period.....	98
7.2	Required test rig	98
7.3	Protocol test-suite description methodology	101
7.4	Detailed protocol test procedures	101
7.4.1	Test-suite overview.....	101
7.4.2	Declarations	105
7.4.3	Constraints	106
7.4.3.1	Abbreviations	106
7.4.3.1.1	Subfield mnemonics	106
7.4.3.1.2	Special characters used in the subfield definitions	107
7.4.3.1.3	Station addresses and positions	107
7.4.3.1.4	Tables of values for use in CPR test cases	108
7.4.3.1.5	Tables of values for use in content checking test cases	119
7.4.3.1.6	VDL4 burst formats.....	122
7.4.3.2	Test cases	140
7.4.3.2.1	Test case macros.....	140
7.4.3.2.2	Test case descriptions.....	142

Annex A (informative):	Cross reference matrix	301
-------------------------------	-------------------------------------	------------

Annex B (informative):	Description of ISO/IEC 9646 Test Methodology.....	317
-------------------------------	--	------------

B.1	Overview of the structure of the ISO/IEC 9646 Test Suites	317
B.2	Test case description	317
B.3	Queue action.....	319
B.4	Repeat construct	319
B.5	Macro definitions	320
B.6	Test case naming	320
Annex C (informative):	Bibliography.....	321
History		326

iTech Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI EN 301 842-2 V1.6.1 \(2011-09\)](#)

<https://standards.iteh.ai/catalog/standards/etsi/1fe001f9-f089-4860-b282-43d776245b96/etsi-en-301-842-2-v1-6-1-2011-09>