

ETSI EN 301 842-3 V1.3.1 (2011-09)



VHF air-ground Digital Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for ground-based equipment; Part 3: Additional broadcast aspects

[ETSI EN 301 842-3 V1.3.1 \(2011-09\)](https://standards.iteh.ai/catalog/standards/etsi/dd06ff5f-3860-4d69-8864-374ce1aeffdf/etsi-en-301-842-3-v1-3-1-2011-09)

<https://standards.iteh.ai/catalog/standards/etsi/dd06ff5f-3860-4d69-8864-374ce1aeffdf/etsi-en-301-842-3-v1-3-1-2011-09>

Reference

REN/AERO-00006-3

Keywords

aeronautical, digital, radio, testing, VHF

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2011.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	5
Foreword.....	5
Introduction	6
1 Scope	7
2 References.	8
2.1 Normative references	8
2.2 Informative references.....	9
3 Definitions and abbreviations.....	9
3.1 Definitions.....	9
3.1.1 Basic reference model definitions.....	9
3.1.2 Service conventions definitions	9
3.1.3 General definitions.....	10
3.2 Abbreviations	10
4 General description of VDL Mode 4 ground station link layer.....	12
4.1 General	12
4.2 Automatic Dependant Surveillance-Broadcast.....	12
4.3 Traffic Information Service-Broadcast.....	13
4.4 Flight Information Service-Broadcast	14
4.5 GNSS Augmentation Service-Broadcast (GNS-B)	15
4.6 Ground Station Coordination	15
5 Minimum performance specification under standard test conditions.....	16
5.1 Requirements for ADS-B	16
5.1.1 Information Field Formats	16
5.1.2 ADS-B Request	26
5.1.2.1 ADS-B request format.....	26
5.1.2.2 Sleep Mode	26
5.1.2.3 Automatic Selection of Variable Information Fields	26
5.1.3 Default ADS-B Reporting	29
5.1.4 ADS-B Procedures.....	29
5.1.5 CTRL Parameters	29
5.1.5.1 Directory of Service (DOS) message	29
5.1.5.2 Channel Management Parameter	30
5.1.6 Definitions for Compact Position Reporting	39
5.1.6.1 Information Field Offset Encoding	39
5.1.6.2 Information Field Offset Decoding	41
5.1.6.3 Patch ID Encoding	42
5.1.6.4 Patch ID Decoding.....	42
5.1.7 Encoding of UDATA (udid)	43
5.2 Requirements for TIS-B	43
5.2.1 Traffic Information Volume (TIV)	43
5.2.2 Message transmission	44
5.2.2.1 Management messages.....	44
5.2.2.2 Target messages	44
5.2.2.3 Airport operation.....	44
5.2.3 Message format.....	45
5.2.4 Management message	46
5.2.5 Aircraft target messages (airborne TIV)	48
5.2.6 Aircraft target messages (ground TIV)	50
5.2.7 Ground vehicle target messages (ground TIV)	51
5.2.8 TIS-B offset encoding.....	52
5.3 Requirements for FIS-B	55
5.3.1 Message format.....	55
5.3.2 Meteorological Aerodrome Report (METAR) message	56

5.3.3	Special Observations and Reports (SPECI) message.....	64
5.3.4	Automatic Terminal Information Service (ATIS) message	65
5.3.5	Runway Condition (RCN) message	68
5.3.6	SIGNificant METeorological Information (SIGMET) message.....	72
5.3.7	Temporary Segregated Areas (TSA) message	73
5.3.8	FIS-B report request message	76
5.3.9	Ground system functions	77
5.4	Requirements for GNSS Augmentation Service Broadcast (GNS-B) message	78
5.4.1	Message format.....	78
5.4.2	Message Type 1	78
5.4.3	Message Type 2	82
5.4.4	Message Type 4	86
5.4.5	CRC Calculation.....	92
5.4.5.1	GNS-B CRC.....	92
5.4.5.2	FAS CRC	92
5.4.5.3	Ephemeris CRC.....	93
6	General design requirements	93
7	Protocol test procedures	93
7.1	General	93
7.2	Required test rig	94
7.3	Protocol test-suite description methodology	96
7.4	Detailed protocol test procedures	96
7.4.1	Test-suite overview.....	96
7.4.2	Declarations	98
7.4.3	Constraints	98
7.4.3.1	Abbreviations	98
7.4.3.1.1	Subfield mnemonics	99
7.4.3.1.2	Station addresses and positions	102
7.4.3.1.3	Tables of values for use in CPR test cases	103
7.4.3.1.4	Tables of values for use in content checking test cases	113
7.4.3.1.5	VDL4 Burst formats	147
7.4.3.2	Test cases	183
7.4.3.2.1	Test case macros.....	184
7.4.3.2.2	Test case descriptions.....	185
Annex A (informative):	Cross reference matrix	257
Annex B (informative):	Bibliography	267
History		273

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (EN) has been produced by ETSI Technical Committee Aeronautics (AERO).

The present document is part 3 of a multi-part deliverable covering the VHF air-ground Digital Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for ground-based equipment, as identified below:

- Part 1: "EN for ground equipment";
- Part 2: "General description and data link layer";
- Part 3: "Additional broadcast aspects";**
- Part 4: "Point-to-point functions";
- Part 5: "Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive".

The present document is accompanied by an equivalent airborne standard, EN 302 842 [6], [7], [8] and [9] parts 1-4, covering the VHF air-ground Digital Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for airborne equipment.

NOTE: Following the decision taken at the ICAO Aeronautical Communication Panel's WG/M (Bangkok, February 2011), it remains to be seen if ICAO Annex 10 Vol III will be amended changing the recommended tuning frequency range from 108-117,975 MHz to 112-117,975 MHz. The present document will be updated accordingly if the amendment is accepted and made publicly available.

National transposition dates

Date of adoption of this EN:	19 September 2011
Date of latest announcement of this EN (doa):	31 December 2011
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 June 2012
Date of withdrawal of any conflicting National Standard (dow):	30 June 2012

Introduction

The present document is part of a set of deliverables developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive [i.5]. The modular structure is shown in EG 201 399 [i.7].

The present document states the technical specifications for Very High Frequency (VHF) Digital Link (VDL) Mode 4 ground-based radio transmitters, transceivers and receivers for air-ground communications operating in the VHF band, using Gaussian-filtered Frequency Shift Keying (GFSK) Modulation with 25 kHz channel spacing and capable of tuning to any of the 25 kHz channels from 118,000 MHz to 136,975 MHz as defined in ICAO VHF Digital Link (VDL) Standards and Recommended Practices (SARPs) [i.4].

The present document considers the additional broadcast functionality required to support ADS-B, TIS-B, FIS-B, and GNS-B services.

The present document may be used to produce tests for the assessment of the performance of the equipment. The performance of the equipment submitted for type testing should be representative of the performance of the corresponding production model.

The present document has been written on the assumption that:

- the type test measurements will be performed only once, in an accredited test laboratory and the measurements accepted by the various authorities in order to grant type approval;
- if equipment available on the market is required to be checked it will be tested in accordance with the methods of measurement specified in the present document or a documented alternative approved by the certifying authority;
- equipment comply with EN 301 489-22 [1], EN 301 842-1 [2] and EN 301 842-2 [3].

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI EN 301 842-3 V1.3.1 \(2011-09\)](#)

<https://standards.iteh.ai/catalog/standards/etsi/dd06ff5f-3860-4d69-8864-374ce1aeffdf/etsi-en-301-842-3-v1-3-1-2011-09>

1 Scope

The present document applies to the following radio equipment types:

- Very High Frequency (VHF) Digital Link (VDL) Mode 4 ground-based radio transmitters and receivers for air-ground communications operating in the VHF band, using Gaussian-filtered Frequency Shift Keying (GFSK) Modulation with 25 kHz channel spacing and capable of tuning to any of the 25 kHz channels from 118,000 MHz to 136,975 MHz as defined in ICAO VHF Digital Link (VDL) Standards and Recommended Practices (SARPs) [i.4].

The present document provides part 3 of the technical specifications.

The present document is designed to ensure that equipment certified to it will be compatible with the relevant ICAO VHF Digital Link (VDL) Standards and Recommended Practices (SARPs) [i.4] and VDL Mode 4 Technical Manual (TM) [i.1].

Manufacturers should note that in future the tuning range for the ground transceivers may also cover any 25 kHz channel from 108,000 MHz to 117,975 MHz.

The scope of the present document is limited to ground stations. The equivalent specification for airborne stations is EN 302 842 [6], [7], [8] and [9].

A description of the scope of the VDL Mode 4 system is provided in EN 301 842-2 [3], clause 1.

EN 301 842-1 [2] deals with tests of the physical layer. EN 301 842-2 [3] deals with tests of the link layer sufficient to support broadcast functionality including requirements and tests sufficient to recognize and respond to transmissions associated with point-to-point communication. The present document provides technical specifications for a VDL Mode 4 ground-based transceiver supporting a full Automatic Dependent Surveillance-Broadcast (ADS-B) capability and, optionally, the additional functionality of either, or a combination of, the following services:

- Traffic Information Service-Broadcast (TIS-B);
- Flight Information Service-Broadcast (FIS-B);
- GNSS Augmentation Service-Broadcast (GNS-B).

The TIS-B, FIS-B or GNS-B functionality in the ground-based equipment is expected to be provided by a TIS-B, FIS-B or GNS-B processor, which could be contained within the VDL Mode 4 transceiver, but could also be housed in a separate physical unit. Therefore to support TIS-B, FIS-B or GNS-B, the minimum functionality demanded of a basic VDL Mode 4 ground-based transceiver unit (i.e. one that does not have a TIS-B, FIS-B or GNS-B processor housed within it) is to receive, from the TIS-B, FIS-B or GNS-B processor, all messages to be transmitted, and to transmit them. In the case of FIS-B there is an additional requirement to receive report request messages (from other VDL4 stations) and to pass those messages to the FIS-B processor.

It should be noted that the specifications for TIS-B, FIS-B and GNS-B in the present document represent a first step towards defining these applications, based on the work carried out as part of the NUP and MEDUP Programmes, and changes to the specifications for these services may therefore occur in the future.

The present document is organized as follows:

- clause 2 provides references to relevant documents;
- clause 3 provides general definitions, abbreviations and symbols used;
- clause 4 describes the VDL Mode 4 ground station functionality to support ADS-B, TIS-B, FIS-B and GNS B;
- clause 5 provides performance specifications for the VDL Mode 4 ground station supporting ADS-B, TIS-B, FIS-B and GNS-B Services;
- clause 6 provides general design requirements;
- clause 7 provides protocol tests which emphasis the ADS-B, TIS-B, FIS-B and GNS-B functions of the system;