



**IMT cellular networks;
Harmonised Standard for access to radio spectrum;
Part 13: Evolved Universal Terrestrial Radio Access (E-UTRA)
User Equipment (UE)**

[ETSI EN 301 908-13 V13.4.0 \(2025-12\)](https://standards.iteh.ai/catalog/standards/etsi/caf3bd8b-5cdb-4a9f-8ab4-d1284ec5650b/etsi-en-301-908-13-v13-4-0-2025-12)

[https://standards.iteh.ai/catalog/standards/etsi/caf3bd8b-5cdb-4a9f-8ab4-d1284ec5650b/etsi-en-301-908-13-v13-4-0-2025-](https://standards.iteh.ai/catalog/standards/etsi/caf3bd8b-5cdb-4a9f-8ab4-d1284ec5650b/etsi-en-301-908-13-v13-4-0-2025-12)

Reference

REN/MSG-TFES-1512

Keywords

3G, 3GPP, cellular, digital, E-UTRA, IMT,
IMT-2000, IMT-Advanced, LTE, LTE-Advanced,
mobile, radio, regulation, UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed,
this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.
In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2025.
All rights reserved.

Contents

Intellectual Property Rights	11
Foreword.....	11
Modal verbs terminology.....	12
Introduction	12
1 Scope	13
2 References	16
2.1 Normative references	16
2.2 Informative references.....	16
3 Definition of terms, symbols and abbreviations.....	18
3.1 Terms.....	18
3.2 Symbols.....	21
3.3 Abbreviations	23
4 Technical requirements specifications	25
4.1 Environmental profile.....	25
4.2 Conformance requirements	25
4.2.0 General.....	25
4.2.1 Introduction.....	25
4.2.2 Transmitter Maximum Output Power	26
4.2.2.1 Transmitter maximum output power for Single Carrier.....	26
4.2.2.1.1 Definition.....	26
4.2.2.1.2 Limits	26
4.2.2.1.3 Conformance	26
4.2.2.2 Transmitter output power for Carrier Aggregation (DL CA and UL CA)	26
4.2.2.2.1 Definition.....	26
4.2.2.2.2 Limits	27
4.2.2.2.3 Conformance	28
4.2.2.3 Transmitter output power for UL-MIMO	28
4.2.2.3.1 Definition.....	28
4.2.2.3.2 Limits	28
4.2.2.3.3 Conformance	28
4.2.2.4 Transmitter output power for category NB1	29
4.2.2.4.1 Definition.....	29
4.2.2.4.2 Limits	29
4.2.2.4.3 Conformance	29
4.2.2.5 Transmitter output power for UE category M1.....	29
4.2.2.5.1 Definition.....	29
4.2.2.5.2 Limits	29
4.2.2.5.3 Conformance	30
4.2.3 Transmitter Spectrum Emission Mask.....	30
4.2.3.1 Transmitter spectrum emission mask for Single Carrier.....	30
4.2.3.1.1 Definition.....	30
4.2.3.1.2 Limits	30
4.2.3.1.3 Conformance	31
4.2.3.2 Transmitter spectrum emission mask for Carrier Aggregation (DL CA and UL CA)	31
4.2.3.2.1 Definition.....	31
4.2.3.2.2 Limits	31
4.2.3.2.3 Conformance	33
4.2.3.3 Transmitter spectrum emission mask for UL-MIMO	33
4.2.3.3.1 Definition.....	33
4.2.3.3.2 Limits	34
4.2.3.3.3 Conformance	34
4.2.3.4 Transmitter spectrum emission mask for Multi-Cluster PUSCH within a component carrier	34
4.2.3.4.1 Definition.....	34
4.2.3.4.2 Limits	34

4.2.3.4.3	Conformance	34
4.2.3.5	Transmitter spectrum emission mask for category NB1	34
4.2.3.5.1	Definition.....	34
4.2.3.5.2	Limits	34
4.2.3.5.3	Conformance	34
4.2.4	Transmitter Spurious Emissions	35
4.2.4.1	Transmitter spurious emissions for Single Carrier	35
4.2.4.1.1	Definition.....	35
4.2.4.1.2	Limits	35
4.2.4.1.3	Conformance	39
4.2.4.2	Transmitter spurious emissions for Carrier Aggregation (DL CA and UL CA)	39
4.2.4.2.1	Definition.....	39
4.2.4.2.2	Limits	40
4.2.4.2.3	Conformance	44
4.2.4.3	Transmitter spurious emissions for UL-MIMO	44
4.2.4.3.1	Definition.....	44
4.2.4.3.2	Limits	45
4.2.4.3.3	Conformance	45
4.2.4.4	Transmitter spurious emissions for Multi-Cluster PUSCH within a component carrier	45
4.2.4.4.1	Definition.....	45
4.2.4.4.2	Limits	45
4.2.4.4.3	Conformance	45
4.2.4.5	Transmitter spurious emissions for category NB1	45
4.2.4.5.1	Definition.....	45
4.2.4.5.2	Limits	45
4.2.4.5.3	Conformance	46
4.2.5	Transmitter Minimum Output Power.....	46
4.2.5.1	Transmitter minimum output power for Single Carrier.....	46
4.2.5.1.1	Definition.....	46
4.2.5.1.2	Limits	46
4.2.5.1.3	Conformance	46
4.2.5.2	Transmitter minimum output power for Carrier Aggregation (DL CA and UL CA)	46
4.2.5.2.1	Definition.....	46
4.2.5.2.2	Limits	46
4.2.5.2.3	Conformance	47
4.2.5.3	Transmitter minimum output power for UL-MIMO	47
4.2.5.3.1	Definition.....	47
4.2.5.3.2	Limits	47
4.2.5.3.3	Conformance	47
4.2.5.4	Transmitter minimum output power for category NB1.....	47
4.2.5.4.1	Definition.....	47
4.2.5.4.2	Limits	47
4.2.5.4.3	Conformance	47
4.2.6	Receiver Adjacent Channel Selectivity (ACS)	48
4.2.6.1	Receiver Adjacent Channel Selectivity (ACS) for Single Carrier	48
4.2.6.1.1	Definition.....	48
4.2.6.1.2	Limits	48
4.2.6.1.3	Conformance	49
4.2.6.2	Receiver Adjacent Channel Selectivity (ACS) for Carrier Aggregation in DL-only bands	49
4.2.6.2.1	Definition.....	49
4.2.6.2.2	Limits	49
4.2.6.2.3	Conformance	50
4.2.6.3	Receiver Adjacent Channel Selectivity (ACS) for category NB1.....	50
4.2.6.3.1	Definition.....	50
4.2.6.3.2	Limits	50
4.2.6.3.3	Conformance	51
4.2.7	Receiver Blocking Characteristics	51
4.2.7.1	Receiver Blocking Characteristics for Single Carrier	51
4.2.7.1.1	Definition.....	51
4.2.7.1.2	Limits	51
4.2.7.1.3	Conformance	53
4.2.7.2	Receiver Blocking Characteristics for Carrier Aggregation in DL-only bands.....	53

4.2.7.2.1	Definition.....	53
4.2.7.2.2	Limits	53
4.2.7.2.3	Conformance	56
4.2.7.3	Receiver Blocking Characteristics for category NB1	57
4.2.7.3.1	Definition.....	57
4.2.7.3.2	Limits	57
4.2.7.3.3	Conformance	58
4.2.8	Receiver Spurious Response.....	58
4.2.8.1	Receiver Spurious Response for Single Carrier	58
4.2.8.1.1	Definition.....	58
4.2.8.1.2	Limits	58
4.2.8.1.3	Conformance	58
4.2.8.2	Receiver Spurious Response for Carrier Aggregation in DL-only bands	59
4.2.8.2.1	Definition.....	59
4.2.8.2.2	Limits	59
4.2.8.2.3	Conformance	59
4.2.8.3	Receiver Spurious Response for category NB1	59
4.2.8.3.1	Definition.....	59
4.2.8.3.2	Limits	59
4.2.8.3.3	Conformance	59
4.2.9	Receiver Intermodulation Characteristic	60
4.2.9.1	Receiver Intermodulation Characteristics for Single Carrier	60
4.2.9.1.1	Definition.....	60
4.2.9.1.2	Limits	60
4.2.9.1.3	Conformance	60
4.2.9.2	Receiver Intermodulation Characteristics for Carrier Aggregation in DL-only bands.....	61
4.2.9.2.1	Definition.....	61
4.2.9.2.2	Limits	61
4.2.9.2.3	Conformance	61
4.2.9.3	Receiver Intermodulation Characteristics for category NB1	61
4.2.9.3.1	Definition.....	61
4.2.9.3.2	Limits	62
4.2.9.3.3	Conformance	62
4.2.10	Receiver Spurious Emissions.....	62
4.2.10.1	Receiver Spurious Emissions for Single Carrier	62
4.2.10.1.1	Definition.....	62
4.2.10.1.2	Limits	62
4.2.10.1.3	Conformance	62
4.2.10.2	Receiver Spurious Emissions in DL-only bands	62
4.2.10.2.1	Definition.....	62
4.2.10.2.2	Limits	63
4.2.10.2.3	Conformance	63
4.2.11	Transmitter Adjacent Channel Leakage Power Ratio.....	63
4.2.11.1	Transmitter adjacent channel leakage power ratio for Single Carrier	63
4.2.11.1.1	Definition.....	63
4.2.11.1.2	Limits	63
4.2.11.1.3	Conformance	64
4.2.11.2	Transmitter adjacent channel leakage power ratio for Carrier Aggregation (DL CA and UL CA).....	64
4.2.11.2.1	Definition.....	64
4.2.11.2.2	Limits for CA UTRA.....	66
4.2.11.2.3	Limits for CA E-UTRA.....	67
4.2.11.2.4	Conformance	67
4.2.11.3	Transmitter adjacent channel leakage power ratio for UL-MIMO.....	67
4.2.11.3.1	Definition.....	67
4.2.11.3.2	Limits	68
4.2.11.3.3	Conformance	69
4.2.11.4	Transmitter adjacent channel leakage power ratio for Multi-Cluster PUSCH within a component carrier	69
4.2.11.4.1	Definition.....	69
4.2.11.4.2	Limits	69
4.2.11.4.3	Conformance	69
4.2.11.5	Transmitter adjacent channel leakage power ratio for category NB1	70

4.2.11.5.1	Definition.....	70
4.2.11.5.2	Limits	70
4.2.11.5.3	Conformance	70
4.2.12	Receiver Reference Sensitivity Level	70
4.2.12.0	General	70
4.2.12.1	Receiver Reference Sensitivity Level for Single Carrier	70
4.2.12.1.1	Definition.....	70
4.2.12.1.2	Limits	70
4.2.12.1.3	Conformance	71
4.2.12.2	Receiver Reference Sensitivity Level for Carrier Aggregation in DL-only bands.....	71
4.2.12.2.1	Definition.....	71
4.2.12.2.2	Limits	71
4.2.12.2.3	Conformance	72
4.2.12.3	Receiver Reference Sensitivity Level for category NB1.....	72
4.2.12.3.1	Definition.....	72
4.2.12.3.2	Limits	73
4.2.12.3.3	Conformance	73
4.2.12.4	Receiver Reference Sensitivity Level for UE category 0.....	73
4.2.12.4.1	Definition.....	73
4.2.12.4.2	Limits	73
4.2.12.4.3	Conformance	74
4.2.12.5	Receiver Reference Sensitivity Level for UE category M1	74
4.2.12.5.1	Definition.....	74
4.2.12.5.2	Limits	74
4.2.12.5.3	Conformance	75
4.2.13	Receiver Total Radiated Sensitivity (TRS).....	75
4.2.13.0	Applicability.....	75
4.2.13.1	Definition	75
4.2.13.2	Limits	76
4.2.13.3	Conformance.....	77
4.2.14	Total Radiated Power (TRP).....	77
4.2.14.0	Applicability.....	77
4.2.14.1	Definition	77
4.2.14.2	Limits	78
5	Testing for compliance with technical requirements.....	79
5.1	Environmental conditions for testing	79
5.2	Void.....	79
5.3	Essential radio test suites.....	79
5.3.0	General.....	79
5.3.1	Transmitter Maximum Output Power	79
5.3.1.1	Transmitter maximum output power for Single Carrier.....	79
5.3.1.1.1	Method of test.....	79
5.3.1.1.2	Test requirements	80
5.3.1.2	Transmitter maximum output power for intra-band contiguous Carrier Aggregation (DL CA and UL CA)	80
5.3.1.2.1	Method of test.....	80
5.3.1.2.2	Test requirements	81
5.3.1.2A	Transmitter maximum output power for inter-band Carrier Aggregation (DL CA and UL CA).....	81
5.3.1.2A.1	Method of test.....	81
5.3.1.2A.2	Test requirements	82
5.3.1.3	Transmitter maximum output power for UL-MIMO	82
5.3.1.3.1	Method of test.....	82
5.3.1.3.2	Test requirements	83
5.3.1.4	Transmitter maximum output power for category NB1	83
5.3.1.4.1	Method of Test	83
5.3.1.4.2	Test requirements	83
5.3.1.5	Transmitter maximum output power for UE category 0	84
5.3.1.5.1	Method of test.....	84
5.3.1.5.2	Test requirements	84
5.3.1.6	Transmitter maximum output power for UE category M1.....	84
5.3.1.6.1	Method of test.....	84

5.3.1.6.2	Test requirements	85
5.3.2	Transmitter Spectrum Emission Mask.....	85
5.3.2.1	Transmitter spectrum emission mask for Single Carrier.....	85
5.3.2.1.1	Method of test.....	85
5.3.2.1.2	Test requirements	86
5.3.2.2	Transmitter spectrum emission mask for intra-band contiguous Carrier Aggregation (DL CA and UL CA)	86
5.3.2.2.1	Method of test.....	86
5.3.2.2.2	Test requirements	87
5.3.2.2A	Transmitter spectrum emission mask for inter-band Carrier Aggregation (DL CA and UL CA)	87
5.3.2.2A.1	Method of test.....	87
5.3.2.2A.2	Test requirements	88
5.3.2.3	Transmitter spectrum emission mask for UL-MIMO	88
5.3.2.3.1	Method of test.....	88
5.3.2.3.2	Test requirements	89
5.3.2.4	Transmitter spectrum emission mask for Multi-Cluster PUSCH within a component carrier	89
5.3.2.4.1	Method of test.....	89
5.3.2.4.2	Test requirements	89
5.3.2.5	Transmitter spectrum emission mask for category NB1	90
5.3.2.5.1	Method of test.....	90
5.3.2.5.2	Test requirements	90
5.3.2.6	Transmitter spectrum emission mask for UE category 0	91
5.3.2.6.1	Method of test.....	91
5.3.2.6.2	Test requirements	91
5.3.2.7	Transmitter spectrum emission mask for UE category M1	91
5.3.2.7.1	Method of test.....	91
5.3.2.7.2	Test requirements	92
5.3.3	Transmitter Spurious Emissions	92
5.3.3.1	Transmitter spurious emissions for Single Carrier	92
5.3.3.1.1	Method of test.....	92
5.3.3.1.2	Test requirements	93
5.3.3.2	Transmitter spurious emissions for intra-band contiguous Carrier Aggregation (DL CA and UL CA).....	93
5.3.3.2.1	Method of test.....	93
5.3.3.2.2	Test requirements	94
5.3.3.2A	Transmitter spurious emissions for inter-band Carrier Aggregation (DL CA and UL CA)	94
5.3.3.2A.1	Method of test.....	94
5.3.3.2A.2	Test requirements	95
5.3.3.3	Transmitter spurious emissions for UL-MIMO	95
5.3.3.3.1	Method of test.....	95
5.3.3.3.2	Test requirements	96
5.3.3.4	Transmitter spurious emissions for Multi-Cluster PUSCH within a component carrier	96
5.3.3.4.1	Method of test.....	96
5.3.3.4.2	Test requirements	97
5.3.3.5	Transmitter spurious emissions for category NB1	97
5.3.3.5.1	Method of test.....	97
5.3.3.5.2	Test requirements	98
5.3.3.6	Transmitter spurious emissions for UE category 0	98
5.3.3.6.1	Method of test.....	98
5.3.3.6.2	Test requirements	98
5.3.3.7	Transmitter spurious emissions for UE category M1	99
5.3.3.7.1	Method of test.....	99
5.3.3.7.2	Test requirements	100
5.3.4	Transmitter Minimum Output Power.....	100
5.3.4.1	Transmitter minimum output power for Single Carrier.....	100
5.3.4.1.1	Method of test.....	100
5.3.4.1.2	Test requirements	100
5.3.4.2	Transmitter minimum output power for intra-band contiguous Carrier Aggregation (DL CA and UL CA)	101
5.3.4.2.1	Method of test.....	101
5.3.4.2.2	Test requirements	101
5.3.4.2A	Transmitter minimum output power for inter-band Carrier Aggregation (DL CA and UL CA).....	102