

ETSI EN 301 908-13 V6.2.1 (2013-10)



**IMT cellular networks;
Harmonized EN covering the essential requirements
of article 3.2 of the R&TTE Directive;
Part 13: Evolved Universal Terrestrial Radio Access (E-UTRA)
User Equipment (UE)**

[ETSI EN 301 908-13 V6.1.3 \(2013-08\)](https://standards.iteh.ai/catalog/standards/etsi/62c03020-dd17-45f6-93ae-3f80b29dfa9d/etsi-en-301-908-13-v6-1-3-2013-08)

<https://standards.iteh.ai/catalog/standards/etsi/62c03020-dd17-45f6-93ae-3f80b29dfa9d/etsi-en-301-908-13-v6-1-3-2013-08>

Reference

REN/MSG-TFES-010-13

Keywords

3G, 3GPP, cellular, digital, E-UTRA, IMT, LTE,
mobile, radio, regulation, UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2013.
All rights reserved.

DECTTM, PLUGTESTSTM, UMTSTM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPPTM and LTETM are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	7
Foreword.....	7
Introduction	7
1 Scope	8
2 References	9
2.1 Normative references	9
2.2 Informative references	9
3 Definitions, symbols and abbreviations	10
3.1 Definitions	10
3.2 Symbols	12
3.3 Abbreviations	14
4 Technical requirements specifications	15
4.1 Environmental profile.....	15
4.2 Conformance requirements	15
4.2.1 Introduction.....	15
4.2.2 Transmitter Maximum Output Power	16
4.2.2.1 Transmitter maximum output power for Single Carrier	16
4.2.2.1.1 Definition.....	16
4.2.2.1.2 Limits	16
4.2.2.1.3 Conformance	16
4.2.2.2 Transmitter output power for intra-band contiguous Carrier Aggregation (DL CA and UL CA).....	16
4.2.2.2.1 Definition.....	16
4.2.2.2.2 Limits	17
4.2.2.2.3 Conformance	17
4.2.2.3 Transmitter output power for UL-MIMO	17
4.2.2.3.1 Definition.....	17
4.2.2.3.2 Limits	18
4.2.2.3.3 Conformance	18
4.2.3 Transmitter Spectrum Emission Mask.....	18
4.2.3.1 Transmitter spectrum emission mask for Single Carrier.....	18
4.2.3.1.1 Definition.....	18
4.2.3.1.2 Limits	18
4.2.3.1.3 Conformance	19
4.2.3.2 Transmitter spectrum emission mask for intra-band contiguous Carrier Aggregation (DL CA and UL CA)	20
4.2.3.2.1 Definition.....	20
4.2.3.2.2 Limits	20
4.2.3.2.3 Conformance	20
4.2.3.3 Transmitter spectrum emission mask for UL-MIMO	21
4.2.3.3.1 Definition.....	21
4.2.3.3.2 Limits	21
4.2.3.3.3 Conformance	21
4.2.4 Transmitter Spurious Emissions	21
4.2.4.1 Transmitter spurious emissions for Single Carrier	21
4.2.4.1.1 Definition.....	21
4.2.4.1.2 Limits	21
4.2.4.1.3 Conformance	24
4.2.4.2 Transmitter spurious emissions for intra-band contiguous Carrier Aggregation (DL CA and UL CA).....	24
4.2.4.2.1 Definition.....	24
4.2.4.2.2 Limits	24
4.2.4.2.3 Conformance	25
4.2.4.3 Transmitter spurious emissions for UL-MIMO	26

4.2.4.3.1	Definition.....	26
4.2.4.3.2	Limits	26
4.2.4.3.3	Conformance	26
4.2.5	Transmitter Minimum Output Power.....	26
4.2.5.1	Transmitter minimum output power for Single Carrier.....	26
4.2.5.1.1	Definition.....	26
4.2.5.1.2	Limits	26
4.2.5.1.3	Conformance	26
4.2.5.2	Transmitter minimum output power for intra-band contiguous Carrier Aggregation (DL CA and UL CA)	26
4.2.5.2.1	Definition.....	26
4.2.5.2.2	Limits	27
4.2.5.2.3	Conformance	27
4.2.5.3	Transmitter minimum output power for UL-MIMO	27
4.2.5.3.1	Definition.....	27
4.2.5.3.2	Limits	27
4.2.5.3.3	Conformance	27
4.2.6	Receiver Adjacent Channel Selectivity (ACS)	27
4.2.6.1	Definition	27
4.2.6.2	Limits	28
4.2.6.3	Conformance	28
4.2.7	Receiver Blocking Characteristics	29
4.2.7.1	Definition	29
4.2.7.2	Limits	29
4.2.7.3	Conformance.....	30
4.2.8	Receiver Spurious Response.....	31
4.2.8.1	Definition	31
4.2.8.2	Limits	31
4.2.8.3	Conformance	31
4.2.9	Receiver Intermodulation Characteristics	31
4.2.9.1	Definition	31
4.2.9.2	Limits	31
4.2.9.3	Conformance	32
4.2.10	Receiver Spurious Emissions.....	32
4.2.10.1	Definition	32
4.2.10.2	Limits	32
4.2.10.3	Conformance.....	32
4.2.11	Transmitter Adjacent Channel Leakage Power Ratio	33
4.2.11.1	Transmitter adjacent channel leakage power ratio for Single Carrier	33
4.2.11.1.1	Definition.....	33
4.2.11.1.2	Limits	33
4.2.11.1.3	Conformance	34
4.2.11.2	Transmitter adjacent channel leakage power ratio for intra-band contiguous Carrier Aggregation (DL CA and UL CA).....	34
4.2.11.2.1	Definition.....	34
4.2.11.2.2	Limits	35
4.2.11.2.3	Conformance	35
4.2.11.3	Transmitter adjacent channel leakage power ratio for UL-MIMO.....	35
4.2.11.3.1	Definition.....	35
4.2.11.3.2	Limits	36
4.2.11.3.3	Conformance	37
5	Testing for compliance with technical requirements.....	37
5.1	Environmental conditions for testing	37
5.2	Interpretation of the measurement results	38
5.3	Essential radio test suites.....	39
5.3.1	Transmitter Maximum Output Power	39
5.3.1.1	Transmitter maximum output power for Single Carrier.....	39
5.3.1.1.1	Method of test.....	39
5.3.1.1.2	Test requirements	39
5.3.1.2	Transmitter maximum output power for intra-band contiguous Carrier Aggregation (DL CA and UL CA)	40

5.3.1.2.1	Method of test.....	40
5.3.1.2.2	Test requirements	40
5.3.1.3	Transmitter maximum output power for UL-MIMO	41
5.3.1.3.1	Method of test.....	41
5.3.1.3.2	Test requirements	41
5.3.2	Transmitter Spectrum Emission Mask.....	42
5.3.2.1	Transmitter spectrum emission mask for Single Carrier.....	42
5.3.2.1.1	Method of test.....	42
5.3.2.1.2	Test requirements	42
5.3.2.2	Transmitter spectrum emission mask for intra-band contiguous Carrier Aggregation (DL CA and UL CA)	42
5.3.2.2.1	Method of test.....	42
5.3.2.2.2	Test requirements	43
5.3.2.3	Transmitter spectrum emission mask for UL-MIMO	43
5.3.2.3.1	Method of test.....	43
5.3.2.3.2	Test requirements	44
5.3.3	Transmitter Spurious Emissions	44
5.3.3.1	Transmitter spurious emissions for Single Carrier	44
5.3.3.1.1	Method of test.....	44
5.3.3.1.2	Test requirements	45
5.3.3.2	Transmitter spurious emissions for intra-band contiguous Carrier Aggregation (DL CA and UL CA).....	45
5.3.3.2.1	Method of test.....	45
5.3.3.2.2	Test requirements	46
5.3.3.3	Transmitter spurious emissions for UL-MIMO	46
5.3.3.3.1	Method of test.....	46
5.3.3.3.2	Test requirements	47
5.3.4	Transmitter Minimum Output Power.....	47
5.3.4.1	Transmitter minimum output power for Single Carrier.....	47
5.3.4.1.1	Method of test.....	47
5.3.4.1.2	Test requirements	48
5.3.4.2	Transmitter minimum output power for intra-band contiguous Carrier Aggregation (DL CA and UL CA)	48
5.3.4.2.1	Method of test.....	48
5.3.4.2.2	Test requirements	49
5.3.4.3	Transmitter minimum output power for UL-MIMO	49
5.3.4.3.1	Method of test.....	49
5.3.4.3.2	Test requirements	49
5.3.5	Receiver Adjacent Channel Selectivity (ACS)	50
5.3.5.1	Method of test	50
5.3.5.1.1	Initial conditions	50
5.3.5.1.2	Procedure.....	50
5.3.5.2	Test requirements	51
5.3.6	Receiver Blocking Characteristics	51
5.3.6.1	Method of test	51
5.3.6.1.1	Initial conditions	51
5.3.6.1.2	In-Band Procedure.....	51
5.3.6.1.3	Out-Of-Band Procedure.....	52
5.3.6.1.4	Narrow-Band Procedure	52
5.3.6.2	Test requirements	53
5.3.7	Receiver Spurious Response.....	53
5.3.7.1	Method of test	53
5.3.7.1.1	Initial conditions	53
5.3.7.1.2	Procedure.....	53
5.3.7.2	Test requirements	53
5.3.8	Receiver Intermodulation Characteristics	53
5.3.8.1	Method of test	53
5.3.8.1.1	Initial conditions	53
5.3.8.1.2	Procedure.....	54
5.3.8.2	Test requirements	54
5.3.9	Receiver Spurious Emissions.....	54
5.3.9.1	Method of test	54

5.3.9.1.1	Procedure.....	55
5.3.9.2	Test requirements.....	55
5.3.10	Transmitter Adjacent Channel Leakage Power Ratio.....	55
5.3.10.1	Transmitter adjacent channel leakage power ratio for Single Carrier	55
5.3.10.1.1	Method of test.....	55
5.3.10.1.2	Test requirements	56
5.3.10.2	Transmitter adjacent channel leakage power ratio for intra-band contiguous Carrier Aggregation (DL CA and UL CA).....	56
5.3.10.2.1	Method of test.....	56
5.3.10.2.2	Test requirements	57
5.3.10.3	Transmitter adjacent channel leakage power ratio for UL-MIMO.....	57
5.3.10.3.1	Method of test.....	57
5.3.10.3.2	Test requirements	58
Annex A (normative):	HS Requirements and conformance Test specifications Table (HS-RTT).....	59
Annex B (normative):	Environmental profile	61
B.1	General	61
B.1.1	Introduction	61
B.1.2	Temperature	61
B.1.3	Voltage	61
B.1.4	Test environment.....	62
Annex C:	Void	63
Annex D (informative):	Bibliography.....	64
History		65

iTeh Standards

(<https://standards.iteh.ai>)

Document Preview

[ETSI EN 301 908-13 V6.1.3 \(2013-08\)](https://standards.iteh.ai/catalog/standards/etsi/62c03020-dd17-45f6-93ae-3f80b29dfa9d/etsi-en-301-908-13-v6-1-3-2013-08)

<https://standards.iteh.ai/catalog/standards/etsi/62c03020-dd17-45f6-93ae-3f80b29dfa9d/etsi-en-301-908-13-v6-1-3-2013-08>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonized European Standard (EN) has been produced by ETSI Technical Committee Mobile Standards Group (MSG).

The present document has been produced by ETSI in response to mandates M/284 and M/406 issued from the European Commission under Directive 98/34/EC [i.1] as amended by Directive 98/48/EC [i.10].

The title and reference to the present document are intended to be included in the publication in the Official Journal of the European Union of titles and references of Harmonized Standard under the Directive 1999/5/EC [i.2].

See article 5.1 of Directive 1999/5/EC [i.2] for information on presumption of conformity and Harmonized Standards or parts thereof the references of which have been published in the Official Journal of the European Union.

The requirements relevant to Directive 1999/5/EC [i.2] are summarized in annex A.

The present document is part 13 of a multi-part deliverable. Full details of the entire series can be found in part 1 [5].

National transposition dates

Date of adoption of this EN:	7 October 2013
Date of latest announcement of this EN (doa):	31 January 2014
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 July 2014
Date of withdrawal of any conflicting National Standard (dow):	31 July 2015

Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive [i.2]. The modular structure is shown in EG 201 399 [i.3].