

**Base Stations (BS), Repeaters and User Equipment (UE)
for IMT-2000 Third-Generation cellular networks;
Part 2: Harmonized EN for IMT-2000,
CDMA Direct Spread (UTRA FDD and E-UTRA FDD) (UE)
covering the essential requirements
of article 3.2 of the R&TTE Directive**

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI EN 301 908-2 V5.2.1 \(2011-07\)](https://standards.iteh.ai/catalog/standards/etsi/3b874ded-bfaa-4d97-a1ad-1593d8194caf/etsi-en-301-908-2-v5-2-1-2011-07)

<https://standards.iteh.ai/catalog/standards/etsi/3b874ded-bfaa-4d97-a1ad-1593d8194caf/etsi-en-301-908-2-v5-2-1-2011-07>



Reference

REN/MSG-TFES-006-2

Keywords

3G, 3GPP, cellular, digital, E-UTRA, IMT-2000, mobile, radio, regulation, UMTS, UTRA, WCDMA

ETSI650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iteh Standards
(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2010.
All rights reserved.

DECTTM, PLUGTESTSTM, UMTSTM, TIPHONTM, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPPTM is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTETM is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	6
Foreword.....	6
Introduction	7
1 Scope	8
2 References	8
2.1 Normative references	9
2.2 Informative references	9
3 Definitions, symbols and abbreviations	10
3.1 Definitions	10
3.2 Symbols	11
3.3 Abbreviations	11
4 Technical requirements specifications	12
4.1 Environmental profile.....	12
4.2 Conformance requirements	12
4.2.1 Introduction.....	12
4.2.2 Transmitter maximum output power.....	13
4.2.2.1 Definition	13
4.2.2.2 Limits	13
4.2.2.3 Conformance	13
4.2.3 Transmitter spectrum emission mask.....	13
4.2.3.1 Definition	13
4.2.3.2 Limits	14
4.2.3.3 Conformance	14
4.2.4 Transmitter spurious emissions.....	14
4.2.4.1 Definition	14
4.2.4.2 Limits	14
4.2.4.3 Conformance	16
4.2.5 Transmitter minimum output power	16
4.2.5.1 Definition	16
4.2.5.2 Limits	16
4.2.5.3 Conformance	16
4.2.6 Receiver Adjacent Channel Selectivity (ACS)	16
4.2.6.1 Definition	16
4.2.6.2 Limits	17
4.2.6.3 Conformance	17
4.2.7 Receiver blocking characteristics	17
4.2.7.1 Definition	17
4.2.7.2 Limits	17
4.2.7.3 Conformance	19
4.2.8 Receiver spurious response.....	19
4.2.8.1 Definition	19
4.2.8.2 Limits	19
4.2.8.3 Conformance	19
4.2.9 Receiver intermodulation characteristics	19
4.2.9.1 Definition	19
4.2.9.2 Limits	20
4.2.9.3 Conformance	20
4.2.10 Receiver spurious emissions	20
4.2.10.1 Definition	20
4.2.10.2 Limits	20
4.2.10.3 Conformance	22
4.2.11 Out-of-synchronization handling of output power.....	22
4.2.11.1 Definition	22

4.2.11.2	Limits	22
4.2.11.3	Conformance	24
4.2.12	Transmitter Adjacent Channel Leakage power Ratio (ACLR)	24
4.2.12.1	Definition	24
4.2.12.2	Limits	24
4.2.12.3	Conformance	24
5	Testing for compliance with technical requirements	24
5.1	Environmental conditions for testing	24
5.2	Interpretation of the measurement results	25
5.3	Essential radio test suites	26
5.3.1	Transmitter maximum output power	26
5.3.1.1	Method of test	26
5.3.1.1.1	Initial conditions	26
5.3.1.1.2	Procedure	26
5.3.1.2	Test requirements	26
5.3.2	Transmitter spectrum emission mask	26
5.3.2.1	Method of test	26
5.3.2.1.1	Initial conditions for UEs not supporting HSDPA and/or E-DCH	26
5.3.2.1.1A	Initial conditions for UEs supporting HSDPA and/or E-DCH	26
5.3.2.1.2	Procedure for UEs not supporting HSDPA and/or E-DCH	27
5.3.2.1.2A	Procedure for UEs supporting HSDPA and/or E-DCH	27
5.3.2.2	Test requirements	27
5.3.3	Transmitter spurious emissions	27
5.3.3.1	Method of test	27
5.3.3.1.1	Initial conditions	27
5.3.3.1.2	Procedure	27
5.3.3.2	Test requirements	27
5.3.4	Transmitter minimum output power	28
5.3.4.1	Method of test	28
5.3.4.1.1	Initial conditions	28
5.3.4.1.2	Procedure	28
5.3.4.2	Test requirements	28
5.3.5	Receiver Adjacent Channel Selectivity (ACS)	28
5.3.5.1	Method of test	28
5.3.5.1.1	Initial conditions	28
5.3.5.1.2	Procedure	28
5.3.5.2	Test requirements	29
5.3.6	Receiver blocking characteristics	29
5.3.6.1	Method of test	29
5.3.6.1.1	Initial requirements	29
5.3.6.1.2	Procedure	29
5.3.6.2	Test requirements	29
5.3.7	Receiver spurious response	29
5.3.7.1	Method of test	29
5.3.7.1.1	Initial conditions	29
5.3.7.1.2	Procedure	30
5.3.7.2	Test requirements	30
5.3.8	Receiver Intermodulation characteristics	30
5.3.8.1	Method of test	30
5.3.8.1.1	Initial conditions	30
5.3.8.1.2	Procedure	30
5.3.8.2	Test requirements	30
5.3.9	Receiver spurious emissions	30
5.3.9.1	Method of test	30
5.3.9.1.1	Initial conditions	30
5.3.9.1.2	Procedure	31
5.3.9.2	Test requirements	31
5.3.10	Out-of-synchronization handling of output power	31
5.3.10.1	Method of test	31
5.3.10.1.1	Initial conditions	31
5.3.10.1.2	Procedure	31

5.3.10.2	Test requirements	31
5.3.11	Transmitter adjacent channel leakage power ratio	32
5.3.11.1	Method of test	32
5.3.11.1.1	Initial conditions for UEs not supporting HSDPA and/or E-DCH	32
5.3.11.1.1A	Initial conditions for UEs supporting HSDPA and/or E-DCH	32
5.3.11.1.2	Procedure for UEs not supporting HSDPA and/or E-DCH	32
5.3.11.1.2A	Procedure for UEs supporting HSDPA and/or E-DCH	32
5.3.11.2	Test requirements	32
Annex A (normative):	HS Requirements and conformance Test specifications Table (HS-RTT)	33
Annex B (normative):	Environmental profile	35
B.1	General	35
B.1.1	Introduction	35
B.1.2	Temperature	35
B.1.3	Voltage	35
B.1.4	Test environment	36
Annex C (informative):	The EN title in the official languages	37
Annex D (informative):	Bibliography	38
History		39

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ETSI EN 301 908-2 V5.2.1 (2011-07)

<https://standards.iteh.ai/catalog/standards/etsi/3b874ded-bfaa-4d97-a1ad-1593d8194caf/etsi-en-301-908-2-v5-2-1-2011-07>