



**IMT cellular networks;
Harmonized EN covering the essential requirements
of article 3.2 of the R&TTE Directive;
Part 2: CDMA Direct Spread (UTRA FDD) User Equipment (UE)**

[ETSI EN 301 908-2 V6.1.3 \(2013-08\)](https://standards.iteh.ai/catalog/standards/etsi/7172277d-5ab8-453c-8371-8bbc6439c095/etsi-en-301-908-2-v6-1-3-2013-08)

<https://standards.iteh.ai/catalog/standards/etsi/7172277d-5ab8-453c-8371-8bbc6439c095/etsi-en-301-908-2-v6-1-3-2013-08>

ReferenceREN/MSG-TFES-010-02

Keywords3G, 3GPP, cellular, digital, IMT, mobile, radio,
regulation, UMTS, UTRA, WCDMA

ETSI650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:
http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2013.
All rights reserved.

DECTTM, PLUGTESTSTM, UMTSTM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPPTM and LTETM are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	6
Foreword.....	6
Introduction	6
1 Scope	7
2 References	8
2.1 Normative references	8
2.2 Informative references	8
3 Definitions, symbols and abbreviations	9
3.1 Definitions	9
3.2 Symbols	10
3.3 Abbreviations	10
4 Technical requirements specifications	12
4.1 Environmental profile.....	12
4.2 Conformance requirements	12
4.2.1 Introduction.....	12
4.2.2 Transmitter maximum output power.....	13
4.2.2.1 Transmitter maximum output power	13
4.2.2.1.1 Definition.....	13
4.2.2.1.2 Limits	13
4.2.2.1.3 Conformance	13
4.2.2.2 Transmitter maximum output power for DC-HSUPA	13
4.2.2.2.1 Definition for DC-HSUPA	13
4.2.2.2.2 Limits for DC-HSUPA	13
4.2.2.2.3 Conformance	14
4.2.3 Transmitter spectrum emission mask.....	14
4.2.3.1 Transmitter spectrum emission mask	14
4.2.3.1.1 Definition.....	14
4.2.3.1.2 Limits	14
4.2.3.1.3 Conformance	15
4.2.3.2 Transmitter spectrum emission mask for DC-HSUPA	15
4.2.3.2.1 Definition for DC-HSUPA	15
4.2.3.2.2 Limits for DC-HSUPA	15
4.2.3.2.3 Conformance	16
4.2.4 Transmitter spurious emissions.....	16
4.2.4.1 Transmitter spurious emissions.....	16
4.2.4.1.1 Definition.....	16
4.2.4.1.2 Limits	16
4.2.4.1.3 Conformance	18
4.2.4.2 Transmitter spurious emissions for DC-HSUPA	18
4.2.4.2.1 Definition for DC-HSUPA	18
4.2.4.2.2 Limits for DC-HSUPA	18
4.2.4.2.3 Conformance	20
4.2.5 Transmitter minimum output power	20
4.2.5.1 Transmitter minimum output power.....	20
4.2.5.1.1 Definition.....	20
4.2.5.1.2 Limits	20
4.2.5.1.3 Conformance	20
4.2.5.2 Transmitter minimum output power for DC-HSUPA	20
4.2.5.2.1 Definition for DC-HSUPA	20
4.2.5.2.2 Limits for DC-HSUPA	20
4.2.5.2.3 Conformance	20
4.2.6 Receiver Adjacent Channel Selectivity (ACS)	21
4.2.6.1 Definition	21

4.2.6.2	Limits	21
4.2.6.3	Conformance	21
4.2.7	Receiver blocking characteristics	21
4.2.7.1	Definition	21
4.2.7.2	Limits	21
4.2.7.3	Conformance	23
4.2.8	Receiver spurious response	23
4.2.8.1	Definition	23
4.2.8.2	Limits	23
4.2.8.3	Conformance	24
4.2.9	Receiver intermodulation characteristics	24
4.2.9.1	Definition	24
4.2.9.2	Limits	24
4.2.9.3	Conformance	25
4.2.10	Receiver spurious emissions	25
4.2.10.1	Definition	25
4.2.10.2	Limits	25
4.2.10.3	Conformance	27
4.2.11	Out-of-synchronization handling of output power	27
4.2.11.1	Definition	27
4.2.11.2	Limits	27
4.2.11.3	Conformance	28
4.2.12	Transmitter Adjacent Channel Leakage power Ratio (ACLR)	28
4.2.12.1	Transmitter adjacent channel leakage power ratio (ACLR)	28
4.2.12.1.1	Definition	28
4.2.12.1.2	Limits	28
4.2.12.1.3	Conformance	29
4.2.12.2	Adjacent channel leakage power ratio for DC-HSUPA	29
4.2.12.2.1	Definition for DC-HSUPA	29
4.2.12.2.2	Limits for DC-HSUPA	29
4.2.12.2.3	Conformance	29
5	Testing for compliance with technical requirements	29
5.1	Environmental conditions for testing	29
5.2	Interpretation of the measurement results	30
5.3	Essential radio test suites	31
5.3.1	Transmitter maximum output power	31
5.3.1.1	Method of test	31
5.3.1.1.1	Initial conditions	31
5.3.1.1.1A	Initial conditions for DC-HSUPA	31
5.3.1.1.2	Procedure	32
5.3.1.1.2A	Procedure for DC-HSUPA	32
5.3.1.2	Test requirements	32
5.3.2	Transmitter spectrum emission mask	32
5.3.2.1	Method of test	32
5.3.2.1.1	Initial conditions for UEs not supporting HSDPA and/or E-DCH	32
5.3.2.1.1A	Initial conditions for UEs supporting HSDPA and/or E-DCH	32
5.3.2.1.1B	Initial conditions for DC-HSUPA	33
5.3.2.1.2	Procedure for UEs not supporting HSDPA and/or E-DCH	33
5.3.2.1.2A	Procedure for UEs supporting HSDPA and/or E-DCH	33
5.3.2.1.2B	Procedure for DC-HSUPA	33
5.3.2.2	Test requirements	33
5.3.3	Transmitter spurious emissions	34
5.3.3.1	Method of test	34
5.3.3.1.1	Initial conditions	34
5.3.3.1.1A	Initial conditions for DC-HSUPA	34
5.3.3.1.2	Procedure	34
5.3.3.1.2A	Procedure for DC-HSUPA	34
5.3.3.2	Test requirements	34
5.3.4	Transmitter minimum output power	35
5.3.4.1	Method of test	35
5.3.4.1.1	Initial conditions	35

5.3.4.1.1A	Initial conditions for DC-HSUPA	35
5.3.4.1.2	Procedure.....	35
5.3.4.1.2A	Procedure for DC-HSUPA	35
5.3.4.2	Test requirements.....	35
5.3.5	Receiver Adjacent Channel Selectivity (ACS)	35
5.3.5.1	Method of test	35
5.3.5.1.1	Initial conditions.....	35
5.3.5.1.2	Procedure.....	36
5.3.5.2	Test requirements.....	36
5.3.6	Receiver blocking characteristics	36
5.3.6.1	Method of test	36
5.3.6.1.1	Initial requirements.....	36
5.3.6.1.2	Procedure.....	36
5.3.6.2	Test requirements.....	37
5.3.7	Receiver spurious response.....	37
5.3.7.1	Method of test	37
5.3.7.1.1	Initial conditions.....	37
5.3.7.1.2	Procedure.....	37
5.3.7.2	Test requirements.....	37
5.3.8	Receiver Intermodulation characteristics.....	37
5.3.8.1	Method of test	37
5.3.8.1.1	Initial conditions.....	37
5.3.8.1.2	Procedure.....	38
5.3.8.2	Test requirements.....	38
5.3.9	Receiver spurious emissions.....	38
5.3.9.1	Method of test	38
5.3.9.1.1	Initial conditions.....	38
5.3.9.1.2	Procedure.....	38
5.3.9.2	Test requirements.....	38
5.3.10	Out-of-synchronization handling of output power.....	38
5.3.10.1	Method of test	38
5.3.10.1.1	Initial conditions.....	38
5.3.10.1.2	Procedure.....	39
5.3.10.2	Test requirements.....	39
5.3.11	Transmitter adjacent channel leakage power ratio.....	39
5.3.11.1	Method of test	39
5.3.11.1.1	Initial conditions for UEs not supporting HSDPA and/or E-DCH	39
5.3.11.1.1A	Initial conditions for UEs supporting HSDPA and/or E-DCH	40
5.3.11.1.1B	Initial conditions for DC-HSUPA	40
5.3.11.1.2	Procedure for UEs not supporting HSDPA and/or E-DCH	40
5.3.11.1.2A	Procedure for UEs supporting HSDPA and/or E-DCH	40
5.3.11.1.2B	Procedure for DC-HSUPA	40
5.3.11.2	Test requirements.....	40

Annex A (normative):	HS Requirements and conformance Test specifications Table (HS-RTT).....	41
-----------------------------	--	-----------

Annex B (normative):	Environmental profile	44
-----------------------------	------------------------------------	-----------

B.1	General	44
B.1.1	Introduction	44
B.1.2	Temperature	44
B.1.3	Voltage	44
B.1.4	Test environment.....	44

Annex C (informative):	Void	46
-------------------------------	-------------------	-----------

Annex D (informative):	Bibliography.....	47
-------------------------------	--------------------------	-----------

History	48
---------------	----

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This draft Harmonized European Standard (EN) has been produced by ETSI Technical Committee Mobile Standards Group (MSG), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure.

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Directive 98/34/EC [i.1] as amended by Directive 98/48/EC [i.10].

The title and reference to the present document are intended to be included in the publication in the Official Journal of the European Union of titles and references of Harmonized Standard under the Directive 1999/5/EC [i.2].

See article 5.1 of Directive 1999/5/EC [i.2] for information on presumption of conformity and Harmonized Standards or parts thereof the references of which have been published in the Official Journal of the European Union.

The requirements relevant to Directive 1999/5/EC [i.2] are summarized in annex A.

The present document is part 2 of a multi-part deliverable. Full details of the entire series can be found in part 1 [10].

National transposition dates

Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive [i.2]. The modular structure is shown in EG 201 399 [i.3].