

ETSI EN 302 065 V1.2.1 (2010-10)

Harmonized European Standard (Telecommunications series)

**Electromagnetic compatibility and
Radio spectrum Matters (ERM);
Short Range Devices (SRD) using
Ultra Wide Band technology (UWB)
for communications purposes;
Harmonized EN covering the essential requirements
of article 3.2 of the R&TTE Directive**

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI EN 302 065 V1.2.1 \(2010-10\)](https://standards.iteh.ai/catalog/standards/etsi/d86dc22f-03c8-46b1-ac26-76d49b6eded3/etsi-en-302-065-v1-2-1-2010-10)

<https://standards.iteh.ai/catalog/standards/etsi/d86dc22f-03c8-46b1-ac26-76d49b6eded3/etsi-en-302-065-v1-2-1-2010-10>



Reference

REN/ERM-TGUWB-0118-1

Keywords

radio, SRD, testing, UWB

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

(https://standards.iteh.ai)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2010.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTE™ is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	6
Foreword.....	6
Introduction	7
1 Scope	9
2 References	9
2.1 Normative references	10
2.2 Informative references.....	10
3 Definitions, symbols and abbreviations	11
3.1 Definitions.....	11
3.2 Symbols.....	12
3.3 Abbreviations	12
4 Technical requirements specification.....	13
4.1 Technical requirements	13
4.1.1 Operating bandwidth.....	13
4.1.1.1 Definition	13
4.1.1.2 Test procedure.....	13
4.1.1.3 Limit.....	13
4.1.1.4 Measurement uncertainty.....	13
4.1.2 Maximum value of mean power spectral density	14
4.1.2.1 Definition	14
4.1.2.2 Test procedure.....	14
4.1.2.3 Limit.....	14
4.1.2.4 Maximum allowable measurement uncertainty.....	15
4.1.3 Maximum value of peak power	15
4.1.3.1 Definition	15
4.1.3.2 Test procedure.....	15
4.1.3.3 Limit.....	15
4.1.3.4 Maximum allowable measurement uncertainty.....	16
4.1.4 Transmit Power Control.....	16
4.1.4.1 Definition	16
4.1.4.2 Test procedure.....	16
4.1.4.3 Limit.....	16
4.1.4.4 Maximum allowable measurement uncertainty.....	17
4.1.5 Receiver spurious emissions	17
4.1.5.1 Definition	17
4.1.5.2 Test procedure.....	17
4.1.5.3 Limit.....	17
4.1.5.4 Maximum allowable measurement uncertainty.....	17
4.1.6 Detect-And-Avoid (DAA)	17
4.1.6.1 Introduction	17
4.1.6.1.1 Applicable frequency ranges	18
4.1.6.1.2 DAA operational modes	18
4.1.6.2 Test procedure.....	18
4.1.6.3 Limit.....	18
4.1.6.4 Maximum allowable measurement uncertainty.....	18
4.1.7 Low Duty Cycle (LDC)	19
4.1.7.1 Definitions.....	19
4.1.7.2 Test procedure.....	19
4.1.7.3 Limits	19
4.1.8 Equivalent mitigation techniques.....	19
5 Essential radio test suites.....	19
5.1 Product information.....	19
5.2 Requirements for the test modulation.....	20

5.3	Test conditions, power supply and ambient temperatures	20
5.3.1	Test conditions	20
5.3.2	Power sources	21
5.3.2.1	Power sources for stand-alone equipment	21
5.3.2.2	Power sources for plug-in radio devices	21
5.3.3	Normal test conditions	21
5.3.3.1	Normal temperature and humidity	21
5.3.3.2	Normal power source	21
5.3.3.2.1	Mains voltage	21
5.3.3.2.2	Lead-acid battery power sources used on vehicles	21
5.3.3.2.3	Other power sources	21
5.4	Choice of equipment for test suites	22
5.4.1	Choice of model	22
5.4.2	Presentation	22
5.4.3	Operating bandwidth and multiband equipment	22
5.4.4	Test sites and general arrangements for radiated measurements	22
5.5	Testing of host connected equipment and plug-in radio devices	23
5.5.1	The use of a host or test fixture for testing plug-In radio devices	23
5.5.2	Testing of combinations	23
5.5.2.1	Alternative A: General approach for combinations	23
5.5.2.2	Alternative B: For host equipment with a plug-in radio device	23
5.5.2.3	Alternative C: For combined equipment with a plug-in radio device	23
5.6	Interpretation of the measurement results	23
5.6.1	Measurement uncertainty is equal to or less than maximum acceptable uncertainty	24
5.6.2	Measurement uncertainty is greater than maximum acceptable uncertainty	24
5.7	Other emissions	25
5.8	Test procedures for essential radio test suites	25
5.8.1	General	25
5.8.2	Maximum mean power spectral density	25
5.8.3	Maximum peak power	26
5.8.4	Operating bandwidth	27
5.8.5	Receiver spurious emissions	27
5.8.6	Low Duty Cycle	28
5.8.7	Test Procedure for the radiolocation systems DAA test	28
5.8.7.1	Introduction	28
5.8.7.2	Initial Start-up test	30
5.8.7.2.1	Test without a radiolocation test signal during the <i>Minimum Initial Channel Availability</i> <i>Check Time, $T_{\text{avail_time_min}}$</i>	30
5.8.7.2.2	Tests with a radiolocation test signal at the beginning of the <i>Minimum Initial Channel</i> <i>Availability Check Time, $T_{\text{avail_time_min}}$</i>	31
5.8.7.2.3	Tests with radiolocation test signal at the end of the <i>Minimum Initial Channel Availability</i> <i>Check Time, $T_{\text{avail_time_min}}$</i>	33
5.8.7.3	In-operation test	35
5.8.7.3.1	In-operation test procedure	35
5.8.7.4	Test patterns for the radiolocation DAA test	36
5.8.8	Test Procedure for BWA systems in the band 3,4 GHz to 3,8 GHz	38
5.8.8.1	Introduction	38
5.8.8.1.1	UWB radio devices with and without victim service identification	38
5.8.8.2	Initial start-up test	38
5.8.8.2.1	Test without a BWA test signal during the <i>Minimum Initial Channel Availability Check</i> <i>Time, $T_{\text{avail_time_min}}$</i>	38
5.8.8.2.2	Tests with a BWA test signal at the beginning of the <i>Minimum Initial Channel Availability</i> <i>Check Time, $T_{\text{avail_time}}$</i>	39
5.8.8.2.3	Tests with a BWA test signal at the end of the <i>Minimum Initial Channel Availability Check</i> <i>Time, $T_{\text{avail_time}}$</i>	40
5.8.8.3	In-operation test	41
5.8.8.4	Test Patterns for BWA Testing	43

Annex A (normative):	HS Requirements and conformance Test specifications Table (HS-RTT)	45
-----------------------------	---	-----------

Annex B (normative):	Radiated measurements	48
-----------------------------	------------------------------------	-----------

B.1	Test sites and general arrangements for measurements involving the use of radiated fields	48
B.1.1	Anechoic chamber	48
B.1.2	Anechoic chamber with a conductive ground plane	49
B.1.3	Test antenna	51
B.1.4	Substitution antenna	51
B.1.5	Measuring antenna	51
B.2	Guidance on the use of a radiation test site	51
B.2.1	Verification of the test site	51
B.2.2	Preparation of the EUT	52
B.2.3	Power supplies to the EUT	52
B.2.4	Range length	52
B.2.5	Site preparation	53
B.3	Coupling of signals	53
B.3.1	General	53
B.3.2	Data Signals	53
B.4	Standard test methods	53
B.4.1	Calibrated setup	53
B.4.2	Substitution method	54
B.5	Standard calibration method	55
Annex C (normative):	Conducted measurements for DAA testing	57
Annex D (informative):	Measurement antenna and preamplifier specifications	58
Annex E (normative):	Radiolocation services in the band 3,1 GHz to 3,4 GHz	59
Annex F (normative):	Broadband wireless access services in the band 3,4 GHz to 3,8 GHz	60
Annex G (normative):	Radiolocation services in the band 8,5 GHz to 9,0 GHz	61
Annex H (informative):	Calculation of peak limit for 3 MHz measurement bandwidth	62
Annex I (normative):	ICS Proforma for DAA radio device	64
I.1	Identification of the protocol	64
I.2	ICS proforma tables	64
I.2.1	Avoidance Modes	64
Annex J (informative):	Bibliography	65
Annex K (informative):	The EN title in the official languages	66
History		67

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonized European Standard (Telecommunications series) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Council Directive 98/34/EC [i.2] (as amended) laying down a procedure for the provision of information in the field of technical standards and regulations.

The present document is intended to become a Harmonized Standard, the reference of which will be published in the Official Journal of the European Communities referencing the Directive 1999/5/EC [i.3] of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity ("the R&TTE Directive").

The present document is intended to cover the provisions of article 3.2 of Directive 1999/5/EC (R&TTE Directive) [i.3].

The present document does not apply to radio equipment for which a specific Harmonized EN applies as such Harmonized EN may specify additional EN requirements relevant to the presumption of conformity under article 3.2 of the R&TTE Directive.

ETSI EN 302 065 V1.2.1 (2010-10)

<https://standards.etsi.org/302065-v1-2-1-2010-10>

National transposition dates

Date of adoption of this EN:	20 September 2010
Date of latest announcement of this EN (doa):	31 December 2010
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 June 2011
Date of withdrawal of any conflicting National Standard (dow):	30 June 2012

Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive. The modular structure is shown in EG 201 399 [i.1].

UWB Technologies

The present document provides a generic set of technical requirements covering many different types of UWB technologies used for short range communications. These technologies can be broken down into two groups:

- 1) Impulse based technologies; and
- 2) RF carrier based technologies.

The following clauses give a brief overview of these UWB technologies and their associated modulation techniques.

Impulse technology

Impulse derived UWB technology consists of a series of impulses created from a dc voltage step whose rise time can be modified to provide the maximum useful number of spectral emission frequencies. This derived impulse can then be suitably modified by the use of filters to locate the resulting waveform within a specific frequency spectrum range. This filter can be a standalone filter or incorporated into an antenna design to reduce emissions outside the designated frequency spectrum.

Modulation techniques include pulse positioning in time, pulse suppression and other techniques to convey information. The transmitted energy is summed at the receiver to reproduce the transmitted pulse.

This technology is suitable for direct and non-direct line of sight communications, any reflected or time delayed emissions being suppressed by the receiver input circuits.

RF carrier based technology

RF carrier based UWB technology is based upon classical radio carrier technology suitably modulated by a baseband modulating process. The modulating process must produce a bandwidth in excess of 50 MHz to be defined as UWB.

Different modulating processes are used to transmit the data information to the receiver and can consist of a series of single hopping frequencies or multi-tone carriers.

This technology can be used for both direct and non-direct line of sight communications, any reflected or time delayed emissions being suppressed by the receiver input circuits.

Test and measurement limitations

The ERA report 2006-0713 [i.9] has shown that there are practical limitations on measurements of RF radiated emissions. The minimum radiated levels that can be practically measured in the lower GHz frequency range by using a radiated measurement setup with a horn antenna and pre-amplifier are typically in the range of about -70 dBm/MHz to -75 dBm/MHz (e.i.r.p) to have sufficient confidence in the measured result (i.e. UWB signal should be at least 6 dB above the noise floor of the spectrum analyser and the measurement is performed under far-field conditions at a one meter distance).

For equipment that have dedicated detachable antennas and provide a 50 ohm antenna port for testing, conducted measurements can be made provided that suitable antenna calibrations can be provided. In the present document, test suites for conducted measurements are only provided for DAA conformance measurements. Transmitter emissions of the radio device are expected to be measured using the radiated measurement setup with the exception of UWB devices which are intended to operate at a mean power spectral density of -70 dBm/MHz or less, then a conducted test procedure can be used.