



HARMONISED EUROPEAN STANDARD

**Navigation radars used on inland waterways;
Harmonised Standard for access to radio spectrum;
Part 1: Magnetron Radars**

get full document from standards.iteh.ai

ReferenceDEN/ERM-TGMAR-540

Keywordsharmonised standard, maritime, navigation, radar,
radio**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed,
this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.
In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2026.
All rights reserved.

ETSI

Contents

| | |
|---|----|
| Intellectual Property Rights | 6 |
| Foreword..... | 6 |
| Modal verbs terminology..... | 7 |
| 1 Scope | 8 |
| 2 References | 8 |
| 2.1 Normative references | 8 |
| 2.2 Informative references..... | 8 |
| 3 Definition of terms, symbols and abbreviations..... | 9 |
| 3.1 Terms..... | 9 |
| 3.2 Symbols..... | 10 |
| 3.3 Abbreviations | 10 |
| 4 Technical requirements specifications | 11 |
| 4.1 Environmental profile..... | 11 |
| 4.2 Conformance requirements | 11 |
| 4.2.1 Transmitter Requirements..... | 11 |
| 4.2.1.1 Occupied Bandwidth..... | 11 |
| 4.2.1.1.1 Definition..... | 11 |
| 4.2.1.1.2 Limits | 11 |
| 4.2.1.1.3 Conformance | 11 |
| 4.2.1.2 Transmitter Peak Power | 11 |
| 4.2.1.2.1 Definition..... | 11 |
| 4.2.1.2.2 Limits | 12 |
| 4.2.1.2.3 Conformance | 12 |
| 4.2.1.3 Measured Bandwidth (B_{20})..... | 12 |
| 4.2.1.3.1 Definition..... | 12 |
| 4.2.1.3.2 Limits | 12 |
| 4.2.1.3.3 Conformance | 12 |
| 4.2.1.4 Out of Band Emissions..... | 12 |
| 4.2.1.4.1 Definition..... | 12 |
| 4.2.1.4.2 Limits | 12 |
| 4.2.1.4.3 Conformance | 13 |
| 4.2.1.5 Spurious Emissions | 13 |
| 4.2.1.5.1 Definition..... | 13 |
| 4.2.1.5.2 Limits | 13 |
| 4.2.1.5.3 Conformance | 14 |
| 4.2.1.6 Stand-by Mode Emissions..... | 14 |
| 4.2.1.6.1 Definition..... | 14 |
| 4.2.1.6.2 Limits | 14 |
| 4.2.1.6.3 Conformance | 14 |
| 4.2.2 Receiver Requirements | 14 |
| 4.2.2.1 Receiver Sensitivity | 14 |
| 4.2.2.1.1 Definition..... | 14 |
| 4.2.2.1.2 Limits | 14 |
| 4.2.2.1.3 Conformance | 14 |
| 4.2.2.2 Receiver Selectivity | 14 |
| 4.2.2.2.1 Definition..... | 14 |
| 4.2.2.2.2 Limits | 15 |
| 4.2.2.2.3 Conformance | 15 |
| 4.2.2.3 Receiver Maximum input Level..... | 16 |
| 4.2.2.3.1 Definition..... | 16 |
| 4.2.2.3.2 Limits | 16 |
| 4.2.2.3.3 Conformance | 16 |
| 4.2.2.4 Receiver non-linearity..... | 16 |
| 4.2.2.4.1 Definition..... | 16 |

| | | |
|-------------------------------|---|-----------|
| 4.2.2.4.2 | Limits | 16 |
| 4.2.2.4.3 | Conformance | 16 |
| 5 | Testing for compliance with technical requirements..... | 16 |
| 5.1 | General Requirements | 16 |
| 5.2 | Environmental conditions for testing | 17 |
| 5.3 | Normal Test Conditions | 17 |
| 5.3.1 | Normal temperature and humidity | 17 |
| 5.3.2 | Normal test power supply | 17 |
| 5.3.2.1 | DC test power supply | 17 |
| 5.4 | Extreme test conditions | 17 |
| 5.4.1 | Extreme temperature and humidity..... | 17 |
| 5.4.2 | Extreme test power supply..... | 17 |
| 5.5 | Radio test suites..... | 18 |
| 5.5.1 | Transmitter test specification..... | 18 |
| 5.5.1.1 | Occupied Bandwidth..... | 18 |
| 5.5.1.2 | Transmitter Peak Power | 18 |
| 5.5.1.3 | Measured Bandwidth (B_{-20})..... | 19 |
| 5.5.1.4 | Out of Band Emissions..... | 19 |
| 5.5.1.5 | Spurious Emissions | 19 |
| 5.5.1.6 | Stand-by Mode Emissions..... | 20 |
| 5.5.1.7 | Pulse Length..... | 20 |
| 5.5.1.8 | Pulse Rise Time | 21 |
| 5.5.2 | Receiver test specifications..... | 22 |
| 5.5.2.1 | Receiver Sensitivity | 22 |
| 5.5.2.2 | Receiver Selectivity | 22 |
| 5.5.2.3 | Receiver Maximum input Level..... | 23 |
| 5.5.2.4 | Receiver non-linearity..... | 24 |
| Annex A (informative): | Relationship between the present document and the essential requirements of Directive 2014/53/EU | 26 |
| Annex B (informative): | Maximum measurement uncertainty..... | 28 |
| Annex C (normative): | Transmitter Pulse Power measurement set up | 29 |
| Annex D (normative): | Occupied Bandwidth and Measured Bandwidth (B_{-20}) measurement set up | 31 |
| Annex E (normative): | Out of Band Emissions, Spurious Emissions and Stand-by Mode Emissions measurement set up | 33 |
| Annex F (normative): | Pulse Length and Pulse Rise Time measurement set up | 35 |
| Annex G (normative): | Receiver Sensitivity measurement setup..... | 37 |
| Annex H (normative): | Receiver Selectivity, Receiver Maximum input Level and Receiver non-linearity measurement setup | 38 |
| Annex I (normative): | Calculation of the -40 dB Bandwidth..... | 40 |
| Annex J (normative): | Setting of B_{ref}, B_m, RBW and VBW for Occupied Bandwidth, Measured Bandwidth (B_{-20}), Out of Band Emissions, Spurious Emissions and Stand-by Emissions | 41 |
| Annex K (normative): | Out of Band Emissions, Spurious Emissions and Stand-by Mode Emissions measurement procedure..... | 42 |
| K.1 | Measurement antenna position..... | 42 |
| K.2 | Correction for variable measurement antenna gain..... | 42 |
| K.3 | Measurement system calibration | 42 |

| | |
|--|-----------|
| K.4 Measurement procedure | 42 |
| Annex L (informative): Checklist | 43 |
| Annex M (informative): Bibliography | 45 |
| Annex N (informative): Change history | 46 |
| History | 47 |

Sample Document

get full document from standards.iteh.ai

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Foreword

This final draft Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the Vote phase of the ETSI Standardisation Request deliverable Approval Procedure (SRdAP).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.1] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.2].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in Table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

The present document is part 1 of a multi-part deliverable covering navigation radars used on inland waterways, as identified below:

Part 1: "Magnetron Radars";

Part 2: "Solid State Radars".

| Proposed national transposition dates | |
|--|---------------------------------|
| Date of latest announcement of this EN (doa): | 3 months after ETSI publication |
| Date of latest publication of new National Standard or endorsement of this EN (dop/e): | 6 months after doa |
| Date of withdrawal of any conflicting National Standard (dow): | 18 months after doa |

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Sample Document

get full document from standards.iteh.ai

1 Scope

The present document specifies technical characteristics and methods of measurements for magnetron-based inland waterways navigational radars having the following characteristics:

- Transmitter peak power not exceeding 10 kW.
- Operating on a pulse modulated single, non-tuneable carrier frequency in the range specified in Table 1.
- At the transmitter output, a 4 port RF-circulator or equivalent is used.
- The antenna is passive, rotating and waveguide based.
- The radar display is an integral part of the equipment.

Table 1: Radio navigation service frequencies

| Radio navigation service frequencies | |
|--------------------------------------|------------------------|
| Transmit | 9 300 MHz to 9 500 MHz |
| Receive | 9 300 MHz to 9 500 MHz |

NOTE: The relationship between the present document and the essential requirements of article 3.2 of Directive 2014/53/EU [i.2] is given in Annex A.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found in the [ETSI docbox](#).

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long-term validity.

The following referenced documents are necessary for the application of the present document.

Not applicable.

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long-term validity.

The following referenced documents may be useful in implementing an ETSI deliverable or add to the reader's understanding, but are not required for conformance to the present document.

- [i.1] [Commission Implementing Decision C\(2015\) 5376 final of 4.8.2015](#) on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.

- [i.2] [Directive 2014/53/EU](#) of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.3] ITU Radio Regulations (2024).
- [i.4] Recommendation ITU-R M.1177-4 (04/2011): "Techniques for measurement of unwanted emissions of radar systems".
- [i.5] ETSI EG 203 336 (V1.2.1) (05-2020): "Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".
- [i.6] ETSI EN 303 676 (V1.1.1) (07-2021): "Navigation radar used on inland waterways; operational, functional and technical requirements".
- [i.7] Recommendation ITU-R SM.1541-7 (09/2024): "Unwanted emissions in the Out of Band domain".
- [i.8] [ERC Recommendation 74-01 \(05/2022\)](#): "Unwanted emissions in the spurious domain".
- [i.9] [ECC Recommendation \(02\)05 \(03/2012\)](#): "Unwanted emissions".
- [i.10] IEC 60945:2002/COR1:2008 including corrigendum 1 (04/2008): "Maritime navigation and radiocommunication equipment and systems - General requirements - Methods of testing and required test results".
- [i.11] IEC 60153-2: 2016: "Hollow metallic waveguides. Part 2: Relevant specifications for ordinary rectangular waveguides".
- [i.12] Recommendation ITU-R SM.332-4 (07/1978): "Selectivity of receivers".

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the following terms apply:

active state: state producing the authorized emission

idle/stand-by state: state where the transmitter is available for traffic but is not in the active state

necessary bandwidth: width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions for a given class of emission

NOTE 1: This definition is taken from ITU Radio Regulation [i.3].

NOTE 2: For the radars covered by the present document the necessary bandwidth B_N is considered to be $B_{.20}$ (20 dB bandwidth) as defined in Recommendation ITU-R SM.1541-7 [i.7].

occupied bandwidth: width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage $\beta/2$ of the total mean power of a given emission

NOTE 1: Unless otherwise specified in a Recommendation ITU-R for the appropriate class of emission, the value of $\beta/2$ should be taken as 0,5 %.

NOTE 2: This definition is taken from ITU Radio Regulations [i.3], chapter I, 1.153.

NOTE 3: For primary radars $\beta/2$ equals 0,5 %.

Peak Envelope Power (PEP): average power supplied to the antenna transmission line by a transmitter during one radio frequency cycle at the crest of the modulation envelope taken under normal operating conditions

NOTE: This definition is taken from ITU Radio Regulations [i.3], chapter I, 1.157.

product configuration: hardware variant of the same typology of system under test (e.g. different power outputs, magnetrons)

pulse length: time between the 50 % amplitude (voltage) points

pulse rise time: time taken for the leading edge of the pulse to increase from 10 % to 90 % of the maximum amplitude (voltage)

radial resolution capability: shortest distance between two targets on the same bearing that can be discriminated

NOTE: This is defined in ETSI EN 303 676 [i.6], clause 5.2.2.5.

3.2 Symbols

For the purposes of the present document, the following symbols apply:

| | |
|-------------|---|
| B_{-20} | -20 dB bandwidth (in MHz) |
| B_{-40} | -40 dB bandwidth (in MHz) |
| B_{IF} | Intermediate frequency bandwidth |
| B_m | Measurement bandwidth |
| B_{ref} | Reference bandwidth |
| dB | decibel |
| dBm | Power ratio expressed in decibels (dB) with reference to one milli watt |
| $dBpp$ | Power ratio expressed in decibels (dB) with reference to peak power |
| f_{image} | Image frequency |
| f_{rx} | Nominal frequency of the receiver |
| f_o | Operating frequency (in MHz) of the magnetron |
| G_s | Gain of the measurement system (dB) |
| k | Boltzmann's constant ($1,38 \times 10^{-23}$ J/K) |
| P_t | Pulse power of transmission |
| t | Time |
| tp | Pulse length |
| tr | Pulse rise time |

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

| | |
|-------|---|
| ANSI | American National Standards Institute |
| dBi | Gain in decibels relative to an isotropic antenna |
| DC | Direct Current |
| ECC | Electronic Communication Committee |
| EFTA | European Free Trade Association |
| EN | European Norm |
| ERC | Electronic Radiocommunication Committee |
| EUT | Equipment Under Test |
| FM | Frequency Modulation |
| FTC | Fast Time Constant |
| GHz | GigaHertz |
| IEC | International Electrotechnical Committee |
| IMD | Intermodulation Distortion |
| ITU-R | International Telecommunication Union - Radiocommunication Sector |
| kHz | kiloHertz |
| kW | kiloWatt |
| LO | Local Oscillator |
| MBR | Measurement Bandwidth Ratio |

| | |
|------|------------------------------|
| MHz | MegaHertz |
| NA | not applicable |
| OoB | Out of Band |
| PEP | Peak Envelope Power |
| RBW | Resolution BandWidth |
| RF | Radio Frequency |
| RML | Receiver Maximal input Level |
| RWB | Referenced BandWidth |
| STC | Sensitive Time Control |
| SWT | SWEEP Time |
| VBW | Video BandWidth |
| VRM | Variable Range Marker |
| VSWR | Voltage Standing Wave Ratio |

4 Technical requirements specifications

4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be in accordance with its intended use, but as a minimum, shall be that specified in the test conditions contained in the present document. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the operational environmental profile defined by its intended use.

4.2 Conformance requirements

4.2.1 Transmitter Requirements

4.2.1.1 Occupied Bandwidth

4.2.1.1.1 Definition

Occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage $\beta/2$ of the total mean power of a given emission as defined in ITU Radio Regulations [i.3], chapter I, 1.153.

4.2.1.1.2 Limits

The occupied bandwidth with $\beta/2 = 0,5 \%$ shall be maintained wholly within the frequency range specified in Table 1.

NOTE: The value of $\beta/2 = 0,5 \%$ is taken from ITU Radio Regulations [i.3], chapter I, 1.153.

4.2.1.1.3 Conformance

The conformance tests are specified in clause 5.5.1.1.

4.2.1.2 Transmitter Peak Power

4.2.1.2.1 Definition

The transmitter peak power of a pulse radar is the peak value of the transmitter pulse power during the transmission pulse.

4.2.1.2.2 Limits

The transmitter peak power shall not exceed 10 kW.

4.2.1.2.3 Conformance

The conformance tests are specified in clause 5.5.1.2.

4.2.1.3 Measured Bandwidth (B_{-20})

4.2.1.3.1 Definition

The measured -20 dB bandwidth (B_{-20}) is the measured bandwidth of the emission 20 dB below the measured peak power.

4.2.1.3.2 Limits

The measured -20 dB bandwidth (B_{-20}) of the signal shall be contained completely within the frequency range specified in Table 1.

4.2.1.3.3 Conformance

The conformance tests are specified in clause 5.5.1.3.

4.2.1.4 Out of Band Emissions

4.2.1.4.1 Definition

Out of Band (OoB) emissions refer to emissions in the region between calculated -40 dB bandwidth (B_{-40}) and the spurious region (see definition of spurious region in clause 4.2.1.5.1).

NOTE 1: The calculated B_{-40} is defined in Annex I.

NOTE 2: More information can be found in Recommendation ITU-R SM.1541-7 [i.7], Annex 8 (OoB domain emission limits for primary radar systems), clause 3.

4.2.1.4.2 Limits

Out of Band (OoB) emissions shall not exceed the limits specified in Table 2 below.

NOTE: These limits are specified in Table 1 of Annex 2 of ECC Recommendation (02)05 [i.9].

The Out of Band mask rolls off at 30 dB/decade from the calculated B_{-40} to the level specified for spurious emissions (see Figure 1 below).

Table 2: Limits for unwanted emissions in the OoB domain

| Offset Frequency x B_{-40} | Limit dB _{pp} | Slope dB/decade |
|---------------------------------|---------------------------|--------------------|
| 0 to 0,5 | 0 | 0 |
| 0,5 | -40 | $-\infty$ |
| 0,5 to 2,3 | -40 to -60 | -30 |